



NSP

Network Services Platform

Release 20.3

Glossary

3HE-16047-AAAA-TQZZA

Issue 1

March 2020

Legal notice

Nokia is a registered trademark of Nokia Corporation. Other products and company names mentioned herein may be trademarks or tradenames of their respective owners.

The information presented is subject to change without notice. No responsibility is assumed for inaccuracies contained herein.

© 2020 Nokia.

Contents

1	Glossary	45
	Numerics	45
1.1	10/100/1000Base-FX	45
1.2	10/100/1000Base-TX	45
1.3	10/100Base-TX	45
1.4	100Base-T	45
1.5	1830 VWM	45
1.6	3-plus-tag	45
1.7	3GPP	45
1.8	5G NR	45
1.9	5-tuple	46
1.10	6over4 tunneling	46
1.11	6PE	46
1.12	6VPE	46
1.13	7210 SAS-D	46
1.14	7210 SAS-Dxp	46
1.15	7210 SAS-E	46
1.16	7210 SAS-K	46
1.17	7210 SAS-M	47
1.18	7210 SAS-Mxp	47
1.19	7210 SAS-R	47
1.20	7210 SAS-S	47
1.21	7210 SAS-Sx	47
1.22	7210 SAS S/Sx VC	48
1.23	7210 SAS-T	48
1.24	7210 SAS-X	48
1.25	7250 IXR	48
1.26	7250 IXR (non-SR OS)	48
1.27	7301 ASAM	49
1.28	7450 ESS	49
1.29	7701 CPAA	49
1.30	7705 SAR	49
1.31	7705 SAR-A	49
1.32	7705 SAR-Ax	49
1.33	7705 SAR-F	49

1.34	7705 SAR-H	49
1.35	7705 SAR-Hc	50
1.36	7705 SAR-M	50
1.37	7705 SAR-W	50
1.38	7705 SAR-Wx	50
1.39	7710 SR	50
1.40	7750 SR	50
1.41	7750 SR MG	51
1.42	7950 XRS	51
1.43	802.1ag	51
1.44	802.1D	51
1.45	802.1p	51
1.46	802.1Q	51
1.47	802.1w	51
1.48	802.1X	51
1.49	9400 NEM	52
1.50	9412 eNodeB	52
1.51	9471 WMM	52
1.52	9500 MPR	52
1.53	9500 MPRe	52
1.54	9500 MPR-SA	52
1.55	9926 DBS	52
1.56	9952 WPS	52
1.57	9958 WTA	53
1.58	9959 NPO	53
A	54
1.59	A	54
1.60	AA	54
1.61	AAA	54
1.62	AAAA	54
1.63	AAL-5	54
1.64	ABM	54
1.65	ABR	54
1.66	ABS	54
1.67	AC	55
1.68	ACK	55
1.69	ACL	55

1.70	ACR.....	55
1.71	AD	55
1.72	AD	55
1.73	ADC.....	55
1.74	adjacency	56
1.75	ADM	56
1.76	admission control	56
1.77	ADP	56
1.78	ADT	56
1.79	AES CTR.....	56
1.80	AF.....	56
1.81	AFI.....	56
1.82	AGW.....	57
1.83	AH	57
1.84	AHPHG	57
1.85	AHPLG	57
1.86	AIM.....	57
1.87	AIS	57
1.88	AISG.....	57
1.89	alarm	57
1.90	ALD	57
1.91	ALG	58
1.92	ALPFGT	58
1.93	ALPHG	58
1.94	AMBR.....	58
1.95	AMF.....	58
1.96	AMI.....	58
1.97	AMR	58
1.98	ANCP	58
1.99	ANL	59
1.100	ANM	59
1.101	ANR.....	59
1.102	ANSI.....	59
1.103	AoC	59
1.104	AOS.....	59
1.105	AP	59
1.106	APAC.....	59

1.107	APCO	59
1.108	API	59
1.109	Apipe	60
1.110	APN	60
1.111	APN AMBR	60
1.112	application server	60
1.113	APR	60
1.114	APS	60
1.115	AQP	60
1.116	arbiter	61
1.117	area	61
1.118	ARP	61
1.119	AS	61
1.120	ASAP MDA	62
1.121	ASBR	62
1.122	ASCII	62
1.123	ASE	62
1.124	AS-MAC	62
1.125	ASM	62
1.126	ASN	62
1.127	ASN.1	62
1.128	ASO	63
1.129	ASR	63
1.130	ATCA	63
1.131	ATM	63
1.132	AU	63
1.133	AU-N	63
1.134	AUG	64
1.135	auto-signed	64
1.136	AUX	64
1.137	auxiliary database	64
1.138	auxiliary server	64
1.139	AVCN	64
1.140	AVP	64
B	65
1.141	B-component	65
1.142	B-MAC	65

1.143	BNG	65
1.144	BSF	65
1.145	B-TAG	65
1.146	B-VID	65
1.147	B-VLAN	65
1.148	B-VPLS	65
1.149	B-VSI	65
1.150	backpressure	66
1.151	BBU	66
1.152	BCB	66
1.153	BCD	66
1.154	BCP	66
1.155	bearer	66
1.156	BEB	66
1.157	BER	66
1.158	BERT	66
1.159	bfd	67
1.160	BGP	67
1.161	BGP AD	67
1.162	BGP AS	67
1.163	BGP LS	67
1.164	BGP LU	67
1.165	BGP-4	67
1.166	BIER	67
1.167	bill shock prevention	68
1.168	binding	68
1.169	BITS	68
1.170	black hole	68
1.171	BMP	68
1.172	BNM	68
1.173	BOF	68
1.174	BOM	68
1.175	BPDU	69
1.176	BRAS	69
1.177	bridge	69
1.178	broadcast TV	69
1.179	BSA	69

1.180	BSID	69
1.181	BSM	69
1.182	BSR	69
1.183	BTS	70
1.184	BTV	70
1.185	bundle	70
C		71
1.186	C	71
1.187	C-MAC	71
1.188	c-plane	71
1.189	C-RP	71
1.190	C-XMA	71
1.191	CA	71
1.192	CAC	71
1.193	CAD	71
1.194	CALEA	71
1.195	CAK	72
1.196	CAM	72
1.197	CBP	72
1.198	CBR	72
1.199	CBS	72
1.200	CBSR	72
1.201	CC	72
1.202	CCA	73
1.203	CCAG	73
1.204	CCF	73
1.205	CCFH	73
1.206	CCM	73
1.207	CCR	74
1.208	CCR-A	74
1.209	CCR-I	74
1.210	CCR-T	74
1.211	CCR-U	74
1.212	Cdbx	74
1.213	CDC-F	74
1.214	CDF	74
1.215	CDR	74

1.216	CE	75
1.217	CEM	75
1.218	certified directory	75
1.219	CES	75
1.220	CESoETH	75
1.221	cflowd	75
1.222	CFM	75
1.223	CFOADM	76
1.224	CFP	76
1.225	CGF	76
1.226	CGI	76
1.227	CHAP	76
1.228	cHDLc	76
1.229	checkpoint (regular)	76
1.230	child form	76
1.231	CHLI	76
1.232	CIDR	77
1.233	CIR	77
1.234	circuit	77
1.235	CIST	77
1.236	CIT	77
1.237	class of service	77
1.238	CLE/ODNC	77
1.239	CLEI	77
1.240	CLI	78
1.241	client delegate server	78
1.242	CLLI	78
1.243	CLM	78
1.244	CM	78
1.245	CMA	78
1.246	CMAS	78
1.247	CMG	79
1.248	CMM	79
1.249	CMU	79
1.250	CNM	79
1.251	CNM toolkit	79
1.252	CNO-ULI	79

1.253	CO	79
1.254	COF	80
1.255	combo port	80
1.256	confederation	80
1.257	control plane.....	80
1.258	CoS	80
1.259	CPAM	80
1.260	CPB	80
1.261	CPE	80
1.262	CPG	81
1.263	Cpipe	81
1.264	CPM	81
1.265	CPU	81
1.266	CRC	81
1.267	credit control.....	81
1.268	CRF	81
1.269	CRL	81
1.270	cron	82
1.271	CS	82
1.272	CSA	82
1.273	CSFB	82
1.274	CSFP	82
1.275	CSG	82
1.276	CSM	82
1.277	CSNP	83
1.278	CSPF	83
1.279	CST	83
1.280	CSU	83
1.281	CSV	83
1.282	CTg	83
1.283	CTP	84
1.284	CUPS	84
1.285	customer	84
1.286	CVLAN	84
1.287	CWDM	84
1.288	CWR8	84
1.289	CWR8-88	84

D	85
1.290 DAPI	85
1.291 data-MDT	85
1.292 DB	85
1.293 DCCA	85
1.294 DCE	85
1.295 DCP	85
1.296 DDN	85
1.297 DDoS	86
1.298 DEM	86
1.299 de-mux	86
1.300 default SAP	86
1.301 degree-2	86
1.302 DEI	86
1.303 demultiplexer	86
1.304 deprecate	86
1.305 DES	86
1.306 device	87
1.307 Device Administrator	87
1.308 DF	87
1.309 DGE	87
1.310 DHCP	87
1.311 DHCP client	87
1.312 DHCP relay	87
1.313 DHCP relay agent	87
1.314 DHCP server	87
1.315 DHCP snooping	88
1.316 Diameter	88
1.317 Diffie-Hellman key exchange	88
1.318 Dijkstra	88
1.319 DLCI	88
1.320 DM	88
1.321 DMM	88
1.322 DNS	88
1.323 DNU	88
1.324 DoD	89
1.325 DOIC	89

1.326	DoS	89
1.327	Dot1N	89
1.328	DP	89
1.329	DPA	89
1.330	DPD	89
1.331	DPI	89
1.332	DPR	90
1.333	DR	90
1.334	DRA	90
1.335	DRC	90
1.336	DRMP	90
1.337	DRR	90
1.338	DRX	91
1.339	DS Lite	91
1.340	DS-N	91
1.341	DSAP	91
1.342	DSC	91
1.343	DSCP	91
1.344	DSL	91
1.345	DSL module	91
1.346	DSLAM	92
1.347	DSU	92
1.348	DTD	92
1.349	DTE	92
1.350	DTE	92
1.351	DU	92
1.352	DUS	92
1.353	DVD	92
1.354	DVD-ROM	93
1.355	DWDM	93
1.356	dynamic host	93
E		94
1.357	e-BGP	94
1.358	E-CSCF	94
1.359	E-LAN	94
1.360	E-Line	94
1.361	E-LSP	94

1.362	E-SNCP	94
1.363	E1	94
1.364	E3	94
1.365	EAC	94
1.366	EAP	94
1.367	EAS	95
1.368	EBGP	95
1.369	EBI	95
1.370	EC	95
1.371	eCCM-U	95
1.372	eCEM-U	95
1.373	ECGI	95
1.374	ECMP	95
1.375	ECT	95
1.376	ED	96
1.377	EDFA	96
1.378	edge	96
1.379	EDPS	96
1.380	EFM	96
1.381	EGP	96
1.382	Egress secondary shaper	96
1.383	eHA	96
1.384	eHRPD	97
1.385	EIC	97
1.386	EIR	97
1.387	EIS	97
1.388	EJB	97
1.389	EM	97
1.390	EMG	97
1.391	eMLPP	97
1.392	eMPS	98
1.393	EMS	98
1.394	eNB	98
1.395	encapsulation	98
1.396	eNodeB	98
1.397	EOP	98
1.398	ePC	98

1.399	ePDG	99
1.400	Epipe	99
1.401	EPS	99
1.402	EPT	99
1.403	E-RAB	99
1.404	ERO	99
1.405	ERP	99
1.406	ERPS	99
1.407	ES	100
1.408	ESI	100
1.409	ESM	100
1.410	ESNCP	100
1.411	ESP	100
1.412	ESS	100
1.413	ETH-BN	100
1.414	ETH-ED	100
1.415	ETH-LBM	100
1.416	ETH-LMM	101
1.417	EtherType	101
1.418	ETR	101
1.419	ETree	101
1.420	eUTRAN	101
1.421	eVOA	101
1.422	EVPL	101
1.423	EVPN	101
1.424	EXP	102
F	103
1.425	FA	103
1.426	failover	103
1.427	fallback	103
1.428	Fast Ethernet	103
1.429	fault	103
1.430	FC	103
1.431	FCAPS	103
1.432	FCC	104
1.433	FD	104
1.434	FDB	104

1.435	FDL	104
1.436	FDN	104
1.437	FEC	104
1.438	FEP	104
1.439	FF	104
1.440	FFD	105
1.441	FIB	105
1.442	FIC	105
1.443	FIPS	105
1.444	FIR	105
1.445	flash memory	105
1.446	flow description	105
1.447	flowspec	105
1.448	FM	105
1.449	FOADM	106
1.450	forwarding class	106
1.451	FP	106
1.452	FP4	106
1.453	FPE	106
1.454	FPGA	106
1.455	Fpipe	106
1.456	FQDN	106
1.457	FR	107
1.458	FRF.5	107
1.459	FRR	107
1.460	FRU	107
1.461	FT	107
1.462	FTP	107
1.463	FUA	107
1.464	FUI	108
1.465	fVOA	108
1.466	FWA	108
1.467	FXO	108
1.468	FXS	108
G	109
1.469	Ga	109
1.470	GARP	109

1.471	GBE.....	109
1.472	GBR	109
1.473	generic NE	109
1.474	GERAN	109
1.475	GGSN.....	109
1.476	GIF	110
1.477	Gig.....	110
1.478	Gig Ethernet	110
1.479	Gigabit Ethernet	110
1.480	GigE	110
1.481	Global MEG.....	110
1.482	GMPLS.....	110
1.483	GMPLS-UNI	110
1.484	Gn.....	111
1.485	GNE.....	111
1.486	GNI	111
1.487	GNSS	111
1.488	golden configuration	111
1.489	Gp.....	111
1.490	GPE	111
1.491	GPON module	111
1.492	GPRS	112
1.493	GPS.....	112
1.494	GPV	112
1.495	GQP	112
1.496	GR	112
1.497	GR/DR.....	112
1.498	GR helper	112
1.499	Gr interface.....	112
1.500	GRE.....	112
1.501	GRT.....	113
1.502	GSM	113
1.503	GSMP	113
1.504	GSN.....	113
1.505	GSU.....	113
1.506	GTP	113
1.507	GTP-C	113

1.508	GTP-U	114
1.509	GUI	114
1.510	GVRP	114
1.511	Gx	114
1.512	Gy	114
H	115
1.513	H-VPLS	115
1.514	HA	115
1.515	HAG	115
1.516	HCM	115
1.517	HDD	115
1.518	HDLC	115
1.519	heartbeat	116
1.520	HIP	116
1.521	HI component	116
1.522	HLI	116
1.523	HMAC	116
1.524	HO	116
1.525	HO-ODUk	116
1.526	Hop	116
1.527	host	116
1.528	HPCFAP	117
1.529	Hpipe	117
1.530	HQoS	117
1.531	HSB	117
1.532	HSDPA	117
1.533	HSGW	117
1.534	HSI	117
1.535	HSM	117
1.536	HSMDA	117
1.537	HSPA	118
1.538	HSS	118
1.539	HSU	118
1.540	HTML	118
1.541	HTTP	118
1.542	HTTP POST	118
1.543	HTTPS	118

1.544	HVPLS.....	118
1.545	hybrid port	118
I	119
1.546	I-component	119
1.547	I-PMSI	119
1.548	I-SID	119
1.549	I-TAG	119
1.550	I-VPLS	119
1.551	I-VSI	119
1.552	I/O.....	119
1.553	I/O module.....	119
1.554	IB-RCC	119
1.555	IBGP	119
1.556	ICAP	120
1.557	ICB	120
1.558	ICCN	120
1.559	ICE	120
1.560	ICMP	120
1.561	ICR	120
1.562	ICRQ	120
1.563	ID.....	120
1.564	IdP.....	120
1.565	IE	121
1.566	IED	121
1.567	IEEE	121
1.568	IES	121
1.569	I-ES	121
1.570	IETF	121
1.571	IGH.....	121
1.572	IGMP	122
1.573	IGMP snooping	122
1.574	IGP	122
1.575	IGP administrative domain	122
1.576	IKE	122
1.577	ILA.....	122
1.578	ILM	122
1.579	ILMI	122

1.580	IMA	123
1.581	IME	123
1.582	IMEI	123
1.583	IMEISV	123
1.584	IMM	123
1.585	IMPM	123
1.586	IMS	123
1.587	IMSI	124
1.588	Interlaken	124
1.589	intermediate system	124
1.590	IOM	124
1.591	IP	124
1.592	IP precedence	124
1.593	IP-CAN	124
1.594	IPCC	124
1.595	IPCP	125
1.596	IPDR	125
1.597	IPFIX	125
1.598	Ipipe	125
1.599	IPsec	125
1.600	IPTV	125
1.601	IPv4	125
1.602	IPv6	125
1.603	IRAT	126
1.604	IRI	126
1.605	IRICC	126
1.606	IS	126
1.607	ISID	126
1.608	IS-IS	126
1.609	ISA	126
1.610	ISA-AA	126
1.611	ISA-IPsec	127
1.612	ISA-L2TP/LNS	127
1.613	ISA-NAT	127
1.614	ISA-TMS	127
1.615	ISA-WLAN	127
1.616	ISC	127

1.617	ISL.....	127
1.618	ISO.....	127
1.619	ISSU.....	128
1.620	IST instance.....	128
1.621	IT.....	128
1.622	ITL.....	128
1.623	ITU.....	128
1.624	ITU-T.....	128
1.625	IWF.....	128
J	129
1.626	J0 byte.....	129
1.627	JAAS.....	129
1.628	Java.....	129
1.629	Java EE.....	129
1.630	JDBC.....	129
1.631	JMS.....	129
1.632	JNLP.....	129
1.633	JRMP.....	130
1.634	JSON.....	130
1.635	JVM.....	130
K	131
1.636	KCI.....	131
1.637	keystore.....	131
1.638	KPI.....	131
1.639	KVM.....	131
L	132
1.640	L.....	132
1.641	L-LSP.....	132
1.642	L0.....	132
1.643	L1.....	132
1.644	L2.....	132
1.645	L2PT.....	132
1.646	L2TP.....	132
1.647	L3.....	133
1.648	LAC.....	133
1.649	LACP.....	133
1.650	LACPDU.....	133

1.651	LAG	133
1.652	LAI	133
1.653	LAIS	133
1.654	LAN	134
1.655	Layer 2	134
1.656	Layer 3	134
1.657	LBM	134
1.658	LBR	134
1.659	LB-VM	134
1.660	LCN	134
1.661	LCP	134
1.662	LD	134
1.663	LDAP	135
1.664	LDP	135
1.665	lease	135
1.666	LED	135
1.667	LER	135
1.668	level	135
1.669	level 1 and level 2 intermediate system	135
1.670	LFA	135
1.671	LFI	136
1.672	LH	136
1.673	LI	136
1.674	LIC	136
1.675	lightRadio Wi-Fi	136
1.676	Linux	136
1.677	LKDI	136
1.678	LLC	136
1.679	LLD	137
1.680	LLDP	137
1.681	LLDPDU	137
1.682	LLID	137
1.683	LM	137
1.684	LMI	137
1.685	LMP	137
1.686	LMT	137
1.687	LNS	138

1.688	load balancing	138
1.689	LOC	138
1.690	LOF	138
1.691	LOS	138
1.692	LO-ODUk	138
1.693	LPE	138
1.694	LPS	138
1.695	LRDI	139
1.696	LS	139
1.697	LSA	139
1.698	LSDB	139
1.699	LSP	139
1.700	LSP classifier	140
1.701	LSP path	140
1.702	LSR	140
1.703	LTE	140
1.704	LTN	140
1.705	LTR	140
M	141
1.706	MA	141
1.707	MAC	141
1.708	MAC pinning	141
1.709	MACsec	141
1.710	MAF	141
1.711	MAID	141
1.712	main server	141
1.713	MAN	142
1.714	mask	142
1.715	MBB	142
1.716	MBH	142
1.717	MBMS	142
1.718	MBS	142
1.719	MC	142
1.720	MC APS	142
1.721	MC LAG	142
1.722	MC MLPPP	143
1.723	MC mobile group	143

1.724	MC peer group	143
1.725	MCC	143
1.726	MCFR	143
1.727	MCM	143
1.728	MCS	143
1.729	MCS Database	143
1.730	MCT	144
1.731	MD	144
1.732	MD5	144
1.733	MDA	144
1.734	MDC	144
1.735	MDCR	144
1.736	MDDb	144
1.737	MDI/MDIX	145
1.738	MDL	145
1.739	MDM	145
1.740	MDT	145
1.741	ME	145
1.742	MED	145
1.743	MEF	145
1.744	MEG	146
1.745	MEI	146
1.746	menu bar	146
1.747	MEP	146
1.748	Mesh	146
1.749	MF bit	146
1.750	MG-VM	146
1.751	MHF	147
1.752	MI	147
1.753	MIB	147
1.754	MIF	147
1.755	MIM	147
1.756	MIP	147
1.757	MIR	147
1.758	mirror service	147
1.759	MLD	148
1.760	MLDP	148

1.761	MLD snooping	148
1.762	MLFR	148
1.763	MLPPP	148
1.764	MME	148
1.765	MMRP	148
1.766	MMS	148
1.767	MNC	149
1.768	MNN	149
1.769	MNO	149
1.770	MO	149
1.771	MOBIKE	149
1.772	MOC	149
1.773	monitoring key	150
1.774	MP	150
1.775	MP-BGP	150
1.776	MPH	150
1.777	MPLS	150
1.778	MPLS-TP	150
1.779	MPR	150
1.780	MPT	150
1.781	MPT-ACC	151
1.782	MPT-HC	151
1.783	MPT-HL	151
1.784	MPT-HQAM	151
1.785	MPT-MC	151
1.786	MPT-XP	151
1.787	MPTCP	151
1.788	MR	151
1.789	MRP	151
1.790	MRRU	152
1.791	MS	152
1.792	MSBN	152
1.793	MS-PW	152
1.794	MSAP	152
1.795	MSB	152
1.796	MSCC	152
1.797	MSCP	152

1.798	MSDP	152
1.799	MSE	153
1.800	MSISDN	153
1.801	MSM	153
1.802	MSP	153
1.803	MSS	153
1.804	MSTI	153
1.805	MSTP	153
1.806	MTC	154
1.807	MTOSI	154
1.808	MTSO	154
1.809	MTU	154
1.810	multi-tier model	154
1.811	multicast CAC	154
1.812	multicast routing	154
1.813	MVAC8B	155
1.814	MVPLS	155
1.815	MVPN	155
1.816	MVR	155
1.817	MVR by proxy	155
1.818	MVR VPLS	155
1.819	MVRF	155
1.820	MVRP	155
1.821	MW	156
1.822	MWA	156
N	157
1.823	N3	157
1.824	N9	157
1.825	N-PE	157
1.826	NA	157
1.827	NAI	157
1.828	NAPT	157
1.829	NAS	157
1.830	NAT	157
1.831	NB-IoT	158
1.832	NBI	158
1.833	NBNS	158

1.834	Nbsf.....	158
1.835	ND	158
1.836	navigation tree.....	158
1.837	NE	158
1.838	NE WO	158
1.839	NEBS	159
1.840	neighbor	159
1.841	NEMO	159
1.842	NETCONF.....	159
1.843	NetLoc.....	159
1.844	NEtO	159
1.845	network topology	159
1.846	NF	159
1.847	NFM-P	160
1.848	NFM-P analytics server	160
1.849	NFM-P auxiliary database	160
1.850	NFM-P auxiliary server.....	160
1.851	NSP Flow Collector	160
1.852	NFM-P client	160
1.853	NFM-P client delegate server.....	161
1.854	NFM-P main database	161
1.855	NFM-P main server	161
1.856	NFM-T	161
1.857	NFV	161
1.858	NGE	161
1.859	NG MVPN	161
1.860	NI.....	161
1.861	NIST	161
1.862	N:K	162
1.863	NLOS	162
1.864	NLRI	162
1.865	NMS	162
1.866	NNI	162
1.867	Nnrf	162
1.868	NOC	162
1.869	NOS	163
1.870	Npcf.....	163

1.871	NPDU	163
1.872	NRC	163
1.873	NRC-P	163
1.874	NRC-T	163
1.875	NRC-X	163
1.876	NRF	163
1.877	nrt-VBR	163
1.878	NSAPI	164
1.879	NSD	164
1.880	NSG	164
1.881	NSP	164
1.882	NSR	164
1.883	NSSA	164
1.884	NSWO	164
1.885	NTP	164
O	165
1.886	O-GLSP	165
1.887	OADM card	165
1.888	OAM	165
1.889	OAMPDU	165
1.890	OAM-VM	165
1.891	OC-N	165
1.892	OCH	165
1.893	OCS	165
1.894	OCS	166
1.895	OCSP	166
1.896	ODU	166
1.897	ODUk	166
1.898	OEO	166
1.899	OFC	166
1.900	OFCS	166
1.901	OFS	166
1.902	OID	166
1.903	OIPS	167
1.904	OLC	167
1.905	OLP	167
1.906	OMC	167

1.907	OMD	167
1.908	OMSP	167
1.909	ONIE	167
1.910	OOS	168
1.911	OPEX	168
1.912	OPR	168
1.913	OPS	168
1.914	OPSA	168
1.915	OPT	168
1.916	Option 82	168
1.917	OPTSG	168
1.918	OPUk	168
1.919	Oracle Advanced Security	168
1.920	ORF	169
1.921	ORR	169
1.922	OS	169
1.923	OS 10K	169
1.924	OS 6250	169
1.925	OS 6350	169
1.926	OS 6400	170
1.927	OS 6450	170
1.928	OS 6450 M/X	170
1.929	OS 6465	170
1.930	OS 6850	170
1.931	OS 6850E	170
1.932	OS 6855	170
1.933	OS 6860	171
1.934	OS 6860E	171
1.935	OS 6865	171
1.936	OS 6900	171
1.937	OS 9600	171
1.938	OS 9700	171
1.939	OS 9700E	171
1.940	OS 9800	172
1.941	OS 9800E	172
1.942	OSC	172
1.943	OSI	172

1.944	OSPF	172
1.945	OSS.....	172
1.946	OSSI.....	173
1.947	OTDR	173
1.948	OTN.....	173
1.949	OTT	173
1.950	OTU.....	173
1.951	OUI.....	173
P	174
1.952	P	174
1.953	P-CSCF	174
1.954	P-GW	174
1.955	P2MP	174
1.956	PAE	174
1.957	PAP	174
1.958	PAT.....	174
1.959	PBB	174
1.960	PBBN	174
1.961	PBN.....	175
1.962	PBR.....	175
1.963	PBS	175
1.964	PC	175
1.965	PCC.....	175
1.966	PCE.....	175
1.967	PCEF.....	175
1.968	PCEP	175
1.969	PCF	175
1.970	PCI	176
1.971	PCM	176
1.972	PCMD.....	176
1.973	PCO	176
1.974	PCP	176
1.975	PCR.....	176
1.976	PCRF	176
1.977	PD	177
1.978	PDF	177
1.979	PDH.....	177

1.980	PDN.....	177
1.981	PDP.....	177
1.982	PDSN	177
1.983	PDU.....	177
1.984	PE	177
1.985	PE bridge	178
1.986	PECF.....	178
1.987	PEM	178
1.988	PEQ.....	178
1.989	PF.....	178
1.990	PFCP.....	178
1.991	PFS	178
1.992	PGW.....	178
1.993	PGW-C.....	178
1.994	PGW-U	179
1.995	PHY.....	179
1.996	Pi.....	179
1.997	PIC	179
1.998	PID	179
1.999	PIM.....	179
1.1000	PIM snooping	179
1.1001	PIM-SM	180
1.1002	PIM-SSM.....	180
1.1003	ping	180
1.1004	PIP	180
1.1005	PIR	180
1.1006	PKI	180
1.1007	PLAR.....	180
1.1008	PLMN	180
1.1009	PLR	181
1.1010	PLSP-ID	181
1.1011	PM.....	181
1.1012	PMC	181
1.1013	PMIP	181
1.1014	PMIPv6.....	181
1.1015	PMSI	181
1.1016	PMT.....	181

1.1017 PNF	181
1.1018 POA.....	182
1.1019 PoE	182
1.1020 PoE Plus	182
1.1021 PoE+	182
1.1022 POS.....	182
1.1023 PPP	182
1.1024 PPP Magic Numbers.....	182
1.1025 PPPoE.....	182
1.1026 PPPRF	183
1.1027 PPTP	183
1.1028 PRA.....	183
1.1029 prefix	183
1.1030 primary CMM.....	183
1.1031 property form identifier link.....	183
1.1032 PS	183
1.1033 PS FCI.....	183
1.1034 PSE	184
1.1035 pseudonode	184
1.1036 pseudowire.....	184
1.1037 PSI	184
1.1038 PSK	184
1.1039 PSN.....	184
1.1040 PSNP	184
1.1041 PSS.....	184
1.1042 PST	185
1.1043 PTB	185
1.1044 PTP	185
1.1045 PVC.....	185
1.1046 PVP	185
1.1047 PVST.....	185
1.1048 PW	185
1.1049 PWRSV	185
1.1050 PXC.....	185
Q	186
1.1051 QAM	186
1.1052 QCI.....	186

1.1053 QER	186
1.1054 QFI	186
1.1055 QinQ	186
1.1056 QL	186
1.1057 QMA	186
1.1058 QoE	186
1.1059 QoS	187
1.1060 QPPB	187
1.1061 QSFP	187
1.1062 QSFP+	187
R	188
1.1063 R-APS	188
1.1064 RAA	188
1.1065 RAB	188
1.1066 RAC	188
1.1067 RADIUS	188
1.1068 RAE	188
1.1069 RAM	188
1.1070 RAN	188
1.1071 RAR	188
1.1072 RAT	189
1.1073 rating group	189
1.1074 RAU	189
1.1075 RCA	189
1.1076 RD	189
1.1077 RDI	189
1.1078 RED	189
1.1079 reference	190
1.1080 Relay Information Option	190
1.1081 residential subscriber	190
1.1082 resync	190
1.1083 RET	190
1.1084 RF	190
1.1085 Rf	190
1.1086 RFC	191
1.1087 RFM	191
1.1088 RG	191

1.1089 RHEL.....	191
1.1090 RIB	191
1.1091 ring group	191
1.1092 RIP	191
1.1093 RJ-45.....	191
1.1094 RMI.....	191
1.1095 RMON	192
1.1096 RMS	192
1.1097 RNC	192
1.1098 RNCV	192
1.1099 ROADM.....	192
1.1100 root bridge	192
1.1101 route flapping	192
1.1102 router.....	193
1.1103 routing domain	193
1.1104 routing instance.....	193
1.1105 routing protocol	193
1.1106 RP	193
1.1107 RPC.....	193
1.1108 RPF	193
1.1109 RPL	193
1.1110 RPS.....	193
1.1111 RRH	194
1.1112 RRO	194
1.1113 RS-232-C	194
1.1114 RSA.....	194
1.1115 RSHG.....	194
1.1116 RSM	194
1.1117 RSRP	194
1.1118 RSRQ.....	194
1.1119 RSTP.....	194
1.1120 RSVP	195
1.1121 RSVP-TE.....	195
1.1122 RT	195
1.1123 rt-VBR	195
1.1124 RTM	195
1.1125 RTU.....	196

1.1126 RUC	196
1.1127 RVPLS (R-VPLS)	196
1.1128 rwa	196
S	197
1.1129 S-GW	197
1.1130 S-PE	197
1.1131 S-PMSI	197
1.1132 S1	197
1.1133 S1-U	197
1.1134 S2a	197
1.1135 S2b	197
1.1136 S4	198
1.1137 S5	198
1.1138 S6b	198
1.1139 S8	198
1.1140 S11	198
1.1141 S12	198
1.1142 SA	198
1.1143 SAA	198
1.1144 SAE	199
1.1145 SAK	199
1.1146 SAE-GW	199
1.1147 SAFI	199
1.1148 SAII	199
1.1149 SAM-L	199
1.1150 SaMOG	199
1.1151 SAP	199
1.1152 SAS	200
1.1153 SBA	200
1.1154 SBFD	200
1.1155 SBI	200
1.1156 SC	200
1.1157 SCADA	200
1.1158 SCEF	200
1.1159 SCI	201
1.1160 SCM	201
1.1161 SCP	201

1.1162	SCR.....	201
1.1163	SCTE35.....	201
1.1164	SCTP.....	201
1.1165	Sd.....	202
1.1166	SDC.....	202
1.1167	SDF.....	202
1.1168	SDH.....	202
1.1169	SDI.....	202
1.1170	SDM.....	202
1.1171	SDN.....	202
1.1172	SDP.....	203
1.1173	SDRAM.....	203
1.1174	SDU.....	203
1.1175	secondary CMM.....	203
1.1176	section.....	203
1.1177	SEG.....	203
1.1178	service class indicator.....	203
1.1179	service tunnel.....	203
1.1180	service-level agreement.....	204
1.1181	SES.....	204
1.1182	set-top box.....	204
1.1183	SFC.....	204
1.1184	SFD.....	204
1.1185	SFM.....	204
1.1186	SFP.....	204
1.1187	SFP+.....	204
1.1188	SFTP.....	205
1.1189	SGi.....	205
1.1190	SGSN.....	205
1.1191	SGW.....	205
1.1192	SGW-C.....	205
1.1193	SGW-U.....	205
1.1194	SHA.....	205
1.1195	SHCV.....	205
1.1196	SHG.....	206
1.1197	SID.....	206
1.1198	SIM.....	206

1.1199 SIP	206
1.1200 SLA	206
1.1201 SLM	206
1.1202 SLOF	206
1.1203 SLOS	206
1.1204 SMA	207
1.1205 SMF	207
1.1206 SMI	207
1.1207 SMM	207
1.1208 SMO	207
1.1209 SMS	207
1.1210 SMTP	207
1.1211 SN	208
1.1212 SNAP	208
1.1213 SNCI	208
1.1214 SNCN	208
1.1215 SNCNC	208
1.1216 sniffer	208
1.1217 SNMP	208
1.1218 SNMP trap	208
1.1219 SNMP trap log ID	208
1.1220 SNTP	209
1.1221 SOAP	209
1.1222 SON	209
1.1223 SONENT	209
1.1224 SPB	209
1.1225 SPF	209
1.1226 spoofing	210
1.1227 SPT	210
1.1228 SPV	210
1.1229 SQL	210
1.1230 SR	210
1.1231 SRGB	210
1.1232 SR TE	210
1.1233 SRLG	211
1.1234 SRRP	211
1.1235 srTCM	211

1.1236 SSAP	211
1.1237 SSD	211
1.1238 SSG	211
1.1239 SSH	211
1.1240 SSH2	211
1.1241 SSID	212
1.1242 SSL	212
1.1243 SSLF	212
1.1244 SSM	212
1.1245 SSO	212
1.1246 SST	212
1.1247 SSU	212
1.1248 STa	212
1.1249 standby	213
1.1250 STAR	213
1.1251 static host	213
1.1252 static MAC	213
1.1253 static subscriber host	213
1.1254 station	213
1.1255 statistics	213
1.1256 STB	213
1.1257 STE	213
1.1258 STM	214
1.1259 STM-N	214
1.1260 STP	214
1.1261 STP 1x1 mode	214
1.1262 STP flat mode	214
1.1263 strict priority	214
1.1264 STS	215
1.1265 subscriber	215
1.1266 subscriber host	215
1.1267 subscriber instance	215
1.1268 SVLAN	215
1.1269 SVN	215
1.1270 sVOA	215
1.1271 switch	215
1.1272 switch fabric processor	215

1.1273	switchover	215
1.1274	SWm	216
1.1275	SWu	216
1.1276	SWw	216
1.1277	Sx	216
1.1278	SX3LIF	216
1.1279	SYN	217
1.1280	SYN/ACK	217
1.1281	SyncE	217
1.1282	Synchronous Ethernet	217
1.1283	syslog	217
T	218
1.1284	T1	218
1.1285	T6c	218
1.1286	T-LDP	218
1.1287	T-PE	218
1.1288	TAC	218
1.1289	TACACS+	218
1.1290	TAF	218
1.1291	TAI	219
1.1292	TAII	219
1.1293	TAU	219
1.1294	TCA	219
1.1295	TCE	219
1.1296	TCN	219
1.1297	TCP	219
1.1298	TCP/IP	219
1.1299	TDF	220
1.1300	TDM	220
1.1301	TE	220
1.1302	TED	220
1.1303	TEDB	220
1.1304	TEI	220
1.1305	TEID	220
1.1306	telco	221
1.1307	Telnet	221
1.1308	Template	221

1.1309	TI-LFA	221
1.1310	tiered architecture	221
1.1311	TISPAN	221
1.1312	TLS	221
1.1313	TLV	222
1.1314	TMA	222
1.1315	TMF	222
1.1316	TMN	222
1.1317	TMS	222
1.1318	TNC	222
1.1319	TOA	223
1.1320	TOADM	223
1.1321	ToS	223
1.1322	T-PDU	223
1.1323	TPM	223
1.1324	TPMR	223
1.1325	TPS	223
1.1326	TPSDA	223
1.1327	Traffica	223
1.1328	transit bridge	224
1.1329	transit SAP	224
1.1330	transit service	224
1.1331	transport tunnel	224
1.1332	TRDU	224
1.1333	triple play	224
1.1334	trTCM	224
1.1335	TRU	224
1.1336	TTL	224
1.1337	TU-N	225
1.1338	TUG	225
1.1339	tunnel	225
1.1340	tuple	225
1.1341	TWAG	225
1.1342	TWAMP	225
1.1343	TWAN	226
1.1344	TWL	226
1.1345	Tx	226

U	227
1.1346 u-plane	227
1.1347 UBR	227
1.1348 UBT	227
1.1349 UCT	227
1.1350 UDM	227
1.1351 UDP	227
1.1352 UE	227
1.1353 UI	228
1.1354 UIC	228
1.1355 UICC	228
1.1356 ULI	228
1.1357 UMTS	228
1.1358 UNI	228
1.1359 UNIVTRM	228
1.1360 UNIX	228
1.1361 UPF	228
1.1362 URPF	229
1.1363 URL	229
1.1364 URR	229
1.1365 user plane	229
1.1366 user VPLS	229
1.1367 USM	229
1.1368 USRPNL	229
1.1369 USU	229
1.1370 UTC	229
1.1371 UTRAN	229
1.1372 UWAN	230
V	231
1.1373 VACM	231
1.1374 VAS	231
1.1375 VBR	231
1.1376 VC	231
1.1377 VCB	231
1.1378 VCC	232
1.1379 VCI	232
1.1380 vCPAA	232

1.1381 vertex	232
1.1382 VHO	232
1.1383 VID	232
1.1384 VINES	232
1.1385 virtual link	232
1.1386 VLAN	233
1.1387 VLAN stacking	233
1.1388 VLAN uplink	233
1.1389 VLL	233
1.1390 VLR	233
1.1391 VM	233
1.1392 VMG	233
1.1393 VMM	233
1.1394 VNF	234
1.1395 VNFC	234
1.1396 VNI	234
1.1397 VNID	234
1.1398 VoD	234
1.1399 VoIP	234
1.1400 VoLTE	234
1.1401 VPA	234
1.1402 VPC	234
1.1403 VPI	235
1.1404 VPLS	235
1.1405 VPM	235
1.1406 VPN	235
1.1407 VPRN	235
1.1408 VPWS	236
1.1409 VQM	236
1.1410 VRF	236
1.1411 VRID	236
1.1412 VRRP	236
1.1413 VRS	236
1.1414 VSAP	236
1.1415 VSC	237
1.1416 VSD	237
1.1417 VSI	237

1.1418 VSM-CCA.....	237
1.1419 VSP	237
1.1420 VSR.....	237
1.1421 VT.....	237
1.1422 VT-N	238
1.1423 VTEP.....	238
1.1424 VTG	238
1.1425 VTL.....	238
1.1426 VWM	238
1.1427 VXLAN	238
W	239
1.1428 WAN	239
1.1429 WDM	239
1.1430 web services	239
1.1431 WFF	239
1.1432 WFQ.....	239
1.1433 Wi-Fi offload	239
1.1434 window	240
1.1435 WLAN GW.....	240
1.1436 WO	240
1.1437 workflow	240
1.1438 working directory	240
1.1439 working panel	240
1.1440 workstation	240
1.1441 WPP	240
1.1442 WR2-88	241
1.1443 WRED	241
1.1444 WRR.....	241
1.1445 WTOCM	241
1.1446 WTR	241
X	242
1.1447 X.25.....	242
1.1448 X.733.....	242
1.1449 X2.....	242
1.1450 XC	242
1.1451 XCM	242
1.1452 XFP	242

1.1453 XMA	242
1.1454 XMDA	242
1.1455 XML	242
1.1456 XML API	243
1.1457 XML-JMS	243
1.1458 XNI	243
1.1459 XNS	243
1.1460 XPIC	243
Y	244
1.1461 YANG	244
Z	245
1.1462 zone	245

1 Glossary

Numerics

1.1 10/100/1000Base-FX

An Ethernet technology that supports data transfer rates of up to 1000 Mb/s using twisted-pair copper wire.

1.2 10/100/1000Base-TX

An Ethernet technology that supports data transfer rates of up to 1000 Mb/s using twisted-pair copper wire.

1.3 10/100Base-TX

An Ethernet standard that supports data transfer rates of up to 100 Mb/s using two pairs of data-grade, twisted-pair copper wire.

1.4 100Base-T

An Ethernet standard that supports data transfer rates of up to 100 Mb/s using twisted-pair copper wire.

1.5 1830 VWM

1830 Versatile WDM

A passive add-on shelf unit that provides [1.1429 “WDM” \(p. 239\)](#) extension to a network element.

1.6 3-plus-tag

A descriptor for Ethernet frames with three or more VLAN ID tags.

1.7 3GPP

3rd Generation Partnership Project

The joint standardization partnership responsible for standardizing UMTS, HSPA, and LTE.

1.8 5G NR

5G new radio

5G NR is an evolution of 3GPP Release 15 or later, for wireless mobile data communication. For the control plane, the existing S1-MME interface is utilized. For the user plane, when Option 3x is supported, the non-standalone (NSA) architecture that uses the LTE EPC and eUTRAN is utilized.

1.9 5-tuple

Information that defines a TCP/IP connection, including source IP address, destination IP address, source port number, destination port number, and the protocol in use.

1.10 6over4 tunneling

6over4 tunneling is a network mechanism that is part of the transition from IPv4 usage to the adoption of IPv6. The mechanism enables IPv6 packet transmission through a multicast-enabled IPv4 network.

1.11 6PE

IPv6 provider edge

6PE allows IPv6 domains to communicate over an MPLS IPv4 network without requiring explicit IPv6 transport.

1.12 6VPE

IPv6 VPN provider edge

6VPE allows IPv6 VPNs to communicate over an MPLS IPv4 network without requiring explicit IPv6 transport.

1.13 7210 SAS-D

7210 Service Access Switch - Demarcation

An intelligent Ethernet edge-demarcation device that extends enhanced Carrier Ethernet VPN service delivery to the CE.

1.14 7210 SAS-Dxp

7210 Service Access Switch - Dxp

An intelligent Ethernet demarcation/access device that supports 2 x 1GE/10GE SFP+ ports, 4 x 100/1000 SFP ports, and 6 x 10/100/1000 Base-T ports. The 7210 SAS-Dxp can be used in locations where they currently use a 7210 SAS-D, with the additional capability of 10GE uplinks and a higher capacity to address the growing bandwidth needs of service aggregation in access networks..

1.15 7210 SAS-E

7210 Service Access Switch - Ethernet

A Carrier Ethernet CLE device that can also be deployed as a cost-effective CE aggregation device for smaller networks.

1.16 7210 SAS-K

7210 Service Access Switch, chassis type K

A Gigabit Ethernet switch typically used for L2 services and mobile backhaul applications. The switch provides aggregation and demarcation for VLL and VPLS services managed to the customer edge.

1.17 7210 SAS-M

7210 Service Access Switch - MPLS

A CE device that provides MPLS-enabled metropolitan and WAN Carrier Ethernet service delivery, Ethernet-based mobile backhaul, and residential service access.

1.18 7210 SAS-Mxp

7210 Service Access Switch, chassis type Mxp

An Ethernet access device that provides IP and MPLS-enabled metropolitan and WAN Carrier Ethernet service delivery, Ethernet-based mobile backhaul, and residential service access.

1.19 7210 SAS-R

7210 Service Access Switch, chassis type R

An Ethernet switch capable of MPLS and MPLS-TP service transport. With multiple IMM card slots and two CPM slots, the 7210 SAS-R supports redundant switching capacity and is suitable for aggregating 1-Gig and 10-Gig rings in access Ethernet networks.

1.20 7210 SAS-S

7210 Service Access Switch, chassis type S

An Ethernet access device that provides IP and MPLS-enabled service delivery, Ethernet-based mobile backhaul, and residential service access. The 7210 SAS-S is similar to the 7210 SAS-Sx, but with a reduced set of hardware features.

The 7210 SAS-S can operate in two modes:

- Standalone mode, in which the NE is managed as an IP/MPLS-enabled service aggregation device at the customer edge.
- Satellite mode, in which the NE is connected by the uplink port to an SR device, and is managed as a shelf unit of the SR device to provide port expansion.

1.21 7210 SAS-Sx

7210 Service Access Switch, chassis type Sx

An Ethernet access device that provides IP and MPLS-enabled service delivery, Ethernet-based mobile backhaul, and residential service access. The 7210 SAS-Sx is similar to the 7210 SAS-S, but with an enhanced set of hardware features.

The 7210 SAS-Sx can operate in two modes:

- Standalone mode, in which the NE is managed as an IP/MPLS-enabled service aggregation device at the customer edge.
- Satellite mode, in which the NE is connected by the uplink port to an SR device, and is managed as a shelf unit of the SR device to provide port expansion.

1.22 7210 SAS S/Sx VC

7210 Service Access Switch, chassis type Virtual Chassis

An Ethernet 7210 SAS-S/Sx VC supports stacking of the SAS-S/Sx variants. It includes support for virtual chassis/stacking with 7210 SAS-Sx/S 1/10GE platforms for EPIPE, VPLS, RVPLS services with IP/MPLS.

To simplify the operations and management, the stack of nodes is presented as a virtual chassis, with a single IP address to use for managing the platform.

1.23 7210 SAS-T

7210 Service Access Switch, chassis type T

An Ethernet access device that provides demarcation for services managed to the customer edge and Ethernet aggregation in smaller network locations.

1.24 7210 SAS-X

7210 Service Access Switch - MPLS Extended

An MPLS-enabled Ethernet aggregation device for small and medium-sized networks that provides business, mobile backhaul, and residential services. It is similar to the 7210 SAS-M, but has 10Gb/s uplink ports, enhanced traffic management, greater scalability, and hierarchical QoS functions.

1.25 7250 IXR

7250 Interconnect Router

An SR-based router suitable for interconnect applications in core, metro, and datacenter networks.

1.26 7250 IXR (non-SR OS)

7250 Interconnect Router, Release earlier than 19.x

The term 7250 IXR (non-SR OS) is used in the NFM-P documentation to describe 7250 IXR NEs that are not SR OS based, that is, 7250 IXR NEs running an NE release earlier than 19.x.

1.27 7301 ASAM

7301 Advanced Services Access Manager

A high-bandwidth, multimedia-ready DSLAM that provides DSL-based high-speed data transmission between a residential subscriber host and an ATM network.

1.28 7450 ESS

7450 Ethernet Service Switch

An Ethernet switch that enables the delivery of metro Ethernet services and high-density service-aware Ethernet aggregation over IP/MPLS networks.

1.29 7701 CPAA

7701 Control Plane Assurance Appliance

A mountable two-unit computing platform that passively monitors a network to collect and analyze routing data. The 7701 CPAA is the hardware component with which the CPAM interacts.

1.30 7705 SAR

7705 Service Aggregation Router

A router that provides IP/MPLS and PW aggregation functions.

1.31 7705 SAR-A

7705 Service Aggregation Router, chassis type A

A 7705 SAR-A router with two variants:

- passively cooled chassis with 12 Ethernet ports and 8 T1/E1 ports
- passively cooled chassis with 12 Ethernet ports and no T1/E1 ports

1.32 7705 SAR-Ax

7705 Service Aggregation Router, chassis type Ax

The 7705 SAR-Ax is designed mainly as a platform for indoor small cell application. The 7705 SAR-Ax transports all types of data from a mobile cell site to a higher aggregation point of presence or to the Evolve packet core (EPC) over a packet switched network or unsecure ISP. The 7705 SAR-Ax also targets fixed and vertical networks.

1.33 7705 SAR-F

7705 Service Aggregation Router— fixed form-factor chassis

1.34 7705 SAR-H

7705 Service Aggregation Router— hardened

A 7705 SAR-H router that is temperature and EMC-hardened to the following specifications: IEEE1613 and IEC61850-3.

1.35 7705 SAR-Hc

7705 Service Aggregation Router— hardened compact

A 7705 SAR-Hc router is a compact version of the 7705 SAR-H.

1.36 7705 SAR-M

7705 Service Aggregation Router, chassis type M

The 7705 SAR-M has the following:

- actively cooled chassis with 16 T1/E1 ports, 7 Ethernet ports, and 1 hot-insertable module slot
- actively cooled chassis with 0 T1/E1 ports, 7 Ethernet ports, and 1 hot-insertable module slot
- passively cooled chassis with 16 T1/E1 ports, 7 Ethernet ports, and 0 module slots
- passively cooled chassis with 0 T1/E1 ports, 7 Ethernet ports, and 0 module slots

1.37 7705 SAR-W

7705 Service Aggregation Router, chassis type W

A 7705 SAR-W router is a passively cooled, universal AC and DC powered unit, equipped with five Gigabit Ethernet ports (three SFP ports and two RJ-45 Power over Ethernet (PoE) ports).

1.38 7705 SAR-Wx

7705 Service Aggregation Router, chassis type Wx

A 7705 SAR-Wx router is a passively cooled, universal AC powered unit; there are three variants:

- AC power input connector, five Gigabit Ethernet data ports (three SFP ports and two RJ-45 Ethernet ports), and an RJ-45 alarm input connector
- AC power input connector, five Gigabit Ethernet data ports (three SFP ports, one RJ-45 Ethernet port, and one RJ-45 Ethernet port with PoE+), and an RJ-45 alarm input connector
- AC power input connector, four Gigabit Ethernet data ports (three SFP ports and one RJ-45 port), one RJ-45 4-pair xDSL port, and an RJ-45 alarm input connector

1.39 7710 SR

7710 Service Router

A 10-Gbyte version of the 7750 SR that provides granular lower-speed private data services with SLAs.

1.40 7750 SR

7750 Service Router

A high-capacity router that provides scalable, high-speed private data services. It is typically deployed in a core network.

1.41 7750 SR MG

7750 Mobile Gateway

An LTE gateway based on the 7750 SR. The 7750 SR MG can be configured as a [1.992 "PGW" \(p. 178\)](#) or an [1.1191 "SGW" \(p. 205\)](#).

1.42 7950 XRS

7950 Extensible Routing System

A large-scale routing system designed for core deployments. The system is based on the SROS and is available in a 20-slot chassis.

1.43 802.1ag

An IEEE standard that specifies protocols, procedures, and managed objects to support transport fault management in Ethernet services. The standard includes specifications for path discovery and verification, and detection and isolation of connectivity faults.

1.44 802.1D

An IEEE standard that specifies a general method for the operation of MAC bridges, including the STP.

1.45 802.1p

An IEEE standard to provide QoS in Ethernet networks. The standard uses packet tags that define up to eight traffic classes, and enables a switch to transmit packets based on the priority value.

1.46 802.1Q

An IEEE standard that defines the operation of VLAN bridges, and the operation and administration of VLAN topologies in a bridged LAN.

1.47 802.1w

An IEEE standard that defines the requirements for a MAC bridge to provide rapid reconfiguration capability.

1.48 802.1X

An IEEE standard for transmitting EAP authentication messages over a LAN. The client EAP messages are encapsulated in Ethernet frames and transported to a network access point, which is typically a port on an edge device, and then to an authentication device such as a RADIUS server.

1.49 9400 NEM

9400 Network Element Manager

The 9400 NEM is a configuration tool for eNodeB devices.

1.50 9412 eNodeB

See [1.396 “eNodeB” \(p. 98\)](#) .

1.51 9471 WMM

9471 Wireless Mobility Manager

An MME based on an ATCA Linux platform.

1.52 9500 MPR

9500 Microwave Packet Radio

A microwave radio transmission device that aggregates, in a unified Ethernet convergence layer, the native IP packet streams of services in a TDM mobile backhaul network.

The 9500 MPR has been renamed Wavence starting in Release 18.

1.53 9500 MPRe

9500 Microwave Packet Radio (Ethernet)

The 9500 MPRe is a 9500 MPR variant that is a standalone outdoor application of the [1.785 “MPT-MC” \(p. 151\)](#) with no shelf unit. The 9500 MPRe provides fixed or mobile Ethernet backhaul and supports converged metropolitan MPLS networks.

The 9500 MPRe has been renamed Wavence SA starting in Release 18.

1.54 9500 MPR-SA

9500 MPR stand-alone. An alternate term for [1.53 “9500 MPRe” \(p. 52\)](#).

1.55 9926 DBS

9926 Distributed Base Station

See [1.396 “eNodeB” \(p. 98\)](#) .

1.56 9952 WPS

9952 Wireless Provisioning System

The 9952 WPS is an LTE software tool for creating CM XML [1.1436 “WO” \(p. 240\)](#) files for LTE NE configuration management.

1.57 9958 WTA

9958 Wireless Trace Analyzer

The 9958 WTA is a client-based tool that performs end-to-end analysis of call-trace data gathered from the eNodeB and 9471 WMM.

1.58 9959 NPO

9959 Network Performance Optimizer

The 9959 NPO is an EMS that monitors LTE RAN networks and provides the NFM-P with QoS support, alarm management, and statistics.

A**1.59 A**

The A resource record defines the IPv4 host address that corresponds with the host FQDN.

1.60 AA

application assurance

A technology that enables policy-based deep packet inspection of subscriber traffic for application-layer subscriber management.

1.61 AAA

authentication, authorization, and accounting

The functions of user security protocols such as RADIUS and TACACS+.

1.62 AAAA

The AAAA resource record defines the IPv6 host address that corresponds with the host FQDN.

1.63 AAL-5

ATM adaptation layer type 5

AAL-5 supports the conversion of [1.1375 “VBR” \(p. 231\)](#), delay-tolerant, connection-oriented traffic such as signaling and control data, and network management data. AAL-5 traffic requires minimal sequencing and minimal error detection.

1.64 ABM

advanced bandwidth manager

A system that performs bandwidth reservation tasks and provides session admission control for VoIP, VoD, or any IP-based application that requires a bandwidth guarantee.

1.65 ABR

area border router

A router on the border of one or more OSPF areas that connects the areas to the backbone network. The ABR is considered to be a member of the OSPF backbone and the attached areas. The router maintains routing tables that describe both the backbone topology and the topologies of other areas.

1.66 ABS

anti-breakdown system

An overload protection process on the 7750 SR MG. ABS contains internal parameters that monitor signaling latency and memory utilization on each ISM-MG. The parameters each have a high and low threshold value.

When the high threshold value is reached, the ABS signals the corresponding application protocol handler, which decides whether the packet is selectively discarded.

When the memory utilization drops below the low threshold value, the ABS stops passing the signal to the application handler, which prevents the packets from being discarded.

1.67 AC

Attachment circuit

An attachment circuit is the circuit connecting PE and CE equipment in an MPLS VPN.

1.68 ACK

acknowledge

An ACK is an acknowledgment signal that confirms the receipt of a data packet.

1.69 ACL

access control list

An ACL, which is also called a filter policy, is a template applied to a service or port to control ingress or egress network traffic based on IP and MAC criteria.

1.70 ACR

accounting requests

1.71 AD

administrative domain

A group of hosts, routers, and the interconnecting networks, that are managed by a single administrative authority.

1.72 AD

add drop

1.73 ADC

application detection and control

ADC detects and reports the stop and start of specified application traffic to the PCRF, and applies the appropriate enforcement actions.

1.74 adjacency

An adjacency is a close link-state relationship between compatible neighboring routers that allows them to share routing information and forward network traffic. In OSPF, routers become fully adjacent when their compatibility is confirmed and they synchronize their link-state databases. In IS-IS, adjacencies proceed in stages from Down to Up; they are Up when their compatibility is confirmed. IS-IS adjacencies are level 1 or level 2, depending on the level capability of the routers.

1.75 ADM

add/drop multiplexer

A device installed at an intermediate point on a transmission line that enables new signals to be added in the line and existing signals to be dropped. Add/drop multiplexing can be done with optical or electrical signals.

1.76 admission control

Admission control is a validation process that matches the availability of network resources with the service authorization level of an end user to establish a network connection.

1.77 ADP

auto discovery process

1.78 ADT

add drop through

1.79 AES CTR

advanced encryption standard counter

AES CTR is a cryptography suite. It allows for decoding to be run in parallel on devices with many cores, and does not have padding of AES blocks.

1.80 AF

application function

The AF is an element that offers applications dynamic policy and/or charging control over the IP-CAN user plane behavior. The AF communicates with the PCRF to transfer dynamic session information that is required for PCRF decisions, and IP-CAN information and bearer-level event notifications.

1.81 AFI

Address Family Identifier

MP-BGP uses routing tables identified by the Address Family Identifier and Subsequent Address Family Identifier (SAFI).

1.82 AGW

access gateway

1.83 AH

Authentication Header

A member of the IPsec protocol suite. AH is a transport-layer protocol that provides data confidentiality, origin authentication, integrity checking, and replay protection. The communicating systems use a shared key to encrypt and decipher data. AH is similar to [1.411 “ESP” \(p. 100\)](#) , but provides IP header protection by default.

1.84 AHPHG

High Power High Gain Amplifier

1.85 AHPLG

High Power Low Gain Amplifier

1.86 AIM

AirFrame Infrastructure Manager

The AirFrame Infrastructure Manager (AIM) is a proxy SNMP agent running on an AirFrame box in a CMG-a2 and CMG-a8 stack. The AIM monitors all hardware components.

1.87 AIS

alarm indication signal

A signal that a system transmits after some part of a communication link fails.

1.88 AISG

Air Interface Standards Group

The AISG is a non-profit consortium that develops international standards for wireless antenna line devices.

1.89 alarm

An alarm is a notification that the NFM-P generates based on a set of conditions; for example, SNMP traps from NEs and NFM-Pevents. NFM-P alarms are displayed in the client GUI client alarms window, and are also available through the XML APIinterface. NFM-P alarms follow the X.733 standard.

1.90 ALD

antenna line device

1.91 ALG

Application Layer Gateway.

A security component that augments a NAT configuration in a network. It allows the configuration of NAT traversal filters that allow address and port translation for specified application layer protocols.

1.92 ALPFGT

Low Power Fixed Gain Amplifier card with total power monitoring

1.93 ALPHG

Low Power High Gain Amplifier card

1.94 AMBR

aggregated maximum bit rate

The upper limit on the aggregate bit rate that is provided across all non-GBR bearers. See 3GPP TS23.401 Section 4.7.3.

1.95 AMF

access and mobility management function

The AMF performs many of the functions that the MME performs, such as terminating the RAN control plane interface, authenticating the UE, and connection management.

1.96 AMI

alternate mark inversion

A type of line encoding that prevents line capacitance charging. AMI uses alternate positive and negative pulses of the same amplitude to represent a binary 1 and a zero-amplitude state to represent a binary 0.

1.97 AMR

adaptive multi-rate

1.98 ANCP

Access Node Control Protocol

ANCP is an IP-based protocol used in DSL networks. ANCP operates between a DSLAM and a core network device to provide SAP-level rate management. ANCP is an extension of GSMP.

1.99 ANL

Access Network Location

ANLs are potential congestion points in the network.

1.100 ANM

Any rate pluggable I/O card

1.101 ANR

automatic neighbor relation

An eNodeB function that automatically determines the optimal neighbor relations for UE hand-off.

1.102 ANSI

American National Standards Institute

1.103 AoC

advice of charge

AoC is a 3GPP functionality whereby subscribers can receive information about the cost of a requested service.

1.104 AOS

Nokia OmniSwitch

1.105 AP

access point

A device that allows wireless devices to connect to a wired network using Wi-Fi.

1.106 APAC

Asia Pacific and China

1.107 APCO

additional protocol configuration options

The APCO information element is used to exchange additional protocol configuration options between the TWAN/EPDG and the PGW.

1.108 API

application programming interface

A set of programming functions that provide an interface between software applications. An API translates high-level program code into low-level computer instructions.

1.109 **Apipe**

ATM pipe

A type of VLL service that provides a point-to-point ATM service between users who connect to NEs directly or through an ATM access network. One endpoint of an Apipe uses ATM encapsulation, and the other endpoint uses ATM or frame relay encapsulation.

1.110 **APN**

access point name

Identifies a [1.475 “GGSN” \(p. 109\)](#) or [1.992 “PGW” \(p. 178\)](#). It includes a network identifier that defines the [1.980 “PDN” \(p. 177\)](#) to which the [1.1352 “UE” \(p. 227\)](#) requests connectivity, and may also include an operator identifier that specifies in which [1.1008 “PLMN” \(p. 180\)](#) the PGW or GGSN is located. See 3GPP TS23.003 Sections 9 and 19.4.2.2.*

1.111 **APN AMBR**

access point name aggregate maximum bit rate

The maximum available bit rate for an LTE user for accessing services on a specific PDN APN.

1.112 **application server**

A software product that provides Java EE services for Java applications, such as JMS or transaction support. The product may include clustering technology to allow communication among multiple JVMs in a network.

1.113 **APR**

automatic power reduction

A function that automatically reduces the output power of an optical amplifier to prevent human exposure to hazardous output levels.

1.114 **APS**

automatic protection switching

The capability of a transmission system to detect a failure on a working line and to switch automatically to a protection line to recover the traffic.

1.115 **AQP**

application QoS policy

An AQP defines the application policy rules (in terms of matches and actions) when actions that require application awareness are to be performed on the traffic.

1.116 arbiter

An arbiter is an object in a policer control policy that controls the amount of bandwidth that may be distributed to a set of child policers. The root arbiter represents the parent policer. The maximum traffic rate defined for the root arbiter specifies the decrement rate for the parent policer that governs the overall aggregate traffic rate of every child policer associated with the policy instance. The root arbiter also contains the parent policer MBS configuration parameters that the system uses to individually configure the priority thresholds for each policer instance. Child policers may be associated directly with the root arbiter, or with one of the tier 1 or tier 2 arbiters created under the root arbiter.

1.117 area

In the OSPF protocol, network management and scalability can be simplified by partitioning a network into regions. These OSPF network regions are called areas. Each area, also called a routing sub-domain, maintains detailed routing information about its own internal composition, and also maintains routing information which allows it to reach other areas.

1.118 ARP

ARP is expanded two ways:

1. Address Resolution Protocol

ARP is a TCP/IP protocol used to convert an IP address into a physical address, such as an Ethernet address.

2. allocation and retention priority

An EPS bearer QoS parameter that prioritizes bearer establishment or modification requests when resources are limited. An ARP can determine that existing bearers with a relatively low priority should be dropped to free up needed resources. An ARP can also determine whether a bearer should be dropped by another bearer with a higher priority. See 3GPP TS 23.203

1.119 AS

AS is expanded two ways:

1. autonomous system

An AS is a collection of routers under one administrative entity that cooperates by using a common IGP (such as OSPF). AS is synonymous with the ISO term "routing domain". Routing between autonomous systems is done with an inter-AS or interdomain EGP, such as BGP-4.

2. alarm surveillance

AS is an application that receives, stores, displays, and manages real-time alarms. The AS tool consists of an IM to receive, filter, and store alarms; and a USM to display and manage alarm information.

1.120 **ASAP MDA**

any service, any port MDA

An MDA that supports channelization down to the DS0 level and accepts one OC-3/STM-1 SFP module. The MDA is based on a programmable data path architecture that enables enhanced L1 and L2 data path functions, such as ATM TM features, MDA-based channel and port queuing, and multilink applications such as IMA and PPP.

1.121 **ASBR**

autonomous system boundary router

In OSPF, an ASBR is a router that exchanges information with devices from other ASs. ASBRs are also used to import routing information about RIP, direct, or static routes from non-OSPF attached interfaces.

1.122 **ASCII**

American Standard Code for Information Interchange

ASCII is a collection of 7-bit character sets allowing per-country definitions, called variants.

1.123 **ASE**

Amplified Spontaneous Emissions

1.124 **AS-MAC**

asynchronous-MAC

1.125 **ASM**

Any-Source Multicast

Any-Source Multicast is the IP multicast service model defined in RFC 1112, host extensions for IP Multicasting. An IP datagram is transmitted to a host group which is a set of zeros and is identified by a single IP destination address (224.0.0.0 through 239.255.255.255 for IPv4). End hosts are able to join or leave a group any time as there is no restriction to the location or number. This model supports multicast groups with a number of senders. Any end host can be transmitted to a host group even if it is not a member of that group.

1.126 **ASN**

autonomous system number

1.127 **ASN.1**

abstract syntax notation one

1.128 ASO

application service option

ASOs are used to define service provider and customer network functions that are common among sets of subscribers. ASOs prevent subscribers from requiring each subscriber-specific entry in the application QoS policies for standard network services.

1.129 ASR

Abort-Session-Request

The ASR command is sent by the CRF to notify the AF that the bearer for the established session has become unavailable.

1.130 ATCA

Advanced Telecommunications Computing Architecture

ATCA is an industry initiative developed by the PCI Industrial Computer Manufacturers Group. It is designed to meet the needs of both network equipment manufacturers, who require platform reuse, lower costs, faster time-to-market, and multi-source flexibility, and carriers and service providers, who require reduced capital and operational expenditures.

1.131 ATM

asynchronous transfer mode

A transport and switching mechanism that employs 53-byte cells as a basic unit of transfer. Information is routed through the network in the cell using addressing information contained in the header.

1.132 AU

administrative unit

See [1.133 "AU-N" \(p. 63\)](#) .

1.133 AU-N

administrative unit - level *N*

A managed entity within the SDH structure that is the top of the STM-1 configuration hierarchy.

AU-3 has the payload pointer for each payload envelope that is consolidated with the respective payload in one unit. An STM-1 frame has three payload envelopes; therefore, the frame has three AU-3 units. AU-4 applies to the entire STM-1 payload. The AU-4 structure is the only AU in an STM-1 frame.

1.134 **AUG**

administrative unit group

One or more AUs that occupy fixed, defined positions in an STM payload.

1.135 **auto-signed**

Refers to a security certificate that is signed locally, rather than by a certification authority, or CA. An auto-signed certificate provides limited external security, and is typically used only for inter-system access in an isolated environment.

1.136 **AUX**

auxiliary

1.137 **auxiliary database**

See [1.849 “NFM-P auxiliary database”](#) (p. 160).

1.138 **auxiliary server**

See [1.850 “NFM-P auxiliary server”](#) (p. 160).

1.139 **AVCN**

Attribute value change notification

1.140 **AVP**

attribute value pair

A fundamental data representation that consists of an attribute name and a value.

The Diameter protocol consists of a header followed by one or more AVPs. An AVP includes a header and is used to encapsulate protocol-specific data and AAA information.

B

1.141 B-component

The VLAN component within a Backbone Edge Bridge that relays frames between Customer Backbone Ports and Provider Network Ports.

1.142 B-MAC

backbone or provider MAC

1.143 BNG

broadband network gateway

1.144 BSF

binding support function

The binding support function (BSF), which is co-located with session management function (SMF), is used to discover the PCF serving the UE based on the UE IP address. This is done using the service operation, Nbsf_Management_Discovery, where the query parameters of the GET request contain the IP address of the UE. The IP domain attribute may be used in the query of the same UE IP address and may be used in a different IP domain. If a matching PDU session is found, the BSF returns the PCF identity either as an FQDN or IP address. The BSF may also return a PCRF identify using the Diameter host and realm. The UE IP address is served by the PCRF.

1.145 B-TAG

backbone VLAN tag

1.146 B-VID

backbone VLAN Id

1.147 B-VLAN

backbone VLAN

1.148 B-VPLS

backbone VPLS

1.149 B-VSI

backbone Virtual Switch Instance. Also referred to as a B-Site.

1.150 **backpressure**

A technique for ensuring that a transmitting port does not send too much data to a receiving port at a specific time. When the buffer capacity of a receiving port is exceeded, the port sends a jam message to the transmitting port to halt transmission.

1.151 **BBU**

base band unit

1.152 **BCB**

backbone core bridge

1.153 **BCD**

binary-coded decimal

A binary-coded notation in which each of the decimal digits is represented by a binary numeral; a code compression scheme in which two binary bits replace the three-zone bits and four binary bits replace the nine data bits.

1.154 **BCP**

Bridging Control Protocol

A protocol that configures, enables, and disables the bridge protocol modules on both ends of a point-to-point link.

1.155 **bearer**

A bearer is an IP packet flow that has a QoS configuration between a gateway and the [1.1352 “UE” \(p. 227\)](#).

1.156 **BEB**

backbone edge bridge

1.157 **BER**

bit error rate

The percentage of bits that have errors relative to the total number of bits received in a transmission.

1.158 **BERT**

bit error rate tester

BERT is a device that determines the BER on a communication channel.

1.159 BFD

bidirectional forwarding detection

BFD is a protocol to detect faults in the bidirectional path between two forwarding devices.

1.160 BGP

Border Gateway Protocol

BGP is an IETF standard EGP used to propagate routing information between autonomous systems.

1.161 BGP AD

BGP Auto Discovery

BGP AD enables a VPLS PE router to discover other PE routers that are part of the same VPLS domain.

1.162 BGP AS

border gateway protocol autonomous system

BGP is an IETF standard EGP used to propagate routing information between autonomous systems.

1.163 BGP LS

border gateway protocol link state

BGP LS is a BGP address family that distributes IGP topology information to external traffic engineering servers to assist in calculating paths.

1.164 BGP LU

Border Gateway Protocol Labeled Unicast

1.165 BGP-4

Border Gateway Protocol 4

A BGP that supports CIDR addressing, which increases the number of available IP addresses.

1.166 BIER

Bit Index Explicit Replication

BIER is used in forwarding multicast packets.

1.167 bill shock prevention

Bill shock occurs when a subscriber is unknowingly charged for a service that requires additional charges. Bill shock prevention service allows network operators to notify roaming subscribers of service costs in real time, and require their acceptance of the charges before a connection is made.

1.168 binding

A collection of configuration parameters, including at least an IP address, associated with a DHCP client. DHCP servers manage bindings.

1.169 BITS

Building Integrated Timing Supply

BITS is a method of distributing precision timing in a network.

1.170 black hole

In networking, black holes refer to places in a network where incoming or outgoing traffic is silently discarded at the routing level without informing the source that the data did not reach its intended recipient. For example, you can configure NFM-P VPLS sites to allow customers under DOS, DDOS, and worm attacks to send all traffic to a null route to quarantine the hostile traffic.

1.171 BMP

BGP Monitoring Protocol

BMP is used to monitor BGP sessions.

1.172 BNM

bandwidth notification message

1.173 BOF

boot option file

A file that specifies the runtime image, configuration files, and other operational parameters during system initialization.

1.174 BOM

byte order mark

The byte order mark is a unicode character used to signal the byte order of a text file or stream.

1.175 BPDU

bridge protocol data unit

BPDU is the frame used by LAN bridges that support 802.1D STP to communicate with each other.

1.176 BRAS

broadband remote access server

1.177 bridge

Bridges connect two or more network segments which increases the network diameter. Bridges also help regulate traffic. They can send and receive transmissions but a bridge does not originate any traffic of its own other than a special Ethernet frame that allows it to communicate with other bridges.

1.178 broadcast TV

See [1.184 “BTV” \(p. 70\)](#) .

1.179 BSA

broadband service aggregator

A high-speed Ethernet aggregation device that supports hundreds of ports, tens of thousands of filter policies, and tens of thousands of queues to aggregate subscriber traffic. The 7450 ESS is a BSA.

1.180 BSID

base station identifier

BSID is the base station identification of a UE.

1.181 BSM

bootstrap message

A PIM message that CBSRs exchange during the BSR election process.

1.182 BSR

BSR is expanded two ways:

1. bootstrap router

A BSR is a PIM router that manages RP and group information in a multicast network.

2. broadband service router

A BSR terminates L2 access services and routes over IP/MPLS, supporting hundreds of ports and sophisticated QoS for services and for differentiating content and source. An example of a BSR is the 7750 SR.

1.183 **BTS**

base transceiver station

In a [1.1070 "RAN" \(p. 188\)](#), the BTS is the terminating point of the radio interface.

1.184 **BTV**

broadcast television

The transmission of television signals that are available to all users. This television service is used on cable, satellite, and off-air systems. BTV is typically part of a triple play service offering.

1.185 **bundle**

A bundle consists of all baud channels of a packet handler access point interface to a specific connection-related function to which users are connected.

C

1.186 C

client port

1.187 C-MAC

customer MAC

1.188 c-plane

See [1.257 “control plane” \(p. 80\)](#) .

1.189 C-RP

candidate rendezvous point

A router that is configured as a potential RP. If the current RP fails, the C-RP participates in an automated RP election process.

1.190 C-XMA

compact XMA

In the 7950 XRS, an XMA that operates at half capacity. See also [1.1453 “XMA” \(p. 242\)](#) .

1.191 CA

certificate authority

1.192 CAC

Connection Admission Control

1.193 CAD

Channel Add Drop

1.194 CALEA

communications assistance for law enforcement act

CALEA is a United States federal law that enables the government to intercept wire and electronic communications and call-identifying information under certain circumstances; for example, to protect national security.

1.195 CAK

CAM can be expanded in two ways:

- connectivity association key
A connectivity association key is a component of MACsec, securing control plane traffic.
- cooperative awareness message

1.196 CAM

content-addressable memory

CAM is a type of computer memory typically used where high-speed searches are required. CAM compares search terms to the memory contents and returns the storage address of any matches, along with additional data if so designed.

1.197 CBP

customer backbone port

A CBP is a Backbone Edge Bridge Port that can receive and transmit frames for multiple customers, and can translate or assign B-MAC, B-VID, and I-SID on the basis of the received I-SID. This is an I-tagged interface. In the context of SR PBB this is the B-Site “port” that is connected to the I-Site.

1.198 CBR

constant bit rate

CBR is an ATM service category that is used to carry traffic characterized by a service bit rate specified by a constant value and an evenly-spaced cell stream.

1.199 CBS

committed burst size

The CBS is the maximum number of bytes that can be transmitted at the link speed and that conform to the CIR.

1.200 CBSR

candidate bootstrap router

A router that is configured as a potential BSR. If the current BSR fails, the CBSR participates in an automated BSR election process.

1.201 CC

CC can be expanded in the following ways:

1. content of communication

2. continuity check

A continuous flow of OAM cells generated by an ATM switch to check connectivity in the forward direction of a VCC or a VPC between two points in the network.

3. credit control

1.202 CCA

CCA can be expanded in two ways:

1. credit control answer

The CCA is a message that is used between the credit control server and the Diameter credit control client to acknowledge a CCR.

2. cross-connect adapter

See [1.1418 "VSM-CCA" \(p. 237\)](#) .

1.203 CCAG

cross-connect aggregation group

VSM-CCAs are placed in a CCAG. A CCAG provides a mechanism to aggregate multiple CCAs into one forwarding group. The CCAG uses conversation hashing to dynamically distribute cross-connect traffic to the active CCAs in the aggregation group. In the event that an active CCA fails or is removed from the group, the conversation hashing function redistributes the traffic over the remaining active CCAs within the group. The conversation hashing mechanism for a CCAG is identical to that used by Ethernet LAGs.

1.204 CCF

charging control function

1.205 CCFH

credit control failure handling

The CCFH AVP establishes the behavior of the credit-control client in fault conditions. The CCFH value may be configured locally or received from the credit-control server or Diameter home AAA server. The CCFH value received from the Diameter home AAA server overrides the locally configured value, while the CCFH value received from the credit-control server in the CCA message overrides any existing value.

The CCFH AVP offers different failure handling options, including terminate, continue, and retry and terminate.

1.206 CCM

CCM is expanded in two ways:

1. continuity check message

In a CFM enabled network, CCM is a multicast PDU transmitted periodically by a MEP to assure the continuity over the MA to which the transmitting MEP belongs.

2. chassis control module

In the 7950 XRS, a module that houses all management connections and supports operator access to the routing system. CCMs include an LCD touch-screen that supports interfaces for functions such as alarm management and timing management. Each 7950 XRS includes two CCMs that are physically connected to a CPM.

1.207 CCR

credit control request

The credit control request is a message used between the Diameter credit control client and the credit control server to request credit authorization for a service.

1.208 CCR-A

credit control request answer

1.209 CCR-I

credit control request initial

1.210 CCR-T

credit control request terminate

1.211 CCR-U

credit control request update

1.212 Cdbx

cloud database interface

The local interface which represents the connectivity between the MG-VM and the database VM.

1.213 CDC-F

colorless, directionless, and contentionless flexible grid

1.214 CDF

charging data function

1.215 CDR

charging data record

A CDR represents a formatted collection of information about a chargeable event and is used by telecom providers for user billing.

1.216 CE

customer edge

A customer device with the required functions to access the services that are made available by a provider.

1.217 CEM

circuit emulation

CEM is an encapsulation mode that emulates circuit characteristics of SONET or SDH packets.

1.218 certified directory

The certified directory contains image and configuration files that are certified by an authorized user as the default files for the switch. If the switch reboots, the switch reloads the files in the certified directory. If a switch is running from the certified directory, you cannot save any changes made in the running configuration. If the switch reboots, the changes made to switch parameters are lost. To save running configuration changes, the switch must be running from the working directory. See also [1.1438 “working directory” \(p. 240\)](#) .

1.219 CES

circuit emulation service

A device function that enables the encapsulation of TDM frames in protocol packets that are tunneled through a core network.

1.220 CESoETH

circuit emulation service over Ethernet

See [1.219 “CES” \(p. 75\)](#)

1.221 cflowd

Enabling cflowd allows for the collection and analysis of traffic flow samples through a router. It is used for network planning and traffic engineering, capacity planning, security, application and user profiling, performance monitoring, and SLA measurement.

1.222 CFM

connectivity fault management

1.223 CFOADM

[1.287 “CWDM” \(p. 84\)](#) Fixed Optical Add Drop Multiplexer

1.224 CFP

compact form factor pluggable

1.225 CGF

charging gateway function

The CGF listens to GTP messages sent from the GSNs on TCP or UDP port 3386 and gathers charging information in discreet records called CDRs from both SGSNs and GGSNs. The CGF compiles the CDRs into files and stores them until forwarding them to one or more billing networks.

1.226 CGI

cell global identity

1.227 CHAP

Challenge Handshake Authorization Protocol

CHAP is a secure method for connecting to a system.

1.228 cHDLC

Cisco HDLC data encapsulation

cHDLC is a Cisco variation of HDLC encapsulation, a bit-oriented synchronous data link layer protocol. HDLC specifies a data encapsulation method on synchronous serial links using frame characters and checksums. cHDLC also uses a control protocol to maintain serial link keep-alives. You can only configure Cisco HDLC on IES SAPs.

1.229 checkpoint (regular)

A checkpoint is a snapshot of a network at a particular point in time. The checkpoint may be as simple as a checkpoint of existences, or as complex as a complete copy of the topology, which models the existence of an object and its attributes.

See also [1.1079 “reference” \(p. 190\)](#) .

1.230 child form

A child form is a form that is opened from another form. Typically, you must save the child form configuration, and also save or apply the changes from the parent.

1.231 CHLI

consecutive high loss interval

1.232 CIDR

classless interdomain routing

An address aggregation process that simplifies routing.

1.233 CIR

committed information rate

The CIR is the guaranteed minimum rate of throughput between two end-user devices over a network under normal operating circumstances. This rate, measured in bits or kb/s, is used in congestion control procedures.

1.234 circuit

A circuit is a communications connection between two points. It has a line interface from which it transmits and receives data and signaling. A circuit is also known as a port, channel, or timeslot. An electronic circuit is one or more electronic components connected together to perform a specific function.

1.235 CIST

common and internal spanning tree

The CIST instance is the spanning tree calculated by the MSTP region IST and the network CST. The CIST is represented by the single spanning tree flat mode instance. By default, all VLANs are associated with the CIST until they are mapped to an MSTI. See [1.1262 "STP flat mode" \(p. 214\)](#).

1.236 CIT

Craft interface terminal

A local interface between the user and an NE. It is used to issue commands to the local system or, by way of a remote login, to another system on the same fiber as the local system.

1.237 class of service

See [1.258 "CoS" \(p. 80\)](#).

1.238 CLE/ODNC

critical link event/OAM discovery not completed

1.239 CLEI

common language equipment identifier

CLEI codes identify telecommunications equipment in networks. The CLEI code uses a 10-character structure, as outlined in the Telcordia specification. These characters define equipment by

specifying basic product type, features, source document, and associated drawings and versions. A CLEI code is unique to a specific piece of equipment and cannot be assigned to any other part.

1.240 CLI

command line interface

A CLI is an interface that allows an operator to interact with a system by typing commands at a prompt.

1.241 client delegate server

See [1.853 “NFM-P client delegate server” \(p. 161\)](#).

1.242 CLLI

common language location identifier

A CLLI is a standardized, 11-character code used to identify the geographic location of an NE.

1.243 CLM

Centralized License Manager

The Nokia Centralized License Manager (CLM) is a standalone tool that provides simplification of network function license management. CLM is used to manage a pool of licenses for supported network functions. Using CLM, operators can flexibly control license entitlement and monitor license pool usage for their managed network functions.

1.244 CM

configuration management

Modification of network elements in the LTE RAN.

1.245 CMA

compact media adapter

Similar to an MDA, but smaller.

1.246 CMAS

confederation member autonomous system

A subdivision of an AS that is recognized only by other peers within the confederation. Within the confederation, a BGP peer treats only the peers in its CMAS as internal peers. Peers in different CMASs are external peers.

1.247 CMG

cloud mobile gateway

The software-only version of the 7750 SR MG.

Formerly known as the VMG.

1.248 CMM

chassis management module

Switches that operate in a stack, in a primary or secondary management role.

1.249 CMU

compact mobility unit

The CMU delivers the common management functions of the CMG and vMM using the NFM-P. Using the NFM-P, the CMU offers single node fault and performance management. The NFM-P manages the CMG and vMM components of the CMU as separate entities.

1.250 CNM

customer network manager

A data integration system that integrates data from the fault, performance, order management, and provisioning systems of a service provider into a near real-time view for the enterprise customer.

1.251 CNM toolkit

The CNM toolkit is comprised of a servlet and related files that provide a simplified distributed interface to the XML API module. The servlet is invoked by CNM applications from a web browser.

1.252 CNO-ULI

core network overload - user location information

CNO-ULI allows network operators to deploy differentiated charging and other business logic based on location, without incurring massive network signaling load.

CNO-ULI constitutes two parts:

- ULI change reporting when the E-RAB/RAB/user plane is established
- presence reporting area information reporting

1.253 CO

central office

See [1.868 "NOC" \(p. 162\)](#) .

1.254 COF

Channel optical filter

1.255 combo port

A port that is shared between a 10/100/1000 RJ-45 copper connection and a fiber 1 Gb/s connection. The copper or fiber connection can be used, but not both at the same time. If the fiber connection fails, the copper connection automatically becomes active. Combo ports are also known as hybrid ports.

1.256 confederation

In BGP, a confederation is an AS that has been subdivided into smaller ASs called CMASs. A confederation appears to be a single AS to other ASs and is recognized only by other confederation members.

1.257 control plane

The portion of the telecommunications network that is involved with signaling and control, including the management of sessions and services. See also [1.188 “c-plane” \(p. 71\)](#).

1.258 CoS

class of service

CoS is the degree of importance assigned to traffic. There are standard and premium classes of services. During queuing and forwarding, service points give preferential treatment to traffic that originates on elements configured for premium CoS.

1.259 CPAM

Control Plane Assurance Manager

A system that captures and displays 7701 CPAA IGP topology information. The CPAM and NFM-P products are integrated and share the platform resources.

1.260 CPB

Commissioning and Power Balancing

1.261 CPE

CPE can be expanded in two ways:

1. customer premises equipment
Network equipment that resides on the customer's premises.
2. customer provider edge

1.262 CPG

client protection group

1.263 Cpipe

A Cpipe, or circuit emulation VLL service, provides a point-to-point CEM service between users who connect to devices in an IP/MPLS network directly. The endpoints of a Cpipe uses CEM encapsulation.

1.264 CPM

control processing module

A CPM is in a device such as the 7750 SR that uses hardware filters to perform traffic management and queuing functions to protect the control plane.

1.265 CPU

central processing unit

1.266 CRC

cyclic redundancy check

CRC checks transmission errors applied to a block of information. CRC involves a bit string (computed from the data to transmit) associated with each transmitted block, and ensures the check on reception.

1.267 credit control

A mechanism that interacts with a subscriber account in real time, and controls or monitors the charges that are associated with service usage. Credit control checks to see if credit is available, reserves credit, deducts credit from a subscriber account when the service is completed, and refunds unused reserved credit.

1.268 CRF

See [1.976 "PCRF"](#) (p. 176)

1.269 CRL

certificate revocation list

CRL allows the network operator to check if a certificate has been revoked by the issuer CA. CRL can be used for both EPDG and CA certificates (root CA and sub CAs). CRL offers the option to configure an offline certificate revocation list file where the EPDG checks for the revocation of a configured certificate. CRL is configured per CA profile entry in the system.

Automatic CRL updates can be configured by providing a number of URLs where the system can automatically download a new CRL list for a given CA profile. The CRL file is automatically

downloaded from a list of configured HTTP URLs either periodically or before the CRL expires. If the downloaded CRL is more recent than the existing one, then the existing one will be replaced.

1.270 cron

A time-based scheduling service in a UNIX-based OS.

1.271 CS

circuit switched

1.272 CSA

Convergent Security Asset

A security solution package that offers single sign-on and access control mechanisms at different levels to provide a highly secure operating environment. The CSA includes an entry-level login and password mechanism.

1.273 CSFB

circuit switched fallback

CSFB allows UE in an LTE network to use non-LTE RAT for services, such as SMS, when the LTE network does not provide that service.

1.274 CSFP

compact small form factor pluggable

A type of SFP transceiver with two bidirectional channels in a conventional SFP module. See also [1.1186 “SFP” \(p. 204\)](#).

1.275 CSG

closed subscriber group

A closed subscriber group that identifies a group of subscribers who are permitted to access a group of cells which have restricted access. A CSG can consist of group of friends or employees that are allowed to connect to either a single small cell hosted by a residential customer or a group of small cells hosted by a business. A CSG ID is used to identify a unique group of subscribers. A CSG list is created based on input from the host of a single or group of small cells and operator. The CSG access list is referred to by the 9471 WMM to validate subscriptions at a CSG cell where it performs access or handover when UE connects to a small cell.

1.276 CSM

control switching module

A CSM is part of the 7705 SAR that uses hardware filters to perform traffic management and queuing functions to protect the control plane.

1.277 CSNP

complete sequence number PDU

A PDU sent by a designated router to ensure database synchronization.

1.278 CSPF

constrained shortest path first

CSPF is a component of constraint-based routing that uses a TED to find the shortest path through an MPLS domain that meets established constraints. The ingress router determines the physical path for each LSP by applying the CSPF algorithm to the TED information. Input to the CSPF algorithm includes topology link-state information learned from the IGP, LSP administrative attributes, and network resource attributes that are carried by IGP extensions and stored in the TED.

As CSPF considers each candidate NE and link for a new LSP, it accepts or rejects a specific path component based on resource availability and whether selecting the component violates policy constraints. The output of the CSPF calculation is an explicit route that consists of a sequence of router addresses. The explicit route is passed to the signaling component, which establishes forwarding states in the routers along the LSP.

1.279 CST

common spanning tree

The CST is the overall network spanning tree topology resulting from STP, RSTP, and/or MSTP calculations to provide a single data path through the network.

1.280 CSU

channel service unit

A CSU connects a digital phone line coming in from the phone company to network access equipment located on the customer premises. A CSU may also be built into the network interface of the network access equipment.

1.281 CSV

comma separated value

CSV is a way of recording parameters and values in text format that separates values with a delimiter, such as a comma or tab.

1.282 CTg

call trace geographic

Complete call trace data collection of call flow, geolocation, neighbor relation, and user experience data.

1.283 CTP

connection termination point

1.284 CUPS

control and user plane separation of EPC nodes

CUPS is a 3GPP Release 14 standard that defines the architecture for the separation of the SGW, PGW, and TDF in the EPC. This separation enables distributed or centralized network deployment and independent scaling between control plane and user plane functions. The functionality of the existing nodes is not affected.

CUPS enables:

- reduction of latency on application services, for example, by selecting user plane nodes which are closer to the RAN
- increased data traffic, by adding user plane nodes without changing the number of SGW-C, PGW-C, or TDF-C nodes in the network
- separate location and scaling of control plane and user plane resources of the EPC nodes
- separate evolution of the control plane and user plane functionality

1.285 customer

In the NFM-P, a customer is the entity that pays for a network service, such as an IES, a VPLS, or a VPRN. The service is a means of transport for the application content, such as HSI or VoIP, that the customer offers to end users.

1.286 CVLAN

customer VLAN

1.287 CWDM

Coarse wavelength division multiplexing

CWDM is the method of combining multiple signals on laser beams at various wavelengths for transmission along fiber optic cables. The number of channels is fewer than in dense wavelength division multiplexing, or [1.355 “DWDM” \(p. 93\)](#), but more than in standard wavelength division multiplexing, or [1.1429 “WDM” \(p. 239\)](#).

1.288 CWR8

8–Channel colorless wavelength router card, 44 channel

1.289 CWR8-88

8–Channel colorless wavelength router card, 88 channel

D

1.290 DAPI

Destination Access Point Identifier

1.291 data-MDT

data multicast distribution tree

A data-MDT is a tunnel for high-bandwidth source traffic through the P-network to interested PE routers. Data-MDTs do not broadcast customer multicast traffic to all PE routers in a multicast domain. Data-MDTs are only supported for VPRN services.

1.292 DB

database

1.293 DCCA

diameter credit-control application

A networking protocol for the diameter application that is used for real-time credit control of user services.

1.294 DCE

data communication equipment

A device that communicates with a DTE device in RS-232C communications.

1.295 DCP

DCP can be expanded in two ways:

1. data collection and processing
2. Distributed CPU Protection

A control traffic rate limiting protection mechanism for the CPM/CFM that operates on the line cards (hence 'distributed'). CPU protection protects the CPU of the node that it is configured on from a DOS/DDOS attack by limiting the amount of traffic coming in from one of its ports and destined to the CPM (to be processed by its CPU) using a combination of the configurable limits.

1.296 DDN

downlink data notification

A message sent from an SGW to an SGSN or 9471 WMM over the S11 or S4 interface when data is received from a UE. The DDN and DDN Ack alert the SGSN or 9471 WMM of the UE reachability and service requests.

1.297 DDoS

distributed denial of service

A DoS attack that occurs from more than one source at the same time. See also [1.326 “DoS” \(p. 89\)](#).

1.298 DEM

Dynamic Experience Management

DEM is a congestion detection and mitigation solution for mobile, Wi-Fi, and fixed networks.

1.299 de-mux

See [1.303 “demultiplexer” \(p. 85\)](#).

1.300 default SAP

A SAP that forwards VLAN traffic with any encapsulation value. Default SAPs are indicated by the 4095 or * VLAN ID tag.

1.301 degree-2

A bidirectional network configuration from east to west or west to east.

1.302 DEI

drop eligible indicator

The DEI bit is a one-bit field in an Ethernet frame that indicates whether a frame can be dropped when traffic congestion occurs.

1.303 demultiplexer

A device that separates signals that have been combined as a single signal by a multiplexer for transmission over a communications channel.

1.304 deprecate

As a class evolves over releases, its API, methods, and parameters may change. As the old transitions to the new, both versions must be maintained for a period. To deprecate an API, method, class, or parameter, the older version is marked as deprecated, but continues to work.

1.305 DES

data encryption standard

An unclassified U.S. government-sanctioned encryption and decryption technology that uses 56-bit encryption, with 8-bit error detection.

1.306 device

A generic term for an NE such as a router, switch, or bridge; the term is typically used to describe the NE in a non-network context.

1.307 Device Administrator

The Device Administrator application provides the ability to discover model-based devices using mediation policies and network rules.

1.308 DF

don't fragment

A bit in an IPv4 header that controls the fragmentation of a datagram.

1.309 DGE

dynamic gain equalizer

1.310 DHCP

Dynamic Host Configuration Protocol

An Internet protocol to automate the configuration of computers that use TCP/IP. The DHCP can be used to automatically assign IP addresses, deliver TCP/IP stack configuration parameters such as the subnet mask and default router, and provide other configuration information such as the addresses for printer, time, and news servers.

1.311 DHCP client

An Internet host that uses DHCP to obtain configuration parameters, such as a network address, from a DHCP server.

1.312 DHCP relay

DHCP relay allows a router to intercept a DHCP broadcast packet and forward the packet to a specific DHCP server.

1.313 DHCP relay agent

A router used to interconnect DHCP clients with a DHCP server that is connected to another LAN segment or network. A DHCP relay agent can also be used to insert client circuit information.

1.314 DHCP server

A server that stores network addresses and delivers configuration parameters to DHCP clients.

1.315 DHCP snooping

DHCP snooping provides network security by monitoring and analyzing DHCP messages from hosts outside the managed network that can cause traffic attacks within the managed network. DHCP snooping builds and maintains a binding table that contains information such as MAC addresses and IP addresses that correspond to the hosts that are connected from outside the managed network.

1.316 Diameter

A base foundation protocol that provides transfer of Diameter messages, negotiation capabilities, routing capabilities, and error handling. Diameter is a type of AAA protocol.

1.317 Diffie-Hellman key exchange

A key agreement algorithm used by two parties to agree on a shared secret.

1.318 Dijkstra

Routing algorithm used by IS-IS and OSPF that uses the length of path to determine a shortest-path spanning tree. Sometimes also called SPF.

1.319 DLCI

data link connection identifier

A DLCI is a 10-bit routing address of the virtual circuit at the UNI or the NNI that identifies a frame as being from a specific PVC. DLCIs are used to multiplex several PVCs over one physical link.

1.320 DM

delay measurement

Ethernet delay measurement measures frame delay and frame delay variations by sending periodic frames to the peer [1.747 “MEP” \(p. 146\)](#) and receiving frames from the peer [1.747 “MEP” \(p. 146\)](#) during the diagnostic interval.

1.321 DMM

delay measurement message

1.322 DNS

domain name system

A system that translates host names to IP addresses.

1.323 DNU

do not use

1.324 DoD

downstream on demand

DoD is a type of LDP that allows LDP peers to request label bindings only for specific FECs, in order to reduce the amount of label information that is exchanged compared to LDP DU. See also [1.351 “DU” \(p. 92\)](#) and [1.664 “LDP” \(p. 135\)](#).

1.325 DOIC

diameter overload indication conveyance

1.326 DoS

denial of service

A type of attack on a network that involves flooding the network with dummy data packets to render the network incapable of transmitting legitimate traffic.

1.327 Dot1N

802.1 level *N*

See [1.44 “802.1D” \(p. 51\)](#), [1.45 “802.1p” \(p. 51\)](#), [1.46 “802.1Q” \(p. 51\)](#), [1.47 “802.1w” \(p. 51\)](#), and [1.48 “802.1X” \(p. 51\)](#).

1.328 DP

drop precedence

Attribute of a packet which affects the probability of the packet being dropped within a CoS.

1.329 DPA

diameter proxy agent

1.330 DPD

dead peer detection

A method that is used to detect a dead IKE peer by using IPsec traffic patterns.

1.331 DPI

deep packet inspection

A computer network packet inspection process that evaluates the data of a packet. The data is examined for protocol non-compliance and for intrusions such as viruses and spam. If the data passes inspection, the packet passes; otherwise, it is routed to a different destination.

1.332 DPR

disconnect peer request

1.333 DR

DR can be expanded in the following ways:

1. designated router

A PIM-enabled router that manages multicast stream delivery for a group of receiver hosts in a multicast network. DRs exchange information regarding multicast sources and dynamically adjust to changes in source availability.

2. disaster recovery

1.334 DRA

Diameter routing agent

A functional element that ensures that all Diameter sessions established over reference points, such as the Gx, for a specific IP-CAN session, reach the same PCRF when there are multiple and separately addressable PCRFs that are deployed in a Diameter realm. The DRA tracks the status of PCRFs that are assigned to specific UEs and IP-CAN sessions across reference points, such as the Gx.

1.335 DRC

Disaster recovery center—a backup site.

1.336 DRMP

diameter routing message priority

The DRMP defines a mechanism that allows diameter nodes, such as the PGW, to indicate the relative priority of diameter transactions using the DRMP AVP. In cases where the DOIC is only run between the DRAs and the diameter servers, the DRA can use the DRMP AVP information to differentiate request message priorities when making throttling decisions when in overload.

1.337 DRR

deficit round robin

A DRR scheduler is designed to address the limitations of WRR scheduling by implementing a scheduling algorithm that is based on the bytes sent on an egress link. The DRR scheduling algorithm maintains a quantum value that defines the total number of credits for each CoS queue and a credit counter that is decremented each time a byte is taken from the queue for transmission. The purpose of the credit counter is to track the use of bandwidth by a CoS queue relative to the amount of bandwidth that has been allocated to the queue.

1.338 DRX

discontinuous reception

A system used in cellular networks to prolong [1.1352 “UE” \(p. 227\)](#) battery life by dividing UE devices into paging channels that are only paged by the designated network devices.

1.339 DS Lite

Dual-Stack Lite

DS Lite allows an Internet service provider to omit the deployment of any IPv4 address to the customer's CPE. Only global IPv6 addresses are provided.

1.340 DS-N

digital signal - level *N*

A digital signaling rate of *N* Mb/s; for example, the DS-1 rate is 1.544 Mb/s.

1.341 DSAP

destination service access point

1.342 DSC

Dynamic Services Controller.

The DSC is a network component that acts as the PCRF in an LTE network.

1.343 DSCP

differentiated services code point

A six-bit value encoded in the type of service field of an IP packet header, which identifies CoS and the DP the packet receives.

1.344 DSL

digital subscriber line

A DSL is a single twisted pair that supports full-duplex transmission at a bit rate of 160 kb/s (144 kb/s for 2B+D data, 12 kb/s for framing and error correction, and 4 kb/s for the embedded operation channel).

1.345 DSL module

A module card that can be configured on the 7705 SAR-M/ME. The DSL module includes eight xDSL lines.

1.346 DSLAM

digital subscriber line access multiplexer

A DSLAM is multiplexing equipment that a telecom operator uses to provide DSL services to end users.

1.347 DSU

data service unit

A DSU adapts the physical interface on a DTE device to a transmission facility such as T1 or E1. The DSU is also responsible for signal timing.

1.348 DTD

document type definition

The DTD defines the document structure and legal elements for a set of XML code.

1.349 DTE

data terminal equipment

A device that communicates with a DCE device in RS-232-C.

1.350 DTE

data terminating entity

1.351 DU

downstream unsolicited

An MPLS LDP technique, where LSRs distribute bindings to LSRs that have not explicitly requested them.

1.352 DUS

do not use for synchronization

1.353 DVD

digital versatile disk

An optical digital disk that stores up to 4.7 GBytes of data. A DVD can be recorded on both sides and in dual layers.

1.354 DVD-ROM

digital versatile disk - read-only memory

A read-only DVD that is used to store data and software, as well as audio and video content.

1.355 DWDM

dense wavelength division multiplexing

In DWDM, the channels that are transported simultaneously over one fiber at different wavelengths without interaction, are closely spaced (100 GHz or below). Each channel is usually Time Division Multiplexed.

1.356 dynamic host

A host that is temporarily configured on the SAP. The NFM-P learns dynamic hosts when the DHCP lease populate function is enabled.

E

1.357 e-BGP

See [1.368 "EBGP" \(p. 95\)](#) .

1.358 E-CSCF

emergency call session control function

1.359 E-LAN

Ethernet Local Area Network

1.360 E-Line

Ethernet Virtual Private Line

1.361 E-LSP

EXP inferred LSP

1.362 E-SNCP

Electrical-Subnetwork Connection Protection

1.363 E1

A European standard for high-speed voice and data transmission at 2.048 Mb/s.

1.364 E3

A wide-area digital transmission scheme used predominantly in Europe that carries data at a rate of 34.368 Mb/s. E3 lines can be leased for private use from common carriers.

1.365 EAC

Ethernet Access Card

1.366 EAP

Extensible Authentication Protocol

EAP provides a generalized framework for different types of authentication methods. This allows access devices to hand off authentication packets to an authentication system, such as a RADIUS server, without knowing the authentication method used.

1.367 EAS

Ethernet Access Switch

1.368 EBGp

Exterior Border Gateway Protocol

A BGP session established between routers in different ASs. EBGPs communicate among different network domains.

1.369 EBI

EPS bearer ID

1.370 EC

Equipment controller

1.371 eCCM-U

enhanced core controller module

The eCCM-U is an eNodeB component that provides the backhaul interface, call processing, data switching, routing, alarms, and frequency/timing.

1.372 eCEM-U

enhanced channel element module

The eCEM-U is an eNodeB component that provides baseband signal processing and supports data, control, and timing interfaces to the [1.183 "BTS" \(p. 70\)](#).

1.373 ECGI

E-UTRAN cell global identifier

1.374 ECMP

equal-cost multipath routing

Technique used by OSPF and IS-IS routing protocols to balance the load of Internet traffic.

1.375 ECT

equal cost tree

Algorithm as defined by 802.1aq where the shortest paths have to follow a subset of the equal cost shortest paths to any destination.

1.376 ED

Edge device

1.377 EDFA

Erbium doped fiber amplifier

1.378 edge

In the context of an NFM-P map, an object which links two vertex objects. Physical links and service tunnels are examples of edges.

1.379 EDPS

event-driven processing server

A server that is used by the 5750 SSC to access network equipment or mediate with other network management systems to access network equipment.

1.380 EFM

Ethernet in the First Mile

EFM refers to the IEEE Std 802.3ah-2004 standard, an amendment to the Ethernet standard. The EFM standard was approved by the IEEE Standards Board in June 2004, and officially published on 7 September 2004.

The EFM amendment deals with a set of additional specifications, allowing users to run the Ethernet protocol over previously unsupported media, such as single pairs of telephone wiring and single strands of single-mode fiber.

1.381 EGP

Exterior Gateway Protocol

A generic term for a routing protocol that is used to exchange routing information between two hosts in a network of ASs. An EGP is typically used between hosts on the Internet to share routing table information.

1.382 Egress secondary shaper

A control mechanism to prevent downstream packet overruns without affecting the class-based scheduling behavior on a port, typically on an HSMDA.

1.383 eHA

enterprise Home Agent

1.384 eHRPD

evolved high rate packet data

Connects the 3GPP2 HRPD access network to the 3GPP EPC IP environment through PMIP.

1.385 EIC

equipment ID code

A character, or group of characters, used to identify or name equipment.

1.386 EIR

excess information rate

The EIR is the excess bandwidth that a frame relay network attempts to carry for a given connection.

1.387 EIS

enhanced Internet service

EIS enhances the Internet service model by catering to the needs of QoS-sensitive applications by providing value-added Internet services that improve delivery performance.

1.388 EJB

Enterprise Java Beans

Used to describe a session bean, which is a Java object tied into system services to provide session management functions. EJB technology is the part of the Java server-side architecture.

1.389 EM

element manager

1.390 EMG

egress multicast group

A group of destination SAPs that receives packets in a single transmission. The advantage of an EMG is the elimination of packet loopbacks to multiple SAPs.

1.391 eMLPP

enhanced multi-level precedence and pre-emption

Specifies levels of precedence for call setup and continuity for HO.

1.392 eMPS

enhanced multimedia priority service

eMPS refers to priority handling of IMS-based multimedia service, and applies to first responders who are required to have priority treatment as per government mandates. In case of disasters resulting in network overload, signaling for emergency responders are less likely to be dropped. The PGW sees the UE as the regular UE in the initial attachment, but the PCRF later updates the eMPS status to the PGW through a bearer modification request.

1.393 EMS

element management system

An application that manages one or more NEs.

1.394 eNB

See [1.396 “eNodeB” \(p. 97\)](#) .

1.395 encapsulation

Encapsulation is the addition of information to the beginning and end of data. Encapsulation is used by layered network protocols as data moves from one stack down to the next. Header and trailer information is added to the data at each layer. Encapsulation is also used to bridge connections between different types of networks.

1.396 eNodeB

Evolved NodeB

The eNodeB is an enhanced BTS system for UE access to the LTE RAN network and LTE services in the 700 MHz spectrum. There are different hardware configurations available for the eNodeB, involving compact configuration (9412 eNodeB) or distributed configuration using remote radio heads (9926 DBS, also known as 9926 BBU).

NFM-P customer documentation refers to the 9926 DBS and 9412 eNodeB collectively as the eNodeB.

1.397 EOP

end-of-packet

1.398 ePC

evolved packet core

The core network in the LTE and SAE system. The ePC provides the overall control of the UE and establishment of the bearers. The main logical NEs of the ePC are the PGW, SGW, and MME.

1.399 ePDG

evolved packet data gateway

The ePDG is part of the SAE that interfaces with untrusted non-3GPP networks that require secure access, such as Wi-Fi. The ePDG secures the data transmission with UE connected to the EPC, and acts as a secure termination node for IPsec tunnels that are established with the UE.

1.400 Epipe

A type of VLL service that provides a point-to-point Ethernet service. One endpoint of an Epipe uses Ethernet encapsulation, and the other endpoint uses Ethernet, ATM, or frame relay encapsulation. Also known as an Ethernet VLL service.

1.401 EPS

EPS is expanded two ways:

1. equipment protection switching
2. evolved packet system

The LTE and SAE together, comprising both an evolved core network and an evolved radio access network.

1.402 EPT

Engineering and Planning Tool

1.403 E-RAB

E-UTRAN radio access bearer

The concatenation of an S1 bearer and the corresponding radio bearer. See 3GPP TS23.401.

1.404 ERO

Explicit Router Object

1.405 ERP

Ethernet ring protection

Ethernet Ring Protection (ERP) as specified in ITU-T G.8032, is a protection mechanism for Ethernet ring topologies that provides a resilient Ethernet network. ERP provides sub-50ms protection and recovery switching for Ethernet traffic in a ring topology, and, at the same time, ensures that loops are not formed at the Ethernet layer.

1.406 ERPS

Ethernet ring protection switching

1.407 ES

Ethernet Segment

1.408 ESI

Ethernet segment identifier

1.409 ESM

See [1.1116 "RSM" \(p. 194\)](#) .

1.410 ESNCP

Electrical sub-block network connection protection

1.411 ESP

encapsulating security payload

A member of the IPsec protocol suite. ESP is a transport-layer protocol that provides data confidentiality, origin authentication, integrity checking, and replay protection. The communicating systems use a shared key to encrypt and decipher data. ESP is similar to [1.83 "AH" \(p. 57\)](#) , but provides IP header protection only in tunnel mode.

1.412 ESS

extended service switch

A network switch, for example, the 7450 ESS, that supports the creation of Ethernet services such as VPLS and VLL.

1.413 ETH-BN

Ethernet bandwidth notification

ETH-BN enables the detection and extraction of ETH-BN messages to the CSM. If the ETH-BN indicates a new throughput value, the CSM programs the new value into the egress-rate of the port.

1.414 ETH-ED

Ethernet-expected defect

The ITU-T Y.1731 standard defines the method by which CCM-enabled MEPs can communicate during expected periods of interruption to peers including the specific ETH-ED sub-code options.

1.415 ETH-LBM

Ethernet-loopback message

1.416 ETH-LMM

Ethernet-loss measurement message

The ITU-T Y.1731 standard defines the method by which Ethernet frame loss measurement statistics are collected to determine the unidirectional frame loss between point-to-point ETH-CFM MEP peers.

1.417 EtherType

A field in the Ethernet frame header that is used to indicate the version of Ethernet protocol.

1.418 ETR

extended temperature range

1.419 ETree

Ethernet tree

An ETree is a VPN service in which each AC is designated either a root or a leaf. Roots can communicate with leaves or other roots; leaves can only communicate with roots.

1.420 eUTRAN

evolved Universal Terrestrial Radio Access Network

The eUTRAN consists of eNodeBs that provide the user-plane and control-plane protocol terminations towards the UE. The eNodeBs can be interconnected with each other using the X2 interface. The eNodeBs are connected to the EPS through the S1 interface.

1.421 eVOA

electrical variable optical attenuator

1.422 EVPL

Ethernet virtual private line

An EVPL is a data service, defined by the Metro Ethernet Forum that provides a point-to-point Ethernet connection between UNIs.

1.423 EVPN

Ethernet virtual private network

EVPN is an Ethernet Layer 2 VPN bridging solution that enables you to connect a group of dispersed customer sites that uses BGP as the control-plane for MAC address signaling over the core.

1.424 EXP

experimental field

A field in an IP packet header that is reserved for experimental use.

F

1.425 FA

foreign agent

A router on the visited network of an MNN which provides routing services to the MNN while registered. The FA detunnels and delivers datagrams to the MNN that were tunneled by the HA of the MNN.

1.426 failover

Failover is the process of changing the roles of a redundant system, for example, when the standby database takes over the role of a failed active database.

1.427 fallback

Fallback is the process of reversing configuration deployments using the activation manager.

1.428 Fast Ethernet

A LAN transmission standard that provides a data rate of 100 Mb/s.

1.429 fault

A fault is a failure or defect in a network, causing the network, or part of the network, to malfunction.

1.430 FC

FC can be expanded the following ways:

- flow control
Flow control is the procedure that shuts down transmission when a receiving station is unable to store the data it is receiving.
- forwarding class
See [1.450 “forwarding class” \(p. 106\)](#) .

1.431 FCAPS

FCAPS is the acronym for a broad categorization of network and service management activities that includes:

- fault management
- configuration management
- accounting/administration management
- performance management
- security management

1.432 FCC

fast channel change

FCC is an HDTV function that provides bursts of cached unicast traffic via separate video servers to provide channel changes in under a second.

1.433 FD

frequency diversity

Two ODUs simultaneously transmit packets on different frequencies. On the receive side, two ODUs receive the packets on two frequencies but only the best signal, as determined by factors such as BER and loss of signal, is processed by the 9500 MPR.

1.434 FDB

FDB is expanded two ways:

1. filtering database
2. forwarding database

1.435 FDL

facilities data link

Used in ESF to support the communication of network information in the form of in-service monitoring and diagnostics.

1.436 FDN

fully distinguished name

1.437 FEC

forwarding equivalency class

A group of IP packets that are forwarded in the same manner, for example, over the same path, with the same forwarding treatment.

1.438 FEP

front end processor

1.439 FF

Flex framer

1.440 FFD

fast fault detection

1.441 FIB

forwarding information base

FIB is the set of information that represents the best forwarding information for a destination. A device derives FIB entries from the reachability information held in the RIB, which is subject to administrative routing.

1.442 FIC

frame ID code

A field in a channel frame that identifies the position of the frame in the frame sequence.

1.443 FIPS

Federal Information Processing Standards

A cryptographic certification standard that defines the requirements for products to become FIPS-140-2 certified.

1.444 FIR

Fair Information Rate

FIR allows the QoS scheduling priority to be modified independently from the marking/drop precedence of the packets being scheduled from a queue.

1.445 flash memory

A rewritable memory chip that retains its content without power.

1.446 flow description

A flow description defines the filters for service data flow, such as the source and destination IP address, port numbers, and the protocol.

1.447 flowspec

The use of BGP to distribute traffic flow specifications (flow routes) throughout a network. A flow route carries the description of a flow, such as source IP address, destination IP address or TCP/UDP port number, and a set of actions to take on packets that match the flow.

1.448 FM

fault management

1.449 FOADM

Fixed optical add/drop multiplexer/multiplexing

1.450 forwarding class

A forwarding class, also called a CoS, provides to NEs a method to weigh the relative importance of one packet over another in a different forwarding class. Each forwarding class is important only in relation to other forwarding classes.

Queues are created for a specific forwarding class to determine the manner in which the queue output is scheduled into the switch fabric and the type of parameters the queue accepts. The forwarding class of the packet, along with the in-profile or out-of-profile state, determines how the packet is queued and handled (the per-hop behavior at each hop along its path to a destination egress point).

1.451 FP

Forwarding Plane

In routing, a forwarding plane, sometimes called the data plane or user plane, defines the part of the router architecture that determines where packets are forwarded to when arriving on an inbound interface. Nokia uses this term with a numeric identifier to distinguish its family of network processors, for example FP3 and FP4 network processors.

1.452 FP4

A high-capacity chipset used in selected models and releases of Nokia network equipment.

1.453 FPE

Forward Path Extension

FPE refers to the functionality where traffic is passed internally from egress to ingress for the purpose of traffic pre-processing.

1.454 FPGA

field programmable gate array

A high density programmable hardware device capable of supporting different applications

1.455 Fpipe

A type of VLL service that provides a point-to-point frame relay service between users over an IP/MPLS network. Both endpoints of an Fpipe use frame relay encapsulation. An Fpipe connects users through frame relay PVCs. An Fpipe is also known as a frame relay VLL service.

1.456 FQDN

fully qualified domain name

1.457 FR

frame relay

A standard for high-speed data communication that offers transmission speeds of at least 2.048 Mb/s. The main application of FR is LAN interconnection.

1.458 FRF.5

Frame Relay/ATM PVC Network Interworking Implementation Agreement

A standard that provides network interworking function, allowing frame relay users to communicate over an intermediate ATM network.

1.459 FRR

fast reroute

1.460 FRU

Field replaceable unit

An FRU is a component that you can replace on-site with minimal or no service interruption. A fan unit is an example of an FRU.

1.461 FT

fault tolerance or fault-tolerant

Fault tolerance enables a system to continue operating properly in the event of the failure of some of its components. When the operating quality decreases at all, the decrease is proportional to the severity of the failure.

TCP fault tolerance allows reliable two-way network communication using links that may be imperfect or overloaded. It does this by requiring the communication endpoints to expect packet loss, duplication, reordering and corruption, so that these conditions do not affect data integrity.

1.462 FTP

File Transfer Protocol

FTP is the Internet standard client-server protocol for transferring files from one computer to another. FTP generally runs over TCP or UDP.

1.463 FUA

fixed uplink allocation

1.464 FUI

final unit indication

The FUI indicates that the given quota is the final quota from the server.

1.465 fVOA

fast variable optical attenuator

1.466 FWA

Fixed Wireless Access

1.467 FXO

Foreign Exchange Office

1.468 FXS

Foreign Exchange Subscriber

G

1.469 Ga

The interface between the:

- [1.992 “PGW” \(p. 178\)](#) and the [1.900 “OFCS” \(p. 166\)](#)
- [1.1191 “SGW” \(p. 205\)](#) and the [1.900 “OFCS” \(p. 166\)](#)

1.470 GARP

Generic Attribute Registration Protocol (formerly Group Address Registration Protocol)

A LAN protocol that defines procedures by which end stations and switches can register and de-register attributes (such as network identifiers or addresses) with each other. By this means, every NE has a record or list of all the other NEs that can be reached at any given time.

1.471 GBE

Gigabit Ethernet

A transmission technology based on the Ethernet frame format and protocol used in local area networks (LANs) that provides a data rate of one billion bits (one Gigabit) per second. Gigabit Ethernet is defined in the IEEE 802.3 standard and is currently used as the backbone in many enterprise networks.

1.472 GBR

guaranteed bit rate

The GBR indicates the guaranteed number of bits delivered to the network within a period of time.

1.473 generic NE

generic network element

An NE, typically a non-Nokia device, for which the NFM-P provides limited management support using SNMP.

1.474 GERAN

GSM Edge Radio Access network

Supports enhanced data rates for global evolution (EDGE), and provides both the radio coverage and intelligent network services. It consists of the Base Transceiver Station (BTS), the Base Station Controller (BSC), the Transcoding and Rate Adaptation Unit (TRAU), a key component in handling and routing information, and the Operation and Maintenance Center (OMC-B).

1.475 GGSN

gateway GPRS support node

GGSN provides network access to external hosts that need to communicate with mobile subscribers. GGSN is the gateway between the GPRS wireless data network and other external PDNs such as radio networks, IP networks, or private networks.

1.476 GIF

graphics interchange format

GIF is a graphics file format that supports up to 256 colors.

1.477 Gig

gigabit

Approximately 1 000 000 000 bits. The exact number is 2^{30} , or 1 073 741 824 bits. The term is used to mean either value.

1.478 Gig Ethernet

See [1.479 “Gigabit Ethernet” \(p. 109\)](#) .

1.479 Gigabit Ethernet

An Ethernet interface with a peak data rate of 1000 Mb/s.

1.480 GigE

See [1.479 “Gigabit Ethernet” \(p. 110\)](#) .

1.481 Global MEG

Global Maintenance Entity Group

A Global MEG is a virtual object that contains more than one MEG. See also [1.744 “MEG” \(p. 146\)](#) .

1.482 GMPLS

generalized multi-protocol label switching

The GMPLS protocol reroutes traffic dynamically around a failure. After a failure in the network is fixed, the connection is returned to its original route automatically, or on-demand, depending on the connection settings.

1.483 GMPLS-UNI

generalized multi-protocol label switching-user network interface

GMPLS-UNI permits dynamic provisioning of optical transport connections between IP routers and optical network elements in order to reduce the operational time and administrative overhead required to provision new connectivity. See also [1.777 “MPLS” \(p. 150\)](#) .

1.484 Gn

Gn is:

- the interface between the [1.992 “PGW” \(p. 178\)](#) and the [1.1190 “SGSN” \(p. 205\)](#)
- the interface between [1.504 “GSN” \(p. 113\)](#) s within a [1.1008 “PLMN” \(p. 180\)](#)

1.485 GNE

See [1.473 “generic NE” \(p. 109\)](#) .

1.486 GNI

Gigabit Ethernet Network Interface

1.487 GNSS

global navigation satellite system

A satellite navigation system is a system of satellites that provides autonomous geo-spatial positioning with global coverage. It allows small electronic receivers to determine their location (longitude, latitude, and altitude) to high precision, using time signals transmitted along a line of sight by radio from satellites. The signals also allow the electronic receivers to calculate the current local time to high precision, which allows time synchronization. A satellite navigation system with global coverage may be termed a global navigation satellite system or GNSS.

1.488 golden configuration

A golden configuration is an NE that is configured to be a standard against which other NE configurations can be compared.

1.489 Gp

Gp is:

- the interface between the [1.992 “PGW” \(p. 178\)](#) and the [1.1190 “SGSN” \(p. 205\)](#)
- the interface between [1.504 “GSN” \(p. 113\)](#) s in different [1.1008 “PLMN” \(p. 180\)](#) s

1.490 GPE

Generic Protocol Extension

1.491 GPON module

gigabit passive optical network module

A module card that can be configured on the 7705 SAR-M/ME. The GPON module is a 1-port optical network terminal which serves as an Ethernet connection point for transmitting data over a GPON network.

1.492 GPRS

General Packet Radio Service

A mobile data service extension to the GSM system. It is often described as “2.5G”. See 3GPP TS43.064 and TS23.060.*

1.493 GPS

global positioning system

1.494 GPV

get parameter values

Type of TR-069 RPC method.

1.495 GQP

Generic QoS Profile

1.496 GR

graceful restart

Many Internet routers implement a separation of control and forwarding functions. These routers can continue to forward data while the control software is restarted or reloaded. This function is called graceful restart. A successful graceful restart requires the use of a GR helper.

1.497 GR/DR

Geo-Redundancy/Disaster Recovery

1.498 GR helper

graceful restart helper

A GR helper is a neighboring router that is configured to cooperate during a graceful restart. The GR helper monitors the network topology for any changes and, if there are none, advertises that the router performing the graceful restart is still active.

1.499 Gr interface

generic requirement interface

The Gr interface is a General Packet Radio Service which is located between the Serving General Packet Radio Service Support Node and the Home Location Register.

1.500 GRE

generic routing encapsulation

A protocol for the encapsulation of an arbitrary network-layer protocol over another arbitrary network-layer protocol.

1.501 GRT

global route table

1.502 GSM

Global System for Mobile communications; a type of 2G network.

1.503 GSMP

General Switch Management Protocol

GSMP is an ATM and TCP/IP protocol designed to control a label switch. This protocol allows a controller to establish and release connections across the switch. For example, adding and deleting leaves on a multicast connection, managing switch ports, and requesting configuration information and statistics.

ANCP is an extension of GSMP.

1.504 GSN

GPRS support node

A GSN is an NE that supports the use of GPRS in a GSM core network.

1.505 GSU

Granted-Service-Unit

1.506 GTP

GPRS tunneling protocol

GTP is the protocol between GSNs in the UMTS/GPRS backbone network. GTP is the standard that specifies interfaces for the GPRS within the 3GPP system:

- the Gn and Gp interfaces of the GPRS
- the Iu, Gn, and Gp interfaces of the UMTS system.

1.507 GTP-C

GTP-control plane

This protocol tunnels signaling messages between the [1.1190 “SGSN” \(p. 205\)](#) and [1.764 “MME” \(p. 148\)](#) over the S3 interface, between the [1.1190 “SGSN” \(p. 205\)](#) and [1.1191 “SGW” \(p. 205\)](#) over the S4 interface, between the [1.1191 “SGW” \(p. 205\)](#) and [1.992 “PGW” \(p. 178\)](#) over the S5/S8 interface, and between [1.764 “MME” \(p. 148\)](#) s over the S10 interface. See 3GPP TS 23.401 Section 5.1.1.*

1.508 GTP-U

GTP-user plane

This protocol tunnels user data between the eNodeB and the [1.1191 “SGW” \(p. 205\)](#) , as well as between the [1.1191 “SGW” \(p. 205\)](#) and the [1.992 “PGW” \(p. 178\)](#) in the backbone network. GTP encapsulates all end-user IP packets. See 3GPP TS23.401 Section 5.1.2.1.*

1.509 GUI

graphical user interface

A GUI is a computer user interface that incorporates graphics to make software easier to use.

1.510 GVRP

GARP VLAN registration protocol

GVRP is a standards-based Layer 2 network protocol for automatic configuration of VLAN information on switches.

1.511 Gx

The Diameter reference point between the [1.976 “PCRF” \(p. 176\)](#) and the [1.967 “PCEF” \(p. 175\)](#) on the [1.992 “PGW” \(p. 178\)](#) that transfers policy and charging rules from the [1.976 “PCRF” \(p. 176\)](#) to [1.967 “PCEF” \(p. 175\)](#) .

1.512 Gy

The reference point between the [1.992 “PGW” \(p. 178\)](#) and the [1.893 “OCS” \(p. 165\)](#) .

H

1.513 H-VPLS

hierarchical virtual private LAN service

1.514 HA

HA is expanded two ways:

1. high-availability
2. home agent

A router on the home network of an MNN, which tunnels datagrams for delivery to the MNN when it is away from home, and maintains current location (IP address) information for the MNN.

1.515 HAG

hybrid access gateway

The gateway for the network mechanisms for hybrid access services. In a hybrid access network, the CPE requires a second WAN interface with 3GPP-based access connectivity, as well as MSBN access. Hybrid access adds a second, wireless LTE access connection to a wired home gateway. Different access technologies, such as LTE and DSL, are aggregated to give subscribers a higher bandwidth.

The HAG gateway functionality is implemented in AA when the CMG diverts TCP traffic to AA, which is accomplished using policy rules. The implementation requires a dual IP CPE. Both of the subscriber IP addresses are part of the subscriber context available in the 7750 SR MG. This allows the 7750 SR MG to treat both accesses as part of the same subscriber session. The subscriber context can be created with static configuration or can be requested from a RADIUS server or PCRF.

1.516 HCM

high capacity multiplexing

HCM is a rate adaption and sub-rate multiplexing scheme that provides a bandwidth granularity of 800bit/s throughout a network. HCM multiplexes multiple V.24 lines into a single G.703 time slot.

1.517 HDD

hard disk drive

1.518 HDLC

high-level data link control

HDLC is a bit-oriented synchronous data link layer protocol. It specifies a data encapsulation mode on synchronous serial links using frame characters and checksums.

1.519 heartbeat

Keep-alive messages that are exchanged between the UE and the application server in the Internet cloud. The message exchange maintains an active application session and prevents the expiration of NAT mapping, which causes IP session disconnection.

1.520 HIP

horizontal integration protocol

A mechanism for connecting external systems to the NFM-P. HIP supports network discovery, alarm forwarding, and alarm management.

1.521 HI component

horizontal integration component

1.522 HLI

high loss interval

1.523 HMAC

key-hash message authentication code

HMAC is a type of message authentication code that is calculated using MD5 and a secret key. It simultaneously verifies the data integrity and the authenticity of a message. The resulting algorithm is termed HMAC-MD5 or HMAC-SHA-1.

1.524 HO

handover

1.525 HO-ODUk

The higher-order ODU (HO-ODU) transparently carries several multiplexed lower-order ODUs.

1.526 Hop

The number of hops in a path indicates the number of full or fractional links a path traverses to get from source to destination. Each link is one hop.

1.527 host

A host is a device that has at least one static or dynamic IP address. The term typically applies to an end-user device, such as a PC, VoIP phone, or set-top box, rather than an NE in a transport network.

1.528 HPCFAP

high power connection fuse and alarm panel

1.529 Hpipe

A type of VLL service that provides point-to-point HDLC service over an MPLS network.

1.530 HQoS

hierarchical quality of service

HQoS provides the ability to perform rate limiting across multiple queues from multiple SAPs.

1.531 HSB

hot standby

One ODU transmits or receives packets on a single frequency. A second ODU is in standby mode and takes over if the other ODU fails.

1.532 HSDPA

high speed data-link packet access

1.533 HSGW

HRPD service gateway

The HRPD service gateway is in HRPD network, and provides interworking between the HRPD and ePC networks. The HSGW connects to the PGW by the S2a reference point.

1.534 HSI

high-speed Internet access

HSI is a broadband Internet access service that is typically part of a triple play service.

1.535 HSM

hardware security module

An HSM is a certified system for MACsec key generation.

1.536 HSMDA

high scale Ethernet MDA

The HSMDA is an MDA for the 7450 ESS and 7750 SR. The HSMDA extends subscriber and service density capabilities of first and second generation IOMs by adding an MDA level of ingress and egress queues, shapers, and schedulers.

1.537 HSPA

high-speed packet access

1.538 HSS

home subscriber server

The HSS is a user database that supports the IMS network entities that handle calls. It contains subscriber profiles, performs authentication and authorization of the user, and can provide information about the subscriber's location and IP information.

1.539 HSU

high capacity subscriber unit

1.540 HTML

hypertext markup language

Language for writing hypertext documents, often for use in a web environment.

1.541 HTTP

Hypertext Transfer Protocol

A set of rules for exchanging text, graphics, sound, video, and other multimedia files on the Web.

1.542 HTTP POST

In HTML, you can specify a GET or POST submission method for a form. The method is specified inside a FORM element using the METHOD attribute. The difference between METHOD="GET" (default) and METHOD="POST" is primarily defined by form data encoding.

1.543 HTTPS

HTTP Secure

An extension of HTTP that provides encryption and decryption of Web page requests and responses for secure browser communication over a network. HTTPS is secured using the [1.1312 "TLS" \(p. 221\)](#) protocol, so is sometimes called HTTP over TLS.

1.544 HVPLS

hierarchical virtual private LAN service

1.545 hybrid port

See [1.255 "combo port" \(p. 80\)](#) .

I

1.546 I-component

An S-VLAN component with PIP

1.547 I-PMSI

inclusive provider multicast service interface

1.548 I-SID

I-component service instance identifier

1.549 I-TAG

service instance TAG

1.550 I-VPLS

I-component VPLS (or I-SID VPLS)

1.551 I-VSI

I-component virtual switch instance. Also referred to as an I-Site.

1.552 I/O

input/output

Connections between a system and its controlled devices (output) and incoming statuses (input).

1.553 I/O module

See [1.590 "IOM" \(p. 124\)](#) .

1.554 IB-RCC

In-band ring control connection

1.555 IBGP

Interior Border Gateway Protocol

IBGP is a type of BGP used within a single AS. IBGP is a protocol for exchanging routing information between gateways within an autonomous network. The routing information can then be used by IP or other network protocols to specify how to route packets.

1.556 ICAP

Internet Content Adaptation Protocol

ICAP is a protocol defined in the IETF RFC 3507 that provides simple object-based content processing for HTTP services. An ICAP client passes an HTTP message to an ICAP server that processes the message and sends a response to the client. A typical ICAP function is to enable parental control of Internet content viewed by children.

1.557 ICB

inter-chassis backup

1.558 ICCN

incoming call connected

1.559 ICE

in case of emergency

1.560 ICMP

Internet control message protocol

ICMP is a protocol that sends and receives the control and error messages used to manage the behavior of the TCP/IP stack. ICMP is defined in RFC 792.

1.561 ICR

inter-chassis redundancy

ICR provides a baseline requirement for providing stateful redundancy on broadband subscriber management equipment, such as routers, gateways, and remote access servers. The redundancy mitigates against network outages and protects routers against link and chassis failures.

1.562 ICRQ

incoming call request

1.563 ID

identifier or identification

1.564 IdP

identity provider

IdP is responsible for acting as the access management authority for SSO-enabled applications and their users.

1.565 IE

information element

An element of a signaling message whose contents are for a specific signaling purpose

1.566 IED

intelligent electronic device

A packet-based remote monitoring and control device used in [1.1157 “SCADA” \(p. 200\)](#) networks

1.567 IEEE

Institute of Electrical and Electronics Engineers

1.568 IES

Internet enhanced service

IES is a routed connectivity service in which a host communicates with an IP router interface to send and receive Internet traffic. An IES has one or more logical IP router interfaces, each with a SAP that acts as the access point to the network. IES allows customer-facing IP interfaces to participate in the same routing instance that is used for core network routing. The IP addressing scheme for a customer must be unique among the provider addressing schemes in the network and possibly in the entire Internet.

The usable IP address space may be limited. A portion of the service provider address is reserved for service IP provisioning and allows administration by a separate but subordinate address authority.

1.569 I-ES

Interconnect Ethernet Segment

An I-ES is a virtual ethernet segment that allows DC GWs with two BGP instances to handle VXLAN access networks.

1.570 IETF

Internet Engineering Task Force

The IETF is the organization that manages the standards and specifications for IP and related protocols.

1.571 IGH

interface group handler

IGH is a fate-sharing group that provides the ability to group multiple IP links and POS links so that if a specified number of links go out of service for any reason, the rest of the links in the IGH also go out of service and can be rerouted to an alternate path.

1.572 IGMP

Internet Group Management Protocol.

IGMP is an IP extension that hosts use to report their multicast group membership to neighboring multicast routers.

1.573 IGMP snooping

IGMP snooping enables a device that relays an IGMP packet to read the IGMP message and thus identify hosts that are members of multicast groups. The device forwards the returning multicast packets to only the hosts in the multicast group.

1.574 IGP

Interior Gateway Protocol

Generic term applied to any protocol used to propagate network reach and routing information within an AS.

1.575 IGP administrative domain

An IGP administrative domain is a collection of routers under one administrative entity that cooperates by using a common IGP (such as OSPF). Routing between IGP administrative domains is done with an inter-AS or interdomain EGP, such as BGP-4.

1.576 IKE

Internet key exchange

Protocol used to establish a security association in the IPsec protocol suite using the Diffie-Hellman Key exchange to establish a shared secret session.

IKE is an IPsec standard protocol used to ensure security for VPN negotiation and remote host or network access. Specified in IETF Request for Comments (RFC) 2409, IKE defines an automatic means of negotiation and authentication for IPsec SAs. IKE protocol ensures security for SA communication without the preconfiguration that would otherwise be required.

1.577 ILA

in-line amplifier

1.578 ILM

incoming label map

1.579 ILMI

interim local management interface

An interim standard defined by the ATM Forum that allows UNI management information to be exchanged between an end user and a public or private network, or between a public network and a private network, including setting and capturing physical layer, ATM layer, virtual path, and virtual circuit parameters on ATM interfaces. ILMI uses SNMP messages without UDP and IP, and organizes managed objects into MIBs.

1.580 IMA

inverse multiplexing over ATM

A cell-based protocol where an ATM cell stream is inverse-multiplexed and de-multiplexed in a cyclical fashion among ATM-supporting paths to form a higher bandwidth logical link, where the logical link concept is referred to as an IMA group.

1.581 IME

interface management entity

Software components that execute the ILMI protocol.

1.582 IMEI

international mobile equipment identity

A unique number that is allocated to each mobile station. It is implemented by the mobile station manufacturer. See 3GPP TS 22.016.*

1.583 IMEISV

international mobile equipment identifier and software version

A unique number that is allocated to each mobile station. It is implemented by the mobile station manufacturer. The software version number identifies the software version number of the mobile equipment.

1.584 IMM

integrated media module

A circuit board that uses the same chassis card slots as an IOM, but combines IOM 3 and high-bandwidth MDA functions in one unit. The IMM does not accept plug-in MDAs because the MDA functions are built into the IMM.

1.585 IMPM

ingress multicast path management

1.586 IMS

Internet protocol multimedia subsystem

An architectural framework for delivering Internet Protocol (IP) multimedia services via UTRAN and E-UTRAN. See 3GPP TS23.228 and TS23.406.*

1.587 IMSI

international mobile subscriber identity

A unique number associated with each mobile phone user. It is stored in the SIM inside the phone and is sent by the phone to the network. It is primarily intended for obtaining information on the use of the PLMN by subscribers. It is also used for other functions, such as to compute the Paging Occasions (PO) in LTE. See 3GPP TS22.016 and TS23.003.*

1.588 Interlaken

Interlaken is a narrow, high-speed, channelized chip-to-chip interface.

1.589 intermediate system

A device such as a router that forwards traffic between end systems.

1.590 IOM

input/output module

A circuit board that contains two independent data paths, with each path connected to an MDA. IOMs implement queuing and IP and MPLS functions. IOMs are available in several variants, such as the IOM 2 and IOM 3, that provide enhancements to the original IOM functions.

1.591 IP

Internet Protocol

IP is the network layer of the TCP/IP protocol suite. It is a connectionless, best-effort packet-switching protocol defined by the IETF.

1.592 IP precedence

A three-bit field in an IP packet header that specifies the level of service a packet is to receive in a network. IP precedence bits are the least significant bits of the DSCP field.

1.593 IP-CAN

IP connectivity access network

The IP-CAN defines the network that connects an IMS subscriber to IMS services. Typically, the IP-CAN is a GPRS that is supported by GERAN or UTRAN functions.

1.594 IPCC

Internet Protocol Communication Channel

1.595 IPCP

IP control protocol

IPCP assigns DNS and NBNS addresses to the UE.

1.596 IPDR

Internet Protocol Detail Record

An IPDR is a type of data record that contains information about IP service usage and traffic flows. The information in a record is typically used by an OSS for purposes such as billing and traffic analysis.

1.597 IPFIX

Internet Protocol Flow Information eXport

IPFIX is an IETF standard that defines how IP flow data are to be formatted and transferred from a flow exporter, such as a managed NE, to a collector, such as an [1.851 “NSP Flow Collector”](#) (p. 160).

1.598 Ipipe

A type of VLL service that provides point-to-point IP connectivity and allows service interworking between different Layer 2 technologies. One endpoint of an Ipipe uses Ethernet encapsulation and the other endpoint uses Ethernet, ATM, frame relay, cHDLc, or PPP encapsulation. An Ipipe is also called an IP interworking VLL service.

1.599 IPsec

Internet protocol security

A structure of open standards to ensure private and secure communication over IP networks using cryptographic security services.

1.600 IPTV

Internet-based television transmission

1.601 IPv4

Internet Protocol version 4

The version of IP in use since the 1970s. IPv4 addresses are 32 bits. IPv4 headers vary in length and are at least 20 bytes.

1.602 IPv6

Internet Protocol version 6

The version of IP that succeeds IPv4. IPv6 addresses are 128 bits. IPv6 headers are 40 bytes.

1.603 IRAT

inter-radio access technology

IRAT refers to functions, particularly [1.1222 “SON” \(p. 209\)](#) functions, that interface between radio technologies such as [1.703 “LTE” \(p. 140\)](#) and [1.1371 “UTRAN” \(p. 229\)](#) .

1.604 IRI

intercept related information

Data about the targeted communication event, including the destination of a voice call, the source of a call, and the time of the call.

1.605 IRICC

intercept related information and content of communication

Data about the call and the data containing the call content.

1.606 IS

See [1.589 “intermediate system” \(p. 124\)](#) .

1.607 ISID

Service Identifier

1.608 IS-IS

intermediate system to intermediate system

IS-IS is an ISO standard link-state routing protocol. Integrated IS-IS allows IS-IS to be used for route determination in IP networks.

1.609 ISA

integrated services adapter

An ISA is an MDA for the 7450 ESS and 7750 SR. As a resource adapter, there are no external interface ports on the ISA. Any IOMs on a system in which the ISA is installed are used to switch traffic internally to the ISA.

1.610 ISA-AA

integrated services adapter - application assurance

ISA-AA is an application assurance function that is configured for 7450 ESS and 7750 SR ISAs. See [1.60 “AA” \(p. 54\)](#) and [1.609 “ISA” \(p. 126\)](#) .

1.611 ISA-IPsec

integrated services adapter - IP security

ISA-IPsec is a IP security function that is configured in the for 7450 ESS and 7750 SR ISAs. On an NE, the ISA-IPsec acts as a concentrator to gather and terminate encrypted IPsec tunnels on an IES or VPRN service. This allows a network provider to offer a secure global service when the hosts are in an uncontrolled or unsecure part of a network.

1.612 ISA-L2TP/LNS

integrated services adapter - L2TP network server

ISA-LNS is a L2TP network server function that is configured on the 7450 ESS and 7750 SR. Any IOMs on a system in which the ISA-LNS is installed are used to switch traffic internally to the ISA-LNS.

1.613 ISA-NAT

integrated services adapter - network address translation

ISA-NAT is a NAT function that is configured on 7450 ESS and 7750 SR ISAs. See [1.830 "NAT" \(p. 157\)](#) and [1.609 "ISA" \(p. 126\)](#) .

1.614 ISA-TMS

integrated services adapter - threat management system

The ISA-TMS is a 7750 SR MDA.

1.615 ISA-WLAN

integrated services adapter - wireless local area network

The ISA-WLAN is a WLAN function that is configured for 7450 ESS and 7750 SR ISAs. See [1.1435 "WLAN GW" \(p. 240\)](#) and [1.609 "ISA" \(p. 126\)](#) .

1.616 ISC

integrated services card

1.617 ISL

inter-switch link

1.618 ISO

International Standards Organization

1.619 ISSU

in-service software upgrade

1.620 IST instance

internal spanning tree instance

The IST instance determines and maintains the CST topology between MSTP switches that belong to the same MSTP region. The IST is a CST that only applies to MSTP region switches while, at the same time, the IST represents the region as a single spanning tree bridge to the network CST.

1.621 IT

information technology

1.622 ITL

Interleaver

1.623 ITU

See [1.624 "ITU-T" \(p. 127\)](#) .

1.624 ITU-T

International Telecommunication Union - Telecommunication Standardization Sector

1.625 IWF

interworking function

IWF provides seamless packet transmission between two protocol stacks. For example, IWF can connect an ATM endpoint with a frame relay endpoint using mappings between the two protocol stacks.

J

1.626 J0 byte

The J0 byte refers to the numeric value for a SONET section trace to verify the physical connectivity of data links. The J0 byte traces the origin of an STS frame as it travels across a SONET network. The value for the J0 byte parameter is inserted continuously at the source and is checked against the value expected by the receiver. After the data links have been verified, they can be grouped to form a single traffic engineering link.

1.627 JAAS

Java authentication and authorization service

A set of packages that enable services to authenticate and enforce access controls on users.

1.628 Java

An object-oriented programming language that creates portable code to support interaction among different objects.

1.629 Java EE

Java Enterprise Edition

A set of services, APIs, and protocols that provide the functions to develop multi-tiered, web-based application components. Java EE is overseen by a partnership of enterprise software and computer vendors, and is available for a range of platforms.

1.630 JDBC

Java Database Connectivity

An application-programming interface that has the same characteristics as Open Database Connectivity, but is specifically designed for use by Java database applications.

1.631 JMS

Java Message Service

JMS is an API that combines Java technology with enterprise messaging. The JMS API defines a common set of interfaces for creating applications using reliable asynchronous communication among components in a distributed computing environment. The applications are portable to different enterprise systems.

1.632 JNLP

Java Network Launching Protocol

JNLP enables an application to be launched on a client desktop by using resources that are hosted on a remote web server. Java Plug-in software and Java Web Start software are considered JNLP

clients because they can launch remotely hosted applets and applications on a client desktop.

1.633 JRMP

Java Remote Method Protocol

A proprietary wire-level protocol that transports Java RMI.

1.634 JSON

JavaScript Object Notation

1.635 JVM

Java virtual machine

A software abstraction layer that enables Java software to run on any processor architecture.

K

1.636 KCI

key capacity indicator

1.637 keystore

A Java security framework class that represents an in-memory collection of keys and trusted certificates.

1.638 KPI

key performance indicator

A statistic counter used to monitor network performance.

1.639 KVM

kernel-based virtual machine

L**1.640 L**

line port

1.641 L-LSP

label only inferred LSP

1.642 L0

Optical layer 0

The optical layer 0 comprises of the OCH, OTU, or ODU trails between WDM or photonic network elements.

1.643 L1

L1 can refer to two terms:

- Optical layer 1
The optical layer 1 comprises of the optical cross connection system between OCS or switching network elements.
- Layer 1
The physical layer of the OSI model that includes network hardware and physical cabling required to transmit raw bits and perform requests from the data link layer.

1.644 L2

Layer 2

The data link or MAC layer of the OSI model. In networking, it is a communications protocol that contains the physical address of a client or server station that is inspected by a bridge or switch.

1.645 L2PT

Layer 2 protocol tunneling

L2PT allows L2 PDUs to tunnel through a network.

1.646 L2TP

Layer 2 Tunneling Protocol

L2TP is a session-layer protocol that extends the PPP model by allowing L2 and PPP endpoints to reside on different devices that are interconnected by a PSN. L2TP extends the PPP sessions between the CPE and PPP/L2TP termination point (LNS), via an intermediate L2TP access concentrator. See also [1.687 “LNS” \(p. 138\)](#) and [1.648 “LAC” \(p. 133\)](#).

1.647 L3

Layer 3

The network layer of the OSI model. In networking, it is a communications protocol that contains the logical address of a client or server station that is inspected by a router, which forwards the address through the network. L3 contains a type field so that traffic can be prioritized and forwarded based on the message type as well as the network destination.

1.648 LAC

LAC can be expanded in the following ways:

- L2TP access concentrator

The LAC is the initiator of an L2TP tunnel. See also [1.687 “LNS” \(p. 138\)](#) and [1.646 “L2TP” \(p. 132\)](#).

- local access control
- location area code

1.649 LACP

Link Aggregation Control Protocol

LACP is used to detect whether all local members of a LAG are physically connected to the remote ports that are part of the far end of the LAG.

1.650 LACPDU

link aggregation control protocol data unit

1.651 LAG

link aggregation group

A LAG increases the bandwidth available between two NEs by grouping up to eight ports into one logical link. The aggregation of multiple physical links allows for load sharing and offers seamless redundancy. If one of the links fails, traffic is redistributed over the remaining links. Up to eight links can be supported in a single LAG, and up to 64 LAGs can be configured on a device.

1.652 LAI

location area identity

The LAI consists of the PLMN and LAC.

1.653 LAIS

line alarm indication signal

A SONET signal that indicates a general line fault.

1.654 LAN

local area network

A LAN is a group of computers or associated devices that share a common communications line and typically share the resources of a single processor or server within a small geographic area, for example, within an office building.

1.655 Layer 2

See [1.643 “L1” \(p. 132\)](#) .

1.656 Layer 3

See [1.647 “L3” \(p. 133\)](#) .

1.657 LBM

loopback message

A loopback message is generated by a [1.747 “MEP” \(p. 146\)](#) to a peer [1.747 “MEP” \(p. 146\)](#) or an intervening [1.756 “MIP” \(p. 147\)](#) .

1.658 LBR

loopback reply

1.659 LB-VM

load balancer VM

1.660 LCN

Lifecycle change notification

1.661 LCP

Link Control Protocol

LCP establishes, configures and tests data-link Internet connections before establishing communications over a point to point link.

1.662 LD

Line driver

1.663 LDAP

Lightweight Directory Access Protocol

LDAP is a networking protocol for querying and modifying directory services that run over TCP/IP.

1.664 LDP

Label Distribution Protocol

LDP is a signaling protocol used for MPLS path setup and teardown. An LDP is used by LSRs to indicate to other LSRs of the meaning of labels used to forward traffic. LDP is defined in RFC 3036. See also [1.324 "DoD" \(p. 89\)](#) and [1.351 "DU" \(p. 92\)](#).

1.665 lease

For DHCP, the amount of time that a specific IP address is valid for a computer.

1.666 LED

light-emitting diode

1.667 LER

label edge router

An LER is a router at the edge of a service-provider network that forwards IP packets using LSPs.

1.668 level

In the IS-IS link-state protocol, level indicates the type of adjacency that can be formed between routers. Routers are assigned a capability for level 1, level 2, or both level 1 and 2. Level 1 routers can form adjacencies with other level 1-capable routers, and forward traffic within an area. Level 2 routers can form adjacencies with level 2-capable routers, and forward traffic between areas. Traffic that moves from one area to another is forwarded through routers that have both level 1 and 2 capability.

1.669 level 1 and level 2 intermediate system

These systems deliver and receive NPDUs from other systems, and relay NPDUs from other source systems to other destination systems. Level 1 systems route directly to systems within their own area, and route towards a level 2 system. A level 2 systems route towards another destination area or another routing area. Level 2 systems constitute the ISIS backbone area.

1.670 LFA

Loop-free alternate

A method of IP re-routing that finds a backup routing path by calculating a loop-free alternate backup path for each hop. The backup paths are included in the routing base in case of a failed link.

Topology independent LFA (TI-LFA) uses segment routing to determine a backup path that is independent of the network topology.

1.671 LFI

link fragmentation and interleaving

LFI interleaves high priority traffic within a stream of fragmented lower priority traffic. LFI helps avoid excessive delays to high priority, delay-sensitive traffic over a low-speed link.

1.672 LH

Long haul

1.673 LI

lawful intercept

A method to monitor target subscriber voice and data communications over an IP network by authorized agencies.

1.674 LIC

location ID code

A field in a SONET frame that identifies the location of an MDL.

1.675 lightRadio Wi-Fi

lightRadio Wi-Fi is a solution that allows the offloading of traffic or data to a wireless network using RADIUS authentication, GRE tunnels, and WLAN GWs.

1.676 Linux

A UNIX-like OS developed using the open-source software development and distribution model. Linux has an independently developed kernel, so is not a UNIX variant. [1.1089 “RHEL” \(p. 191\)](#) is a commercial Linux version.

1.677 LKDI

license key delivery infrastructure

An Nokia web service that you can use to create and download LTE RAN license files for import into the NFM-P

1.678 LLC

logical link control

LLC is the upper sublayer of the ISO model data link layer. LLC governs packet transmission as specified by IEEE 802.2.

1.679 LLD

link layer discovery

1.680 LLDP

Link Layer Discovery Protocol

LLDP, defined by IEEE 802.1AB, is a standard that provides a solution for the configuration issues caused by expanding LANs. LLDP defines a standard information advertising and discovery method for Ethernet devices. The protocol runs in the datalink layer only, which allows NEs running different network-layer protocols to learn about each other.

1.681 LLDPDU

Link Layer Discovery Protocol data unit

See also [1.680 “LLDP” \(p. 137\)](#) .

1.682 LLID

Logical Link Identifier

A means for a service provider to track a subscriber, based on a virtual port (the LLID).

1.683 LM

loss measurement

Ethernet loss measurement is used to count the number of service frames which are not successfully delivered to the specified destinations.

1.684 LMI

local management interface

LMI is a signaling standard that is used between routers and FR switches. LMI communication takes place between a router and the first FR switch in the signaling path and involves the exchange of keep-alive, addressing, and virtual circuit status information.

1.685 LMP

link management protocol

LMP is used to establish and maintain an [1.594 “IPCC” \(p. 124\)](#) between adjacent peers.

1.686 LMT

local maintenance terminal

1.687 LNS

L2TP network server

The LNS is the server, which waits for L2TP tunnels. See also [1.648 “LAC” \(p. 133\)](#) and [1.646 “L2TP” \(p. 132\)](#).

1.688 load balancing

Load balancing is the distribution of network traffic among the ports by a device so that no single port is overwhelmed, and network bandwidth is optimized.

1.689 LOC

loss of clock

A field in a SONET frame that indicates the loss of the line clock signal.

1.690 LOF

loss of frame

A field in a SONET frame that indicates the loss of a line frame in the frame sequence.

1.691 LOS

LOS can be expanded in two ways:

- loss of signal
A field in a SONET frame that indicates the loss of line signaling.
- line of sight
The propagation characteristic of high-frequency radio is called line-of-sight. Any obstruction between a transmitting antenna and a receiving antenna will block a signal. The ability to visually see a transmitting antenna roughly corresponds to the ability to receive a radio signal from it.

1.692 LO-ODUK

Lower Order-Optical Data Unit-k (k=1 to 8)

1.693 LPE

logical provider edge

A set of devices in a provider network that implement the functions of a service, such as VPLS.

1.694 LPS

learned port security

A mechanism for authorizing source learning of MAC addresses on Ethernet and Gigabit Ethernet ports.

1.695 LRDI

line remote defect indication

A field in a channel frame that indicates a remote LOF, LOC, or LOS.

1.696 LS

Link State

1.697 LSA

link state advertisement

LSA describes the local state of a device or network, including the state of the device's interfaces and adjacencies. Each LSA is flooded throughout the routing domain. The collected LSAs of all devices and networks form the protocol's topological database.

1.698 LSDB

link state database

A link state database, or topological database, contains the collection of LSAs received from all of the routers in an AS. The collected LSAs of all of the devices and networks form the protocol's LSDB. The LSDB is updated on a continuous basis as LSAs are advertised and when the network topology is updated.

1.699 LSP

label switched path

LSPs support MPLS functions and allow network operators to perform traffic engineering.

There are several types of LSPs:

- static LSP

A static LSP specifies a static path. All devices that the LSP traverses must be configured manually with labels. No signaling is required.

- signaled (dynamic) LSP

A signaled LSP is set up using a signaling protocol. The signaling protocol facilitates path selection and allows labels to be assigned from an ingress device to an egress device. Signaling is triggered by the ingress router; only the ingress router requires configuration.

- bypass-only LSP

A bypass-only LSP has manually configured bypass tunnels on PLR NEs and is used exclusively for bypass protection.

- segment routing TE LSP

A segment routing TE LSP is established with traffic engineering and protection requirements based on different parameters, such as hop limit, IGP shortcut , BGP shortcut and maximum segment routing labels.

- Point-to-Multipoint LSP

A Point-to-Multipoint LSP allows the source of multicast traffic to forward packets to one or many multicast receivers over a network without requiring a multicast protocol, such as PIM, to be configured in the network.

1.700 LSP classifier

A method of filtering IP traffic flows on to an LSP.

1.701 LSP path

An LSP associated with an MPLS path. This path could be an actual route, or a configured route. A configured route can be primary, secondary, or standby. An LSP could have at most one actual route, one primary route, and multiple standby or secondary routes.

1.702 LSR

label switched router

An LSR is an MPLS NE that runs MPLS control protocols and is capable of forwarding packets based on labels. An MPLS NE may also be capable of forwarding native Layer 3 packets.

1.703 LTE

Long Term Evolution

LTE is a standard for wireless mobile broadband networks. LTE networks can offer higher data throughput to mobile terminals than other technologies. LTE is the accepted evolution path for GSM, WCDMA, and CDMA networks. LTE is developed and maintained by the 3GPP standards body.

1.704 LTN

LSP ID to NHLFE

[1.699 "LSP" \(p. 139\)](#) ID to Next Hop Label Forwarding Entry

1.705 LTR

Link Trace Response

M

1.706 MA

maintenance association

MA is a set of MEPs, each configured with the same ID and MD level.

1.707 MAC

media access control

MAC is a sublayer of the data link layer, defined in IEEE 802.2 specifications that accesses the LAN medium. The MAC layer handles the recognition and identification of individual network devices. Every computer and network device has a MAC address that is hardware-encoded.

1.708 MAC pinning

MAC pinning is a restriction on a MAC entry in the MAC forwarding table such that it cannot be relearned on another port within the lifetime of the entry. The entry can still age.

1.709 MACsec

Media Access Control Security

MACsec provides secure communication for almost all types of traffic on Ethernet links.

1.710 MAF

MAF can be expanded in two ways:

1. management access filter

A filter that specifies the type of management access and underlying connection protocol usage for an NE, as well as the IP addresses and ports that can access the device.

2. 9471 MME application function

1.711 MAID

maintenance association ID

A MAID is a unique identifier for the MA. The MAID has two parts, the maintenance domain name and the MA name.

1.712 main server

See [1.855 “NFM-P main server”](#) (p. 161).

1.713 MAN

metropolitan area network

A telecommunications network that covers a geographic area such as a city or suburb.

1.714 mask

A filter that selectively includes or excludes certain values. For example, when you define a database field, you can assign a mask that indicates the type of value for the field. Values that do not conform to the mask cannot be entered.

1.715 MBB

make before break

1.716 MBH

microwave backhaul

Microwave backhaul refers to the transportation of traffic (voice, video and data) between distributed sites and a more centralized point of presence via a radio link

1.717 MBMS

multimedia broadcast multicast service

A [1.955 "P2MP" \(p. 174\)](#) interface specification for RAN and core network broadcast and multicast services.

1.718 MBS

maximum burst size

MBS refers to the number of cells that can be sent at PCR and still conform to the SCR.

1.719 MC

multichassis

A redundancy configuration that includes two peer NEs.

1.720 MC APS

multi chassis automatic protection switching

1.721 MC LAG

multi chassis link aggregation group

1.722 MC MLPPP

multiclass MLPPP

Fragmentation of packets of various priorities into multiple classes, allowing high-priority packets to be sent between fragments of lower priorities. See [1.763 "MLPPP" \(p. 148\)](#).

1.723 MC mobile group

A child group object of an MC peer group. When you create an MC mobile group, the NFM-P automatically creates the child group members using the peer objects in the MC peer group.

1.724 MC peer group

An NFM-P object that defines the relationship between two peer NEs to provide system redundancy in an Ethernet network. An MC peer group configuration includes a list of protocols and objects with state information that is to be synchronized between the peers.

1.725 MCC

mobile country code

A three-digit code defined in ITU-T Recommendation E212 that identifies a country or group of networks.

1.726 MCFR

Fragmentation of packets of various priorities into multiple classes, allowing high-priority packets to be sent between fragments of lower priorities. See [1.762 "MLFR" \(p. 148\)](#).

1.727 MCM

MDA carrier module

A hardware component of a 7450 ESS or 7750 SR that plugs into a card slot and accepts the installation of one or more MDAs.

1.728 MCS

MCS can be expanded in two ways:

1. multichassis synchronization
2. MC mobile interface

1.729 MCS Database

multi chassis synchronization database

A database that contains the dynamic state information created on any of the NEs by any application using its services. The individual entries in the MCS Database are always paired by

peering-relation, sync-tag and application-id. At any time, the specific entry is related to the single redundant-pair objects (such as two saps on two different NEs), and hence stored in a local MCS Database of the respective NEs.

1.730 MCT

microwave craft terminal

A type of local craft terminal. An MCT can provision or manage an NE remotely over a network connection, or directly over a local connection. A local connection allows on-site management of the NE. An MCT includes the terminal and the software required to perform NE management.

1.731 MD

maintenance domain

An MD is a network or part of a network for which faults in connectivity can be managed using the IEEE 802.1ag standard protocols. Each MD can include multiple MAs.

1.732 MD5

message digest 5

MD5 is a security algorithm that takes an input message of arbitrary length and produces as an output a 128-bit message digest of the input. MD5 is intended for digital signature applications, where a large file must be compressed securely before being encrypted.

1.733 MDA

media dependent adapter

An MDA is a pluggable interface module that distributes traffic between the network and the system IOM. Also referred to as a daughter card.

1.734 MDC

modeled device configurator

The MDC application allows for viewing the state and configuration of model-based devices, and for editing the device configuration.

1.735 MDCR

minimum desired cell rate

MDCR is equivalent to MIR.

1.736 MDDDB

multidrop data bridge

An MDDDB broadcasts a single stream from a [1.1157 “SCADA” \(p. 200\)](#) master to multiple remote devices and allows communication from individual remote devices back to the master.

1.737 MDI/MDIX

medium-dependent interface/medium-dependent interface crossed

A type of Ethernet port connection that uses twisted-pair cabling, as specified in the IEEE 802.3 standard. Network adapter cards on computers typically connect to a network using RJ-45 interface ports that use pins 1 and 2 to transmit, and pins 3 and 6 to receive. Uplink ports on hubs and switches use the same pin assignments. Normal ports on hubs and switches use the opposite pin assignment: pins 1 and 2 are used to receive, and pins 3 and 6 are used to transmit. Such ports are called MDIX ports.

1.738 MDL

message data link

A data transmission path that is used to communicate identification or test signal information at the data link layer.

1.739 MDM

model-driven mediation

A mediation framework that manages network devices using adaptors. The MDM framework supports Nokia and 3rd party devices.

1.740 MDT

multicast distribution tree

An MDT is a group of network paths in a multicast domain that originate at a common multicast source and terminate at CE devices.

1.741 ME

metro Ethernet

1.742 MED

multi-exit discriminator

An attribute that is used by an external AS to determine the preferred route into the AS that is advertising the attribute.

1.743 MEF

Metro Ethernet Forum

1.744 MEG

maintenance entity group

An MD is a network, or part of a network, that is provisioned with a set of maintenance entity groups, or MEGs, which are groups of service sites. Typically, a MEG represents one service and consists of a group of MEPs. A MEG can be associated with only one service, while one service can be associated with multiple MEGs.

1.745 MEI

mobile equipment identity

1.746 menu bar

The menu bar is a tool on the GUI that organizes tasks across broad headings. You can perform functions on the application by selecting an action from the menu bar.

1.747 MEP

maintenance entity point

In a CFM enabled network MEPs can be any SAP or SDP binding in a service and associated to a MA. A set of MEPs configured with the same MA ID defines a MA. CFM tests detect connectivity failures between any pair of local and remote MEPs in a MA.

1.748 Mesh

A type of network configuration that combines ROADMs to support mesh channel connectivity between the ROADMs without O-E-O for transmission. It is operated as a single NE with as many as four degrees (bidirectional DWDM interfaces) that comprise two lines for the east and two for the west.

1.749 MF bit

more fragments bit

A bit in an IP header that indicates the occurrence of data fragmentation and signals that at least one packet fragment follows. When a packet becomes fragmented, the MF bit in the current packet is set to 1. The MF bit is reset in the last packet of the fragmented datagram to indicate that there are no more fragments.

1.750 MG-VM

mobile gateway VM

Provides services that include 3GPP control and data plane call processing, PCEF, and application assurance, in which the PCEF is enhanced with ADC for application detection and control and L7 service classification for policy charging control. The MG-VM supports all 3GPP gateway functions, including SGW, PGW/GGSN, and SAE-GW. Supported service functions depend on the configurable personality of the MG-VM.

1.751 MHF

MIP half function

In a CFM enabled network MIP half-function objects allow MIPs to be recognized as MIPs on one MD level and MEPs on a higher level.

1.752 MI

management interface

1.753 MIB

management information base

A formal description of a set of network objects that can be managed using SNMP.

1.754 MIF

9471 WMM interface function

1.755 MIM

management information model

1.756 MIP

MIP is expanded two ways:

1. maintenance domain intermediate point

In a CFM enabled network a MIP is an intermediate point between 2 MEPs and consists of 2 MHFs.

2. mobile Internet Protocol

An IETF communications protocol that allows mobile device users to move between networks while retaining the same permanent IP address.

1.757 MIR

minimum information rate

MIR is the minimum data transfer rate for a path, such as a frame relay, VPC, or VCC path.

1.758 mirror service

A mirror service is a type of service that copies the packets from a specific customer service to a destination outside the service for troubleshooting or surveillance purposes.

1.759 MLD

Multicast Listener Discovery Protocol

MLD is an asymmetric protocol used by IPv6 routers to discover the presence of NEs that wish to receive multicast packets on their directly-attached links, and to discover which multicast addresses are of interest to those neighboring NEs.

1.760 MLDP

Multicast Label Distribution Protocol

MLDP provides extensions to [1.664 "LDP" \(p. 135\)](#) for the setup of [1.955 "P2MP" \(p. 174\)](#) [1.699 "LSP" \(p. 139\)](#)s in [1.777 "MPLS" \(p. 150\)](#) networks.

1.761 MLD snooping

Multicast listener discovery snooping is essentially the IPv6 version of IGMP snooping.

1.762 MLFR

An aggregation of multiple physical links into a single logical bundle to improve bandwidth between two peer systems. See [1.457 "FR" \(p. 107\)](#) .

1.763 MLPPP

multilink PPP

An aggregation of multiple physical links into a single logical bundle to improve bandwidth between two peer systems. See [1.1023 "PPP" \(p. 182\)](#) .

1.764 MME

mobility management entity

The control NE that processes the signaling between the UE and the core network. The MME also provides VLR functions for the EPS and supports functions related to bearer and connection management.

1.765 MMRP

Multiple MAC Registration Protocol

1.766 MMS

multimedia messaging service

A method to send multimedia content messages to and from mobile devices.

1.767 MNC

mobile network code

A two- or three-digit code defined in ITU-T Recommendation E212 that together with the MCC identifies a network.

1.768 MNN

mobile network node

A node that is located inside a mobile network.

1.769 MNO

mobile network operator

A telecommunications company that provides mobile services to subscribers. An MNO typically holds a radio spectrum license.

1.770 MO

mobile originating

1.771 MOBIKE

mobility and multihoming Internet key exchange

The MOBIKE protocol is a mobility and multihoming extension to the IKEv2.

Base IKEv2 procedures allow a UE and EPDG to establish a set of SAs between single UE and EPDG IP addresses. However, since the UE typically uses an IP address allocated by the access network (perhaps by the WiFi AP), there are mobility scenarios wherein this “outer” IP address may change. Using the base IKEv2 protocol, the UE would have to delete and re-establish a new set of SAs with the EPDG using this new source address.

MOBIKE allows one or both of the IKEv2 endpoints to change the IP address used for its side of the SA without re-establishing the SA. MOBIKE can be used for both mobility and multihoming scenarios. Multihoming means that the IKEv2 endpoint may have multiple IP addresses and be connected to multiple interfaces. The IKEv2 endpoint can use MOBIKE to switch to a different IP interface after the IKEv2 SA and IPsec SAs have been established. For example, it may choose to try a new IP interface if it notices that it cannot reach its peer using the current IP interface.

In the mobility case, the UE informs the EPDG that it has moved and would like to use a new source IP address. MOBIKE does not change the EPDG IP address.

1.772 MOC

managed object class

1.773 monitoring key

A monitoring key groups services that share a common allowed usage. A monitoring key identifies a usage monitoring control instance. Many PCC rules share the same monitoring key.

1.774 MP

Multi Point

1.775 MP-BGP

Multiprotocol Border Gateway Protocol

An enhanced BGP that carries IP multicast routes. MP-BGP carries two sets of routes: one set for unicast routing and one set for multicast routing. The routes associated with multicast routing are used by PIM to build multicast data distribution trees.

1.776 MPH

MME packet handler service

The MPH service terminates the external signaling SCTP, UDP, and TCP stacks on the 9471 WMM to offload the MIF service from this function.

1.777 MPLS

multiprotocol label switching

MPLS is a technology in which forwarding decisions are based on fixed-length labels inserted between the data link layer and network layer headers to increase forwarding performance and flexibility in path selection.

1.778 MPLS-TP

multiprotocol label switching - transport profile

MPLS-TP is a set of MPLS protocol functions that enables the use of MPLS in transport networks and applications. MPLS-TP enables MPLS to be deployed in a statically configured transport network without the need for a dynamic control plane.

1.779 MPR

microwave packet radio

1.780 MPT

microwave packet transport

An MPT is an outdoor microwave radio which forms the radio component of a Wavence SM or Wavence SA unit.

1.781 MPT-ACC

microwave packet transport-access

1.782 MPT-HC

microwave packet transport-high capacity

1.783 MPT-HL

microwave packet transport-high capacity long haul

MPT-HL provides full indoor RF transceiver packages connecting to ports on an Ethernet Access Switch (EAS) module.

1.784 MPT-HQAM

microwave packet transport-hierarchical quadrature amplitude modulation

1.785 MPT-MC

microwave packet transport-medium capacity

1.786 MPT-XP

microwave packet transport-eXtreme power

1.787 MPTCP

multipath transmission control protocol

MPTCP is a TCP connection that uses many paths to maximize resource usage and increase redundancy.

1.788 MR

mobile router

A device that has one or more subnets that connects to an IP host. The MR hides its mobility from the hosts on the HRPD network. The hosts on the subnets are fixed in relationship to the MR and move homogeneously, or as a whole. The MR connects the mobile network to the Internet.

1.789 MRP

Multiple Registration Protocol

1.790 MRRU

maximum received reconstructed unit

MRRU is the maximum frame size that can be reconstructed from multilink fragments.

1.791 MS

mobile station

An MS comprises all user equipment and software needed for communication with a mobile network. In 3G systems it is often referred to as UE.

1.792 MSBN

multi-service broadband network

1.793 MS-PW

multi-segment pseudowire

MS-PW routing allows inter-domain routed services to dynamically maintain paths using [1.1130 "S-PE" \(p. 197\)](#) and [1.1287 "T-PE" \(p. 218\)](#) NEs.

1.794 MSAP

managed service access point

See also [1.1151 "SAP" \(p. 199\)](#) .

1.795 MSB

most significant bit

1.796 MSCC

multiple services credit control

An AVP in CCA and CCR messages that is used to grant and report quota for each rating group. When the MSCC AVP is included in CCA messages, it represents quota that is granted. When it is included in CCR messages, it represents usage that is reported. If the quota or usage is reported for more than one rating group, multiple MSCC AVPs are present in the message.

1.797 MSCP

The MSCP is a communication protocol used by speech servers to provide services such as voice recognition and synthesis.

1.798 MSDP

Multicast Source Discovery Protocol

MSDP allows PIM-SM domains to communicate with each other using their own RPs. MSDP also enables multiple RPs in a single PIM-SM domain to establish MDSP mesh-groups, and can be used between anycast RPs to synchronize information about the active sources being served by each anycast RP peer.

1.799 MSE

mean squared error

1.800 MSISDN

mobile station international subscriber directory number

The telephone number of a mobile user. The MSISDN is included in the EPS bearer context. See 3GPP TS 23.003 Section 3.3.*

1.801 MSM

mobility service module

1.802 MSP

multiplex section protection

1.803 MSS

MSS can be expanded in two ways:

- Microwave Service Switch

The MSS is a multiservice aggregation switch in which TDM traffic is circuit-emulated according to MEF 8. Inverse Multiplexing over ATM (IMA) is terminated, aggregated natively, then converted into packet using PWE3 (IETF RFC 4717).

- Maximum Segment Size

The largest amount of data that a device can receive in a TCP segment.

1.804 MSTI

multiple spanning tree instance

An enhancement to the IEEE 802.1Q CST. An MSTI is a single spanning tree instance that represents a group of VLANs.

1.805 MSTP

Multiple Spanning Tree Protocol

An RSTP that allows different spanning trees to co-exist on the same Ethernet switched network.

1.806 MTC

machine-type communications

MTC specifies machine-to-machine communications and is a 3GPP standard.

1.807 MTOSI

multi-technology operations systems interface

A TMF team creating new standards for OSSs to simplify integration between different vendor systems by using a common open interface.

1.808 MTSO

Mobile Telephone Switching Office

1.809 MTU

maximum transmission unit

MTU is the largest unit of data that can be transmitted over a specific interface type in one packet. The MTU can change over a network.

1.810 multi-tier model

Logical partitioning of software products to enable distributed implementations and modular deployments. Logical partitioning can be from three layers (user interface, application server or middleware, database server) to five or more layers. One model uses the client, presentation, business, integration, and resource layers to define software components.

1.811 multicast CAC

multicast connection admission control

Multicast CAC manages the amount of bandwidth consumed by BTV distribution services to avoid network congestion and maintain QoS standards. The multicast CAC function is supported on any IGMP and PIM interface, and in the case of BTV distribution, on VPLS SAPs and SDPs where IGMP snooping is enabled.

1.812 multicast routing

Multicast routing delivers source traffic to multiple receivers without any additional burden to the source or the receivers. Multicast packets are replicated in the network by routers that are enabled with PIM, which results in the efficient delivery of data to multiple receivers.

Multicast routing is based on an arbitrary group of receivers that expresses an interest in receiving a specific data stream. The group does not have physical boundaries—the hosts can be located anywhere on the Internet. The hosts must join the group using IGMP to receive the data stream.

1.813 MVAC8B

Multiple Variable Attenuator Card Bidirectional

The bidirectional card is used to control the power level and insert WaveTracker keys on optical signals received from client equipment.

1.814 MVPLS

management virtual private LAN service

An MVPLS is created to run RSTP and manage traffic on the associated VPLS. An MVPLS is required to remove topology loops when redundant spoke SDPs or L2 access interfaces have been created for HVPLS configurations. RSTP must be run on the redundant spoke SDPs or L2 access interfaces to block some of them from passing traffic. VPLS that have redundant spoke SDPs or L2 access interfaces that are managed by the MVPLS also have their traffic blocked appropriately.

1.815 MVPN

A multicast [1.1406 “VPN” \(p. 235\)](#) is an IP VPN service that supports the transmission of IP multicast packets between sites.

1.816 MVR

multicast VLAN registration

See [1.818 “MVR VPLS” \(p. 154\)](#) .

1.817 MVR by proxy

A 7450 ESS feature that allows multicast VPLS traffic to be copied to an SAP other than the SAP from which the IGMP message originated.

1.818 MVR VPLS

Also known as a multicast VPLS, an MVR VPLS distributes multicast traffic through a network. An MVR VPLS also acts as a user VPLS when it contains SAPs that receive multicast traffic.

MVR on VPLS allows multiple subscriber hosts to remain in separate VLANs while sharing a single multicast VPLS. The 7450 ESS uses MVR on VPLS and IGMP snooping to provide BTV services.

1.819 MVRF

The multiple virtual routing and forwarding feature provides the ability to configure separate virtual routing instances on the same NE. See [1.1410 “VRF” \(p. 236\)](#) .

1.820 MVRP

Multi-VLAN Registration Protocol

1.821 MW

microwave

1.822 MWA

microwave-aware

N

1.823 N3

The 5G interface between the RAN and UPF.

1.824 N9

The 5G interface between the UPF and UPF.

1.825 N-PE

network-facing provider edge

A device that implements the control and signaling functions of an LPE.

1.826 NA

Neighbor Advertisement

1.827 NAI

network access identifier

The NAI is used to address a user in a specific Internet domain. The format of an NAI is similar to that of an address. It is comprised of a user portion that identifies the individual node and a realm portion that identifies an administrative domain in the Internet. The two portions are separated by an @ sign. The ROAMOPS working group is in liaison with bodies such as the ITU and 3GPP in order to integrate NAI with variables such as the E.164 telephone number range and the IMSI.

1.828 NAPT

network address port translation

An enhancement of regular [1.830 “NAT” \(p. 157\)](#) that allows a large number of devices on a private network to simultaneously “share” a single inside global address by changing the port numbers used in TCP and UDP messages.

1.829 NAS

non-access stratum

A functional layer in the UMTS and LTE wireless telecom protocol stacks between the core network and UE, used to direct communication sessions and to maintain steady communications with the UE as it changes locations.

1.830 NAT

network address translation

NAT is a method by which IP addresses are mapped from one group to another group; the method is transparent to end users. Many network addresses and their TCP/UDP ports are translated into a network address and its TCP/UDP ports. As a result, a realm with private addresses can be connected to an external realm with globally unique registered addresses, typically the Internet.

1.831 NB-IoT

NarrowBand Internet of Things

NB-IoT is a lower power WAN radio technology 3GPP standard developed to connect IoT user devices and services on established mobile networks. NB-IoT improves the power consumption of the devices and increases coverage, system capacity, and spectrum efficiency.

1.832 NBI

north-bound interface

1.833 NBNS

NetBIOS name server

1.834 Nbsf

The Nbsf service is used by the BSF to provide a PDU session binding function. It ensures that an AF request for a PDU session reaches the PCF that has the PDU session information. The Nbsf service configuration defines the TCP port used for service access. The Nbsf service allows NF consumers to retrieve, update, and remove the binding information.

1.835 ND

node discovery

1.836 navigation tree

The navigation tree displays a view of all managed equipment, services, and protocols, and allows you to navigate through these components.

1.837 NE

network element

A physical device, such as a router, switch, or bridge, that participates in a network.

1.838 NE WO

network element work order

See [1.1436 "WO" \(p. 240\)](#) .

1.839 NEBS

Network Equipment Building Standards

The requirement for equipment deployed in a central office environment. Covers spatial, hardware, craftsperson interface, thermal, fire resistance, handling and transportation, earthquake and vibration, airborne contaminants, grounding, acoustical noise, illumination, electromagnetic compatibility, and electrostatic discharge requirements.

1.840 neighbor

An adjacent system reachable by traversing a single sub-network by a PDU

1.841 NEMO

network mobility

A mobile network that can change its connection point to the Internet. MRs within the NEMO provide the connection to the Internet by maintaining a tunnel with an HA that resides in the home network of the MNN and the NEMO. While the MR changes its link locations, it obtains new IP addresses from the visited links. Traffic generated by the MNNs inside the NEMO network is forwarded by the MR to the HA through the tunnel. Packets from the Internet that are destined for the NEMO network are tunneled by the HA to the MR, then forwarded to the final destination inside the NEMO network.

1.842 NETCONF

Network Configuration Protocol

1.843 NetLoc

Network-provided location information for IMS

NetLoc refers to a situation where the network may require the cellphone ID for purposes such as lawful interception or charging. Cellphone ID information, provided by the UE, cannot be trusted as it is coming from the untrusted WLAN, therefore, the network provides the cellphone ID.

1.844 NEtO

Network Element Overview

A GUI-based Wavence NE management system.

1.845 network topology

The general layout of a network in terms of, for example, NE interconnection, grouping, or communication protocol.

1.846 NF

network function

A processing function in a network, defined by 3GPP. An NF can be implemented as a network element or software instance running on hardware, or as a virtualized function instantiated on a platform, such as on a cloud infrastructure.

1.847 NFM-P

Network Functions Manager - Packet

The NFM-P is an advanced IP/MPLS and mobile network management system that has a modular, scalable architecture. The system provides multiple GUI, web, and OSS interfaces, and can integrate with other management systems.

1.848 NFM-P analytics server

An NFM-P analytics server is a scalable NFM-P system component that uses business intelligence software, aggregated statistics, and raw data to report on network conditions and trends. The graphical and tabular reports are accessible from the NSP Analytics application.

Depending on the deployment type, scale, and reporting scope, an analytics server uses the NFM-P main database or an NFM-P auxiliary database as a data store.

1.849 NFM-P auxiliary database

An NFM-P auxiliary database is a scalable NFM-P system component that increases the data throughput and storage for demanding operations such as statistics collection. An auxiliary database can be deployed on one station, or as a distributed database on separate stations to provide fault tolerance and enable load balancing.

1.850 NFM-P auxiliary server

An NFM-P auxiliary server is a scalable NFM-P system component that performs routine functions such as statistics collection. Auxiliary server deployment is supported only in a distributed NFM-P system.

1.851 NSP Flow Collector

An NSP Flow Collector is a scalable NSP system component that collects flow statistics data from managed NEs for processing by consumers such as OSS applications.

1.852 NFM-P client

An NFM-P client is an entity that interacts with an NFM-P main server to perform network management operations. For example, an NFM-P GUI client uses an NFM-P graphical interface, an NFM-P OSS client uses an NFM-P API or similar mechanism, and an NFM-P application client uses NFM-P browser-based applications.

1.853 NFM-P client delegate server

An NFM-P client delegate server is a scalable NFM-P component that can host multiple concurrent GUI client sessions. A client delegate server has one NFM-P client software instance that is invoked by local and remote NFM-P users.

1.854 NFM-P main database

An NFM-P main database is a mandatory NFM-P system component that acts as the main NFM-P data store.

1.855 NFM-P main server

An NFM-P main server is the processing engine that co-ordinates and performs NFM-P network management operations that include responding to [1.852 “NFM-P client” \(p. 160\)](#) requests, and mediation between the managed network and other entities.

1.856 NFM-T

Network Functions Manager — Transport

The NFM-T provides unified optical end-to-end network management and operational support for all network element products in the Nokia’s optics portfolio.

1.857 NFV

Network function virtualization

Allows network administrators to uncouple network functions from underlay hardware NEs so that the functions can run as software images.

1.858 NGE

Network Group Encryption

A mechanism for the end-to-end encryption of MPLS-based traffic.

1.859 NG MVPN

next generation MVPN

Transports user traffic over M-LSPs and GRE tunnels using BGP for signaling multicast information.

1.860 NI

network ID

1.861 NIST

National Institute of Standards and Technology

1.862 N:K

A resource deployment redundancy model where N represents the active (primary) resource, and K represents the standby (secondary) resource that is activated when the active resource (N) fails. For deployments that do not require zone level failure (when half of all resources are impacted), the overhead of computing resources can be reduced by creating a shared pool of standby resources that can be used for processing sessions that are impacted due to limited scope failure.

1.863 NLOS

non-line-of-sight

A radio transmission across a path that is partially obstructed, usually by an object.

1.864 NLRI

network layer reachability information

1.865 NMS

network management system

A system that manages at least part of a network. An NMS is typically a reasonably powerful and well equipped computer that communicates with external agents to monitor and manage network resources.

1.866 NNI

NNI is expanded two ways:

1. network-to-network interface

An NNI is a standard interface between two ATM devices or two frame relay devices.

An NNI is also a port that resides on a PE bridge or a transit bridge, and connects to a service provider network.

2. network node interface

NNI is the interface between two ATM network devices that operate under different administrative domains, such as a vendor ATM switch and an ATM switch from another vendor.

1.867 Nnrf

An interface of the NRF. The Nnrf allows the NRF to be exposed to the CMG.

1.868 NOC

network operations center

The group that is responsible for the configuration and monitoring of the network and service elements using network switching equipment and management systems.

1.869 NOS

Network Operating System

1.870 Npcf

Service-based interface for the PCF (policy control function) in an SBA

1.871 NPDU

network protocol data unit

1.872 NRC

Network Resource Controller

1.873 NRC-P

Network Resource Controller — Packet

1.874 NRC-T

Network Resource Controller — Transport

1.875 NRC-X

Network Resource Controller — Cross Domain

1.876 NRF

NF repository function

The NRF is a network entity in the 5G core network that:

- maintains NF profiles
- allows other NF instances to subscribe to, and be notified about, the registration in the NRF of new NF instances
- supports service discovery function by receiving NF discovery requests from NF instances, and provides information about NF instances

The NRF is an API that is exposed to the CMG via the Nnrf interface. The NRF belongs to a PLMN and all NFs in the PLMN interact with the NRF instance.

1.877 nrt-VBR

non real-time variable bit rate

nrt-VBR is an ATM service category that guarantees low cell loss and low delay for applications, such as video and frame relay, which are characterized by an on/off source with known, predictable transmission patterns. During the on period, cells are transmitted at the peak information rate. No

cells are transmitted during the off period. nrt-VBR allows statistical multiplexing gains using the traffic descriptors (PCR and SCR). It does not provide delay commitments.

1.878 NSAPI

network service access point identifier

1.879 NSD

Network Services Director

1.880 NSG

network services gateway

The NSG is a network element representing the network forwarding plane for customer network services at the remote business location. The VNS solution manages NSGs at each enterprise site to act as a CPE, allowing it to create overlay VPNs to network customer sites and data centers.

1.881 NSP

Network Services Platform

1.882 NSR

non-stop routing

Non-stop routing prevents the outage of the control plane of a router due to the introduction of fault tolerance.

1.883 NSSA

not-so-stubby-area

NSSA is an OSPF area type where OSPF propagates any external routes that it obtains from the AS.

1.884 NSWO

non-seamless WLAN offload

1.885 NTP

Network Time Protocol

An Internet protocol that network devices use to synchronize their clocks.

O

1.886 O-GLSP

optical-generalized label switched path

1.887 OADM card

optical add/drop multiplexer card

An MDA that can be configured on the 7705 SAR to add or drop specific wavelengths while allowing others to pass through. This card comes in 1, 2, 4, or 8-channel variants.

1.888 OAM

operations, administration, and maintenance

A general term used to describe the costs, tasks involved, or other aspects of operating, administering, and managing a telecommunications network. The NFM-P provides a series of OAM tools to monitor and administer the network.

1.889 OAMPDU

operations, administration, and maintenance protocol data unit

1.890 OAM-VM

operations, administration, and management VM

1.891 OC-N

optical carrier - level *N*

An optical SONET signal carried at the speed of *N*, for example, OC-12 is a signal at 622.08 Mb/s.

1.892 OCH

optical channel

An optical wavelength band for WDM optical communications.

1.893 OCS

online charging system

A charging system that records accounting information for network resource usage. The OCS performs real-time credit control, including the management of transactions and subscriber accounts. The OCS authorizes the network, upon request, to grant resource usage to a subscriber. See 3GPP TS 32.240 for more information.

1.894 OCS

optical core switch

1.895 OCSP

online certificate status protocol

OCSP is a method of checking the state of a certificate. Unlike the CRL, which relies on checking against an offline file, the OCSP provides online information regarding the revocation status of a certificate. Like the CRL, the network operator can define an OCSP server per CA profile configuration.

1.896 ODU

optical channel data unit

outdoor unit

1.897 ODUk

The Optical Data Unit (ODU) provides end-to-end bandwidth management for a sub-wavelength signal in the electronic domain. The ODU is a fixed-sized container with in-band OAM tools for quality supervision and SLA assurance. The ODU functions as primary bearer for client traffic.

1.898 OEO

optical-to-electrical to optical

The process of converting an optical signal to an electrical equivalent and then back to optical data.

1.899 OFC

OpenFlow Controller

1.900 OFCS

offline charging system

A charging system that records charging information and sends the data from the network to an external billing system, after the resource usage has occurred. The OFCS relies on clients in the NE that initiate, modify, and terminate charging reporting based on a set of parameters that are relevant to each NE. See 3GPP TS 32.240 for more information.

1.901 OFS

OpenFlow Switch

1.902 OID

object identifier

An OID is a sequence of integers that uniquely identifies a MIB object. Each MIB object has an OID. A management system uses an OID to request an object value from a MIB. The OID defines a path to the object through a tree-like structure called the OID tree, or registration tree.

1.903 OIPS

Open Interfaces Professional Support

The Nokia OIPS portfolio provides OSS developers with network management integration solutions for the NFM-P. OSS integration initiatives include project review, design consultation, development support, and training for integration projects.

1.904 OLC

object life cycle

The OLC state specifies whether a service or network object is in maintenance or in-service mode to filter alarms. The default value of the OLC state for NEs can be specified in the discovery rules.

1.905 OL P

optical line protection

OLP protects the path between two adjacent network element degrees by splitting the fibers and selecting from two transmission fibers.

1.906 OMC

Optical Management Console

1.907 OMD

Optical multiplexer/demultiplexer

1.908 OMSP

Optical multiplex section protection

1.909 ONIE

Open Network Install Environment

An open source initiative which enables automatic installation of a Network Operating System (NOS).

ONIE provides the following services:

- Installing and reinstalling an OS
- Booting in rescue mode
- Formatting the system

1.910 OOS

out of service

1.911 OPEX

operating expenditures

1.912 OPR

Optical power receive

1.913 OPS

An optical circuit pack that provides WDM protection.

OPS is expanded in two ways:

1. off-premise station
2. optical protection switch

1.914 OPSA

Optical protection switch - advanced card

1.915 OPT

Optical power transmit

1.916 Option 82

See [1.1080 "Relay Information Option" \(p. 190\)](#) .

1.917 OPTSG

OPU1 Timing Slot Group

1.918 OP Uk

Optical Channel Payload Unit-k (k=1,2, or 3)

1.919 Oracle Advanced Security

A security option for the Oracle database product that provides security features to protect enterprise networks and securely extend corporate networks to the Internet. Oracle Advanced Security combines message encryption, database encryption, strong authentication, and authorization to address customer privacy and compliance requirements.

1.920 ORF

outbound route filtering

ORF is used to reduce the amount of time required to filter routes from a BGP peer.

1.921 ORR

Optimal Route Reflection

BGP Optimal Route Reflection (BGP-ORR) can be configured on a route reflector to advertise the best path to the BGP-ORR client groups.

1.922 OS

OS is expanded in two ways:

1. operating system
2. OmniSwitch

A Nokia family of devices. These devices support L2 forwarding and L3 routing, and have an extensive array of networking features.

1.923 OS 10K

OmniSwitch 10K

The OS 10K is a high-capacity, high-performance modular Ethernet LAN switch that provides 5.12 terabits per second of switching performance. The OS 10K has a 12 slot chassis configuration: 4 slots for CMM/fabric cards; and 8 slots for XNI or GNI cards that provide Ethernet, GigE, and 10 GigE capabilities.

1.924 OS 6250

OmniSwitch 6250

Layer 2+ Fast Ethernet Stackable LAN family of switches which includes the OS 6250SME (small and medium enterprise) for the enterprise segment, and the OS 6250M, for the Metro access segment.

1.925 OS 6350

OmniSwitch 6350

Stackable family is a series of fixed-configuration Gigabit Ethernet switches available as 10-, 24- and 48- port, Power-over-Ethernet (PoE) and non-PoE models to create the exact network for your small business. The network capabilities of the OmniSwitch 6350 family include advanced security, quality of service and high availability features for your business-class data, voice and wireless technologies.

1.926 OS 6400

OmniSwitch 6400

The OS 6400 family of devices is a set of stackable Layer 2+ GigE LAN switches.

1.927 OS 6450

OmniSwitch 6450

The OS 6450 family of devices is a set of stackable GigE LAN switches available in 10-, 24-, or 48-ports variants, with optional upgrade paths for 10 GigE stacking, 10 GigE uplinks, and metro Ethernet services.

1.928 OS 6450 M/X

OmniSwitch 6450 M/X

See [1.927 “OS 6450 ” \(p. 170\)](#).

1.929 OS 6465

OmniSwitch 6465

The OS 6465 family of devices is a shock-resistant, fully managed, gigabit Ethernet switches offering high security, reliability, performance and easy management. With support for MACSec on all ports, OS 6465 enables end-to-end encrypted networks. The OS 6465 family offers advanced system and network level resiliency features and convergence through standardized protocols in a space efficient form factor.

1.930 OS 6850

OmniSwitch 6850

The OS 6850 family of devices is a set of stackable Ethernet switches that provides wire-rate L2 forwarding and L3 routing with advanced service support.

This family includes the OS 6850E, an enhanced chassis that has a different form factor, updated transceiver support, and a different stacking mode.

1.931 OS 6850E

OmniSwitch 6850E

See [1.930 “OS 6850” \(p. 170\)](#) .

1.932 OS 6855

OmniSwitch 6855

The OS 6855 is a stackable, hardened Ethernet switch that has up to 24 Gigabit copper and fiber ports; it is designed to operate reliably in harsh electrical and severe temperature environments.

1.933 OS 6860

OmniSwitch 6860

The OS 6860 is a family of stackable high-density Gigabit and 10 Gigabit L2/L3 switches that can be positioned as edge, aggregation, or data center devices, or in a small enterprise network core.

1.934 OS 6860E

OmniSwitch 6860E

The OS 6860E is a family of high-density Gigabit and 10 Gigabit L2/L3 switches that provide application monitoring and enforcement, deep packet inspection, and advanced security.

1.935 OS 6865

OmniSwitch 6865

The OS 6865 is a stackable 1-GigE and 10-GigE L2/L3 hardened Ethernet switch suitable for outdoor installations. It is designed to operate in harsh environments and severe temperatures.

1.936 OS 6900

OmniSwitch 6900

The OS 6900 is a family of standalone aggregation switches.

1.937 OS 9600

OmniSwitch 9600

The OS 9600 is a five-slot Ethernet switch that supports one CMM and four network interface modules. It offers a wide range of GigE and 10GigE interfaces, and supports power-over-Ethernet for devices such as IP telephones, WLAN access points and video cameras. The OS 9600 supports up to two load-sharing power supplies.

1.938 OS 9700

OmniSwitch 9700

The OS 9700 family of devices is a set of high-density ten-slot Ethernet switches that use two slots for control and eight for network interfaces. Designed for smart continuous switching operation, the two center slots are dedicated to CMMs that support redundancy. The OS 9700 supports up to three power supplies.

This family includes the OS 9700E, which offers eight slots for Gigabit and 10-GigE network interface modules. The remaining two slots are reserved for redundant CMMs.

1.939 OS 9700E

OmniSwitch 9700E

See [1.938 "OS 9700" \(p. 171\)](#) .

1.940 OS 9800

OmniSwitch 9800

The OS 9800 family of devices is a set of high performance 18-slot switches. 16 slots are reserved for Gigabit and 10-GigE network interface modules. The remaining two slots are reserved for primary and redundant CMMs. The OS 9800 supports up to four power supplies.

This family includes the OS 9800E, which offers 16 slots for Gigabit and 10-GigE network interface modules. The remaining two slots are reserved for redundant CMMs.

1.941 OS 9800E

OmniSwitch 9800E

See [1.940 "OS 9800" \(p. 172\)](#) .

1.942 OSC

optical supervisory channel

A designated optical channel used to carry communications related to maintenance and operational functions of the network rather than customer traffic.

The OSC supports the following communications:

- NE-to-NE
- interworking
- client LAN
- orderwire communication

1.943 OSI

open systems interconnection

A reference model of protocols organized in seven layers. OSI standards and applications facilitate the interworking of equipment from different manufacturers.

1.944 OSPF

open shortest path first

OSPF is an IETF standard link-state routing protocol used to determine the most direct path for a transmission in IP networks.

1.945 OSS

operations support system

A network management system supporting a specific management function, such as alarm surveillance and provisioning, in a service provider network.

1.946 OSSI

operations support system interface

A set of APIs that allow OSSs to manipulate a well defined set of managed objects that are identified by management applications to automate operational procedures and allow flow-through provisioning.

1.947 OTDR

Optical time domain reflectometer

1.948 OTN

Optical Transport Network

A fiber-optic network, such as an SDH or SONET network, that is designed to transport customer traffic,

1.949 OTT

Over The Top

OTT services are services used in addition to the network services provided by the service provider, also called “value added” services. An example is Skype.

1.950 OTU

optical transport unit

1.951 OUI

organizationally unique identifier

A three-octet field in a SNAP header that identifies an organization.

P**1.952 P**

provider core

1.953 P-CSCF

proxy-call session control function

An IMS SIP server that is the first point of contact in a VoLTE call. The P-CSCF has the following functions:

- forwards SIP messages to other IMS nodes and to the UE
- interacts with the PCRF for billing and policy rules
- maintains a security association with the UE
- detects and forwards emergency calls to the local E-CSCF

1.954 P-GW

See [1.992 “PGW” \(p. 178\)](#) .

1.955 P2MP

point to multi-point

1.956 PAE

port access entity

A logical entity that supports the IEEE 802.1X protocol that is associated with a port.

1.957 PAP

Password Authentication Protocol

A protocol to communicate with a security server for a user authentication.

1.958 PAT

program association table

1.959 PBB

provider backbone bridge or provider backbone bridging

1.960 PBBN

provider backbone bridged network

1.961 PBN

provider bridge network

1.962 PBR

Policy-based Routing

1.963 PBS

peak burst size

The maximum number of bytes that can be sent at the network interface speed without exceeding the PIR.

1.964 PC

personal computer

1.965 PCC

PCC can be expanded in two ways:

- policy and charging control
PCC encompasses flow-based charging, including charging control and online credit control and policy control (e.g. gating control, QoS control, QoS signaling). See 3GPP TS23.203.*
- path computation client

1.966 PCE

IP path computational engine

1.967 PCEF

policy and charging enforcement function

This encompasses SDF detection, policy enforcement and flow-based charging functions. See 3GPP TS23.203 Section 6.2.2.*

1.968 PCEP

path computation element protocol

1.969 PCF

policy control function

The PCF in the 5G core network provides the same function as the PCRF. The PCF provides policy rules for control plane functions, including network slicing; accesses subscription information for policy decisions; and, supports the 5G QoS policy and charging control functions.

1.970 PCI

physical cell identification

PCI prevents signal collision during UE handover between wireless cells of eNodeBs.

1.971 PCM

pulse code modulation

1.972 PCMD

per-call measurement data

In a CDMA network, PCMD is the data associated with a call, such as the subscriber identifier, start time, duration, type, system identifiers, and call geometry parameters. The data is used for operations such as call hand-off, tracking, and traffic analysis.

1.973 PCO

protocol configuration options

The PCO provides additional optional information about the destination network to which the UE is connecting. The PCO information element transfers parameters, such as external network protocol options, between the UE and the PDN APN, which are sent transparently through the MME and the SGW. The PCO may include the address allocation preference indicating that the UE prefers to obtain an IP address only after the default bearer activation. See 3GPP TS23.401.

1.974 PCP

port control protocol

Port control protocol allows an IPv4 or IPv6 host to control how incoming IPv4 or IPv6 packets are translated and forwarded by a NAT or firewall, and also allows a host to optimize its outgoing NAT keepalive messages.

1.975 PCR

PCR is expanded in two ways:

1. peak cell rate

PCR is the cell rate, in cells per second, that the endpoint may never exceed.

2. program clock reference

1.976 PCRF

policy control and charging rules function

Enables operators to have rules-based, real-time dynamic control over bandwidth, charging, and usage in an LTE network.

1.977 PD

powered device

Any device that uses a PoE data cable as the only source of power.

1.978 PDF

portable document format

The file format in Adobe Acrobat document exchange technology.

1.979 PDH

plesiochronous digital hierarchy

A technology used in telecommunications networks to transport large quantities of data over digital transport equipment such as fiber optic and microwave radio systems.

1.980 PDN

packet data network

The network through which a UE obtains a packet data connection to the Internet.

1.981 PDP

packet data protocol

In UMTS, the PDP uses a packet data connection over which the user equipment and the network exchange IP packets. The use of the packet data connections is restricted to specific services. The services can be accessed using access points.

1.982 PDSN

public data switched network

1.983 PDU

protocol data unit

A PDU is a message of a specific protocol comprising payload and protocol-specific control information, typically contained in a header. PDUs pass over the protocol interfaces which exist between the layers of protocols, as indicated in the OSI model.

1.984 PE

provider edge

The name of the device or set of devices at the edge of the provider network with the functions required to interface with the customer network and the MPLS network.

1.985 PE bridge

An Ethernet switch that resides on the edge of the service provider network. The PE bridge interconnects customer networks with service provider networks. A switch is a PE bridge when the switch transports packets between a customer-facing port and a network port or between two customer-facing ports.

1.986 PECF

policy enforcement and charging function

1.987 PEM

power entry module

1.988 PEQ

power equalization module

The 7950 XRS power supply which provides DC power to the chassis.

1.989 PF

power filter

1.990 PFCP

packet forwarding control protocol

PFCP is a message delivery protocol that is used on the interface between the control plane and user plane functions in a CUPS context.

1.991 PFS

perfect forwarding secrecy

A key-establishment protocol for secure VPN communications. PFS requires the use of public key cryptography. No key used for the transfer of data may be used to derive keys for future transmission. Diffie-Hellman key exchange is a cryptographic protocol that provides perfect forward secrecy.

1.992 PGW

packet data network gateway

The gateway that terminates the interface towards the PDN. If a UE is accessing multiple PDNs, there may be more than one PGW for that UE.

1.993 PGW-C

packet data network gateway - control plane

The PGW that exists in the control plane.

1.994 PGW-U

packet data network gateway - user plane

The PGW that exists in the user plane.

1.995 PHY

physical

PHY refers to the physical layer, or L1 of the OSI model.

1.996 Pi

The reference point between the PGW and the PDSN.

1.997 PIC

prefix independent convergence

PIC is a method for speeding up convergence of the FIB under failover conditions in large networks, by using a hierarchical path structure in the FIB.

1.998 PID

PID is expanded in two ways:

1. protocol identification
A two-octet field in a SNAP header that specifies the protocol type.
2. packet identification

1.999 PIM

protocol independent multicast

PIM is a family of multicast routing protocols for IP networks that provide one-to-many and many-to-many distribution of data over a LAN, WAN or the Internet. It is termed protocol-independent because PIM does not include its own topology discovery mechanism, but instead uses routing information supplied by other traditional routing protocols such as BGP, IS-IS, OSPF, RIP, or static.

1.1000 PIM snooping

PIM snooping for VPLS allows a VPLS PE router to build multicast states by snooping PIM protocol packets that are sent over the VPLS. The VPLS PE then forwards multicast traffic based on the multicast states.

1.1001 PIM-SM

PIM sparse mode

1.1002 PIM-SSM

PIM-source specific multicast

1.1003 ping

packet Internet groper

An ICMP echo message and its reply. Often used in IP networks to test the reachability of a network device.

1.1004 PIP

provider instance port

A PIP is a backbone edge bridge port that can transmit or receive frames from one or multiple customers, adding or removing I-TAGs. In the context of SR PBB, it could be the I-Site “port” that is connected to the B-Site.

1.1005 PIR

peak information rate

The PIR is the peak data transfer rate for a path, such as a frame relay, VPC, VCC, or DE service path. The PIR is the PCR converted to kb/s.

1.1006 PKI

public key infrastructure

PKI represents the set of hardware, software, people, policies and procedures needed to create, manage, store, distribute, and revoke public key certificates based on public-key cryptography.

1.1007 PLAR

Private Line Automatic Ringdown

1.1008 PLMN

public land mobile network

Typically the mobile network run by one network operator in one country. See 3GPP TS23.002 Section 3.1.*

1.1009 PLR

point-of-local-repair

A functional NE in a path in which a manual bypass is implemented for a defective NE in the path.

1.1010 PLSP-ID

Path LSP-ID

1.1011 PM

PM is expanded in two ways:

1. path monitoring
For an optical channel data unit.
2. performance monitoring

1.1012 PMC

packet microwave card

1.1013 PMIP

proxy mobile IP

A network-based mobility management protocol. It is an amendment to mobile IPv6 which allows mobility control to be moved from the mobile node to a proxy in the network.

1.1014 PMIPv6

proxy mobile IPv6

A network-based mobility management protocol. It allows mobility control to be moved from a mobile NE to a proxy in the network.

1.1015 PMSI

provider multicast service interface

1.1016 PMT

program map table

1.1017 PNF

physical network function

The physical network function variants of the CMG and CMM VNF application software.

1.1018 POA

program off-air

1.1019 PoE

power over Ethernet

A technology that provides in-line power directly from switch Ethernet ports. PDs such as IP phones, wireless LAN stations, Ethernet hubs, and other access points can be plugged directly into an Ethernet port. The Ethernet port provides both electrical power and data flow.

1.1020 PoE Plus

power over Ethernet plus

A technology that provides greater in-line power over Ethernet than PoE.

1.1021 PoE+

See [1.1020 "PoE Plus" \(p. 182\)](#) . See also [1.1019 "PoE" \(p. 182\)](#) .

1.1022 POS

packet over SONET

A technology that allows IP packets to be sent directly over SONET/SDH frames.

1.1023 PPP

Point-to-Point Protocol

PPP is a protocol for communication between two computers using a serial interface, typically a PC connected by phone line to a server. PPP uses IP. It is considered as a member of the TCP/IP suite of protocols.

1.1024 PPP Magic Numbers

Magic numbers are identifiers which are inserted into PPP control packets and are sent to the other end of the link in the form of an echo. The echo-request should be answered with an echo-reply containing the magic number of the other end. See [1.1023 "PPP" \(p. 182\)](#) .

1.1025 PPPoE

Point-to-Point Protocol over Ethernet

See also [1.1023 "PPP" \(p. 182\)](#) .

1.1026 PPPRF

Point-to-Point Protocol over Radio Frequency

See also [1.1023 “PPP” \(p. 182\)](#) .

1.1027 PPTP

Point-to-Point Tunneling Protocol

A protocol that provides VPN connections for home or mobile users to gain secure access to an enterprise network. Encrypted payload is transported over a GRE tunnel that is negotiated over a TCP control channel.

1.1028 PRA

presence reporting areas

The PRA is a defined area within the 3GPP packet domain that indicates the presence of a UE. The charging information for the UEs within the PRA is collected by the SGWs or PGWs that serve the UE for the purpose of charging and policy control. Multiple PRAs refer to the UE presence in many PRAs.

1.1029 prefix

The first 64 bits of an IPv6 address that identify the network to which a host belongs. The IPv6 prefix is analogous to the IPv4 subnet mask.

1.1030 primary CMM

primary chassis management module

When switches operate in a stack, one switch in the stack, known as the primary CMM, always performs the primary management role.

1.1031 property form identifier link

A window identifier link is a unique internal address that the NFM-P assigns to a form or window.

1.1032 PS

packet switched

1.1033 PS FCI

Packet Switched Furnish Charging Information

Specific information about an online charging session. PS FCI includes charging information per rating group when it is sent by the OCS. See 3GPP 32.298.

1.1034 PSE

power source equipment

PSE provides power to a single link section. The PSE main functions include searching the PD, optionally classifying the PD, supplying power to the link section if the PD is detected, monitoring the power on the link section, and scaling power back to detect level when power is no longer requested or required.

1.1035 pseudonode

A pseudonode is the LAN identifier for a broadcast subnetwork (ISIS).

1.1036 pseudowire

A mechanism that emulates the essential attributes of a service such as ATM, frame relay, or Ethernet over a PSN.

1.1037 PSI

program specific information

1.1038 PSK

pre-shared key

The pre-shared key is a component of MACsec.

1.1039 PSN

PSN can be expanded in two ways:

- packet-switched network
A data-transmission network that uses the packet-switching technique. Unlike circuit switching, packet switching allocates multiplexing and switching resources only when data is present. There are public and private packet-switched networks.
- pseudonode number
A one-octet field in an ISIS header that specifies the virtual node identifier in a type 24 TLV.

1.1040 PSNP

partial sequence number PDU

A PDU that is sent by a router, which has established an adjacency with a neighboring router, to transmit link-state information to ensure synchronization of routing tables throughout the network.

1.1041 PSS

Photonic Service Switch

1.1042 PST

Primary state

1.1043 PTB

Packet Too Big

A PTB message is sent when a router receives a packet with a size that exceeds the MTU of the link.

1.1044 PTP

Precision Time Protocol

A time synchronization protocol for networks.

1.1045 PVC

permanent virtual circuit

A PVC is an ATM end-to-end logical connection that extends between host interfaces on a network. A single PVC may pass through several ATM switching devices.

1.1046 PVP

permanent virtual path

A permanent ATM connection that is used to carry one or more PVCs.

1.1047 PVST

Per-VLAN spanning tree

PVST maintains a spanning tree instance for each VLAN configured in the network to help load balance L2 traffic without causing spanning tree loops.

1.1048 PW

See [1.1036 “pseudowire” \(p. 184\)](#) .

1.1049 PWRSV

Power-save mode

1.1050 PXC

Photonic Cross Connect

Q

1.1051 QAM

quadrature amplitude modulation

1.1052 QCI

quality of service class identifier

A parameter of the QoS profile of an EPS bearer. It is a scalar quantity that refers to access-device-specific parameters that control bearer-level packet forwarding treatment, for example, scheduling weights, admission thresholds, queue management thresholds, and link layer protocol configuration. See 3GPP TS23.401 Section 4.7.3 and TS23.203 Annex J.*

1.1053 QER

QoS enforcement rule

The QER is an enforcement rule for processing data traffic that instructs the user plane function to enforce QoS policing on the packets, within the context of CUPS. The QER is a rule that is provisioned by the Sx reference point when it establishes a session between the control and user plane functions.

1.1054 QFI

QoS flow identifier

1.1055 QinQ

QinQ is a type of Ethernet encapsulation in which a second 802.1Q VLAN tag is added to an 802.1Q frame. Service providers can then use VLAN IDs to segregate customer services and still allow customers to assign their own VLAN IDs without the possibility of ID duplication.

1.1056 QL

quality level

1.1057 QMA

Quick-locking SMA

A QMA is a type of RF coaxial connector; see [1.1204 “SMA” \(p. 207\)](#).

1.1058 QoE

quality of experience

1.1059 QoS

quality of service

QoS is a term for the set of parameters and their values that determine the performance of a virtual circuit. A service level is typically described in terms of network delay, bandwidth, and jitter.

1.1060 QPPB

QoS policy propagation via BGP

QPPB is a mechanism that allows propagation of QoS policy and classification by the sending party, based on access lists, community lists and AS paths, thereby helping to classify based on destination instead of source address.

1.1061 QSFP

Quad Small Form-factor Pluggable

QSFP ports allow a single port to serve as four independent port connections, to increase port density on a device. See also [1.1186 "SFP" \(p. 204\)](#).

1.1062 QSFP+

Quad Small Form-factor Pluggable (enhanced)

An enhanced version of QSFP that supports data rates up to 10 Gb/s. See also [1.1061 "QSFP" \(p. 187\)](#).

R

1.1063 R-APS

ring automatic protection switching

1.1064 RAA

Re-Auth Answer

An RAA message is sent by the PCEF to the PCRF to acknowledge that the PCEF has executed the new PCC rules that were carried in an RAR message sent by the PCRF.

1.1065 RAB

radio access bearer

1.1066 RAC

routing area code

1.1067 RADIUS

remote authentication dial-in user service

A remote user authentication, authorization, and accounting protocol.

1.1068 RAE

remote antenna extension

1.1069 RAM

random access memory

A group of memory chips that function as the primary workspace of the computer. Each byte of storage in the chip can be directly accessed without regard to the bytes before or after it.

1.1070 RAN

radio access network

1.1071 RAR

Re-Auth-Request

An RAR command is sent by the CRF to notify the AF that the bearer for the established session has become unavailable.

An RAR command is also sent by the PCRF to the PCEF to execute new PCC rules when an event-trigger event occurs. The RAR message carries the new PCC rules.

1.1072 RAT

radio access technology

The RAT is the type of radio technology used in a radio access network (RAN) to access the core network (CN), e.g. UMTS, GSM, CDMA2000.

1.1073 rating group

An AVP, within the MSCC AVP, that is used to indicate service. Each quota allocated to a Diameter credit control session has a unique rating group value.

1.1074 RAU

routing area update

1.1075 RCA

root cause analysis

Problem solving methods used to determine the root cause of a problem.

1.1076 RD

route distinguisher

An eight-byte BGP field that allows an operator to create a distinct route to a common IP address prefix.

1.1077 RDI

remote defect indication

A signal sent to transmitting equipment by receiving equipment when defects are detected on an incoming signal.

1.1078 RED

random early detection

RED is an algorithm that detects and avoids traffic congestion in a PSN. Incoming congestion is detected by calculating the average queue size. If the gateway decides that the average queue size exceeds a predetermined threshold, it either randomly drops packets arriving at the gateway, or sets a bit in the packet headers. The packet transmission rate is reduced until all the packets reach their destination.

1.1079 reference

A reference is used by the CPAM to determine the existence of an object, and determines the color of objects and links on the GUI topology maps.

See also [1.229 “checkpoint \(regular\)” \(p. 76\)](#) .

1.1080 Relay Information Option

The Relay Information Option is defined in RFC 3046 and allows a DHCP relay agent to append to the relayed DHCP request information that identifies where the originating DHCP request was sent. Also known as Option 82.

1.1081 residential subscriber

See [1.1265 “subscriber” \(p. 215\)](#) .

1.1082 resync

An OSS operation that maintains a local mirror of NFM-P state information, such as inventory or current alarm states, performs a resync when it knows or suspects that the locally stored state information is out of sync with the state information stored in the NFM-P. The OSS does this by requesting information via the XML API. An OSS that does not monitor events periodically performs resyncs to maintain synchronization with the NFM-P. An OSS that does monitor events requires a resync in situations where there are missed events.

1.1083 RET

RET is expanded two ways:

1. retransmission
2. remote electrical tilt

1.1084 RF

radio frequency

1.1085 Rf

Rf is:

- the reference point between an [1.586 “IMS” \(p. 123\)](#) element and the [1.893 “OCS” \(p. 165\)](#)
- the reference point between an [1.586 “IMS” \(p. 123\)](#) element and the [1.893 “OCS” \(p. 165\)](#)
- the interface between the [1.992 “PGW” \(p. 178\)](#) and the [1.204 “CCF” \(p. 73\)](#)
- the interface between the [1.1191 “SGW” \(p. 205\)](#) and the [1.204 “CCF” \(p. 73\)](#)

1.1086 RFC

request for comments

A document that describes a technology specification. RFCs are used by the IETF and other standards bodies.

1.1087 RFM

radio frequency module

1.1088 RG

rating group

1.1089 RHEL

Red Hat Enterprise Linux

RHEL is the supported [1.676 “Linux” \(p. 136\)](#) distribution for NFM-P deployment.

1.1090 RIB

routing information base

A router database that contains the routing information necessary for packet forwarding.

1.1091 ring group

A group of network devices that connect to each other in a ring topology for the efficient distribution of multicast or broadcast network traffic.

1.1092 RIP

Routing Information Protocol

RIP is a Bellman-Ford routing protocol based on distance vector algorithms, which measure the shortest path between two points on a network in terms of the number of hops between those points. Various forms of RIP distribute routing information in IP, XNS, IPX, and VINES networks.

See also [1.944 “OSPF” \(p. 172\)](#) .

1.1093 RJ-45

registered jack 45

A telephone connector that holds up to eight wires. RJ-45 plugs and sockets are used in Ethernet and Token Ring Type 3 devices.

1.1094 RMI

remote method invocation

A standard for distributed objects written in Java. RMI is a remote procedure call that allows Java objects to be managed remotely.

1.1095 RMON

remote network monitoring

1.1096 RMS

resource management server

A server that tracks the use of services in a network by an end host. An RMS can enforce quotas, ensure that specific service levels are met, optimize resources, manage IP addresses, and generate real-time active session reports.

1.1097 RNC

radio network controller

Controls radio resource management in the radio access networks of universal mobile telecommunications systems. An RNC is equipment in the UTRAN radio network subsystem that manages the use of radio resources.

1.1098 RNCV

ring node connectivity verification

1.1099 ROADM

Reconfigurable Optical Add/Drop Multiplexer

An optical network element with a configuration that can be changed remotely. This remote reconfigurability reduces [1.911 “OPEX” \(p. 168\)](#) when operating a [1.355 “DWDM” \(p. 93\)](#) network. [1.911 “OPEX” \(p. 168\)](#) is reduced because the ROADM eases network provisioning and line tuning at both the initial installation and any upgrades (to increase the capacity or re-allocate resources to a new demand matrix).

1.1100 root bridge

The bridge with the highest priority ID, selected as the root in a spanning tree.

1.1101 route flapping

A routing problem caused by network problems where an advertised route between two devices changes back and forth between two different paths.

1.1102 router

An interface device that connects two networks. It maintains configuration tables and uses various network protocols to select cost-effective routes that move data between a source and destination device. Also called a device.

1.1103 routing domain

In OSPF, a routing domain is an OSPF area. In IS-IS, a routing domain does not map to the ISIS area, but is a group of routers that participate in an ISIS level, that are visible to each other in their link state database.

1.1104 routing instance

The configuration of a router, including information such as protocols, interfaces, routing, and policies.

1.1105 routing protocol

A routing protocol is used to determine the correct route for packets within IP and IP/MPLS networks.

1.1106 RP

rendezvous point

An RP is a PIM-enabled router that is elected by PIM as a central distribution source for multicast groups in a multicast domain.

1.1107 RPC

remote procedure call

An RPC is a procedure call between applications that run on the same or different stations.

1.1108 RPF

reverse path forwarding

A mechanism used by PIM to forward multicast packets down a distribution tree.

1.1109 RPL

ring protection link

Loop avoidance in an Ethernet Ring is achieved by guaranteeing that, at any time, traffic may flow on all but one of the ring links which is designated as the RPL.

1.1110 RPS

radio protection switching

1.1111 RRH

remote radio head

1.1112 RRO

record route object

1.1113 RS-232-C

recommended standard - 232 - current

The physical interface and protocol used to connect serial devices.

1.1114 RSA

Rivest, Shamir, Adleman

RSA is an algorithm for public key encryption in which a public key consists of the product of two prime numbers and an auxiliary value.

1.1115 RSHG

residential split horizon group

A type of SHG with dual-pass queue optimization. Downstream broadcast and multicast traffic are not supported. SAPs associated with an RSHG are lightweight SAPs.

1.1116 RSM

residential subscriber management

A versatile TPSDA model, sometimes called enhanced subscriber management, which supports a variety of delivery configurations, such as one VLAN per host, one VLAN per application, one VLAN for all applications, and one VLAN per service provider per application. See [1.1265 “subscriber” \(p. 215\)](#).

1.1117 RSRP

reference signal received power

1.1118 RSRQ

reference signal received quality

1.1119 RSTP

Rapid Spanning Tree Protocol

RSTP is an enhanced version of STP, as defined in IEEE standard 802.1w-2001 and incorporated in IEEE standard 802.1D-2004. RSTP supersedes STP for standards conformance. RSTP provides faster automatic reconfiguration for route failures than STP by facilitating a rapid change in port roles.

1.1120 RSVP

Resource Reservation Protocol

RSVP is a network-control protocol in the IP suite that is used for communicating application QoS requirements to intermediate transit NEs in a network. RSVP uses a soft-state mechanism to maintain path and reservation states on each NE in the reservation path.

1.1121 RSVP-TE

resource reservation protocol-traffic engineering

RSVP-TE is an extension of RSVP that is described in RFC 3209. RSVP-TE allows the establishment of LSPs based on network constraints such as available bandwidth and explicit hops.

1.1122 RT

route target or retransmission

In BGP/MPLS VPNs, an RT is an attribute that identifies a set of sites.

1.1123 rt-VBR

real-time variable bit rate

rt-VBR is a variant of the VBR service category available only for VPC paths and VCC paths. It allows statistical multiplexing gains using the traffic descriptors (PCR and SCR), and provides delay commitments. rt-VBR supports variable bit rate traffic with sustained and peak traffic parameters, which require strict delay control, such as packetized voice or video.

An rt-VBR is an ATM service category that guarantees very low cell loss and very low delay for time-sensitive applications such as voice and video, which are characterized by unpredictable, bursty transmission patterns.

rt-VBR is a variant of the VBR service category that is only available for VPC and VCC paths. nrt-VBR is the other variant of VBR available for these paths.

1.1124 RTM

routing table manager

An RTM is an application that operates in a multiprotocol network to create and maintain a RIB that contains all active static routes in the network. The RTM calculates the best routes from the RIB and stores the information in the FIB.

1.1125 RTU

remote terminal unit

A remote monitoring and control device used in industrial networks. An RTU, also called a slave or remote, typically uses RS-232 links back to the master.

1.1126 RUC

rack user commissioning

An RUC is an eNodeB component that is comprised of front and back RUC cards and a fan rack.

1.1127 RVPLS (R-VPLS)

Routed VPLS

Routed VPLS associates an L3 access interface on an IES or VPRN service to a VPLS service on the same site. Traffic with a destination MAC matching that of the associated interface is routed based on the IP forwarding table; all other traffic is forwarded based on the VPLS forwarding table.

1.1128 rwa

read-write access

S

1.1129 S-GW

See [1.1191 “SGW” \(p. 205\)](#) .

1.1130 S-PE

switching-provider edge

In [1.793 “MS-PW” \(p. 152\)](#) routing, switching-provider edge NEs are automatically created to forward inter-domain traffic between [1.1287 “T-PE” \(p. 218\)](#) NEs.

1.1131 S-PMSI

selective provider multicast service interface

1.1132 S1

The interface between an eNodeB and the Core Network (CN). See 3GPP TS36.300 Section 19 and TS36.410 to TS36.414.*

1.1133 S1-U

S1-user plane

Provides non-guaranteed delivery of user plane [1.983 “PDU” \(p. 177\)](#) s between the eNodeB and the [1.1191 “SGW” \(p. 205\)](#) . It is built on [1.591 “IP” \(p. 124\)](#) transport, and [1.508 “GTP-U” \(p. 114\)](#) is used on top of [1.1351 “UDP” \(p. 227\)](#) / [1.591 “IP” \(p. 124\)](#) to carry the user plane [1.983 “PDU” \(p. 177\)](#) s between the eNodeB and the [1.1191 “SGW” \(p. 205\)](#) . It supports inter-eNodeB path switching during handover. See 3GPP TS36.300 Section 19.1 and TS36.414.*

1.1134 S2a

A reference point that provides the user plane with control and mobility support between trusted non-[1.7 “3GPP” \(p. 45\)](#) [1.591 “IP” \(p. 124\)](#) access and the mobile gateway.

The interface between the PGW and the TWAN.

1.1135 S2b

A reference point that provides the user plane with control and mobility support between the [1.399 “ePDG” \(p. 99\)](#) and the mobile gateway.

1.1136 S4

An interface between the:

- 1.1191 “SGW” (p. 205) and 1.1190 “SGSN” (p. 205) that provides control and mobility support between the 1.492 “GPRS” (p. 112) core and the 1.7 “3GPP” (p. 45) anchor function of the 1.1191 “SGW” (p. 205)
- combined SGW/PGW and the SGSN

1.1137 S5

The interface between the 1.1191 “SGW” (p. 205) and the 1.992 “PGW” (p. 178) in the same 1.1008 “PLMN” (p. 180) .*

1.1138 S6b

The Diameter interface between the 1.992 “PGW” (p. 178) and the 1.7 “3GPP” (p. 45) 1.61 “AAA” (p. 54) server/proxy.

1.1139 S8

The interface between the 1.1191 “SGW” (p. 205) and the 1.992 “PGW” (p. 178) in different 1.1008 “PLMN” (p. 180) s.*

1.1140 S11

The interface between the:

- 1.1191 “SGW” (p. 205) and the 1.764 “MME” (p. 148)
- combined SGW/PGW and the 9471 WMM

1.1141 S12

The interface between the:

- 1.1191 “SGW” (p. 205) and the 1.1097 “RNC” (p. 192)
- combined SGW/PGW and the 1.1097 “RNC” (p. 192)

1.1142 SA

security association

The SA is a security relationship that provides security guarantees for data transmitted among the members, such as IPsec peers, or MACsec CA members.

1.1143 SAA

service assurance agent

The SAA is a SROS-based CLI command tool that allows operators to configure a number of different tests that can be used to provide performance information such as delay, jitter, loss of services, or network segments. The test results are saved in SNMP tables or summarized XML files.

1.1144 SAE

system architecture evolution

The part of the evolved packet system (EPS), which involves non-radio aspects. It includes the evolved packet core (ePC) network, and accompanies LTE.*

1.1145 SAK

security association key; see [1.1142 “SA” \(p. 198\)](#)

A security association key is a component of MACsec, securing data plane traffic.

1.1146 SAE-GW

SGW combined with PGW/GGSN

1.1147 SAFI

Subsequent Family Address Identifier

See [1.81 “AFI” \(p. 56\)](#).

BGP messages in which AFI=1 and SAFI=66 are "MDT-SAFI" messages.

1.1148 SAI

Source Attachment Individual Identifier

1.1149 SAM-L

security assertion markup language

An XML-based standard for exchanging authentication and authorization data between security domains, such as identity providers (producers of assertions) and service providers (consumers of assertions). SAM-L is a product of the OASIS Security Services Technical Committee.

1.1150 SaMOG

S2a Mobility Over GTP

See [1.1341 “TWAG” \(p. 225\)](#)

1.1151 SAP

service access point

A SAP is a point of communication exchange between an application and the LLC, or between layers of software.

1.1152 SAS

service assurance system

SAS refers to the grouping of OAM diagnostic tests into test suites for end-to-end testing of customer services. SAS test suites can be scheduled. They can provide more network monitoring and troubleshooting capability than individual OAM activities.

1.1153 SBA

service-based architecture

SBA provides a modular framework where common applications can be deployed using components from different sources. The control plane and common data repositories of a 5G network are delivered by interconnected network functions (NF). Network functions can access each other's services.

1.1154 SBFD

Seamless bidirectional forwarding detection

Seamless BFD avoids the negotiation and state establishment for [1.159 "BFD" \(p. 67\)](#) sessions, primarily by pre-determining the session discriminator and distributing the discriminators to remote network entities. This allows client applications or protocols to more quickly initiate and perform connectivity tests.

1.1155 SBI

south-bound interface

1.1156 SC

service component

An SC is a customer service that is a component of a composite service.

1.1157 SCADA

Supervisory Control And Data Acquisition

An industrial data management system that monitors and controls IEDs

1.1158 SCEF

service capability exposure function

The SCEF is a core network node that is defined by 3GPP Release 13. The SCEF enables the 3GPP network to securely expose its services and capabilities to third-party application servers

using APIs. The APIs can be RESTful APIs, XML over HTTP, diameter, or anything else depending on, for example, interface needs. Additional features include authentication and authorization and policy management and enforcement.

1.1159 SCI

service class indicator

1.1160 SCM

Secure certification mode

1.1161 SCP

SCP is expanded two ways:

1. secure copy protocol

The SCP securely transfers files between local and remote hosts, or between two remote hosts, using SSH2.

2. service connection point

An SCP is a type of connector endpoint in a composite service. It can be a SAP, service interface, or network port, depending on the device.

1.1162 SCR

sustainable cell rate

An upper limit on the conforming average rate of an ATM connection. An SCR uses a time scale that is long relative to the time scale of the PCR.

1.1163 SCTE35

society of cable telecommunications engineers

1.1164 SCTP

Stream Control Transmission Protocol

A transport layer protocol, similar to TCP and UDP. Like TCP, SCTP ensures that data is transported across the network sequentially and without error. SCTP is also similar to TCP in that a relationship is created between the endpoints of an SCTP session before the data is transmitted, and this relationship is maintained until the data transmission is completed.

Unlike TCP, SCTP provides multi-streaming and multi-homing, which increase performance and reliability of the Diameter application message exchange.

Multi-streaming allows data to be partitioned into multiple streams that can be delivered independently, so that message loss in any of the streams only affects delivery within that stream.

Multi-homing is the ability of an SCTP endpoint to support multiple IP addresses, which can mean greater survivability of the session in the presence of network failures. In a single-homed session, the failure of a local LAN access can isolate the end system, while failures within the core network can disrupt transport until the IP routing protocols reconverge around the point of failure. With multi-homed SCTP, redundant LANs can be used to reinforce the local access and, in the core network, the risk of failure from one address can be reduced.

1.1165 Sd

The interface between the PCRF and the TDF/SSG.

1.1166 SDC

service data container

1.1167 SDF

service data flow

An aggregate set of packet flows that match a set of filters based on packet headers, such as source and destination IP addresses, in a policy and charging control rule. See 3GPP TS23.203.*

1.1168 SDH

synchronous digital hierarchy

SDH is a hierarchical set of digital transport structures, standardized for the transport of suitably adapted payloads over physical transmission networks. SDH is a standard for communicating digital information over optical fiber and microwaves. SDH was developed to replace the PDH system for transporting large amounts of telephone and data traffic.

1.1169 SDI

serial data interface

An SDI is an MDA configurable on the 7705 SAR-8/18. It can be configured to operate in access mode for a V35, RS232, or X.21 interface.

1.1170 SDM

subscriber data management

SDM is a central repository used by carriers to consolidate and manage subscriber data across multiple domains. The data can include subscriber presence, preferences, authentication, services, identities, and location.

1.1171 SDN

software-defined networking

1.1172 SDP

service distribution point

The NFM-P uses this term interchangeably with service tunnel.

1.1173 SDRAM

synchronous dynamic random-access memory

The NFM-P uses this term interchangeably with service tunnel.

1.1174 SDU

service data unit

An SDU is a unit of information from an upper-layer protocol that defines a service request to a lower-layer protocol.

1.1175 secondary CMM

secondary chassis management module

When switches operate in a stack, one of the switches in the stack operates in a secondary management role. This switch serves as a backup, and is always ready to perform the primary management role if the primary CMM fails or is taken offline.

1.1176 section

A single fiber run that an NE or optical regenerator terminates. The main functions of the section layer are to properly format the SONET frames and to convert the electrical signals to optical signals.

1.1177 SEG

security gateway

A SEG is one or both ends of an IPsec tunnel.

1.1178 service class indicator

A 3GPP standard that identifies the service class associated with downlink user plane packets, so that the GERAN can optimize the deployment of radio resources for packet-switched traffic.

1.1179 service tunnel

A service tunnel acts as a logical way of unidirectionally directing traffic from one device to another device. The service tunnel is provisioned to a specific encapsulation method, such as GRE, and the services are mapped to the service tunnel. A distributed service spans more than one router. Distributed services use Service Distribution Points to direct traffic to another router through a service tunnel.

1.1180 service-level agreement

See [1.1200 “SLA” \(p. 206\)](#) .

1.1181 SES

severely errored second

A one-second interval during which the error ratio on a transmission line is greater than a specified limit, and transmission performance is significantly degraded.

1.1182 set-top box

A set-top box is a type of residential subscriber end-user device that receives network traffic. An example of a set-top box is a consumer device that converts BTV IP data into video and audio signals for a television.

1.1183 SFC

SFC is expanded two ways:

1. Static Filter CWDM

A static filter card used with a CWDM circuit pack.

2. Service Function Chain

A service function chain uses SDN capabilities to create a service chain of network services, such as firewalls and NAT, that are connected in a virtual chain. Network operators can then set up suites of connected services that use a single network connection. SFC automates the setup of virtual network connections to handle traffic flows for connected services.

1.1184 SFD

Static Filter DWDM

A static filter card used with a DWDM circuit pack.

1.1185 SFM

Switch Fabric Module

1.1186 SFP

Small Form-factor Pluggable

A high-speed, compact, and hot-swappable optical modular transceiver.

1.1187 SFP+

Small Form-factor Pluggable (enhanced)

An enhanced version of SFP that supports data rates up to 10 Gb/s. See also [1.1186 “SFP” \(p. 204\)](#) .

1.1188 SFTP

Secure File Transfer Protocol

A secure file transfer protocol is included with version 2 of the SSH application.

1.1189 SGi

The reference point between the PGW and the PDN.

1.1190 SGSN

serving GPRS support node

SGSN mediates access to network resources, on behalf of mobile subscribers, and implements the packet scheduling policy between different QoS classes. SGSN establishes the Packet Data Protocol context with the GGSN upon activation. See also [1.475 “GGSN” \(p. 109\)](#) .

1.1191 SGW

serving gateway

The SGW is positioned at the edge of the eUTRAN and terminates the connection from the eNodeB.

1.1192 SGW-C

serving gateway - control plane

The SGW that exists in the control plane.

1.1193 SGW-U

serving gateway - user plane

The SGW that exists in the user plane.

1.1194 SHA

secure hash algorithm

A NIST standard hash algorithm, also known as SHA-1.

1.1195 SHCV

subscriber host connectivity verification

A method of using periodic ARP requests and DHCP snooping to maintain connectivity state information for the subscriber hosts on a SAP.

1.1196 SHG

split horizon group

A group of SAPs or spoke SDPs. Members of the group cannot send traffic to each other.

1.1197 SID

Segment Identifier

SIDs are used in segment routing.

1.1198 SIM

Subscriber Identity Module

The SIM card stores the information needed to identify and authenticate the subscriber of a mobile device.

1.1199 SIP

session initiation protocol

An application-layer control (signaling) protocol for creating, modifying, and terminating sessions with one or more participants. These sessions include Internet telephone calls, multimedia distribution, and multimedia conferences.

1.1200 SLA

service-level agreement

An SLA is a service contract, between a network service provider and a customer, which guarantees a specific QoS level. SLAs specify criteria such as network availability and data delivery reliability.

1.1201 SLM

synthetic loss measurement

Ethernet synthetic loss measurement is used to count the number of synthetic [1.683 “LM” \(p. 137\)](#) frames which are not successfully delivered to the specified destinations.

1.1202 SLOF

section loss of frame

A field in a SONET channel frame that indicates the loss of a frame in the section frame sequence.

1.1203 SLOS

section loss of signal

A field in a SONET channel frame that indicates the loss of section signaling.

1.1204 SMA

SubMiniature version A

An SMA is a type of RF coaxial connector.

1.1205 SMF

session management function

The SMF is a fundamental element of the 5G SBA. The SMF performs session management functions that are handled by the MME, SGW-C and PGW-C. The SMF interacts with the user plane that has been decoupled from the control plane, modifies PDU sessions, manages sessions with the UPF, manages the communications for all user plane services, allocates IP addresses to the UEs, and manages the control plane lawful intercept, among other things.

1.1206 SMI

structure of management information

A description of the common structure and identification scheme for the definition of information used to manage TCP/IP-based internetworks. Formal descriptions of the structure are provided using ASN.1. SMI, which is defined in RFC 1155.

1.1207 SMM

Site Monitoring Module

1.1208 SMO

This term is used in template propagation related to wireless provisioning. The Flexi MR BTS model introduces the notion of unordered sets of complex data structures (also known as “SMO lists” or “multi-instance SMO”). These complex data structures are represented as basic managed objects belonging to a list or container object.

1.1209 SMS

short message service

A communication service component of the GSM mobile communication system, using standardized communications protocols that allow the exchange of short text messages between mobile devices.

1.1210 SMTP

simple mail transfer protocol

An application in the TCP/IP suite that manages the sending and receiving of e-mail messages.

1.1211 SN

sequence number

1.1212 SNAP

subnetwork access protocol

An Internet protocol that operates between a network entity in the subnetwork and a network entity in the end system. The SNAP specifies a standard method of encapsulating IP datagrams and ARP messages on IEEE networks. The SNAP entity in the end system uses the subnetwork services and performs three key functions: data transfer, connection management, and QoS selection.

1.1213 SNCI

subnetwork connection (protection) inherent monitoring

1.1214 SNCN

subnetwork connection (protection) non-intrusive monitoring

1.1215 SNCNC

subnetwork connection non-intrusive monitoring client protection

1.1216 sniffer

A software tool that is used to monitor and analyze network traffic for troubleshooting or surveillance purposes.

1.1217 SNMP

Simple Network Management Protocol

A protocol used for the transport of network management information between a network manager and an NE. SNMP is the most commonly used standard for interworking devices.

1.1218 SNMP trap

An SNMP trap is an unsolicited notification that indicates that the SNMP agent on an NE has detected an event, and that the network management domain should be aware of the event. SNMP trap information typically includes alarm and status information, and standard SNMP messages.

1.1219 SNMP trap log ID

SNMP trap log ID is the ID of a log. A valid log ID must exist for alarms and traps to be sent to the trap receiver.

1.1220 **SNTP**

Simple Network Time Protocol

A rudimentary version of NTP with only the features that devices commonly require.

1.1221 **SOAP**

Simple Object Access Protocol

An XML-based protocol for the exchange of information in a decentralized, distributed environment.

1.1222 **SON**

self-organizing network

SON is a 3GPP standard for LTE RAN that includes functions such as self-optimization, self-healing, [1.101 “ANR” \(p. 59\)](#), and [1.970 “PCI” \(p. 176\)](#).

1.1223 **SONET**

synchronous optical network

SONET is an ANSI standard for fiber optic transmission of high-speed digital traffic. SONET allows internetworking of transmission products from multiple vendors and defines a physical interface, optical line rates known as OC signals, frame format, and an OAM protocol. The base rate is 51.84 Mb/s (OC-1), and higher rates are multiples of the base rate.

SONET uses synchronous high-speed signals and provides easy access to low-speed signals by mapping them into VTs.

SONET is a North American standard that is technically consistent with SDH, which is an international standard.

1.1224 **SPB**

shortest path bridging

SPB, defined in IEEE 802.1aq, simplifies how customers create and configure networks—across the enterprise and for the cloud— by requiring service provisioning only at the edge of the network. It uses IS-IS to dynamically build the topology between NEs, enabling multipath routing and virtually eliminating human error.

1.1225 **SPF**

shortest path first

SPF is an algorithm used by IS-IS and OSPF to make routing decisions based on the state of network links.

1.1226 spoofing

A technique used to gain unauthorized access to devices, whereby the intruder sends messages using a source IP address that appears to come from a trusted host.

In IP spoofing, an IP packet is generated with a false source IP address that was not assigned by the PGW in order to hide the identity of the UE or impersonate another computing system.

1.1227 SPT

shortest path tree

SPT is an algorithm used by PIM to make routing decisions based on the state of network links.

1.1228 SPV

set parameter values

Type of TR-069 RPC method.

1.1229 SQL

structured query language

A specialized language for accessing relational databases.

1.1230 SR

SR is expanded in three ways:

1. short reach

An optical interface specification for distances of less than 2 km.

2. service router

A network router, for example, the 7750 SR, that supports the creation of IP and MPLS network-layer services such as IES and VPRN services.

3. segment routing

Segment routing adds to the IS-IS and OSPF routing protocols the ability to perform shortest path routing and source routing using the concept of abstract segment.

1.1231 SRGB

Segment Routing Global Block

1.1232 SR TE

segment routing with traffic engineering

1.1233 **SRLG**

shared risk link group

A situation in which links in a group share a common attribute, whose failure may affect all of the links in the set.

1.1234 **SRRP**

Subscriber Routed Redundancy Protocol

A set of functions and messaging protocols that allows a system to create a set of redundant gateway IP addresses shared by local and remote NEs.

1.1235 **srTCM**

single rate three color marking

1.1236 **SSAP**

source service access point

1.1237 **SSD**

source statistics descriptor

The characteristic of traffic in the conversational UMTS traffic class. The SSD can be either speech or unknown.

1.1238 **SSG**

service selection gateway

The SSG provides policy-driven traffic steering and service chaining, which provides the network carrier with the ability to quickly introduce new services and the flexibility to introduce value-added services to the user traffic path.

1.1239 **SSH**

secure shell

The SSH protocol is used to protect communication between two hosts by encrypting a Telnet, FTP, or SCP connection between the NEs. Both ends of the connection are authenticated, and passwords are encrypted.

1.1240 **SSH2**

SSH version 2

SSH2 is a more secure, efficient, and portable version of SSH that includes SCP. See [1.1239 “SSH” \(p. 211\)](#) .

1.1241 SSID

Service Set Identifier

An SSID is the name of a wireless local area network (WLAN). All wireless devices on a WLAN must use the same SSID in order to communicate with each other.

1.1242 SSL

Secure Sockets Layer

A security protocol that is deprecated by the IETF, and replaced by [1.1312 “TLS” \(p. 221\)](#).

1.1243 SSLF

section synchronization line failure

A SONET alarm that indicates a failure of the frame synchronization for a section.

1.1244 SSM

SSM can be expanded in the following ways:

- source-specific multicast
An extension of PIM that enables a receiving client to obtain content directly from the source rather than from the shared RP.
- synchronous status message

1.1245 SSO

single sign on

1.1246 SST

secondary state

1.1247 SSU

synchronization supply unit

A timing synchronization unit that filters and distributes synchronization signals to local equipment.

1.1248 STa

The interface between the 3GPP AAA proxy/server and the TWAN. The STa reference point is used to authenticate and authorize the UE, to transport PMIPv6, and to transport charging-related information and information about IP mobility mode selection.

1.1249 **standby**

A standby database or standby server is an NFM-P component that is not currently in service, but provides protection for the active system. For example, the standby server is a system that can read and write to the active database. However, it is in standby mode, and ignores events from the network. An NFM-P client cannot connect to a standby server.

1.1250 **STAR**

Self-Tuned Adaptive Routing

A load-balancing and optimal-path-placement algorithm used by the NRC-P.

1.1251 **static host**

See [1.1253 “static subscriber host” \(p. 212\)](#) .

1.1252 **static MAC**

A MAC address that is manually configured in a FIB, rather than dynamically learned. Static MAC addresses are assigned to network objects such as SAPs, SDPs (service circuits), or endpoints.

1.1253 **static subscriber host**

A host that is explicitly configured on a SAP rather than through a dynamic learning process.

1.1254 **station**

A generic term for a physically discrete piece of processing or transmission equipment, for example, a personal computer or mobile communication relay agent. See also [1.1440 “workstation” \(p. 240\)](#) .

1.1255 **statistics**

Statistics are the quantitative data collected by the NFM-P for entities such as equipment, network protocols, interfaces, and alarms.

1.1256 **STB**

See [1.1182 “set-top box” \(p. 204\)](#) .

1.1257 **STE**

section terminating equipment

SONET equipment that originates, accesses, modifies, or terminates section header information.

1.1258 STM

STM is expanded two ways:

1. service test manager

An NFM-P facility that allows the manual creation and automatic generation of tests and test suites. STM tests and test suites can be run on demand or scheduled to run periodically on services and service transport components for SLA QoS validation and troubleshooting.

2. synchronous transfer mode

The synchronous end-to-end transmission of data or voice containers in a network. STM is a component of SDH.

1.1259 STM-N

synchronous transfer mode - level *N*

An SDH signal carried at the speed of *N*; for example, STM-4 is a signal at 622.08 Mb/s.

1.1260 STP

Spanning Tree Protocol

The STP is specified in IEEE 802.1D. This protocol automatically ensures a loop-free topology in any interconnection of Ethernet LAN or WAN devices.

1.1261 STP 1x1 mode

The STP 1x1 mode is a proprietary implementation of the STP that applies a single spanning tree instance per VLAN.

1.1262 STP flat mode

The STP flat mode applies a single spanning tree instance per switch. In the STP flat mode, when you choose MSTP as the STP mode, you can configure MSTIs in addition to the CST instance. Each MSTI is mapped to a set of VLANs. Therefore, flat mode supports the forwarding of VLAN traffic over separate data paths.

1.1263 strict priority

In strict priority scheduling, each CoS queue associated with the egress port is serviced in priority order from highest 7 to lowest 0. All traffic for a specific CoS is transmitted before the scheduler proceeds to the next highest priority queue. The purpose of strict priority scheduling is to ensure lower latency and priority transmission of critical traffic by always transmitting higher priority traffic before lower priority traffic.

1.1264 STS

synchronous transport signal

The electrical equivalent of the SONET optical signal. In SDH, STS is known as STM.

1.1265 subscriber

In the NFM-P, a subscriber represents a unique identifier that associates a group of end-user devices with policies and resources.

1.1266 subscriber host

In the NFM-P, a subscriber host is an end device, such as a set-top box, that receives the network traffic. See also [1.527 “host” \(p. 116\)](#).

1.1267 subscriber instance

In the NFM-P, a subscriber instance refers to the instantiation of a specific subscriber and the associated policies on a device. A subscriber may have multiple subscriber instances in a network, but only one instance on a specific NE.

1.1268 SVLAN

service provider VLAN

1.1269 SVN

software version number

1.1270 sVOA

slow variable optical attenuator

1.1271 switch

Switches are Layer 2 devices that make it possible for several users to send information over a network at the same time without slowing each other down. Switches allow different NEs to communicate directly with one another in an efficient manner.

1.1272 switch fabric processor

A processor that handles traffic passing through the switch fabric.

1.1273 switchover

Switchover is the process of switching the roles of a redundant system; for example, switching the roles of an active and standby database. A switchover is reversible.

1.1274 SWm

The reference point between the EPDG and 3GPP AAA server. SWm uses Diameter protocol for communication.

1.1275 SWu

The reference point between the UE and EPDG. SWu uses the IPsec tunnel to carry bearer traffic between the UE and EPDG.

1.1276 SWw

The interface between the UE and the TWAN.

1.1277 Sx

Sx is the reference point between a control plane function and a user plane function. An Sx session is established between control plane and user plane functions to provision rules, such as URR or QER, on how to process certain traffic.

The Sx interface utilizes the PFCP for control traffic and the GTP-U protocol for any data traffic between the control plane and user plane functions.

The 7750 SR MG and CMG can be configured as control plane functions (SGW-C, PGW-C, or combined SGW/PGW-C) that can manage all control signaling; likewise, the 7750 SR MG and CMG can be configured as user plane functions (SGW-U, PGW-U, or combined SGW/PGW-U) that can manage all user plane traffic.

The Sx interface consists of the following interfaces:

- Sxa—used for communication between the SGW-C and the SGW-U
- Sxb—used for communication between the PGW-C and the PGW-U
- Sxab—used for communication between the combined SGW/PGW-C and the SGW/PGW-U

1.1278 SX3LIF

split X3 interworking function

Split X3 LI interworking function is an LI-specific functional element that can be colocated with a user plane function (SGW-U and PGW-U), a control plane function (SGW-C and PGW-C), or can be a standalone point.

The user plane duplicates the user plane packets of the traffic to be intercepted, as instructed by the control plane, and then sends the duplicated packets to the SX3LIF over the X3 reference point. The control plane provides the intercept control information (such as correlation identifier, target identity, and intercepted packet identification rules) to the SX3LIF over the X3 reference point. The SX3LIF associates the user plane packets with the target interception based on the IRI that it receives from the control plane and then delivers the content of communications to the DF3 over the X3 reference point.

1.1279 SYN

synchronize

SYN is a message that is sent by TCP during the initiation of a new connection to synchronize the TCP packet sequence numbers on the connecting computers. The SYN is acknowledged by a SYN/ACK from the responding computer.

1.1280 SYN/ACK

synchronize acknowledged

An SYN/ACK is a message that is sent by TCP during the initiation of a new connection in response to a synchronization attempt from another computer.

1.1281 SyncE

See [1.1282 “Synchronous Ethernet” \(p. 216\)](#) .

1.1282 Synchronous Ethernet

An ITU-T standard for transmitting clock signals over an Ethernet network. Clock signals are traceable to an external master clock that meets certain accuracy requirements.

1.1283 syslog

A message logging standard used by network devices to send event messages to a logging server (syslog). Syslog separates the software that generates the messages, the system that stores them, and the software that reports and analyzes them.

T

1.1284 T1

A 1.544-Mb/s point-to-point dedicated digital circuit provided by the telephone companies in North America.

1.1285 T6c

The reference point between the PGW and the SCEF. The SCEF uses the T6c reference point to send a request to the PGW. The request contains the UE IP address and the APN. The response contains the host name of the PCRF and the PCEF (the PGW).

1.1286 T-LDP

Targeted-Label Distribution Protocol

An LDP session between indirect connect peers.

1.1287 T-PE

termination-provider edge

In [1.793 “MS-PW” \(p. 152\)](#) routing, termination-provider edge NEs are the endpoints of the MS-PW service. T-PEs are configured with PW SDPs that connect to [1.1130 “S-PE” \(p. 197\)](#) NEs.

1.1288 TAC

TAC is expanded in the following ways:

1. technical assistance center

The front end, or customer-facing, product support structure in which the first- and second-level support reside.

2. tracking area code

3. type allocation code

The first eight-digit part of the 15-digit IMEI and 16-digit IMEISV codes that is used to uniquely identify wireless devices.

1.1289 TACACS+

terminal access controller access control system

A remote user authentication, authorization, and accounting protocol.

1.1290 TAF

time-average-factor

Specifies a weight factor between the previous shared buffer average utilization and current shared buffer instantaneous utilization when a new shared buffer average utilization is calculated.

1.1291 TAI

tracking area identity

An identity used to identify tracking areas, composed of a TAC, an MNC, and an MCC. See 3GPP TS23.003 Section 19.4.2.3.

1.1292 TAI

Target Attachment Individual Identifier

1.1293 TAU

tracking area update

1.1294 TCA

Threshold-crossing alert

A TCA occurs when a statistics counter value crosses the defined threshold during a 15-min interval.

1.1295 TCE

trace-collection entity

1.1296 TCN

topology change notification

A bridge uses TCN BPDUs to notify the root bridge about a detected topology change.

1.1297 TCP

Transmission Control Protocol

TCP is a protocol used, along with the IP, to send data in the form of message units between computers over the Internet. While IP takes care of handling the actual delivery of the data, TCP takes care of keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

1.1298 TCP/IP

transmission control protocol/Internet protocol

TCP/IP is a set of protocols that link different computers across many kinds of networks. It is commonly used over subnetworks, including Ethernet, ATM, frame relay, and leased line. TCP corresponds to the network layer and transport layer of the OSI model. It is a multivendor, non-proprietary standard.

1.1299 TDF

traffic detection function

TDF enables carriers to create personalized application-based services that match subscriber preferences, such as gaming, social networking, and video streaming, by allowing operators to identify subscribers and their applications, content use, and devices. The personalized service also allows for individualized subscriber pricing plans.

1.1300 TDM

time division multiplexing

Multiplexing in which a separate periodic time interval is allocated to each tributary channel in a common aggregated channel.

1.1301 TE

traffic engineering

The process of selecting the paths from one node to another to provide efficient and reliable network operations while considering bandwidth availability and traffic characteristics in an MPLS network.

1.1302 TED

traffic engineering database

A TED is a database used by CSPF for storing route constraint information.

1.1303 TEDB

TE database

1.1304 TEI

transport error indicator

1.1305 TEID

tunnel endpoint identifier

The TEID is a 32-bit field that is present in the GTP header and indicates to which tunnel a T-PDU belongs. The GTP-U multiplexes different packets between a given pair of tunnel endpoints.

1.1306 telco

telephone company

A company that provides local, or local and long-distance, telephone services.

1.1307 Telnet

Telnet is an application in the TCP/IP suite that provides remote terminal connection service. It allows a user at one site to interact with a timesharing system at another site as though the user terminal directly connects to the remote system.

1.1308 Template

Templates based on standard network and service configurations can be used to provision network services.

Attach a template to a service to configure multiple parameters at one time, configure parameters not available in the Service Fulfilment application, or apply the same parameter values to multiple services.

A template can be created in the Policy Management application, or can be requested through Nokia Professional Services.

1.1309 TI-LFA

See [1.670 “LFA” \(p. 135\)](#).

1.1310 tiered architecture

Tiered architecture refers to the way in which the GUI and the network management components use a Java-based technology that provides distributed, secure, and scalable applications. The tiered architecture allows for scaling and fair load balancing, which improves performance.

1.1311 TISPAN

telecommunications and Internet converged services and protocols for advanced networking

TISPAN is the ETSI core competence center for all aspects of standardization for fixed and converged networks, including NGNs. TISPAN defines standards for service aspects, architectural aspects, protocol aspects, QoS support, security-related matters, and mobility aspects within fixed networks to meet the business requirements and commercial objectives of the ETSI members. ETSI TISPAN writes the key standard specifications that define the fixed and converged networks as well as the NGN architecture.

1.1312 TLS

TLS is expanded two ways:

1. Transparent LAN Service

A network service that links remote Ethernet networks to provide the appearance and functions

of one contiguous network to users, regardless of the underlying technology.

2. Transport Layer Security

A security protocol that replaces the deprecated [1.1242 “SSL” \(p. 212\)](#) protocol. TLS provides communication security, privacy, and message integrity over a computer network, and is used in applications such as web browsing, e-mail, and instant messaging.

The NFM-P uses TLS to encrypt the communication between system components.

1.1313 TLV

type length value

Traffic engineering information is carried by signaling objects, such as LDPs. The type, length, and values of this traffic engineering information is specified in the TLV.

1.1314 TMA

tower mounted amplifier

A tower mounted amplifier is a low-noise amplifier for [1.183 “BTS” \(p. 70\)](#) .

1.1315 TMF

telemanagement forum

A non-profit global organization that provides leadership, strategic guidance, and practical solutions to improve the management and operation of information and communications services.

1.1316 TMN

telecommunications management network

A TMN is an industry-standard model defined by the ITU-T for the layering of management functions in telecommunications networks.

TMN is a network that interfaces with a telecommunications network at several points to receive information from, and to control the operation of, the telecommunications network. A TMN may use parts of the managed telecommunications network to provide for the TMN communications.

1.1317 TMS

threat management system

A TMS is a server that identifies and removes network and application-layer attacks without interrupting the flow of legitimate traffic.

1.1318 TNC

tech non-conformant

1.1319 TOA

transport stream off-air

1.1320 TOADM

tunable optical add/drop multiplexer

A tunable [1.1099 “ROADM” \(p. 192\)](#) that yields the ultimate in operational flexibility, especially when used in conjunction with transponders with tunable wavelength lasers.

1.1321 ToS

type of service

An eight-bit field in an IP packet header that contains a three-bit IP precedence value or six-bit DSCP value. This value is used to identify the level of service that a packet receives in the network.

1.1322 T-PDU

The inner IP packet in a GTPv1-U packet.

1.1323 TPM

Template Provisioning Manager

1.1324 TPMR

two port MAC relay

1.1325 TPS

transmission protection switching

1.1326 TPSDA

triple play service delivery architecture

A model of service delivery for triple play that attempts to guarantee delay, jitter, and packet loss characteristics. TPSDA provides QoS customization for high-speed Internet data services with per-user bandwidth controls.

1.1327 Traffica

Traffica is a PCMD collector and post-processing and analyzing node and real-time network analytics tool. Traffica provides monitoring and troubleshooting while giving insights into traffic, network, locations, devices and subscribers. It helps all areas of the operator organization – from operations and engineering to customer care and marketing – acquire insights from the subscriber perspective.

1.1328 transit bridge

An Ethernet switch that resides inside the service provider network and provides a connection between multiple provider networks. The transit bridge uses the same SVLAN on two or more network ports. This SVLAN does not terminate on the switch. Traffic that ingresses a network port is switched to other network ports. The same switch can also function as both a PE bridge and a transit bridge.

1.1329 transit SAP

An access interface on a VLL or VPLS that forwards traffic with any encapsulation values transparently through the service.

1.1330 transit service

A service tunnel that uses transit SAPs to pass traffic for existing VLL or VPLS data services or composite services.

1.1331 transport tunnel

Routers are connected to physical links that are used to carry traffic. When a service is set up using MPLS, transport LSP tunnels are set up between Provider Edge routers. Each service or customer sends traffic through a service tunnel within the transport LSP tunnel. Transport tunnel LSPs are identified by MPLS labels that are swapped at each intermediate NE, or transit LSR, along the LSP from the ingress to the egress of the MPLS network.

1.1332 TRDU

transceiver duplexer unit

1.1333 triple play

Triple play refers to the offering of voice, video and data applications over the same network connection. Triple play services are available through technologies that range from DSL to broadband wireless connections.

1.1334 trTCM

two rate three color marking

1.1335 TRU

top rack unit

1.1336 TTL

time-to-live

A field in an IP header that specifies the maximum number of hops for a data packet before the packet expires and is discarded.

1.1337 TU-N

tributary unit - level *N*

The basic unit of an SDH payload, which includes management overheads and synchronization data. The TU consists of a virtual container and a TU pointer. It provides a unit of bandwidth that is required to convey a T1- or E1-framed carrier.

1.1338 TUG

tributary unit group

A TUG consists of identical TUs. A multiplexing scheme that is used to assemble the TUs into a higher unit of bandwidth.

1.1339 tunnel

A method of setting up a communication session between two or more points that hides the complexity of the underlying technologies.

1.1340 tuple

In programming languages, a tuple is an ordered set of values. The delimiter for each value is often a comma, depending on the rules of the specific language. As a data type, a tuple can be used to pass a string of parameters from one program to another.

1.1341 TWAG

trusted WLAN access gateway

A trusted WLAN access gateway that interfaces with the PGW using the S2a interface. In a trusted access, the UE is connected through a TWAG in the Wi-Fi core, and the TWAG is connected with the PGW using a secure GTP tunnel. The TWAG also acts as a DHCP server for the UE.

1.1342 TWAMP

two-way active measurement protocol

Two-way Active Measurement Protocol (TWAMP), based on the One-way Active Measurement Protocol (OWAMP), adds two-way or round-trip measurement capabilities. The TWAMP measurement architecture is usually comprised of two hosts with specific roles. Devices that implement TWAMP provide the capability to identify performance issues on all IP network segments. TWAMP initiates a control session between any two points in the network using TCP and then sends a test session using UDP packets. The UDP test packets are sent from the client and are reflected by the server, providing a round-trip measurement.

1.1343 TWAN

trusted WLAN access network

The TWAN provides access for UEs across a trusted non-3GPP access network. When the WLAN is considered as trusted by the network operator, the TWAN is interfaced with the EPC as a trusted non-3GPP access to the PGW using the S2a interface, and to the 3GPP AAA server/proxy using the STa interface.

1.1344 TWL

TWAMP Light

TWAMP Light tests target Layer 3 interfaces. See [1.1342 “TWAMP” \(p. 225\)](#).

1.1345 Tx

transmit

U

1.1346 u-plane

See [1.1365 “user plane” \(p. 229\)](#) .

1.1347 UBR

unspecified bit rate

UBR is an ATM service category that is used for applications, which do not require guarantees of low cell loss or low delay. Specifically, UBR does not include the notion of a per-connection negotiated bandwidth. No numerical commitments are made with respect to the cell loss ratio experienced by a UBR connection, or as to the cell transfer delay experienced by cells on the connection. UBR emulates the connectionless services provided by conventional bridged and routed data networks. It provides best effort delivery.

1.1348 UBT

Ultra Broadband Transceiver

1.1349 UCT

universal coordinated time

UCT is also known as Greenwich Mean Time.

1.1350 UDM

unified data management

The UDM performs some HSS functions, such as user identification, access authorization, and subscription management.

1.1351 UDP

User Datagram Protocol

A minimal transport protocol above the IP network layer that does not guarantee datagram delivery. The UDP is used by applications that do not require the level of service of TCP or that need to use communications services, such as multicast or broadcast delivery, which are not available from TCP.

1.1352 UE

user equipment

The mobile unit, which allows a user to access network services. The UE connects to the UTRAN or eUTRAN through a radio interface.

1.1353 UI

user interface

See [1.509 “GUI” \(p. 114\)](#) .

1.1354 UIC

unit ID code

A field in an MDL message that identifies the CSU or DSU of the originating equipment.

1.1355 UICC

universal integrated circuit card

A smart card that maintains the security of personal data and is employed in mobile terminals in GSM and UMTS networks.

1.1356 ULI

user location information

1.1357 UMTS

Universal Mobile Telecommunication System

1.1358 UNI

user-network interface

UNI is an interface point between ATM end users and a private ATM switch, or between a private ATM switch and the public carrier ATM network. The physical and protocol specifications of the ATM Forum UNI documents define the standard for a connection between end stations and a local ATM network switch.

A switch UNI is a port that resides on a PE bridge and that connects to a customer network and carries customer traffic. The UNI may consist of a single port or a group of ports, and can accept tagged or untagged traffic.

1.1359 UNIVTRM

universal transmission

1.1360 UNIX

A multi-user, multitasking OS on which Linux is modeled.

1.1361 UPF

user plane function

1.1362 URPF

Unified reverse path forwarding

1.1363 URL

uniform resource locator

1.1364 URR

usage reporting rule

The URR is a usage reporting rule for processing data traffic that instructs the user plane function to measure and report traffic usage, within the context of CUPS. The URR is a rule that is provisioned by the Sx reference point when it establishes a session between the control plane and user plane functions.

1.1365 user plane

The portion of a telecommunications network that is involved with user traffic, including voice, data, and video. See also [1.1346 “u-plane” \(p. 227\)](#) .

1.1366 user VPLS

A VPLS that contains SAPs that receive multicast traffic from an MVR VPLS.

1.1367 USM

user service manager

A GUI application for a management system. It usually functions as a manager towards an information manager application, but it may also connect directly with the managed system.

1.1368 USRPNL

user interface panel

1.1369 USU

used service unit

1.1370 UTC

Coordinated Universal Time

primary time standard by which the world regulates clocks and time

1.1371 UTRAN

universal terrestrial radio access network

UTRAN consists of RNCs and NodeBs of a UMTS network. UTRAN allows connectivity between the UE and the core network.

1.1372 UWAN

untrusted wireless access network

V

1.1373 VACM

view-based access control model

A model of the access control subsystem of an SNMP engine, which defines a set of services that an application can use for checking access rights.

1.1374 VAS

vendor-specific attribute

An attribute that is set by a remote-server vendor to allow a vendor-specific extension of existing remote server attributes.

1.1375 VBR

variable bit rate

VBR is an ATM service category that provides guaranteed low cell loss and low delay for applications such as video and frame relay, and is characterized by an on/off source with known, predictable transmission patterns. During the on period, cells are transmitted at the peak information rate. No cells are transmitted during the off period.

VBR supports VBR data traffic with average and peak traffic parameters.

VBR is intended for applications that generate bursty traffic at a rate that varies with time. There are two service categories in VBR. The first is rt-VBR and is used by real-time applications. The second one is nrt-VBR and is intended for non-real-time applications.

See also [1.877 "nrt-VBR" \(p. 163\)](#) and [1.1123 "rt-VBR" \(p. 195\)](#).

1.1376 VC

virtual connection

A technique ensuring that packets are delivered to the correct recipient in the same order as they were submitted.

1.1377 VCB

voice conference bridge

The voice conference bridge application provides a simultaneous communication path between two or more voice circuits. VCBs are deployed in a central location with remote devices connected to the bridge via an NE over an IP/MPLS or TDM network. Inputs to the VCB are 4-wire E&M analog interfaces.

VCBs can be used as a conference bridge with any-to-any connectivity (all branches participate) or as a bridge in broadcast mode where one branch broadcasts to the other branches that are in listen-only mode.

1.1378 VCC

virtual channel connection

A VCC is the series of cross-connections used to traverse an ATM network end-to-end. This ATM concept describes a type of path through an ATM network, defined by its VPI and VCI values.

VCCs represent a specific instance of a PVC, SPVC, or SVC. They are formed as a concatenation of one-hop connections that are cross-connected on workgroup switches. VCCs are unidirectional. They do not use bandwidth if there is no data to transmit.

1.1379 VCI

virtual channel identifier

The VCI is part of the address of a VCC. The complete address of the VCC consists of the VCI and the VPI. A unique numerical tag, as defined by a 16-bit field in the ATM cell header, identifies a virtual channel, over which the cell is to travel. VCIs are assigned for one hop only. Each switch cross-connects cells from one VC to the next, reassigning VCIs.

1.1380 vCPAA

virtual control plane assurance adaptor

1.1381 vertex

In the context of an NFM-P map, an object other than a link between objects. Network elements and NE groups are examples of vertexes.

1.1382 VHO

video head end office

The VHO is where the video server complex resides.

1.1383 VID

VLAN Identifier

A VID is a 12-bit field in an Ethernet frame that uniquely identifies the VLAN to which the frame belongs.

1.1384 VINES

virtual networking system

1.1385 virtual link

Virtual links connect separate elements of a backbone, and function as if they are unnumbered point-to-point networks between two devices. A virtual link uses the intra-area routing of its transit area (the non-backbone area that both devices share) to forward packets.

1.1386 VLAN

virtual LAN

A logical grouping of two or more NEs, which are not necessarily on the same physical network segment, but which share the same IP network number.

1.1387 VLAN stacking

VLAN stacking provides a mechanism to tunnel multiple customer VLANs through a service provider network, using one or more stacked VLANs that use 802.1Q double-tagging or VLAN translation. VLAN stacking allows service providers to offer their customers TLS. This service is multipoint to support multiple customer sites or networks, which are distributed over the edges of a service provider network.

1.1388 VLAN uplink

A logical object in the NFM-P that is automatically created between SAPs on two NEs which have a physical link and are on the same service. VLAN uplinks are also automatically created when the underlying transport mechanism is a transit service or composite transit service, rather than a direct physical link.

1.1389 VLL

virtual leased line

A virtual leased line is a type of VPN where IP traffic is transported in a point-to-point manner.

1.1390 VLR

Visitor Location Register

A database that stores information about all the mobiles under the jurisdiction of a Mobile Switching Centre (MSC), which the database serves. See 3GPP TS23.002 Section 4.1.1.2.*

1.1391 VM

virtual machine

1.1392 VMG

Virtual Mobile Gateway

The software-only version of the 7750 SR MG. Also known as CMG (cloud mobile gateway).

1.1393 VMM

Virtual Mobility Manager

The software-only version of the 9471 WMM.

1.1394 VNF

Virtual Network Function

A virtualized network element that represents a physical node.

1.1395 VNFC

Virtual Network Function Component

1.1396 VNI

VXLAN Network Identifier

1.1397 VNID

See [1.1396 "VNI" \(p. 234\)](#) .

1.1398 VoD

video on demand

An application that provides a specific, non-broadcast video stream to an end user. Triple play service sometimes includes VoD.

1.1399 VoIP

Voice over Internet Protocol

A telephone service that uses the Internet as a global telephone network. VoIP is typically part of a triple play service.

1.1400 VoLTE

voice over LTE

Voice and SMS services over an LTE network using IMS.

1.1401 VPA

VLAN port assignment

By default, all switch ports on an OmniSwitch are non-mobile ports that are manually assigned to a specific VLAN and can only belong to one VLAN at a time. When a port is defined as a mobile port, switch software compares traffic coming in on the port with configured VLAN rules. If any of the mobile port traffic matches any of the VLAN rules, the port and the matching traffic become a member of that VLAN.

1.1402 VPC

virtual path connection

A VPC is a series of linked VPs that extend between the point where the VCI values are assigned and the point where those values are translated or removed.

A VPC carries VCCs between sites. VPC traffic is carried on full ATM trunks. VPCs use physical bandwidth only when the end devices pass traffic over the network; they do not use bandwidth if there is no data to transmit.

A VPC is a concatenation of VP links. The endpoints of a VPC are the points at which the ATM payload is passed to, or received from, the users of the ATM layer.

1.1403 VPI

virtual path identifier

The VPI is an 8-bit field in the ATM cell header, which indicates the virtual path over which the cell should be routed.

The VPI is assigned on a connection set up by the devices at the two ends of a hop. Multihop VPC paths use multiple VPIs to go from source to destination. Each switch that the VPC traverses cross-connects the VPC from one port and VPI to another port and VPI.

1.1404 VPLS

virtual private LAN service

A VPLS is a type of VPN in which a number of sites are connected in a single bridged domain over an IP/MPLS network. The services may be from different locations, but in a VPLS, they appear to be on the same LAN.

When implemented with Layer 2 interfaces, this service is called VPLS. When implemented with Layer 3 interfaces, this service is called an IP-VPN.

1.1405 VPM

VLAN port membership

Mobile ports on an OmniSwitch can join more than one VLAN. However, certain rules, such as MAC address rules, can limit port membership to one VLAN.

1.1406 VPN

virtual private network

A private network that is configured within a public network (a carrier network or the Internet) takes advantage of the economies of scale and management facilities of large networks. VPNs are used by enterprises to create WANs that span large geographic areas in order to provide site-to-site connections to branch offices, and to allow mobile users to dial up their company LANs.

1.1407 VPRN

virtual private routed network

A network exhibiting at least some of the characteristics of a private network, even though it uses the resources of a public switched network.

1.1408 VPWS

Virtual Private Wire Service

1.1409 VQM

video quality monitoring

VQM monitors video quality in the stages of transmission just prior reaching the STB.

1.1410 VRF

virtual routing and forwarding

A logical or virtual routing function, with an associated routing table, which can be instantiated in a device capable of supporting IP VPN services.

1.1411 VRID

virtual router ID

A number that is used with an IP address to uniquely identify the virtual router created using VRRP. Only one VRID can be used in a VLAN.

1.1412 VRRP

Virtual Router Redundancy Protocol

VRRP is a protocol to provide redundancy in statically defined routed networks, rather than in dynamically defined networks, such as RIP and OSPF. VRRP is an election protocol that dynamically assigns responsibility for one or more virtual router(s) to the VRRP router(s), allowing several routers on a multiaccess link to utilize the same virtual IP address. A VRRP router is configured to run the VRRP protocol in conjunction with one or more other routers.

1.1413 VRS

Virtual Routing and Switching

VRS is a service solution is implemented and monitored by the VSD.

1.1414 VSAP

Virtualized Services Assurance Platform

VSAP provides the network management component for the Nokia Data Centers Service Delivery solution. VSAP provides network management functionality using web-based applications. The

applications provide inventory management, network fault monitoring, troubleshooting purposes, and policy creation. The applications are external to the NFM-P client GUI and do not require a local client installation.

1.1415 VSC

Virtualized Services Controller

The VSC is the data center network control plane. The VSC manages virtual routing and switching elements to program the network forwarding plane. The VSC communicates with the VSD policy engine using XMPP.

1.1416 VSD

Virtualized Services Directory

The VSD is a policy-based system which can be used for creating virtualized services and provisioning them on the 7850 VSG. It has a web-based UI for administrator and tenant onboarding. The VSD is responsible for user management databases, policy creation, and cross-system interfaces. The VSD represents the user- or service-based outward functionality of the data center network.

1.1417 VSI

virtual switch instance

1.1418 VSM-CCA

versatile service module cross-connect adapter

The VSM-CCA is a type of MDA for the 7450 ESS and 7750 SR that provides an extra set of egress and ingress forwarding paths through a set of virtual ports. This design eliminates the need for a physical port MAC address, cable, or other MDA-specific component.

1.1419 VSP

Virtualized Services Platform

VSP is a software-defined networking solution that provides data center network virtualization and manages connectivity between compute resources.

1.1420 VSR

Virtual Service Router

A software-only version of the 7750 SR.

1.1421 VT

virtual trunk

An aggregation of ATM VCs. All connections on a VT map to a single VPC with a public network-assigned VPI.

1.1422 VT-N

virtual tributary - level *N*

A SONET format for mapping a lower-rate signal into a SONET payload; for example, VT1.5 is used to transport a DS-1 signal.

1.1423 VTEP

[1.1427 “VXLAN” \(p. 237\)](#) Tunnel End Point

1.1424 VTG

virtual tributary group

One or more virtual tributaries of the same rate that are bundled into an STS-1 payload.

1.1425 VTL

velocity template language

1.1426 VWM

Versatile WDM Module

See [1.5 “1830 VWM” \(p. 45\)](#) .

1.1427 VXLAN

Virtual Extensible LAN

W

1.1428 WAN

wide-area network

A geographically dispersed, long-haul telecommunications network that usually consists of backbone links. A WAN may be privately owned or leased. The term usually connotes the inclusion of public networks that are highly regulated, and provides superior reliability and resilience.

1.1429 WDM

Wavelength Division Multiplexing

Several signals (or channels) are transported simultaneously over one fiber but at different wavelengths without interaction. Each channel is usually [1.1300 "TDM" \(p. 220\)](#). The capacity of a WDM system is thus given by the number of wavelengths \times the bit rate of the [1.1300 "TDM" \(p. 220\)](#) channel.

1.1430 web services

Web services are network functions that can be accessed through a standard interface. For example, the XML metalanguage and the SOAP protocol allow the definition and transmission of messages between software components that run on heterogeneous platforms. This allows development teams to independently build components that run as distributed, independent implementations, linked only by their XML interfaces.

1.1431 WFF

weighting factor file

1.1432 WFQ

weighted fair queuing

Weighted fair queuing classifies all current traffic flows on an interface. Packets are sorted into flows based on a number of criteria such as MAC addresses, IP addresses, ports, priority codes (e.g., DiffServ, 802.11p), VLANs, and even DLCIs. These flows are then assigned to either a low-volume or high-volume queue. Interactive traffic, such as Telnet, is almost always placed in the low-volume queue; high-volume flows, such as FTP or HTTP, are placed in high-volume queues. The low-volume and high-volume queues are then serviced in a WRR manner, meaning that 20 low-volume packets might be processed for every high-volume packet. This type of queuing is weighted, but it allows each queue fair access to the interface.

1.1433 Wi-Fi offload

Wi-Fi offload is a process by which traffic or data on a cellular network is offloaded to an available wireless network.

1.1434 **window**

A window is a form, panel of information, equipment drawing, or graphic that appears on a screen. A window commonly allows an operator to enter data and initiate functions, but some windows only display information.

1.1435 **WLAN GW**

wireless local area network gateway

A WLAN is a network to which users can establish a wireless connection via an access point within the coverage area.

1.1436 **WO**

work order

A WO is an XML file that contains eNodeB configuration data. WOs are created by the [1.56 “9952 WPS” \(p. 52\)](#) and deployed by the NFM-P to eNodeBs.

1.1437 **workflow**

The NFM-P workflow is a defined series of tasks that describe how to install, configure, create, and manage services.

1.1438 **working directory**

The working directory contains image and configuration files that may or may not be the same as the files in the certified directory. The working directory is a holding place for new files. Files in the working directory must be tested before they can be committed to the certified directory. You can save configuration changes to the working directory. See also [1.218 “certified directory” \(p. 75\)](#).

1.1439 **working panel**

The working panel is a component of the NFM-P GUI that can include windows, drawings, and configuration forms.

1.1440 **workstation**

A computer system with a local set of input and output devices, such as a keyboard and monitor.

1.1441 **WPP**

web portal protocol

The WPP is used for web portal authentication of WLAN users (DHCP host) and runs between a BNG and a web portal server.

1.1442 WR2-88

2-degree, 88-channel wavelength router card

1.1443 WRED

weighted random early detection

WRED is a variation of RED, but instead of dropping packets randomly when there is high traffic congestion, the packets are dropped based on traffic priority.

1.1444 WRR

weighted round robin

This queuing technique creates a number of queues and allows a user to assign incoming traffic to each queue by some distinguishing factor. This could be service class, address, protocols, or any other number of factors. To ensure each queue is serviced fairly, the user defines a weighting for each queue. Like round robin queuing, the scheduler visits each queue in turn. However, the weighting impacts the number of packets released from each queue when it is visited.

The primary problem with WRR is that it operates at the packet level. This means that if the queues contain packets of differing average lengths, the packet percentages won't be realized as bandwidth percentages.

1.1445 WTOCM

Wavelength Tracker Optical Channel Monitoring card

1.1446 WTR

wait to restore

A period of time that must elapse after a failed working line has recovered, before switching back to the working line from the protection line.

X

1.1447 X.25

An ITU-T data communications protocol and interface for public packet-switched communication between a network user and the network.

1.1448 X.733

X.733 is the standard that describes the alarm reporting function.

1.1449 X2

The interface used to interconnect eNodeBs. See 3GPP S36.300 Section 20 and TS36.420 to TS36.424.*

1.1450 XC

Cross Connect

1.1451 XCM

XMA Control Module

In the 7950 XRS, an interface module that is inserted into one of the I/O slots on the 7950 XRS shelf. An XCM includes two input slots for XMA or C-XMA cards.

1.1452 XFP

10 Gigabit Small Form Factor Pluggable

1.1453 XMA

XRS Media Adapter

In the 7950 XRS, an interface module that is installed on an XCM. An XMA card slot is also configurable with a C-XMA, which operates at half the capacity of an XMA.

1.1454 XMDA

extended media dependent adapter.

See [1.733 "MDA" \(p. 144\)](#) .

1.1455 XML

extensible markup language

XML defines the syntax to customize markup languages. The markup languages are used to create, manage, and transmit documents across the web.

1.1456 XML API

NFM-P Extensible Markup Language Application Program Interface

An NFM-P software module that provides an interface for NFM-P communication with OSS applications.

1.1457 XML-JMS

extensible markup language Java Message Service

The OSS client sends requests and receives responses using raw XML over a JMS queue. The requests and responses do not use SOAP headers.

1.1458 XNI

10 Gigabit Network Interface

1.1459 XNS

Xerox network standard

The term for the suite of Internet protocols developed by researchers at the Xerox Corporation.

1.1460 XPIC

Cross Polarization Interference Cancellation

The 9500 MPR has XPIC capabilities that double the potential capacity of a microwave path. It allows the assignment of the same frequency to both the vertical and horizontal polarization on a path.

Y

1.1461 YANG

Yet Another Next Generation

Z

1.1462 zone

A portion of the namespace defined by the [1.322 “DNS” \(p. 88\)](#) protocol over which a system or organization has authority. The DNS namespace is a hierarchical concatenation of zone identifiers in a tree structure, with the highest-level zone as the rightmost. A period serves as the separator between two zones in a namespace.

