

# LDP Command Reference

## Command Hierarchies

- LDP Commands on page 493
- Show Commands on page 496
- Clear Commands on page 497
- Debug Commands on page 497
- Tools Commands on page 497

## LDP Commands

```

config
  — router
    — [no] ldp
      — [no] adv-adj-addr-only
      — [no] aggregate-prefix-match
        — prefix-exclude policy-name [policy-name...(up to 5 max)]
        — no prefix-exclude
        — [no] shutdown
      — egress-statistics
        — [no] fec-prefix ip-prefix[/mask]
          — accounting-policy policy-id
          — no accounting-policy
          — [no] collect-stats
          — [no] shutdown
        — export policy-name [policy-name...(up to 5 max)]
        — no export
        — [no] fast-reroute
        — [no] export-tunnel-table policy-name
        — fec-originate ip-prefix/mask [advertised-label in-label] next-hop ip-address
          [swap-label out-label] interface interface-name
        — no fec-originate ip-prefix/mask next-hop ip-address interface interface-name
        — fec-originate ip-prefix/mask [advertised-label in-label] pop interface interface-name
        — no fec-originate ip-prefix/mask pop interface interface-name
        — [no] graceful-restart
          — maximum-recovery-time interval
          — no maximum-recovery-time
          — neighbor-liveness-time interval
          — no neighbor-liveness-time
        — [no] implicit-null-label
        — import policy-name [policy-name...(up to 5 max)]
        — no import
      — interface-parameters
        — bfd
        — hello timeout factor
        — no hello

```

- [no] **interface** *ip-int-name*
  - [no] **bfd-enable**
  - **hello** *timeout factor*
  - **no hello**
  - **keepalive** *timeout factor*
  - **no keepalive**
  - [no] **multicast-traffic** {enable|disable}
  - **local-lsr-id** {system | interface | interface-name *interface-name*}
  - **no local-lsr-id**
  - [no] **shutdown**
  - **transport-address** {system | interface}
  - **no transport-address**
  - **keepalive** *timeout factor*
  - **no keepalive**
  - **transport-address** {system | interface}
  - **no transport-address**
- **label-withdrawal-delay** *seconds*
- [no] **mcast-upstream-frr**
- **mp-mbb-time** *interval*
- **no mp-mbb-time**
- **peer-parameters**
  - **peer** *ip-address*
  - **no peer** [*ip-address*]
    - [no] **adv-adj-addr-only**
    - **auth-keychain** *name*
    - **authentication-key** [*authentication-key* | *hash-key*] [**hash** | **hash2**]
    - **no authentication-key**
    - [no] **dod-label-distribution**
    - [no] **export-prefixes** *policy-name*
    - [no] **fec129-cisco-interop**
    - [no] **import-prefixes** *policy-name*
    - [no] **path-mtu-discovery**
    - [no] **pe-id-mac-flush-interop**
    - **ttl-security** *min-ttl-value*
    - **no ttl-security**
  - [no] **mp-mbb-time**
  - [no] **prefer-tunnel-in-tunnel**
  - [no] **shortcut-transit-ttl-propagate**
  - [no] **shortcut-local-ttl-propagate**
  - [no] **shutdown**
  - **targeted-session**
    - [no] **disable-targeted-session**
    - **export-prefixes** *policy-name* [*policy-name*...(up to 5 max)]
    - **no export-prefixes**
    - **hello** *timeout factor*
    - **no hello**
    - **hello-reduction** {enable *factor* | disable}
    - **no hello-reduction**
    - **import-prefixes** *policy-name* [*policy-name*...(up to 5 max)]
    - **no import-prefixes**
    - **keepalive** *timeout factor*
    - **no keepalive**
    - **local-lsr-id** *interface-name*

```
— no local-lsr-id
— peer ip-address
— no peer ip-address
    — [no] bfd-enable
    — hello timeout,factor
    — no hello
    — hello-reduction {enable,factor | disable}
    — no hello-reduction
    — keepalive timeout,factor
    — no keepalive
    — local-lsr-id interface-name
    — no local-lsr-id
    — [no] shutdown
    — [no] tunneling
        — [no] ldp
— [no] peer-template
    — [no] bfd-enable
    — hello timeout,factor
    — no hello
    — hello-reduction {enable,factor | disable}
    — no hello-reduction
    — keepalive timeout,factor
    — no keepalive
    — local-lsr-id interface-name
    — no local-lsr-id
    — [no] shutdown
    — [no] tunneling
    — peer-template-map template-name policy peer-prefix-policy1 [peer-
        prefix-policy2... up to 5]
        — no peer-template-map template-name
— tunnel-down-damp-time seconds
— no tunnel-down-damp-time
— [no] ldp-shortcut
```

## Show Commands

```

show
  — router
    — ldp
      — adv-adj-addr-only
      — auth-keychain [keychain]
      — bindings active [prefix ip-prefix/mask] [summary | egress-nh ip-prefix/mask | egress-if port-id | egress-lsp tunnel-id]
      — bindings active [fec-type prefixes] [prefix <ip-prefix/mask>] [egress-nh <ip-prefix/mask> | egress-if <port-id> | egress-lsp <tunnel-id>] [summary]
      — bindings active [fec-type p2mp] [p2mp-id <identifier> root <ip-address>] [egress-nh <ip-prefix/mask> | egress-if <port-id> | egress-lsp <tunnel-id>] [summary]
      — bindings[fec-type fec-type [detail | summary]] [session ip-addr[:label-space]]
      — bindings [label-type] [start-label [end-label]]
      — bindings {prefix ip-prefix/mask [detail]} [session ip-addr[:label-space]]
      — bindings active [prefix ip-prefix/mask] [summary | egress-nh ip-prefix/mask | egress-if port-id | egress-lsp tunnel-id]
      — bindings service-id service-id [detail]
      — bindings vc-type vc-type [{vc-id vc-id} agi agi} [session ip-addr[:label-space]]]
      — discovery [{peer [ip-address]} | {interface [ip-int-name]}] [state state] [detail] [adjacency-type type]
      — fec-egress-stats [ip-prefix/mask]
      — fec-egress-stats active
      — fec-originate ip-prefix/mask [operation-type]
      — interface [ip-int-name | ip-address] [detail]
      — parameters
      — peer [ip-address] [detail]
      — peer-parameters peer-ip-address
      — peer-template
      — peer-template-map [tldp-peers]
      — session [ip-addr[:label-space]] [detail | statistics [packet-type]] [session-type]
      — status
      — statistics-summary

```

Note: See *7750 SR OS OAM and Diagnostics Guide* for tools command descriptions, syntax, and usage information.

## Clear Commands

```
clear
  — router
    — ldp
      — fec-egress-statistics [ip-prefix/mask]
      — instance
      — interface [ip-int-name]
      — peer [ip-address] [statistics]
      — session [ip-addr[:label-space]] [statistics]
      — statistics
```

## Debug Commands

```
[no] debug
  — router
    — [no] ldp
      — [no] interface interface-name
        — [no] event
          — [no] messages
        — [no] packet [detail]
          — hello [detail]
          — no hello
      — peer ip-address
        — [no] event
          — [no] bindings
          — [no] messages
        — [no] packet
          — hello [detail]
          — no hello
          — init [detail]
          — no init
          — [no] keepalive
          — label [detail]
          — no label
```

## Tools Commands

See 7750 SR OS OAM and Diagnostics Guide for CLI description and syntax.

```
tools
  — dump
    — ldp-tretrace {prefix ip-prefix/mask| manual-prefix ip-prefix/mask}[path-destination ip-
      address] [trace-tree]
    — router
      — ldp
        — peer ip-address
```

