Triple Play Security Command Reference

Command Hierarchies

- Anti-Spoofing Commands on page 677
- Layer 2 Security Commands on page 678
- ARP Handling Commands on page 678

Note: This command tree is limited to those commands specific to Triple Play security. For the full command trees of a particular service type, consult the 7750 SR OS Services Guide.

Anti-Spoofing Commands

```
config
       service
              — vpls service-id [customer customer-id] [vpn vpn-id] [m-vpls]
                       — sap sap-id [split-horizon-group group-name]
                                 — anti-spoof {ip | mac | ip-mac}
                                - no anti-spoof
config

    service

              ies service-id [customer customer-id] [vpn vpn-id]
                       — [no] interface ip-int-name
                                  sap sap-id
                                          — anti-spoof {ip | mac | ip-mac}
                                          — no anti-spoof

    subscriber-interface

                                — group-interface ip-int-name
                                          — sap sap-id
                                                   — anti-spoof {ip | ip-mac}
                                                   - no anti-spoof
```

Layer 2 Security Commands

```
config

— service

— [no] vpls service-id [customer customer-id] [vpn vpn-id] [m-vpls]

— mac-protect

— [no] mac [ieee-mac-address]

— [no] split-horizon-group [group-name] [residential-group]

— [no] restrict-protected-src

— [no] restrict-unprotected-dst

— mesh-sdp sdp-id[:vc-id] [vc-type {ether | vlan}]

— [no] mac-pinning

— [no] restrict-unprotected-src

— [no] restrict-unprotected-src

— [no] restrict-unprotected-src

— [no] restrict-unprotected-dst

— spoke-sdp sdp-id[:vc-id] [vc-type {ether | vlan | vpls}] [split-horizon-group group-name]

— [no] mac-pinning
```

ARP Handling Commands

```
config

    service

              — [no] vpls service-id [customer customer-id] [vpn vpn-id] [m-vpls]
                       — sap sap-id
                                 — arp-reply-agent [sub-ident]
                                 — no arp-reply-agent
config

    service

                ies service-id [customer customer-id] [vpn vpn-id]
                       — [no] interface ip-int-name
                                 — [no] arp-populate
                                 — arp-timeout seconds
                                 — no arp-timeout
                                 — [no] local-proxy-arp
                                 — proxy-arp-policy policy-name [policy-name...(up to 5 max)]
                                 — no proxy-arp-policy
                                 — [no] remote-proxy-arp
                                 — static-arp ip-address ieee-address
                                 — no static-arp ip-address [ieee-address]
```