

Triple Play Multicast Command Reference

Command Hierarchies

- MCAST Management Commands on page 683
- Multicast Info Policy Bundle Commands on page 685
- Triple Play Multicast Service Commands on page 687
- Ingress Multicast Path Management Commands on page 690
- Show Commands on page 693
- Clear Commands on page 694
- Debug Commands on page 694

MCAST Management Commands

```

config
  — mcast-management
    — bandwidth-policy policy-name [create]
    — no bandwidth-policy policy-name
      — admin-bw-threshold kilo-bits-per-second
      — no admin-bw-threshold
      — ancillary-path
        — path-limit megabits-per-second
        — no path-limit
        — queue-parameters
          — cbs percentage
          — no cbs
          — hi-priority-only percent-of-mbs
          — no hi-priority-only
          — mbs percentage
          — no mbs
      — description description
      — no description
      — falling-percent-reset percent-of-highest
      — no falling-percent-reset
      — mcast-pool percent-of-total percent-of-buffers resv-cbs percent-of-pool slope-policy policy-name
      — no mcast-pool
    — chassis-level
      — [no] mmrp-impm	override
      — [no] per-mcast-plane-capacity
        — mcast-capacity primary-percentage secondary secondary-percentage
        — no mcast-capacity
        — redundant-mcast-capacity primary-percentage secondary secondary percentage

```

Command Hierarchies

```
    — no redundant-mcast-capacity
    — total-capacity capacity
    — no total-capacity
    — [no] round-robin-inactive-records
— mcast-reporting-dest mcast-reporting-dest-name [create]
— no mcast-reporting-dest mcast-reporting-dest-name
    — description description
    — no description
    — dest-ip-address ip-address
    — no dest-ip-address
    — max-tx-delay delay
    — no max-tx-delay
    — udp-dst-port port
    — no udp-dst-port
    — [no] shutdown
```

Multicast Info Policy Bundle Commands

```

config
  — mcast-management
    — multicast-info-policy policy-name [create]
    — no multicast-info-policy policy-name
      — bundle bundle-name [create]
      — no bundle bundle-name
        — admin-bw kbps
        — no admin-bw
        — bw-activity {use-admin-bw|dynamic [falling-delay seconds]} [black-hole-rate kbytes]
        — no bw-activity
        — channel ip-address [ip-address] [create]
        — no channel ip-address [ip-address]
          — admin-bw kbytes
          — no admin-bw
          — bw-activity {use-admin-bw|dynamic [falling-delay seconds]} [black-hole-rate kbytes]
          — no bw-activity
          — explicit-sf-path {primary | secondary | ancillary}
          — no explicit-sf-path
          — keepalive-override keepalive-timer
          — no keepalive-override
          — preference preference-level
          — no preference
          — primary-tunnel-interface {rsvp-p2mp | ldp-p2mp p2mp-id\lsp-name sender ip-address}
          — no primary-tunnel-interface
          — source-override ip-address [create]
          — no source-override ip-address
            — admin-bw kbytes
            — no admin-bw
            — bw-activity {use-admin-bw|dynamic [falling-delay seconds]} [black-hole-rate kbytes]
            — no bw-activity
            — cac-type {mandatory | optional}
            — no cac-type
            — explicit-sf-path {primary | secondary | ancillary}
            — no explicit-sf-path
            — keepalive-override keepalive-timer
            — no keepalive-override
            — preference preference-level
            — no preference
            — primary-tunnel-interface {rsvp-p2mp | ldp-p2mp p2mp-id\lsp-name sender ip-address}
            — no primary-tunnel-interface
            — cong-priority-threshold preference-level
            — no cong-priority-threshold
            — description description
            — no description
            — ecmp-opt-threshold preference-level
            — no ecmp-opt-threshold
            — explicit-sf-path {primary | secondary | ancillary}
            — no explicit-sf-path

```

Command Hierarchies

```
    — keepalive-override keepalive-timer
    — no keepalive-override
    — preference preference-level
    — no preference
    — primary-tunnel-interface {rsvp-p2mp | ldp-p2mp p2mp-id} lsp-name
        sender ip-address
        — no primary-tunnel-interface
    — description description-string
    — no description
```

Refer to the 7750 SR OS Interface Configuration Guide for command descriptions.

config

```
    — card
        — fp [fp-number]
            — ingress
                — multicast-path-management
                    — bandwidth-policy policy-name
                    — no bandwidth-policy
                    — [no] shutdown
    — mda
        — ingress
            — multicast-path-management
                — ancillary-override
                    — path-limit megabits-per-second
                    — no path-limit
                — bandwidth-policy policy-name
                — no bandwidth-policy
                — primary-override
                    — path-limit megabits-per-second
                    — no path-limit
                — secondary-override
                    — path-limit megabits-per-second
                    — no path-limit
                — [no] shutdown
```

Triple Play Multicast Service Commands

```

config
  — service
    — [no] vpls service-id [customer customer-id] [vpn vpn-id] [m-vpls]
      — igmp-snooping
        — mvr
          — description description-string
          — no description
          — group-policy policy-name
          — no group-policy
          — [no] shutdown
          — query-interval seconds
          — no query-interval
          — query-src-ip ipv6-address
          — no query-src-ip
          — report-src-ip ipv6-address
          — no report-src-ip
          — robust-count robust-count
          — no robust-count
          — [no] shutdown
          — fdb-table-high-wmark high-water-mark
          — no fdb-table-high-wmark
          — fdb-table-low-wmark low-water-mark
          — no fdb-table-low-wmark
          — fdb-table-size table-size
          — no fdb-table-size
          — mld-snooping
            — mvr
              — description description-string
              — no description
              — group-policy policy-name
              — no group-policy
              — [no] shutdown
              — query-interval seconds
              — no query-interval
              — query-src-ip ipv6-address
              — no query-src-ip
              — report-src-ip ipv6-address
              — no report-src-ip
              — robust-count robust-count
              — no robust-count
              — [no] shutdown
            — multicast-info-policy policy-name
            — no multicast-info-policy
            — sap sap-id [split-horizon-group group-name]
            — no sap sap-id
              — igmp-snooping
                — [no] fast-leave
                — import policy-name
                — no import
                — last-member-query-interval interval
                — no last-member-query-interval
                — max-num-groups max-num-groups
                — no max-num-groups

```

```

    — [no] mrouter-port
    — mvr
        — from-vpls vpls-id
        — no from-vpls
        — to-sap sap-id
        — no to-sap
    — query-interval interval
    — no query-interval
    — query-response-interval interval
    — no query-response-interval
    — robust-count count
    — no robust-count
    — [no] send-queries
    — static
        — [no] group group-address
        — [no] source ip-addr
        — [no] starg
    — mesh-sdp sdp-id[:vc-id] [vc-type {ether | vlan | vpls}]
    — no mesh-sdp sdp-id[:vc-id]
        — igmp-snooping
            — [no] fast-leave
            — import policy-name
            — no import
            — last-member-query-interval interval
            — no last-member-query-interval
            — max-num-groups max-num-groups
            — no max-num-groups
            — mcac
                — policy policy-name
                — no policy
                — unconstrained-bw bandwidth mandatory-bw mandatory-bw
                — no unconstrained-bw
                — query-interval interval
                — no query-interval
                — query-response-interval interval
                — no query-response-interval
                — robust-count count
                — no robust-count
                — [no] send-queries
                — static
                    — [no] group group-address
                    — [no] source ip-addr
                    — [no] starg
        — mld-snooping
            — [no] disable-router-alert-check
            — [no] fast-leave
            — import policy-name
            — no import
            — last-member-query-interval interval
            — no last-member-query-interval
            — max-num-groups max-num-groups
            — no max-num-groups
            — mvr
                — fast-leave service-id

```

- **no fast-leave**
- **to-sap sap-id**
- **no to-sap**
- **query-interval seconds**
- **no query-interval**
- **query-response-interval seconds**
- **no query-response-interval**
- **robust-count robust-count**
- **no robust-count**
- **[no] send-queries**
- **spoke-sdp sdp-id[:vc-id] [vc-type {ether | vlan | vpls}] [split-horizon-group group-name]**
- **no spoke-sdp sdp-id[:vc-id]**
 - **igmp-snooping**
 - **[no] fast-leave**
 - **import policy-name**
 - **no import**
 - **last-member-query-interval interval**
 - **no last-member-query-interval**
 - **max-num-groups max-num-groups**
 - **no max-num-groups**
 - **query-interval interval**
 - **no query-interval**
 - **query-response-interval interval**
 - **no query-response-interval**
 - **robust-count count**
 - **no robust-count**
 - **[no] send-queries**
 - **static**
 - **[no] group group-address**
 - **[no] source ip-addr**
 - **[no] starg**
 - **mvr**
 - **fast-leave service-id**
 - **no fast-leave**
 - **to-sap sap-id**
 - **no to-sap**
 - **query-interval seconds**
 - **no query-interval**
 - **query-response-interval seconds**
 - **no query-response-interval**
 - **robust-count robust-count**
 - **no robust-count**
 - **[no] send-queries**

Ingress Multicast Path Management Commands

```

config
  — mcast-management
    — bandwidth-policy policy-name [create]
    — no bandwidth-policy policy-name
      — admin-bw-threshold kilo-bits-per-second
      — no admin-bw-threshold
    — ancillary-path
      — path-limit megabits-per-second
      — no path-limit
      — queue-parameters
        — cbs percentage
        — no cbs
        — hi-priority-only percent-of-mbs
        — no hi-priority-only
        — mbs percentage
        — no mbs
    — description description-string
    — no description
    — falling-percent-reset percent-of-highest
    — no falling-percent-reset
    — mcast-pool percent-of-total percent-of-buffers resv-cbs percent-of-pool slope-policy policy-name
    — no mcast-pool
    — primary-path
      — path-limit megabits-per-second
      — no path-limit
      — queue-parameters
        — cbs percentage
        — no cbs
        — hi-priority-only percent-of-mbs
        — no hi-priority-only
        — mbs percentage
        — no mbs
    — secondary-path
      — path-limit megabits-per-second
      — no path-limit
      — queue-parameters
        — cbs percentage
        — no cbs
        — hi-priority-only percent-of-mbs
        — no hi-priority-only
        — mbs percentage
        — no mbs
    — t2-paths
      — primary-path
        — queue-parameters
          — cbs percentage
          — no cbs
          — hi-priority-only percent-of-mbs
          — no hi-priority-only
          — mbs percentage
          — no mbs
      — secondary-path

```

```
— number-paths number-of-paths [dual-sfm number-of-paths]
— queue-parameters
    — cbs percentage
    — no cbs
    — hi-priority-only percent-of-mbs
    — no hi-priority-only
    — mbs percentage
    — no mbs

config
  — router
    — multicast-info-policy policy-name
    — no multicast-info-policy
    — pim
      — [no] mc-ecmp-balance
      — mc-ecmp-balance-hold minute
      — no mc-ecmp-balance-hold

tools
  — perform
    — router
      — pim
        — mc-ecmp-rebalance [ecmp-opt-threshold]
```

Multicast Redirection

```
config
  — router/service VPRN
    — policy-options
      — policy-statement
        — entry
          — action {accept|next-entry|next-policy|reject}
          — no action
    — igmp
      — interface port:tags
      — mld
        — interface port:tags
config
  — service
    — ies service-id
    — vprn service-id
      — interface port:tags
```

Show Commands

```

show
  — service
    — id service-id
      — host-tracking
        — saps [detail|statistics|summary|mcast-reporting-statistics]
        — saps sap sap-id [host ip-address] [detail|statistics|summary|mcast-reporting-statistics]
      — igmp-snooping
        — all
        — mroutes [detail]
        — mvr
        — port-db sap sap-id [detail]
        — port-db sap sap-id group grp-address
        — port-db sdp-id:vc-id [detail]
        — port-db sdp sdp-id:vc-id group grp-address
        — proxy-db [detail]
        — proxy-db group grp-address
        — static [sap sap-id | sdp sdp-id:vc-id]
        — static [sap sap-id | sdp sdp-id:vc-id]
      — mfib brief
      — mfib [group grp-address]
      — mfib statistics [group grp-address]
    — mld-snooping
      — all
      — base
      — mroutes [detail]
      — mvr
      — port-db sap sap-id
      — port-db sap sap-id detail
      — port-db sap sap-id group grp-ipv6-address
      — port-db sdp sdp-id:vc-id
      — port-db sdp sdp-id:vc-id detail
      — port-db sdp sdp-id:vc-id group grp-ipv6-address
      — proxy-db [detail]
      — proxy-db group grp-ipv6-address
      — querier
      — static [sap sap-id | sdp sdp-id:vc-id]
      — statistics [sap sap-id | sdp sdp-id:vc-id]

show
  — router
    — pim
      — mc-ecmp-balance [detail]

show
  — mcast-management
    — bandwidth-policy [policy-name] [detail]
    — channel [router router-instance | vpls service-id] [mda slot[/mda]] [group ip-address [source ip-address]] [path path-type] [detail]
    — mcast-reporting-dest [mcast-reporting-dest-name]
    — mda [slot[/mda]] [path path-type]

show

```

Show Commands

```
— router
  — igmp
    — group [grp-ip-address]
    — group summary
    — group-interface [fwd-service service-id] [ip-int-name] [detail]
    — hosts [group grp-address] [detail] [fwd-service service-id] [grp-interface ip-int-name]
    — hosts [host ip-address] [group grp-address] [detail]
    — hosts summary
    — interface [ip-int-name|ip-address] [group] [grp-ip-address] [detail]
    — mcast-reporting-statistics [host]
    — mld
      — interface port:tags
    — ssm-translate [interface-name]
    — static [ip-int-name|ip-addr]
    — statistics [ip-int-name|ip-address]
    — statistics host [ip-address]
    — status
    — tunnel-interface
```

Clear Commands

```
clear
  — service
    — id
      — igmp-snooping
        — port-db sap sap-id [group grp-address [source ip-address]]
        — port-db sdp sdp-id:vc-id [group grp-address [source ip-address]]
        — querier
        — querier [all | sap sap-id | sdp sdp-id:vc-id]
    — mfib
      — statistics [all | group grp-address ]
    — mld-snooping
      — port-db sap sap-id [group grp-ipv6-address]
      — port-db sap sap-id group grp-ipv6-address source src-ipv6-address
      — port-db sdp sdp-id:vc-id [group grp-ipv6-address]
      — port-db sdp sdp-id:vc-id group grp-ipv6-address source src-ipv6-address
      — querier
      — statistics all
      — statistics sap sap-id
      — statistics sdp sdp-id:vc-id
```

Debug Commands

```
debug
  — mcast-management
    — [no] mcast-reporting-dest [dest-name]
      — [no] igmp [host ip-address] [group grp-address]
  — service
    — id service-id
      — mld-snooping
        — detail-level {low|medium|high}
```

- **no detail-level**
- [no] **mac** *ieee-address*
- **mode** {dropped-only|ingr-and-dropped|egr-ingr-and-dropped}
- **no mode**
- [no] **sap** *sap-id*
- [no] **sdp** *sdp-id:vc-id*

Show Commands