

Triple Play Service Delivery Architecture

In This Section

This section provides TPSDA configuration information for the following topics:

- [ARP Hosts on page 1961](#)
- [Bridged CO on page 1989](#)
- [IPv4 DHCP Hosts on page 2031](#)
- [ESM Basics on page 2077](#)
- [ESM IPv4: Multicast in a Wholesale/Retail Scenario on page 2125](#)
- [ESM IPv4: Multicast with Redirection on page 2141](#)
- [ESM IPv4: Multicast with SRRP on page 2179](#)
- [ESMv4: PPPoE Hosts on page 2213](#)
- [ESMv6: IPoE Dual Stack Hosts on page 2263](#)
- [ESMv6: PPPoE Dual Stack Hosts on page 2307](#)
- [Establishing a Diameter Peering Session on page 2343](#)
- [Flexible Authentication Model in ESM on page 2359](#)
- [Ingress Multicast Path Management on page 2405](#)
- [L2TP for Subscriber Access — LAC on page 2449](#)
- [Managed SAPs with Routed CO on page 2511](#)
- [Multi-Chassis Ring Layer 2 with Enhanced Subscriber Management on page 2545](#)
- [Python Cache Support for ESM Applications on page 2579](#)
- [RADIUS-Triggered Dynamic Data Service Provisioning on page 2605](#)
- [Raw Formatting of DHCPv4/v6 Options in ESM on page 2651](#)
- [Routed CO on page 2687](#)
- [Subscriber Redundancy for Routed-CO on page 2735](#)

In This Section

- [WiFi Aggregation and Offload – Migrant User Support on page 2769](#)