



Nokia Service Router Linux

LOG EVENTS GUIDE RELEASE 22.3

**3HE 18311 AAAA TQZZA
Issue 01**

March 2022

© 2022 Nokia.

Use subject to Terms available at: www.nokia.com/terms/.

Nokia is committed to diversity and inclusion. We are continuously reviewing our customer documentation and consulting with standards bodies to ensure that terminology is inclusive and aligned with the industry. Our future customer documentation will be updated accordingly.

This document includes Nokia proprietary and confidential information, which may not be distributed or disclosed to any third parties without the prior written consent of Nokia.

This document is intended for use by Nokia's customers ("You"/"Your") in connection with a product purchased or licensed from any company within Nokia Group of Companies. Use this document as agreed. You agree to notify Nokia of any errors you may find in this document; however, should you elect to use this document for any purpose(s) for which it is not intended, You understand and warrant that any determinations You may make or actions You may take will be based upon Your independent judgment and analysis of the content of this document.

Nokia reserves the right to make changes to this document without notice. At all times, the controlling version is the one available on Nokia's site.

No part of this document may be modified.

NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF AVAILABILITY, ACCURACY, RELIABILITY, TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, IS MADE IN RELATION TO THE CONTENT OF THIS DOCUMENT. IN NO EVENT WILL NOKIA BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO SPECIAL, DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL OR ANY LOSSES, SUCH AS BUT NOT LIMITED TO LOSS OF PROFIT, REVENUE, BUSINESS INTERRUPTION, BUSINESS OPPORTUNITY OR DATA THAT MAY ARISE FROM THE USE OF THIS DOCUMENT OR THE INFORMATION IN IT, EVEN IN THE CASE OF ERRORS IN OR OMISSIONS FROM THIS DOCUMENT OR ITS CONTENT.

Copyright and trademark: Nokia is a registered trademark of Nokia Corporation. Other product names mentioned in this document may be trademarks of their respective owners.

The registered trademark Linux® is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

© 2022 Nokia.

Table of contents

1 About this guide.....	16
1.1 What's new.....	16
1.2 Precautionary and information messages.....	16
1.3 Conventions.....	16
2 Log events overview.....	18
2.1 Example log event.....	18
2.2 Log event properties.....	19
3 Summary of log event changes.....	21
4 aaa.....	22
4.1 serverDown.....	22
4.2 serverGroupDown.....	22
4.3 serverRouteUnavailable.....	23
4.4 serverTimeout.....	23
4.5 sessionClosed.....	23
4.6 sessionDisconnected.....	24
4.7 sessionOpened.....	24
4.8 userAuthenticationFailed.....	25
4.9 userAuthenticationSucceeded.....	25
5 acl.....	27
5.1 aclCpmlpv4MatchedPacket.....	27
5.2 aclCpmlpv6MatchedPacket.....	27
5.3 aclInterfaceInputIpv4MatchedPacket.....	28
5.4 aclInterfaceInputIpv6MatchedPacket.....	28
5.5 aclInterfaceOutputIpv4MatchedPacket.....	29
5.6 aclInterfaceOutputIpv6MatchedPacket.....	29
5.7 aclTcamProgComplete.....	30
5.8 platformAclHighUtilization.....	30
5.9 platformAclHighUtilizationLowered.....	31
5.10 platformTcamHighUtilization.....	31
5.11 platformTcamHighUtilizationLowered.....	32

6 arpd	33
6.1 ipArpEntryUpdated	33
6.2 ipSubinterfaceDuplicateIpv4Address	33
6.3 ipSubinterfaceDuplicateIpv6Address	34
6.4 ipSubinterfaceDuplicateMacAddress	34
6.5 ipSubinterfaceInvalidArp	35
6.6 ipSubinterfaceInvalidIpv6NeighborSolicitation	35
6.7 ipv6NeighborEntryUpdated	36
7 bfd	37
7.1 bfdDownEvent	37
7.2 bfdMaxSessionActive	37
7.3 bfdProtocolClientAdd	38
7.4 bfdProtocolClientRemove	38
7.5 bfdSessionDeleted	39
7.6 bfdSessionUp	39
7.7 microbfdDownEvent	40
7.8 microbfdMaxSessionActive	41
7.9 microbfdSessionDeleted	41
7.10 microbfdSessionUp	41
8 bgp	43
8.1 bgpIncomingDynamicPeerLimitReached	43
8.2 bgpInstanceConvergenceStateTransition	43
8.3 bgpLowMemory	44
8.4 bgpNeighborBackwardTransition	44
8.5 bgpNeighborClosedTCPConn	45
8.6 bgpNeighborEstablished	45
8.7 bgpNeighborGRHelpingStarted	46
8.8 bgpNeighborGRHelpingStopped	46
8.9 bgpNeighborHoldTimeExpired	47
8.10 bgpNeighborInvalidLocalIP	47
8.11 bgpNeighborNoOpenReceived	47
8.12 bgpNeighborPrefixLimitReached	48
8.13 bgpNeighborPrefixLimitThresholdReached	48
8.14 bgpNeighborUnknownRemoteIP	49

8.15	bgpNLRInvalid.....	49
8.16	bgpNotificationReceivedFromNeighbor.....	50
8.17	bgpNotificationSentToNeighbor.....	50
8.18	bgpOutgoingDynamicPeerLimitReached.....	51
8.19	bgpPathAttributeDiscarded.....	51
8.20	bgpPathAttributeMalformed.....	52
8.21	bgpRouteWithdrawnDueToError.....	53
8.22	bgpUpdateInvalid.....	53
9	bridgetable.....	54
9.1	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilization.....	54
9.2	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilizationLowered.....	54
9.3	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitLowered.....	55
9.4	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitReached.....	55
9.5	I2SubinterfaceBridgeTableDuplicateMacAddressDeleted.....	56
9.6	I2SubinterfaceBridgeTableDuplicateMacAddressDetected.....	56
9.7	I2SubinterfaceBridgeTableMacLimitHighUtilization.....	57
9.8	I2SubinterfaceBridgeTableMacLimitHighUtilizationLowered.....	57
9.9	I2SubinterfaceBridgeTableMacLimitLowered.....	58
9.10	I2SubinterfaceBridgeTableMacLimitReached.....	58
9.11	networkInstanceBridgeTableDuplicateMacAddressDeleted.....	59
9.12	networkInstanceBridgeTableDuplicateMacAddressDetected.....	59
9.13	networkInstanceBridgeTableMacLimitHighUtilization.....	60
9.14	networkInstanceBridgeTableMacLimitHighUtilizationLowered.....	60
9.15	networkInstanceBridgeTableMacLimitLowered.....	61
9.16	networkInstanceBridgeTableMacLimitReached.....	61
9.17	networkInstanceBridgeTableProxyArpDuplicateIpAddressDeleted.....	62
9.18	networkInstanceBridgeTableProxyArpDuplicateIpAddressDetected.....	62
9.19	networkInstanceBridgeTableProxyArpLimitHighUtilization.....	63
9.20	networkInstanceBridgeTableProxyArpLimitHighUtilizationLowered.....	63
9.21	systemBridgeTableMacLimitHighUtilization.....	64
9.22	systemBridgeTableMacLimitHighUtilizationLowered.....	64
9.23	systemBridgeTableMacLimitLowered.....	65
9.24	systemBridgeTableMacLimitReached.....	65
9.25	systemBridgeTableProxyArpLimitHighUtilization.....	66
9.26	systemBridgeTableProxyArpLimitHighUtilizationLowered.....	66
9.27	vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilization.....	67

9.28 vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilizationLowered.....	67
9.29 vxlanInterfaceBridgeTableMulticastDestinationsLimitLowered.....	68
9.30 vxlanInterfaceBridgeTableMulticastDestinationsLimitReached.....	69
10 chassis.....	70
10.1 platformDatapathResourceHighUtilization.....	70
10.2 platformDatapathResourceHighUtilizationLowered.....	70
10.3 platformDatapathResourceLimitCleared.....	71
10.4 platformDatapathResourceLimitReached.....	71
10.5 platformMtuHighUtilization.....	72
10.6 platformMtuHighUtilizationLowered.....	72
10.7 platformPipelineResourceHighUtilization.....	73
10.8 platformPipelineResourceHighUtilizationLowered.....	73
10.9 platformPipelineResourceLimitCleared.....	74
10.10 platformPipelineResourceLimitReached.....	74
10.11 portDown.....	75
10.12 portUp.....	75
10.13 subinterfaceDown.....	76
10.14 subinterfaceUp.....	76
10.15 transceiverChannelHighInputPowerAlarm.....	77
10.16 transceiverChannelHighInputPowerAlarmClear.....	77
10.17 transceiverChannelHighInputPowerWarning.....	78
10.18 transceiverChannelHighInputPowerWarningClear.....	78
10.19 transceiverChannelHighLaserBiasCurrentAlarm.....	79
10.20 transceiverChannelHighLaserBiasCurrentAlarmClear.....	79
10.21 transceiverChannelHighLaserBiasCurrentWarning.....	80
10.22 transceiverChannelHighLaserBiasCurrentWarningClear.....	80
10.23 transceiverChannelHighOutputPowerAlarm.....	81
10.24 transceiverChannelHighOutputPowerAlarmClear.....	81
10.25 transceiverChannelHighOutputPowerWarning.....	82
10.26 transceiverChannelHighOutputPowerWarningClear.....	82
10.27 transceiverChannelLowInputPowerAlarm.....	83
10.28 transceiverChannelLowInputPowerAlarmClear.....	83
10.29 transceiverChannelLowInputPowerWarning.....	84
10.30 transceiverChannelLowInputPowerWarningClear.....	84
10.31 transceiverChannelLowLaserBiasCurrentAlarm.....	85
10.32 transceiverChannelLowLaserBiasCurrentAlarmClear.....	85

10.33	transceiverChannelLowLaserBiasCurrentWarning.....	86
10.34	transceiverChannelLowLaserBiasCurrentWarningClear.....	86
10.35	transceiverChannelLowOutputPowerAlarm.....	87
10.36	transceiverChannelLowOutputPowerAlarmClear.....	87
10.37	transceiverChannelLowOutputPowerWarning.....	88
10.38	transceiverChannelLowOutputPowerWarningClear.....	88
10.39	transceiverHighInputPowerAlarm.....	89
10.40	transceiverHighInputPowerAlarmClear.....	89
10.41	transceiverHighInputPowerWarning.....	90
10.42	transceiverHighInputPowerWarningClear.....	90
10.43	transceiverHighLaserBiasCurrentAlarm.....	91
10.44	transceiverHighLaserBiasCurrentAlarmClear.....	91
10.45	transceiverHighLaserBiasCurrentWarning.....	91
10.46	transceiverHighLaserBiasCurrentWarningClear.....	92
10.47	transceiverHighOutputPowerAlarm.....	92
10.48	transceiverHighOutputPowerAlarmClear.....	93
10.49	transceiverHighOutputPowerWarning.....	93
10.50	transceiverHighOutputPowerWarningClear.....	94
10.51	transceiverLowInputPowerAlarm.....	94
10.52	transceiverLowInputPowerAlarmClear.....	95
10.53	transceiverLowInputPowerWarning.....	95
10.54	transceiverLowInputPowerWarningClear.....	96
10.55	transceiverLowLaserBiasCurrentAlarm.....	96
10.56	transceiverLowLaserBiasCurrentAlarmClear.....	97
10.57	transceiverLowLaserBiasCurrentWarning.....	97
10.58	transceiverLowLaserBiasCurrentWarningClear.....	98
10.59	transceiverLowOutputPowerAlarm.....	98
10.60	transceiverLowOutputPowerAlarmClear.....	99
10.61	transceiverLowOutputPowerWarning.....	99
10.62	transceiverLowOutputPowerWarningClear.....	100
10.63	transceiverModuleDown.....	100
10.64	transceiverModuleHighTemperatureAlarm.....	100
10.65	transceiverModuleHighTemperatureAlarmClear.....	101
10.66	transceiverModuleHighTemperatureWarning.....	101
10.67	transceiverModuleHighTemperatureWarningClear.....	102
10.68	transceiverModuleHighVoltageAlarm.....	102
10.69	transceiverModuleHighVoltageAlarmClear.....	103

10.70	transceiverModuleHighVoltageWarning.....	103
10.71	transceiverModuleHighVoltageWarningClear.....	104
10.72	transceiverModuleLowTemperatureAlarm.....	104
10.73	transceiverModuleLowTemperatureAlarmClear.....	105
10.74	transceiverModuleLowTemperatureWarning.....	105
10.75	transceiverModuleLowTemperatureWarningClear.....	105
10.76	transceiverModuleLowVoltageAlarm.....	106
10.77	transceiverModuleLowVoltageAlarmClear.....	106
10.78	transceiverModuleLowVoltageWarning.....	107
10.79	transceiverModuleLowVoltageWarningClear.....	107
10.80	transceiverModuleUp.....	108
11	debug.....	109
11.1	setAllConfigLevels.....	109
11.2	setAllStartupLevels.....	109
11.3	setHighBaselineLogLevels.....	110
12	dhcp.....	111
12.1	dhcp6ClientAddressDeclined.....	111
12.2	dhcp6ClientIpv6AddressValidLifetimeExpired.....	111
12.3	dhcp6ClientRebindAttempted.....	112
12.4	dhcp6ClientReconfigureMsgDropped.....	112
12.5	dhcp6ClientRenewSuccess.....	112
12.6	dhcpClientAddressDeclined.....	113
12.7	dhcpClientLeaseExpired.....	113
12.8	dhcpClientRebindAttempted.....	114
12.9	dhcpClientRenewSuccess.....	114
12.10	dhcpv4RelayAdminDisable.....	115
12.11	dhcpv4RelayAdminEnable.....	115
12.12	dhcpv4RelayAllDhcpv4ServersUnreachable.....	116
12.13	dhcpv4RelayOperDown.....	116
12.14	dhcpv4RelayOperUp.....	117
12.15	dhcpv6RelayAdminDisable.....	117
12.16	dhcpv6RelayAdminEnable.....	118
12.17	dhcpv6RelayAllDhcpv6ServersUnreachable.....	118
12.18	dhcpv6RelayOperDown.....	119
12.19	dhcpv6RelayOperUp.....	119

12.20	giAddressMismatch.....	120
12.21	sourceAddressMismatch.....	120
13	evpn.....	122
13.1	ethernetsegmentNetworkInstanceBgpInstanceDfStatusChanged.....	122
13.2	ethernetsegmentPreferenceOperValueChanged.....	122
13.3	evpnAutoDiscoveryEviRouteAddDroppedDueToUnexpectedEthTag.....	123
13.4	evpnAutoDiscoveryEviRouteWithdrawDroppedDueToUnexpectedEthTag.....	123
13.5	evpnAutoDiscoveryEviRouteWithdrawnDueToUnexpectedVni.....	124
13.6	evpnInclMcastRouteAddDroppedDueToUnexpectedEthTag.....	125
13.7	evpnInclMcastRouteWithdrawDroppedDueToUnexpectedEthTag.....	125
13.8	evpnInclMcastRouteWithdrawnDueToUnexpectedVni.....	126
13.9	evpnIpPrefixRouteNotImportedDueToUnexpectedVni.....	126
13.10	evpnIpPrefixRouteWithdrawnDueToNoGwMac.....	127
13.11	evpnIpPrefixRouteWithdrawnDueToUnexpectedGwIp.....	128
13.12	evpnMacRouteAddDroppedDueToUnexpectedEthTag.....	128
13.13	evpnMacRouteWithdrawDroppedDueToUnexpectedEthTag.....	129
13.14	evpnMacRouteWithdrawnDueToUnexpectedVni.....	129
14	gnmi.....	131
14.1	globalConfigUpdate.....	131
14.2	gnmiServerStart.....	131
14.3	gnmiServerStop.....	132
14.4	networkInstanceConfigUpdate.....	132
14.5	subscriptionEnd.....	133
14.6	subscriptionRequestReceived.....	133
14.7	subscriptionStart.....	133
14.8	unixSocketGnmiOperDown.....	134
14.9	unixSocketGnmiOperUp.....	134
15	gribi.....	136
15.1	globalConfigUpdate.....	136
15.2	gribiServerStart.....	136
15.3	gribiServerStop.....	137
15.4	networkInstanceConfigUpdate.....	137
15.5	unixSocketGribiOperDown.....	138
15.6	unixSocketGribiOperUp.....	138

16 isis	139
16.1 isisAdjacencyBfdSessionSetupFailed.....	139
16.2 isisAdjacencyChange.....	139
16.3 isisAdjacencyRestartStatusChange.....	140
16.4 isisAreaMismatch.....	140
16.5 isisAuthDataFail.....	141
16.6 isisAuthTypeMismatch.....	141
16.7 isisCircuitIdsExhausted.....	142
16.8 isisCircuitMtuTooLow.....	142
16.9 isisCorruptedLspDetected.....	143
16.10 isisLdpSyncExited.....	143
16.11 isisLdpSyncTimerStarted.....	144
16.12 isisLspFragmentTooLarge.....	144
16.13 isisLspPurge.....	145
16.14 isisLspSequenceNumberSkip.....	145
16.15 isisMaxAreaAddressesMismatch.....	146
16.16 isisMaxLspSequenceNumberExceeded.....	146
16.17 isisOverloadEntry.....	147
16.18 isisOverloadExit.....	147
16.19 isisOwnLspPurge.....	148
16.20 isisSystemIdLengthMismatch.....	148
16.21 isisVersionMismatch.....	148
17 json	150
17.1 authenticationError.....	150
17.2 globalConfigUpdate.....	150
17.3 httpJsonRpcOperDown.....	151
17.4 httpJsonRpcOperUp.....	151
17.5 httpsJsonRpcOperDown.....	151
17.6 httpsJsonRpcOperUp.....	152
17.7 jsonRpcRequestReceived.....	152
17.8 jsonRpcResponseSent.....	153
17.9 networkInstanceConfigUpdate.....	153
17.10 unixSocketJsonRpcOperDown.....	154
17.11 unixSocketJsonRpcOperUp.....	154
17.12 userAuthenticated.....	155

17.13 userAuthenticationErrorWrongPassword.....	155
18 lag.....	157
18.1 lagDown.....	157
18.2 lagDownMinLinks.....	157
18.3 lagMemberLinkAdded.....	158
18.4 lagMemberLinkRemoved.....	158
18.5 lagMemberOperDown.....	159
18.6 lagMemberOperUp.....	159
18.7 lagUp.....	160
19 ldp.....	161
19.1 ldpInterfaceDown.....	161
19.2 ldpInterfaceUp.....	161
19.3 ldplpv4InstanceDown.....	162
19.4 ldplpv4InstanceUp.....	162
19.5 ldpSessionDown.....	163
19.6 ldpSessionFecLimitReached.....	163
19.7 ldpSessionLocalIPv4Overload.....	164
19.8 ldpSessionPeerIPv4Overload.....	164
19.9 ldpSessionUp.....	165
20 linux.....	166
20.1 cpuUsageCritical.....	166
20.2 cpuUsageHigh.....	166
20.3 cpuUsageNormal.....	167
20.4 dateAndTimeChanged.....	167
20.5 domainChanged.....	168
20.6 hostnameChanged.....	168
20.7 memoryUsageCritical.....	168
20.8 memoryUsageFull.....	169
20.9 memoryUsageHigh.....	169
20.10 memoryUsageNormal.....	170
20.11 partitionStateChange.....	170
20.12 partitionUsageCritical.....	171
20.13 partitionUsageFull.....	171
20.14 partitionUsageNormal.....	172

20.15 partitionUsageWarning.....	172
20.16 serviceConfigChanged.....	173
20.17 serviceDownInNetworkInstance.....	173
20.18 serviceUpInNetworkInstance.....	174
20.19 tlsProfileExpired.....	174
20.20 tlsProfileExpiresSoon.....	175
21 lldp.....	176
21.1 remotePeerAdded.....	176
21.2 remotePeerRemoved.....	176
21.3 remotePeerUpdated.....	177
22 log.....	178
22.1 bufferRollover.....	178
22.2 configUpdate.....	178
22.3 fileRollover.....	179
22.4 networkNamespaceChanged.....	179
22.5 subsystemFacilityChanged.....	180
23 mgmt.....	181
23.1 checkpointGenerated.....	181
23.2 checkpointRevertRequestReceived.....	181
23.3 commitFailed.....	182
23.4 commitSucceeded.....	182
23.5 exclusiveConfigSessionBlockedByOtherSessionError.....	182
23.6 exclusiveConfigSessionError.....	183
23.7 privateConfigSessionError.....	183
23.8 privateSharedMismatch.....	184
23.9 sharedConfigSessionBlockedByOtherSessionError.....	184
24 mirror.....	186
24.1 mirrorDestinationDelete.....	186
24.2 mirrorDestinationOperDown.....	186
24.3 mirrorDestinationOperUP.....	187
24.4 mirrorDestnationAdd.....	187
24.5 mirrorInstanceAdminDisable.....	188
24.6 mirrorInstanceAdminEnable.....	188

24.7 mirrorInstanceOperDown.....	189
24.8 mirrorInstanceOperUp.....	189
24.9 mirrorSourceAdd.....	190
24.10 mirrorSourceDelete.....	190
25 netinst.....	192
25.1 networkInstanceInterfaceDown.....	192
25.2 networkInstanceInterfaceUp.....	192
25.3 networkInstanceStateDown.....	193
25.4 networkInstanceStateUp.....	193
26 ospf.....	194
26.1 ospfAdjacencyBfdSessionSetupFailed.....	194
26.2 ospfAdjacencyChange.....	194
26.3 ospfAdjacencyRestartStatusChange.....	195
26.4 ospfAsMaxAgeLSA.....	195
26.5 ospfExportLimitReached.....	196
26.6 ospfExportLimitWarning.....	196
26.7 ospfFailure.....	197
26.8 ospfIfLdpSyncStateChange.....	197
26.9 ospfIfRxBadPacket.....	198
26.10 ospfIfStateChange.....	198
26.11 ospfLsdbApproachingOverflow.....	199
26.12 ospfLsdbOverflow.....	199
26.13 ospfNbrMtuMismatch.....	200
26.14 ospfOverloadEntry.....	200
26.15 ospfOverloadExit.....	201
26.16 ospfOverloadWarning.....	201
26.17 ospfSpfRunRestarted.....	202
26.18 ospfSpfRunsStopped.....	202
26.19 ospfAuthDataFailure.....	203
27 platform.....	204
27.1 airflowCorrected.....	204
27.2 airflowMismatch.....	204
27.3 componentBooting.....	205
27.4 componentDown.....	205

27.5 componentFailed.....	206
27.6 componentInserted.....	206
27.7 componentLocatorDisabled.....	206
27.8 componentLocatorEnabled.....	207
27.9 componentRemoved.....	207
27.10 componentRestarted.....	208
27.11 componentTemperatureExceeded.....	208
27.12 componentTemperatureFailure.....	209
27.13 componentTemperatureNormal.....	209
27.14 componentUp.....	210
27.15 controlModuleActivityChange.....	210
27.16 controlModuleConfigSynchronized.....	211
27.17 controlModuleImageSynchronized.....	211
27.18 controlModuleInSync.....	212
27.19 controlModuleOverlaySynchronized.....	212
27.20 controlModuleSyncLost.....	213
27.21 controlModuleSyncStart.....	213
27.22 fantrayEmpty.....	214
27.23 linecardCapacityDegraded.....	214
27.24 linecardCapacityNormal.....	215
27.25 platformLowPower.....	215
27.26 platformLowReservePower.....	216
27.27 platformNormalPower.....	216
27.28 psuInputDown.....	217
27.29 psuInputUp.....	217
27.30 psuOutputDown.....	218
27.31 psuOutputUp.....	218
27.32 psuTemperatureFault.....	219
27.33 psuTemperatureNormal.....	219
27.34 systemInServiceSoftwareUpgrade.....	220
27.35 systemReboot.....	220
27.36 systemWarmReboot.....	221
27.37 systemWarmRebootAborted.....	221
28 qos.....	223
28.1 platformQoSProfileHighUtilization.....	223
28.2 platformQoSProfileHighUtilizationLowered.....	223

29 ra_guard-agent	225
29.1 ra_guardAdd.....	225
29.2 ra_guardRemove.....	225
30 sflow	226
30.1 sFlowAgentChange.....	226
30.2 sFlowCollectorUnreachable.....	226

1 About this guide

This document provides guidance for operators to interpret log events for the Nokia Service Router Linux (SR Linux). This document is intended for users who need to access and understand log events for SR Linux.

**Note:**

This manual covers the current release and may also contain some content that will be released in later maintenance loads. See the *SR Linux Release Notes* for information about features supported in each load.

1.1 What's new

See the [Summary of log event changes](#) for a list of log events that have been added or removed.

1.2 Precautionary and information messages

The following are information symbols used in the documentation.



DANGER: Danger warns that the described activity or situation may result in serious personal injury or death. An electric shock hazard could exist. Before you begin work on this equipment, be aware of hazards involving electrical circuitry, be familiar with networking environments, and implement accident prevention procedures.



WARNING: Warning indicates that the described activity or situation may, or will, cause equipment damage, serious performance problems, or loss of data.



Caution: Caution indicates that the described activity or situation may reduce your component or system performance.



Note: Note provides additional operational information.



Tip: Tip provides suggestions for use or best practices.

1.3 Conventions

Nokia SR Linux documentation uses the following command conventions.

- **Bold** indicates a command that the user must enter.
- Input and output examples are displayed in Courier text.
- An open right angle bracket indicates a progression of menu choices or simple command sequence (often selected from a user interface). Example: **start > connect to**

-
- A vertical bar (|) indicates a mutually exclusive argument.
 - Square brackets ([]) indicate optional elements.
 - Braces ({ }) indicate a required choice. When braces are contained within square brackets, they indicate a required choice within an optional element.
 - *Italic* indicates a variable.

Generic IP addresses are used in examples. Replace these with the appropriate IP addresses used in the system.

2 Log events overview

This section provides general information about the log events described in this guide for the Nokia Service Router Linux (SR Linux).

For more information about logging, see the *SR Linux Configuration Basics Guide*.

2.1 Example log event

The following contains an example log event entry from this guide for the `bgpNeighborBackwardTransition` log event.

Table 1: bgpNeighborBackwardTransition properties

Property name	Value
Application name	bgp
Event name	bgpNeighborBackwardTransition
Default severity	warning
Message format string	In network-instance <code>\$network-instance\$</code> , the BGP session with <code>\$peer-address\$</code> moved from higher state <code>\$last-state\$</code> to lower state <code>\$session-state\$</code> due to event <code>\$last-event\$</code>
Cause	No routes can be exchanged with this peer
Effect	N/A

The table title for a log event entry is the event name. Each entry contains the information described in the table that follows.

Table 2: Log event entry field descriptions

Label	Description
Application name	Name of the application generating the log message
Event name	Name of the log event
Default severity	Severity level of the log event (see Table 3: Log event entry field descriptions for the severity level)
Message format string	Text description of the log event
Cause	Cause of the log event

Label	Description
Effect	Effect of the log event

2.2 Log event properties

Log events that are forwarded to a destination are formatted. All application-generated events have the following properties:

- time stamp in UTC or local time
- generating application
- router name identifying the VRF-ID that generated the event
- subject identifying the affected object
- short message describing the event

A log event with a memory, console, or file destination has the following format:

```
nnnn YYYY/MM/DD HH:MM:SS.SS TZONE <severity>: <application> <router-name>
<subject>
<message>
```

Format properties are described in [Table 3: Log event entry field descriptions](#).

Table 3: Log event entry field descriptions

Label	Description
nnnn	Log event entry sequence number
YYYY/MM/DD	UTC or local date stamp for the log event entry: YYYY — Year MM — Month DD — Day
HH:MM:SS.SS	UTC time stamp for the event: HH — Hours (24-hour format) MM — Minutes SS.SS — Seconds.hundredths of a second
TZONE	Time zone (for example, UTC, EDT)
<severity>	Severity level of the log event: emerg — System is unusable alert — Action must be taken immediately crit — Critical conditions err — Error conditions

Label	Description
	warning — Warning conditions notice — Normal but significant condition info — Informational messages debug — Debug-level messages
<application>	Name of the application generating the log event message
<router>	Router name representing the VRF-ID that generated the log event
<subject>	Subject/affected object for the log event
<message>	Text description of the log event

3 Summary of log event changes

Table 4: Event Changes from previous release

Event Name	Change
globalConfigUpdate	New
gribiServerStart	New
gribiServerStop	New
networkInstanceConfigUpdate	New
unixSocketGribiOperDown	New
unixSocketGribiOperUp	New
linecardCapacityDegraded	New
linecardCapacityNormal	New
mirrorDestinationDelete	New
mirrorDestinationOperDown	New
mirrorDestinationOperUP	New
mirrorDestnationAdd	New
mirrorInstanceAdminDisable	New
mirrorInstanceAdminEnable	New
mirrorInstanceOperDown	New
mirrorInstanceOperUp	New
mirrorSourceAdd	New
mirrorSourceDelete	New

4 aaa

4.1 serverDown

serverDown:aaa

Table 5: *serverDown* properties

Property name	Value
Application name	aaa
Event name	serverDown
Default severity	error
Message format string	Server server_address in group server_group is down
Cause	The specified server is down, either via being unreachable, or a timeout.
Effect	The specified server can no longer be used for authentication, authorization, or accounting transactions.

4.2 serverGroupDown

serverGroupDown:aaa

Table 6: *serverGroupDown* properties

Property name	Value
Application name	aaa
Event name	serverGroupDown
Default severity	critical
Message format string	All servers in server group server_group are down
Cause	All servers within the specified server group are no longer available.
Effect	The specified server group can no longer be used for authentication, authorization, or accounting transactions.

4.3 serverRouteUnavailable

serverRouteUnavailable:aaa

Table 7: *serverRouteUnavailable* properties

Property name	Value
Application name	aaa
Event name	serverRouteUnavailable
Default severity	error
Message format string	No route available to reach remote server server_address in server group server_group via network instance network_instance
Cause	No routes are available in the specified network instance to reach the remote server.
Effect	The specified server can no longer be used for authentication, authorization, or accounting transactions.

4.4 serverTimeout

serverTimeout:aaa

Table 8: *serverTimeout* properties

Property name	Value
Application name	aaa
Event name	serverTimeout
Default severity	error
Message format string	Server server_address in group server_group has timed out
Cause	The connection between the AAA manager and the remote server has timed out. The server will be tried again in 30 seconds, or immediately if a valid response is received.
Effect	The specified server can no longer be used for authentication, authorization, or accounting transactions.

4.5 sessionClosed

sessionClosed:aaa

Table 9: sessionClosed properties

Property name	Value
Application name	aaa
Event name	sessionClosed
Default severity	notice
Message format string	Closed session for user user_name from host remote_host
Cause	The specified user has closed a session on the system.
Effect	None.

4.6 sessionDisconnected

sessionDisconnected:aaa

Table 10: sessionDisconnected properties

Property name	Value
Application name	aaa
Event name	sessionDisconnected
Default severity	notice
Message format string	Session for user user_name from remote host remote_host disconnected by administrative action
Cause	The specified user has been disconnected from the system by an administrators action.
Effect	The specified user is disconnected.

4.7 sessionOpened

sessionOpened:aaa

Table 11: sessionOpened properties

Property name	Value
Application name	aaa
Event name	sessionOpened
Default severity	notice
Message format string	Opened session for user user_name from host remote_host
Cause	The specified user has opened a session on the system.
Effect	None.

4.8 userAuthenticationFailed

userAuthenticationFailed:aaa

Table 12: userAuthenticationFailed properties

Property name	Value
Application name	aaa
Event name	userAuthenticationFailed
Default severity	warning
Message format string	User user_name authentication failed from host remote_host
Cause	The specified user has failed authentication.
Effect	None.

4.9 userAuthenticationSucceeded

userAuthenticationSucceeded:aaa

Table 13: userAuthenticationSucceeded properties

Property name	Value
Application name	aaa
Event name	userAuthenticationSucceeded

Property name	Value
Default severity	notice
Message format string	User user_name successfully authenticated from host remote_host
Cause	The specified user has successfully authenticated.
Effect	None.

5 acl

5.1 aclCpmlpv4MatchedPacket

aclCpmlpv4MatchedPacket:acl

Table 14: *aclCpmlpv4MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclCpmlpv4MatchedPacket
Default severity	notice
Message format string	An IPv4 packet, len packet-length , protocol ip-protocol , received by linecard incoming-linecard was action by entry sequence-id of the IPv4 cpm-filter. source-ip(source-port) -> dest-ip(dest-port)
Cause	This event is generated when an IPv4 packet matches an entry of the CPM IPv4 filter and that entry specifies a log action
Effect	None

5.2 aclCpmlpv6MatchedPacket

aclCpmlpv6MatchedPacket:acl

Table 15: *aclCpmlpv6MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclCpmlpv6MatchedPacket
Default severity	notice
Message format string	An IPv6 packet, len packet-length , protocol last-next-header , received by linecard incoming-linecard was action by entry sequence-id of the IPv6 cpm-filter. source-ip(source-port) -> dest-ip(dest-port)

Property name	Value
Cause	This event is generated when an IPv6 packet matches an entry of the CPM IPv6 filter and that entry specifies a log action
Effect	None

5.3 aclInterfaceInputIpv4MatchedPacket

aclInterfaceInputIpv4MatchedPacket:acl

Table 16: *aclInterfaceInputIpv4MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclInterfaceInputIpv4MatchedPacket
Default severity	notice
Message format string	An IPv4 packet, len packet-length , protocol ip-protocol , received on incoming-interface was action by entry sequence-id of filter filter-name . source-ip(source-port) -> dest-ip(dest-port)
Cause	This event is generated when an IPv4 packet matches an entry of an IPv4 filter applied to ingress traffic on a subinterface and that entry specifies a log action
Effect	None

5.4 aclInterfaceInputIpv6MatchedPacket

aclInterfaceInputIpv6MatchedPacket:acl

Table 17: *aclInterfaceInputIpv6MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclInterfaceInputIpv6MatchedPacket
Default severity	notice

Property name	Value
Message format string	An IPv6 packet, len packet-length , protocol last-next-header , received on incoming-interface was action by entry sequence-id of filter filter-name . source-ip(source-port) -> dest-ip(dest-port)
Cause	This event is generated when an IPv6 packet matches an entry of an IPv6 filter applied to ingress traffic on a subinterface and that entry specifies a log action
Effect	None

5.5 aclInterfaceOutputIpv4MatchedPacket

aclInterfaceOutputIpv4MatchedPacket:acl

Table 18: *aclInterfaceOutputIpv4MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclInterfaceOutputIpv4MatchedPacket
Default severity	notice
Message format string	An IPv4 packet, len packet-length , protocol ip-protocol , intended for transmit on outgoing-interface was action by entry sequence-id of filter filter-name . source-ip(source-port) -> dest-ip(dest-port)
Cause	This event is generated when an IPv4 packet matches an entry of an IPv4 filter applied to egress traffic on a subinterface and that entry specifies a log action
Effect	None

5.6 aclInterfaceOutputIpv6MatchedPacket

aclInterfaceOutputIpv6MatchedPacket:acl

Table 19: *aclInterfaceOutputIpv6MatchedPacket* properties

Property name	Value
Application name	acl
Event name	aclInterfaceOutputIpv6MatchedPacket

Property name	Value
Default severity	notice
Message format string	An IPv6 packet, len packet-length , protocol last-next-header , intended for transmit on outgoing-interface was action by entry sequence-id of filter filter-name . source-ip(source-port) -> dest-ip(dest-port)
Cause	This event is generated when an IPv6 packet matches an entry of an IPv6 filter applied to egress traffic on a subinterface and that entry specifies a log action
Effect	None

5.7 aclTcamProgComplete

aclTcamProgComplete:acl

Table 20: *aclTcamProgComplete* properties

Property name	Value
Application name	acl
Event name	aclTcamProgComplete
Default severity	notice
Message format string	All TCAM banks on all linecards have been reprogrammed with the latest ACL configuration changes.
Cause	This event is generated when all TCAM banks on all linecards have been reprogrammed with the latest ACL configuration changes.
Effect	None

5.8 platformAclHighUtilization

platformAclHighUtilization:acl

Table 21: *platformAclHighUtilization* properties

Property name	Value
Application name	acl

Property name	Value
Event name	platformAclHighUtilization
Default severity	warning
Message format string	The ACL resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex . Only free-entries entries are remaining.
Cause	This event is generated when the utilization of an ACL resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

5.9 platformAclHighUtilizationLowered

platformAclHighUtilizationLowered:acl

Table 22: platformAclHighUtilizationLowered properties

Property name	Value
Application name	acl
Event name	platformAclHighUtilizationLowered
Default severity	notice
Message format string	The ACL resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex .
Cause	This event is generated when the utilization of an ACL resource has decreased to a level that may no longer warrant concern
Effect	None

5.10 platformTcamHighUtilization

platformTcamHighUtilization:acl

Table 23: *platformTcamHighUtilization* properties

Property name	Value
Application name	acl
Event name	platformTcamHighUtilization
Default severity	warning
Message format string	The TCAM resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex . Only free-entries entries are remaining.
Cause	This event is generated when the utilization of a TCAM resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

5.11 platformTcamHighUtilizationLowered

platformTcamHighUtilizationLowered:acl

Table 24: *platformTcamHighUtilizationLowered* properties

Property name	Value
Application name	acl
Event name	platformTcamHighUtilizationLowered
Default severity	notice
Message format string	The TCAM resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex .
Cause	This event is generated when the utilization of a TCAM resource has decreased to a level that may no longer warrant concern
Effect	None

6 arpnd

6.1 ipArpEntryUpdated

ipArpEntryUpdated:arpnd

Table 25: *ipArpEntryUpdated* properties

Property name	Value
Application name	arpnd
Event name	ipArpEntryUpdated
Default severity	informational
Message format string	The ARP entry for ipv4-address on interface.subinterface-index has been updated from mac old-mac type old-type to mac new-mac and type new-type .
Cause	This event is generated whenever an existing static or dynamic ARP entry for an IPv4 address is overwritten. This could be a triggered by a change of entry type (static vs dynamic) or a change of MAC address or a change of the subinterface binding.
Effect	None

6.2 ipSubinterfaceDuplicateIpv4Address

ipSubinterfaceDuplicateIpv4Address:arpnd

Table 26: *ipSubinterfaceDuplicateIpv4Address* properties

Property name	Value
Application name	arpnd
Event name	ipSubinterfaceDuplicateIpv4Address
Default severity	notice
Message format string	The IPv4 address ipv4-address assigned to interface.subinterface-index is being used by another host or router on the same subnet.

Property name	Value
Cause	This event is generated when ARP detects that another system is using the same IPv4 address
Effect	Unreliable communications

6.3 ipSubinterfaceDuplicateIpv6Address

ipSubinterfaceDuplicateIpv6Address:arpnd

Table 27: *ipSubinterfaceDuplicateIpv6Address* properties

Property name	Value
Application name	arpnd
Event name	ipSubinterfaceDuplicateIpv6Address
Default severity	notice
Message format string	The IPv6 address ipv6-address assigned to interface.subinterface-index is being used by another host or router on the same subnet.
Cause	This event is generated when IPv6 DAD detects that another system is using the same IPv6 address
Effect	Unreliable communications

6.4 ipSubinterfaceDuplicateMacAddress

ipSubinterfaceDuplicateMacAddress:arpnd

Table 28: *ipSubinterfaceDuplicateMacAddress* properties

Property name	Value
Application name	arpnd
Event name	ipSubinterfaceDuplicateMacAddress
Default severity	notice
Message format string	The MAC address mac-address used by interface.subinterface-index is being used by another host or router on the same subnet.

Property name	Value
Cause	This event is generated when ARP or IPv6 Neighbor Discovery detects that another system is using the same MAC address
Effect	Unreliable communications

6.5 ipSubinterfaceInvalidArp

ipSubinterfaceInvalidArp:arpnd

Table 29: *ipSubinterfaceInvalidArp* properties

Property name	Value
Application name	arpnd
Event name	ipSubinterfaceInvalidArp
Default severity	notice
Message format string	An ARP request for ipv4-address was received on interface.subinterface-index and there is no matching IPv4 subnet.
Cause	This event is generated when ARP receives an ARP request for an invalid IPv4 address
Effect	None

6.6 ipSubinterfaceInvalidIpv6NeighborSolicitation

ipSubinterfaceInvalidIpv6NeighborSolicitation:arpnd

Table 30: *ipSubinterfaceInvalidIpv6NeighborSolicitation* properties

Property name	Value
Application name	arpnd
Event name	ipSubinterfaceInvalidIpv6NeighborSolicitation
Default severity	notice
Message format string	An IPv6 neighbor solicitation for ipv6-address was received on interface.subinterface-index and there is no matching IPv6 subnet.

Property name	Value
Cause	This event is generated when IPv6 neighbor discovery receives a NS message for an invalid IPv6 address
Effect	None

6.7 ipv6NeighborEntryUpdated

ipv6NeighborEntryUpdated:arpnd

Table 31: *ipv6NeighborEntryUpdated* properties

Property name	Value
Application name	arpnd
Event name	ipv6NeighborEntryUpdated
Default severity	informational
Message format string	The IPv6 neighbor discovery entry for ipv6-address on interface.subinterface-index has been updated from mac old-mac type old-type to mac new-mac and type new-type .
Cause	This event is generated whenever an existing static or dynamic neighbor entry for an IPv6 address is overwritten. This could be a triggered by a change of entry type (static vs dynamic) or a change of MAC address or a change of the subinterface binding.
Effect	None

7 bfd

7.1 bfdDownEvent

bfdDownEvent:bfd

Table 32: *bfdDownEvent* properties

Property name	Value
Application name	bfd
Event name	bfdDownEvent
Default severity	warning
Message format string	BFD: Network-instance network-instance - Session from local-address:local-discriminator to remote-address:remote-discriminator has transitioned to the down-state state with local-diagnostic code: local-diagnostic-str (local-diagnostic-code) and remote-diagnostic code: remote-diagnostic-str (remote-diagnostic-code)
Cause	This notification is generated when a BFD sessions transitions to the Down or Admin Down state from an Up state.
Effect	The specified BFD sessions is now down. If the new state is Down, the session is down due to a failure see the local or remote diagnostic code. If the new state is Admin-Down the session is down due to administrative reasons.

7.2 bfdMaxSessionActive

bfdMaxSessionActive:bfd

Table 33: *bfdMaxSessionActive* properties

Property name	Value
Application name	bfd
Event name	bfdMaxSessionActive
Default severity	warning

Property name	Value
Message format string	BFD: Network-instance network-instance - Session from local-address to remote-address requested by client-protocol could not be created because the maximum number of BFD sessions bfd-max-session are active.
Cause	This notification is generated when a BFD session cannot be created because the maximum number of BFD sessions are already active.
Effect	No more BFD sessions can be created until some existing sessions are removed.

7.3 bfdProtocolClientAdd

bfdProtocolClientAdd:bfd

Table 34: *bfdProtocolClientAdd* properties

Property name	Value
Application name	bfd
Event name	bfdProtocolClientAdd
Default severity	notice
Message format string	BFD: Network-instance network-instance - The protocol client-protocol is now using BFD session from local-address:local-discriminator to remote-address: remote-discriminator
Cause	This notification is generated when a new protocol begins to use a BFD session to track liveness.
Effect	The specified protocol will be notified by BFD if the associated sessions transitions from an Up to a Down state. It will be up to the receiving protocol to determine the course of action.

7.4 bfdProtocolClientRemove

bfdProtocolClientRemove:bfd

Table 35: *bfdProtocolClientRemove* properties

Property name	Value
Application name	bfd

Property name	Value
Event name	bfdProtocolClientRemove
Default severity	notice
Message format string	BFD: Network-instance network-instance - The protocol client-protocol using BFD session from local-address:local-discriminator to remote-address: remote-discriminator has been cleared
Cause	This notification is generated when a protocol stops using a BFD session to track liveliness.
Effect	The specified protocol will no longer be notified by BFD if the associated sessions transitions from an Up to a Down state

7.5 bfdSessionDeleted

bfdSessionDeleted:bfd

Table 36: *bfdSessionDeleted* properties

Property name	Value
Application name	bfd
Event name	bfdSessionDeleted
Default severity	notice
Message format string	BFD: Network-instance network-instance - Session from local-address:local-discriminator to remote-address:remote-discriminator has been deleted
Cause	This notification is generated when a BFD session has been removed from the configuration.
Effect	The BFD session has been removed.

7.6 bfdSessionUp

bfdSessionUp:bfd

Table 37: *bfdSessionUp* properties

Property name	Value
Application name	bfd
Event name	bfdSessionUp
Default severity	notice
Message format string	BFD: Network-instance network-instance - Session from local-address:local-discriminator to remote-address:remote-discriminator is UP
Cause	This notification is generated when a BFD sessions transitions to the up state.
Effect	The BFD session is now operational.

7.7 microbfdDownEvent

microbfdDownEvent:bfd

Table 38: *microbfdDownEvent* properties

Property name	Value
Application name	bfd
Event name	microbfdDownEvent
Default severity	warning
Message format string	BFD: LAG lag-interface member member-interface - Session from local-address:local-discriminator to remote-address:remote-discriminator has transitioned to the down-state state with local-diagnostic code: local-diagnostic-str (local-diagnostic-code) and remote-diagnostic code: remote-diagnostic-str (remote-diagnostic-code)
Cause	This notification is generated when a BFD sessions transitions to the Down or Admin Down state from an Up state.
Effect	The specified BFD sessions is now down. If the new state is Down, the session is down due to a failure see the local or remote diagnostic code. If the new state is Admin-Down the session is down due to administrative reasons.

7.8 microbfdMaxSessionActive

microbfdMaxSessionActive: bfd

Table 39: *microbfdMaxSessionActive* properties

Property name	Value
Application name	bfd
Event name	microbfdMaxSessionActive
Default severity	warning
Message format string	BFD: LAG lag-interface member member-interface - Session from local-address to remote-address could not be created because the maximum number of BFD sessions bfd-max-session are active.
Cause	This notification is generated when a BFD session cannot be created because the maximum number of BFD sessions are already active.
Effect	No more BFD sessions can be created until some existing sessions are removed.

7.9 microbfdSessionDeleted

microbfdSessionDeleted: bfd

Table 40: *microbfdSessionDeleted* properties

Property name	Value
Application name	bfd
Event name	microbfdSessionDeleted
Default severity	notice
Message format string	BFD: LAG lag-interface member member-interface - Session from local-address:local-discriminator to remote-address:remote-discriminator has been deleted
Cause	This notification is generated when a BFD session has been removed from the configuration.
Effect	The BFD session has been removed.

7.10 microbfdSessionUp

microbfdSessionUp:bfd

Table 41: *microbfdSessionUp* properties

Property name	Value
Application name	bfd
Event name	microbfdSessionUp
Default severity	notice
Message format string	BFD: LAG lag-interface member member-interface - Session from local-address:local-discriminator to remote-address:remote-discriminator is UP
Cause	This notification is generated when a BFD sessions transitions to the up state.
Effect	The BFD session is now operational.

8 bgp

8.1 bgpIncomingDynamicPeerLimitReached

bgpIncomingDynamicPeerLimitReached:bgp

Table 42: *bgpIncomingDynamicPeerLimitReached* properties

Property name	Value
Application name	bgp
Event name	bgpIncomingDynamicPeerLimitReached
Default severity	notice
Message format string	In network-instance network-instance , an incoming BGP connection from peer-address was rejected because the limit for the maximum number of incoming dynamic peers, max-sessions , has been reached.
Cause	The configured limit on the number of incoming sessions associated with dynamic peers has been reached.
Effect	The incoming connection attempt is rejected.

8.2 bgpInstanceConvergenceStateTransition

bgpInstanceConvergenceStateTransition:bgp

Table 43: *bgpInstanceConvergenceStateTransition* properties

Property name	Value
Application name	bgp
Event name	bgpInstanceConvergenceStateTransition
Default severity	notice
Message format string	In network-instance network-instance , the BGP convergence state for the address-family address family transitioned from the previous-state state to the new-state state

Property name	Value
Cause	This event is generated when the BGP convergence process is being tracked and a state transition occurs
Effect	Dependent on the new state

8.3 bgpLowMemory

bgpLowMemory:bgp

Table 44: *bgpLowMemory* properties

Property name	Value
Application name	bgp
Event name	bgpLowMemory
Default severity	critical
Message format string	In network-instance network-instance , the BGP session with peer-address was terminated immediately because BGP has out of memory.
Cause	BGP has run out of memory and this peer has been shutdown to reclaim some memory.
Effect	No routes can be exchanged with this peer.

8.4 bgpNeighborBackwardTransition

bgpNeighborBackwardTransition:bgp

Table 45: *bgpNeighborBackwardTransition* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborBackwardTransition
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address moved from higher state last-state to lower state session-state due to event last-event

Property name	Value
Cause	This event is generated when the BGP FSM moves from a higher numbered state to a lower numbered state.
Effect	No routes can be exchanged with this peer.

8.5 bgpNeighborClosedTCPConn

bgpNeighborClosedTCPConn:bgp

Table 46: *bgpNeighborClosedTCPConn* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborClosedTCPConn
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address was closed because the neighbor closed the TCP connection.
Cause	The router received a TCP FIN message from its peer.
Effect	No routes can be exchanged with this peer.

8.6 bgpNeighborEstablished

bgpNeighborEstablished:bgp

Table 47: *bgpNeighborEstablished* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborEstablished
Default severity	notice
Message format string	In network-instance network-instance , the BGP session with peer-address moved into the ESTABLISHED state
Cause	The BGP session entered the ESTABLISHED state.

Property name	Value
Effect	Routes of negotiated address families can now be exchanged with this peer.

8.7 bgpNeighborGRHelpingStarted

bgpNeighborGRHelpingStarted:bgp

Table 48: *bgpNeighborGRHelpingStarted* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborGRHelpingStarted
Default severity	notice
Message format string	In network-instance network-instance , the router has started providing GR helper service to the neighbor peer-address
Cause	GR helper is activated
Effect	Routes previously received from the peer, prior to its restart, are retained as stale until the stale-routes-time expires.

8.8 bgpNeighborGRHelpingStopped

bgpNeighborGRHelpingStopped:bgp

Table 49: *bgpNeighborGRHelpingStopped* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborGRHelpingStopped
Default severity	notice
Message format string	In network-instance network-instance , the router has stopped providing GR helper service to the neighbor peer-address
Cause	GR helper is deactivated
Effect	Any remaining stale routes are immediately removed.

8.9 bgpNeighborHoldTimeExpired

bgpNeighborHoldTimeExpired:bgp

Table 50: *bgpNeighborHoldTimeExpired* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborHoldTimeExpired
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address was terminated because a KEEPALIVE message was not received before the holdtime limit of negotiated-hold-time was reached.
Cause	BGP did not receive a KEEPALIVE message from the peer before the negotiated holdtime expired.
Effect	No routes can be exchanged with this peer.

8.10 bgpNeighborInvalidLocalIP

bgpNeighborInvalidLocalIP:bgp

Table 51: *bgpNeighborInvalidLocalIP* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborInvalidLocalIP
Default severity	warning
Message format string	In network-instance network-instance , an incoming BGP connection from peer-address was rejected because the destination IP address does not match the allowed local-address, local-address .
Cause	BGP configuration does not allow an incoming BGP connection to this IP address.
Effect	No routes can be exchanged with this peer.

8.11 bgpNeighborNoOpenReceived

bgpNeighborNoOpenReceived: bgp

Table 52: *bgpNeighborNoOpenReceived* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborNoOpenReceived
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address was terminated because an OPEN message was not received before the configured holdtime limit was reached.
Cause	BGP did not receive an OPEN message from the peer before the configured holdtime expired.
Effect	No routes can be exchanged with this peer.

8.12 bgpNeighborPrefixLimitReached

bgpNeighborPrefixLimitReached: bgp

Table 53: *bgpNeighborPrefixLimitReached* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborPrefixLimitReached
Default severity	notice
Message format string	In network-instance network-instance , the number of family routes received from the neighbor peer-address has exceeded the configured limit.
Cause	The number of received routes from the peer has exceeded the configured limit for the associated address family.
Effect	No effect. Routes above the limit are still received and processed.

8.13 bgpNeighborPrefixLimitThresholdReached

bgpNeighborPrefixLimitThresholdReached: bgp

Table 54: *bgpNeighborPrefixLimitThresholdReached* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborPrefixLimitThresholdReached
Default severity	notice
Message format string	In network-instance network-instance , the number of family routes received from the neighbor peer-address has exceeded the configured threshold, which is warning-threshold-pct% of the limit.
Cause	The number of received routes from the peer has exceeded the configured threshold for the associated address family.
Effect	No effect. Routes above the threshold are still received and processed.

8.14 bgpNeighborUnknownRemoteIP

bgpNeighborUnknownRemoteIP: bgp

Table 55: *bgpNeighborUnknownRemoteIP* properties

Property name	Value
Application name	bgp
Event name	bgpNeighborUnknownRemoteIP
Default severity	warning
Message format string	In network-instance network-instance , an incoming BGP connection from peer-address was rejected because the source IP address does not match the address of any configured neighbor or any dynamic-neighbor block.
Cause	BGP configuration does not allow an incoming BGP connection from this IP address.
Effect	No routes can be exchanged with this peer.

8.15 bgpNLRIInvalid

bgpNLRIInvalid:bgp

Table 56: *bgpNLRIInvalid* properties

Property name	Value
Application name	bgp
Event name	bgpNLRIInvalid
Default severity	warning
Message format string	In network-instance network-instance , a route for NLRI nlri was received from neighbor peer-address and it was ignored because it is considered an invalid NLRI.
Cause	The router received an UPDATE with an invalid NLRI
Effect	The route associated with the NLRI is not added or removed from the BGP RIB.

8.16 bgpNotificationReceivedFromNeighbor

bgpNotificationReceivedFromNeighbor:bgp

Table 57: *bgpNotificationReceivedFromNeighbor* properties

Property name	Value
Application name	bgp
Event name	bgpNotificationReceivedFromNeighbor
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address was closed because the neighbor sent a NOTIFICATION with code last-notification-error-code and subcode last-notification-error-subcode
Cause	The router received a NOTIFICATION message from its peer.
Effect	No routes can be exchanged with this peer.

8.17 bgpNotificationSentToNeighbor

bgpNotificationSentToNeighbor: bgp

Table 58: *bgpNotificationSentToNeighbor* properties

Property name	Value
Application name	bgp
Event name	bgpNotificationSentToNeighbor
Default severity	warning
Message format string	In network-instance network-instance , the BGP session with peer-address was closed because the router sent this neighbor a NOTIFICATION with code last-notification-error-code and subcode last-notification-error-subcode
Cause	The router sent a NOTIFICATION message to its peer.
Effect	No routes can be exchanged with this peer.

8.18 bgpOutgoingDynamicPeerLimitReached

bgpOutgoingDynamicPeerLimitReached: bgp

Table 59: *bgpOutgoingDynamicPeerLimitReached* properties

Property name	Value
Application name	bgp
Event name	bgpOutgoingDynamicPeerLimitReached
Default severity	notice
Message format string	In network-instance network-instance , no session was initiated towards the LLDP-discovered address peer-address because the limit for the maximum number of outgoing dynamic peers, max-sessions , has been reached.
Cause	The configured limit on the number of outgoing sessions associated with dynamic peers has been reached.
Effect	No connection attempt is made by the router.

8.19 bgpPathAttributeDiscarded

bgpPathAttributeDiscarded:bgp

Table 60: *bgpPathAttributeDiscarded* properties

Property name	Value
Application name	bgp
Event name	bgpPathAttributeDiscarded
Default severity	warning
Message format string	In network-instance network-instance , a path attribute of type attribute-type and length attribute-length was discarded in a route received from the neighbor peer-address .
Cause	The path attribute was malformed and the attribute-discard approach is used for this type of attribute.
Effect	The intended meaning of that path attribute is not applied but the UPDATE message is still processed for new reachability information.

8.20 bgpPathAttributeMalformed

bgpPathAttributeMalformed:bgp

Table 61: *bgpPathAttributeMalformed* properties

Property name	Value
Application name	bgp
Event name	bgpPathAttributeMalformed
Default severity	warning
Message format string	In network-instance network-instance , a path attribute of type attribute-type and length attribute-length that was received in a route from the neighbor peer-address was considered malformed.
Cause	The router considers a path attribute to be malformed, for example not the expected length. The UPDATE message can still be parsed though.
Effect	Dependent on the type of the malformed path attribute. Either the malformed attribute is discarded or else the entire UPDATE message is considered to have unreachable NLRI.

8.21 bgpRouteWithdrawnDueToError

bgpRouteWithdrawnDueToError: bgp

Table 62: *bgpRouteWithdrawnDueToError* properties

Property name	Value
Application name	bgp
Event name	bgpRouteWithdrawnDueToError
Default severity	warning
Message format string	In network-instance network-instance , a route for NLRI nlri was received from neighbor peer-address and it was considered withdrawn because of a recoverable error in the UPDATE message.
Cause	The router received a malformed UPDATE and the malformed path attribute(s) require as a treat-as-withdraw error handling behavior for the included set of routes.
Effect	There is no reachability for the NLRI in the malformed UPDATE message.

8.22 bgpUpdateInvalid

bgpUpdateInvalid: bgp

Table 63: *bgpUpdateInvalid* properties

Property name	Value
Application name	bgp
Event name	bgpUpdateInvalid
Default severity	warning
Message format string	In network-instance network-instance , an UPDATE message received from neighbor peer-address was considered invalid and caused the connection to be closed because the NLRI could not be parsed correctly.
Cause	The router received a malformed UPDATE which made it is impossible to identify all of the NLRI correctly.
Effect	The session is shutdown.

9 bridgetable

9.1 evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilization

evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilization:bridgetable

Table 64: *evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilization
Default severity	warning
Message format string	The number of Evpn-Mpls Multicast Destinations in the bridge table for the bgp-instance network-instance.bgp-instance has reached pct-threshold% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of Evpn-Mpls Multicast Destinations in the bgp-instance reaches the warning threshold percentage of the allowed limit.
Effect	None

9.2 evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilizationLowered

evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilizationLowered:bridgetable

Table 65: *evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilizationLowered* properties

Property name	Value
Application name	bridgetable
Event name	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitHighUtilizationLowered
Default severity	notice

Property name	Value
Message format string	The number of Evpn-Mpls Multicast Destinations in the bridge table for the bgp-instance network-instance.bgp-instance is now below a pct-threshold% minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of Evpn-Mpls Multicast Destinations in the bgp-instance is 5% below the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.3 evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitLowered

evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitLowered:bridgetable

Table 66: *evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitLowered* properties

Property name	Value
Application name	bridgetable
Event name	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitLowered
Default severity	notice
Message format string	The number of Evpn-Mpls Multicast Destinations in the bridge table for the bgp-instance network-instance.bgp-instance is now below the allowed limit of maximum-entries .
Cause	This event is generated when the number of Evpn-Mpls Multicast Destinations in a bgp-instance goes below the allowed limit, after being above the allowed limit
Effect	New Evpn-Mpls Multicast Destinations can be added to the multicast list of the network-instance.

9.4 evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitReached

evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitReached:bridgetable

Table 67: *evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitReached* properties

Property name	Value
Application name	bridgetable

Property name	Value
Event name	evpnMplsBgpInstanceBridgeTableMulticastDestinationsLimitReached
Default severity	warning
Message format string	The number of Evpn-Mpls Multicast Destinations in the bridge table for the bgp-instance network-instance.bgp-instance is at the allowed limit of maximum-entries .
Cause	This event is generated when the number of Evpn-Mpls Multicast Destinations in a bgp-instance is at the allowed limit.
Effect	New Evpn-Mpls Multicast Destinations cannot be added to the multicast list of the network-instance.

9.5 I2SubinterfaceBridgeTableDuplicateMacAddressDeleted

I2SubinterfaceBridgeTableDuplicateMacAddressDeleted:bridgetable

Table 68: I2SubinterfaceBridgeTableDuplicateMacAddressDeleted properties

Property name	Value
Application name	bridgetable
Event name	I2SubinterfaceBridgeTableDuplicateMacAddressDeleted
Default severity	notice
Message format string	A duplicate MAC address mac-address detected on sub-interface interface.subinterface-index is now deleted.
Cause	This event is generated when a duplicate MAC address is deleted.
Effect	The duplicate mac-address is now deleted.

9.6 I2SubinterfaceBridgeTableDuplicateMacAddressDetected

I2SubinterfaceBridgeTableDuplicateMacAddressDetected:bridgetable

Table 69: I2SubinterfaceBridgeTableDuplicateMacAddressDetected properties

Property name	Value
Application name	bridgetable

Property name	Value
Event name	I2SubinterfaceBridgeTableDuplicateMacAddressDetected
Default severity	notice
Message format string	A duplicate MAC address mac-address was detected on sub-interface interface.subinterface-index .
Cause	This event is generated when a duplicate MAC address is detected, qualified by the bridge-table mac-duplication configuration under the network-instance and the sub-interfaces configured under the network-instance.
Effect	depending on the mac-duplication configuration, traffic destined to the duplicate mac-address maybe blackholed or not reprogrammed against any other sub-interface on the network-instance

9.7 I2SubinterfaceBridgeTableMacLimitHighUtilization

I2SubinterfaceBridgeTableMacLimitHighUtilization:bridgetable

Table 70: I2SubinterfaceBridgeTableMacLimitHighUtilization properties

Property name	Value
Application name	bridgetable
Event name	I2SubinterfaceBridgeTableMacLimitHighUtilization
Default severity	warning
Message format string	The number of MAC addresses in the bridge table for sub-interface interface.subinterface-index has reached pct-threshold% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table for a sub-interface reaches the configured warning threshold percentage of the allowed limit.
Effect	None

9.8 I2SubinterfaceBridgeTableMacLimitHighUtilizationLowered

I2SubinterfaceBridgeTableMacLimitHighUtilizationLowered:bridgetable

Table 71: I2SubinterfaceBridgeTableMacLimitHighUtilizationLowered properties

Property name	Value
Application name	bridgetable
Event name	I2SubinterfaceBridgeTableMacLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table for sub-interface interface.subinterface-index is below pct-threshold% (minus 5%) of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table for a sub-interface is below 5% minus the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.9 I2SubinterfaceBridgeTableMacLimitLowered

I2SubinterfaceBridgeTableMacLimitLowered:bridgetable

Table 72: I2SubinterfaceBridgeTableMacLimitLowered properties

Property name	Value
Application name	bridgetable
Event name	I2SubinterfaceBridgeTableMacLimitLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table for the sub-interface interface.subinterface-index is below the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table for a sub-interface is below the allowed limit, after being above the allowed limit
Effect	new mac-addresses for the sub-interface can now be added to the bridge table.

9.10 I2SubinterfaceBridgeTableMacLimitReached

I2SubinterfaceBridgeTableMacLimitReached:bridgetable

Table 73: I2SubinterfaceBridgeTableMacLimitReached properties

Property name	Value
Application name	bridgetable
Event name	I2SubinterfaceBridgeTableMacLimitReached
Default severity	warning
Message format string	The number of MAC addresses in the bridge table for the sub-interface interface.subinterface-index has reached the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table for the sub-interface is at the allowed limit.
Effect	new mac-addresses for the sub-interface cannot be added in the bridge table.

9.11 networkInstanceBridgeTableDuplicateMacAddressDeleted

networkInstanceBridgeTableDuplicateMacAddressDeleted:bridgetable

Table 74: networkInstanceBridgeTableDuplicateMacAddressDeleted properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableDuplicateMacAddressDeleted
Default severity	notice
Message format string	A duplicate MAC address mac-address detected on network-instance is now deleted.
Cause	This event is generated when a duplicate MAC address is deleted.
Effect	The duplicate mac-address is now deleted.

9.12 networkInstanceBridgeTableDuplicateMacAddressDetected

networkInstanceBridgeTableDuplicateMacAddressDetected:bridgetable

Table 75: *networkInstanceBridgeTableDuplicateMacAddressDetected* properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableDuplicateMacAddressDetected
Default severity	notice
Message format string	A duplicate MAC address mac-address was detected on network-instance .
Cause	This event is generated when a duplicate MAC address is detected, qualified by the bridge-table mac-duplication configuration under the network-instance and the sub-interfaces configured under the network-instance.
Effect	depending on the mac-duplication configuration, traffic destined to the duplicate mac-address maybe blackholed or not reprogrammed against any other sub-interface on the network-instance

9.13 networkInstanceBridgeTableMacLimitHighUtilization

networkInstanceBridgeTableMacLimitHighUtilization:bridgetable

Table 76: *networkInstanceBridgeTableMacLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableMacLimitHighUtilization
Default severity	warning
Message format string	The number of MAC addresses in the bridge table of network-instance network-instance has reached pct-threshold% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of a network-instance reaches the configured warning threshold percentage of the allowed limit.
Effect	None

9.14 networkInstanceBridgeTableMacLimitHighUtilizationLowered

networkInstanceBridgeTableMacLimitHighUtilizationLowered:bridgetable

Table 77: networkInstanceBridgeTableMacLimitHighUtilizationLowered properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableMacLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table of network-instance network-instance is now at pct-threshold % minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of the network-instance is at 5% minus the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.15 networkInstanceBridgeTableMacLimitLowered

networkInstanceBridgeTableMacLimitLowered:bridgetable

Table 78: networkInstanceBridgeTableMacLimitLowered properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableMacLimitLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table of network-instance network-instance is now below the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of a network-instance goes below the allowed limit, after being above the allowed limit
Effect	new mac-addresses can now be added to the bridge table.

9.16 networkInstanceBridgeTableMacLimitReached

networkInstanceBridgeTableMacLimitReached:bridgetable

Table 79: networkInstanceBridgeTableMacLimitReached properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableMacLimitReached
Default severity	warning
Message format string	The number of MAC addresses in the bridge table of network-instance network-instance is at the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of a network-instance is at the allowed limit.
Effect	new mac-addresses cannot be added in the bridge table.

9.17 networkInstanceBridgeTableProxyArpDuplicateIpAddressDeleted

networkInstanceBridgeTableProxyArpDuplicateIpAddressDeleted:bridgetable

Table 80: networkInstanceBridgeTableProxyArpDuplicateIpAddressDeleted properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableProxyArpDuplicateIpAddressDeleted
Default severity	notice
Message format string	A duplicate proxy ARP IP ip-address detected on network-instance is now deleted.
Cause	This event is generated when a duplicate proxy ARP IP is deleted.
Effect	The duplicate proxy ARP IP is now deleted.

9.18 networkInstanceBridgeTableProxyArpDuplicateIpAddressDetected

networkInstanceBridgeTableProxyArpDuplicateIpAddressDetected:bridgetable

Table 81: *networkInstanceBridgeTableProxyArpDuplicateIpAddressDetected* properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableProxyArpDuplicateIpAddressDetected
Default severity	notice
Message format string	A duplicate link-layer-address new-mac-address was detected for proxy ARP IP ip-address link-layer-address old-mac-address on network-instance .
Cause	This event is generated when when duplicate detection criteria is met when a new link-layer-address overwrites the existing link-layer-address for the proxy ARP IP on the network-instance.
Effect	A traffic disruption may occur if both systems are active

9.19 networkInstanceBridgeTableProxyArpLimitHighUtilization

networkInstanceBridgeTableProxyArpLimitHighUtilization:bridgetable

Table 82: *networkInstanceBridgeTableProxyArpLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableProxyArpLimitHighUtilization
Default severity	warning
Message format string	The number of proxy ARP entries in the bridge table of network-instance network-instance has reached pct-threshold % of the allowed limit of maximum-entries .
Cause	This event is generated when the number of proxy ARP entries in the bridge table of a network-instance reaches the warning threshold percentage of the allowed limit.
Effect	None

9.20 networkInstanceBridgeTableProxyArpLimitHighUtilizationLowered

networkInstanceBridgeTableProxyArpLimitHighUtilizationLowered:bridgetable

Table 83: *networkInstanceBridgeTableProxyArpLimitHighUtilizationLowered* properties

Property name	Value
Application name	bridgetable
Event name	networkInstanceBridgeTableProxyArpLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of proxy ARP entries in the bridge table of network-instance network-instance is now at pct-threshold% minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of proxy ARP entries in the bridge table of the network-instance is at 5% minus the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.21 systemBridgeTableMacLimitHighUtilization

systemBridgeTableMacLimitHighUtilization:bridgetable

Table 84: *systemBridgeTableMacLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableMacLimitHighUtilization
Default severity	warning
Message format string	The number of MAC addresses in the bridge table of the system has reached pct-threshold% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of the system reaches the configured warning threshold percentage of the allowed limit.
Effect	None

9.22 systemBridgeTableMacLimitHighUtilizationLowered

systemBridgeTableMacLimitHighUtilizationLowered:bridgetable

Table 85: *systemBridgeTableMacLimitHighUtilizationLowered* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableMacLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table of the system is now at pct-threshold% minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of the system is at 5% minus the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.23 systemBridgeTableMacLimitLowered

systemBridgeTableMacLimitLowered:bridgetable

Table 86: *systemBridgeTableMacLimitLowered* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableMacLimitLowered
Default severity	notice
Message format string	The number of MAC addresses in the bridge table of the system is now below the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of the system goes below the allowed limit, after being above the allowed limit
Effect	new mac-addresses can now be added to the bridge table.

9.24 systemBridgeTableMacLimitReached

systemBridgeTableMacLimitReached:bridgetable

Table 87: *systemBridgeTableMacLimitReached* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableMacLimitReached
Default severity	warning
Message format string	The number of MAC addresses in the bridge table of the system is at the allowed limit of maximum-entries .
Cause	This event is generated when the number of MAC addresses in the bridge table of the system is at the allowed limit.
Effect	new mac-addresses cannot be added in any bridge table in the system.

9.25 systemBridgeTableProxyArpLimitHighUtilization

systemBridgeTableProxyArpLimitHighUtilization:bridgetable

Table 88: *systemBridgeTableProxyArpLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableProxyArpLimitHighUtilization
Default severity	warning
Message format string	The number of proxy ARP entries in the bridge table of the system has reached pct-threshold% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of proxy ARP entries in the bridge table the system reaches the warning threshold percentage of the allowed limit.
Effect	None

9.26 systemBridgeTableProxyArpLimitHighUtilizationLowered

systemBridgeTableProxyArpLimitHighUtilizationLowered:bridgetable

Table 89: *systemBridgeTableProxyArpLimitHighUtilizationLowered* properties

Property name	Value
Application name	bridgetable
Event name	systemBridgeTableProxyArpLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of proxy ARP entries in the bridge table of the system is now at pct-threshold % minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of proxy ARP entries in the bridge table of the system is at 5% minus the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.27 vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilization

vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilization:bridgetable

Table 90: *vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilization* properties

Property name	Value
Application name	bridgetable
Event name	vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilization
Default severity	warning
Message format string	The number of Vxlan Multicast Destinations in the bridge table for the vxlan-interface tunnel-interface.vxlan-interface has reached pct-threshold % of the allowed limit of maximum-entries .
Cause	This event is generated when the number of Vxlan Multicast Destinations in the vxlan-interface reaches the warning threshold percentage of the allowed limit.
Effect	None

9.28 vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilizationLowered

vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilizationLowered:bridgetable

Table 91: *vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilizationLowered* properties

Property name	Value
Application name	bridgetable
Event name	vxlanInterfaceBridgeTableMulticastDestinationsLimitHighUtilizationLowered
Default severity	notice
Message format string	The number of Vxlan Multicast Destinations in the bridge table for the vxlan-interface tunnel-interface.vxlan-interface is now below a pct-threshold% minus 5% of the allowed limit of maximum-entries .
Cause	This event is generated when the number of Vxlan Multicast Destinations in the vxlan-interface is 5% below the warning threshold percentage of the allowed limit, after having exceeded the maximum percentage threshold of the allowed limit.
Effect	None

9.29 vxlanInterfaceBridgeTableMulticastDestinationsLimitLowered

vxlanInterfaceBridgeTableMulticastDestinationsLimitLowered:bridgetable

Table 92: *vxlanInterfaceBridgeTableMulticastDestinationsLimitLowered* properties

Property name	Value
Application name	bridgetable
Event name	vxlanInterfaceBridgeTableMulticastDestinationsLimitLowered
Default severity	notice
Message format string	The number of Vxlan Multicast Destinations in the bridge table for the vxlan-interface tunnel-interface.vxlan-interface is now below the allowed limit of maximum-entries .
Cause	This event is generated when the number of Vxlan Multicast Destinations in a vxlan-interface goes below the allowed limit, after being above the allowed limit
Effect	New Vxlan Multicast Destinations can be added to the vxlan-interface.

9.30 vxlanInterfaceBridgeTableMulticastDestinationsLimitReached

vxlanInterfaceBridgeTableMulticastDestinationsLimitReached:bridgetable

Table 93: vxlanInterfaceBridgeTableMulticastDestinationsLimitReached properties

Property name	Value
Application name	bridgetable
Event name	vxlanInterfaceBridgeTableMulticastDestinationsLimitReached
Default severity	warning
Message format string	The number of Vxlan Multicast Destinations in the bridge table for the vxlan-interface tunnel-interface.vxlan-interface is at the allowed limit of maximum-entries .
Cause	This event is generated when the number of Vxlan Multicast Destinations in a vxlan-interface is at the allowed limit.
Effect	New Vxlan Multicast Destinations cannot be added to the vxlan-interface.

10 chassis

10.1 platformDatapathResourceHighUtilization

platformDatapathResourceHighUtilization:chassis

Table 94: platformDatapathResourceHighUtilization properties

Property name	Value
Application name	chassis
Event name	platformDatapathResourceHighUtilization
Default severity	warning
Message format string	The datapath resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex
Cause	This event is generated when the utilization of a datapath resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

10.2 platformDatapathResourceHighUtilizationLowered

platformDatapathResourceHighUtilizationLowered:chassis

Table 95: platformDatapathResourceHighUtilizationLowered properties

Property name	Value
Application name	chassis
Event name	platformDatapathResourceHighUtilizationLowered
Default severity	notice
Message format string	The datapath resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex

Property name	Value
Cause	This event is generated when the utilization of a datapath resource has decreased to a level that may no longer warrant concern
Effect	None

10.3 platformDatapathResourceLimitCleared

platformDatapathResourceLimitCleared:chassis

Table 96: platformDatapathResourceLimitCleared properties

Property name	Value
Application name	chassis
Event name	platformDatapathResourceLimitCleared
Default severity	notice
Message format string	The datapath resource called resource-name has decreased from 100% utilization back to 95% or less utilization on linecard linecard , forwarding complex forwarding-complex
Cause	This event is generated when the utilization of a datapath resource has decreased to a level such that resource exhaustion is no longer imminent
Effect	None

10.4 platformDatapathResourceLimitReached

platformDatapathResourceLimitReached:chassis

Table 97: platformDatapathResourceLimitReached properties

Property name	Value
Application name	chassis
Event name	platformDatapathResourceLimitReached
Default severity	warning

Property name	Value
Message format string	The datapath resource called resource-name has reached 100% utilization on linecard linecard , forwarding complex forwarding-complex
Cause	This event is generated when the utilization of a datapath resource has exhausted the resource
Effect	None

10.5 platformMtuHighUtilization

platformMtuHighUtilization:chassis

Table 98: platformMtuHighUtilization properties

Property name	Value
Application name	chassis
Event name	platformMtuHighUtilization
Default severity	warning
Message format string	The MTU resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex . Only free-entries entries are remaining.
Cause	This event is generated when the utilization of an MTU resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

10.6 platformMtuHighUtilizationLowered

platformMtuHighUtilizationLowered:chassis

Table 99: platformMtuHighUtilizationLowered properties

Property name	Value
Application name	chassis
Event name	platformMtuHighUtilizationLowered

Property name	Value
Default severity	notice
Message format string	The MTU resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex .
Cause	This event is generated when the utilization of an MTU resource has decreased to a level that may no longer warrant concern
Effect	None

10.7 platformPipelineResourceHighUtilization

platformPipelineResourceHighUtilization:chassis

Table 100: platformPipelineResourceHighUtilization properties

Property name	Value
Application name	chassis
Event name	platformPipelineResourceHighUtilization
Default severity	warning
Message format string	The pipeline resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex , pipeline pipeline
Cause	This event is generated when the utilization of a pipeline resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

10.8 platformPipelineResourceHighUtilizationLowered

platformPipelineResourceHighUtilizationLowered:chassis

Table 101: platformPipelineResourceHighUtilizationLowered properties

Property name	Value
Application name	chassis

Property name	Value
Event name	platformPipelineResourceHighUtilizationLowered
Default severity	notice
Message format string	The pipeline resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex , pipeline pipeline
Cause	This event is generated when the utilization of a pipeline resource has decreased to a level that may no longer warrant concern
Effect	None

10.9 platformPipelineResourceLimitCleared

platformPipelineResourceLimitCleared:chassis

Table 102: platformPipelineResourceLimitCleared properties

Property name	Value
Application name	chassis
Event name	platformPipelineResourceLimitCleared
Default severity	notice
Message format string	The pipeline resource called resource-name has decreased from 100% utilization back to 95% or less utilization on linecard linecard , forwarding complex forwarding-complex , pipeline
Cause	This event is generated when the utilization of a pipeline resource has decreased to a level such that resource exhaustion is no longer imminent
Effect	None

10.10 platformPipelineResourceLimitReached

platformPipelineResourceLimitReached:chassis

Table 103: platformPipelineResourceLimitReached properties

Property name	Value
Application name	chassis
Event name	platformPipelineResourceLimitReached
Default severity	warning
Message format string	The pipeline resource called resource-name has reached 100% utilization on linecard linecard , forwarding complex forwarding-complex, pipeline
Cause	This event is generated when the utilization of a pipeline resource has exhausted the resource
Effect	None

10.11 portDown

portDown:chassis

Table 104: portDown properties

Property name	Value
Application name	chassis
Event name	portDown
Default severity	warning
Message format string	Interface interface_name is now down for reason: oper_down_reason
Cause	The interface has transitioned from the up state to the down state
Effect	The interface is now down

10.12 portUp

portUp:chassis

Table 105: portUp properties

Property name	Value
Application name	chassis
Event name	portUp
Default severity	notice
Message format string	Interface interface_name is now up
Cause	The interface has transitioned from the down state to the up state
Effect	The interface is now up

10.13 subinterfaceDown

subinterfaceDown:chassis

Table 106: subinterfaceDown properties

Property name	Value
Application name	chassis
Event name	subinterfaceDown
Default severity	warning
Message format string	The subinterface subinterface_name is now down for reason: oper_down_reason
Cause	This event is generated when the subinterface has transitioned from the up state to the down state
Effect	The subinterface is now down

10.14 subinterfaceUp

subinterfaceUp:chassis

Table 107: subinterfaceUp properties

Property name	Value
Application name	chassis

Property name	Value
Event name	subinterfaceUp
Default severity	notice
Message format string	The subinterface subinterface_name is now up
Cause	This event is generated when the subinterface has transitioned from the down state to the up state.
Effect	The subinterface is now up

10.15 transceiverChannelHighInputPowerAlarm

transceiverChannelHighInputPowerAlarm:chassis

Table 108: transceiverChannelHighInputPowerAlarm properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighInputPowerAlarm
Default severity	critical
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The input power of the optical channel has increased
Effect	High input power may affect transceiver performance

10.16 transceiverChannelHighInputPowerAlarmClear

transceiverChannelHighInputPowerAlarmClear:chassis

Table 109: transceiverChannelHighInputPowerAlarmClear properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighInputPowerAlarmClear

Property name	Value
Default severity	informational
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The input power of the optical channel has decreased
Effect	High input power may affect transceiver performance

10.17 transceiverChannelHighInputPowerWarning

transceiverChannelHighInputPowerWarning:chassis

Table 110: *transceiverChannelHighInputPowerWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighInputPowerWarning
Default severity	warning
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The input power of the optical channel has increased
Effect	High input power may affect transceiver performance

10.18 transceiverChannelHighInputPowerWarningClear

transceiverChannelHighInputPowerWarningClear:chassis

Table 111: *transceiverChannelHighInputPowerWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighInputPowerWarningClear
Default severity	informational

Property name	Value
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The input power of the optical channel has decreased
Effect	High input power may affect transceiver performance

10.19 transceiverChannelHighLaserBiasCurrentAlarm

transceiverChannelHighLaserBiasCurrentAlarm:chassis

Table 112: *transceiverChannelHighLaserBiasCurrentAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighLaserBiasCurrentAlarm
Default severity	critical
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold mA or more
Cause	Laser bias increases with temperature and age. Consider lowering the ambient temperature or replacing the laser.
Effect	High laser bias may affect transceiver performance

10.20 transceiverChannelHighLaserBiasCurrentAlarmClear

transceiverChannelHighLaserBiasCurrentAlarmClear:chassis

Table 113: *transceiverChannelHighLaserBiasCurrentAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighLaserBiasCurrentAlarmClear
Default severity	informational

Property name	Value
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold mA
Cause	Laser bias current has decreased
Effect	High laser bias may affect transceiver performance

10.21 transceiverChannelHighLaserBiasCurrentWarning

transceiverChannelHighLaserBiasCurrentWarning:chassis

Table 114: *transceiverChannelHighLaserBiasCurrentWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighLaserBiasCurrentWarning
Default severity	warning
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold mA or more
Cause	Laser bias increases with temperature and age. Consider lowering the ambient temperature or replacing the laser.
Effect	High laser bias may affect transceiver performance

10.22 transceiverChannelHighLaserBiasCurrentWarningClear

transceiverChannelHighLaserBiasCurrentWarningClear:chassis

Table 115: *transceiverChannelHighLaserBiasCurrentWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighLaserBiasCurrentWarningClear
Default severity	informational

Property name	Value
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold mA
Cause	Laser bias current has decreased
Effect	High laser bias may affect transceiver performance

10.23 transceiverChannelHighOutputPowerAlarm

transceiverChannelHighOutputPowerAlarm:chassis

Table 116: *transceiverChannelHighOutputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighOutputPowerAlarm
Default severity	critical
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The output power of the optical channel has increased
Effect	High output power may affect transceiver performance

10.24 transceiverChannelHighOutputPowerAlarmClear

transceiverChannelHighOutputPowerAlarmClear:chassis

Table 117: *transceiverChannelHighOutputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighOutputPowerAlarmClear
Default severity	informational

Property name	Value
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The output power of the optical channel has decreased
Effect	High output power may affect transceiver performance

10.25 transceiverChannelHighOutputPowerWarning

transceiverChannelHighOutputPowerWarning:chassis

Table 118: *transceiverChannelHighOutputPowerWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighOutputPowerWarning
Default severity	warning
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The output power of the optical channel has increased
Effect	High output power may affect transceiver performance

10.26 transceiverChannelHighOutputPowerWarningClear

transceiverChannelHighOutputPowerWarningClear:chassis

Table 119: *transceiverChannelHighOutputPowerWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelHighOutputPowerWarningClear
Default severity	informational

Property name	Value
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The output power of the optical channel has decreased
Effect	High output power may affect transceiver performance

10.27 transceiverChannelLowInputPowerAlarm

transceiverChannelLowInputPowerAlarm:chassis

Table 120: *transceiverChannelLowInputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowInputPowerAlarm
Default severity	critical
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The input power of the optical channel has decreased
Effect	Low input power may affect transceiver performance

10.28 transceiverChannelLowInputPowerAlarmClear

transceiverChannelLowInputPowerAlarmClear:chassis

Table 121: *transceiverChannelLowInputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowInputPowerAlarmClear
Default severity	informational

Property name	Value
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The input power of the optical channel has increased
Effect	Low input power may affect transceiver performance

10.29 transceiverChannelLowInputPowerWarning

transceiverChannelLowInputPowerWarning:chassis

Table 122: *transceiverChannelLowInputPowerWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowInputPowerWarning
Default severity	warning
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The input power of the optical channel has decreased
Effect	Low input power may affect transceiver performance

10.30 transceiverChannelLowInputPowerWarningClear

transceiverChannelLowInputPowerWarningClear:chassis

Table 123: *transceiverChannelLowInputPowerWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowInputPowerWarningClear
Default severity	informational

Property name	Value
Message format string	The input power measured for channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The input power of the optical channel has increased
Effect	Low input power may affect transceiver performance

10.31 transceiverChannelLowLaserBiasCurrentAlarm

transceiverChannelLowLaserBiasCurrentAlarm:chassis

Table 124: *transceiverChannelLowLaserBiasCurrentAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowLaserBiasCurrentAlarm
Default severity	critical
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold mA or less
Cause	The laser bias current of the optical channel has decreased
Effect	Low laser bias current may affect transceiver performance

10.32 transceiverChannelLowLaserBiasCurrentAlarmClear

transceiverChannelLowLaserBiasCurrentAlarmClear:chassis

Table 125: *transceiverChannelLowLaserBiasCurrentAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowLaserBiasCurrentAlarmClear
Default severity	informational

Property name	Value
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold mA
Cause	The laser bias current of the optical channel has increased
Effect	Low laser bias current may affect transceiver performance

10.33 transceiverChannelLowLaserBiasCurrentWarning

transceiverChannelLowLaserBiasCurrentWarning:chassis

Table 126: *transceiverChannelLowLaserBiasCurrentWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowLaserBiasCurrentWarning
Default severity	warning
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold mA or less
Cause	The laser bias current of the optical channel has decreased
Effect	Low laser bias current may affect transceiver performance

10.34 transceiverChannelLowLaserBiasCurrentWarningClear

transceiverChannelLowLaserBiasCurrentWarningClear:chassis

Table 127: *transceiverChannelLowLaserBiasCurrentWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowLaserBiasCurrentWarningClear
Default severity	informational

Property name	Value
Message format string	The laser bias current supplied to channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold mA
Cause	The laser bias current of the optical channel has increased
Effect	Low laser bias current may affect transceiver performance

10.35 transceiverChannelLowOutputPowerAlarm

transceiverChannelLowOutputPowerAlarm:chassis

Table 128: *transceiverChannelLowOutputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowOutputPowerAlarm
Default severity	critical
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The output power of the optical channel has decreased
Effect	Low output power may affect transceiver performance

10.36 transceiverChannelLowOutputPowerAlarmClear

transceiverChannelLowOutputPowerAlarmClear:chassis

Table 129: *transceiverChannelLowOutputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowOutputPowerAlarmClear
Default severity	informational

Property name	Value
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The output power of the optical channel has increased
Effect	Low output power may affect transceiver performance

10.37 transceiverChannelLowOutputPowerWarning

transceiverChannelLowOutputPowerWarning:chassis

Table 130: transceiverChannelLowOutputPowerWarning properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowOutputPowerWarning
Default severity	warning
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The output power of the optical channel has decreased
Effect	Low output power may affect transceiver performance

10.38 transceiverChannelLowOutputPowerWarningClear

transceiverChannelLowOutputPowerWarningClear:chassis

Table 131: transceiverChannelLowOutputPowerWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverChannelLowOutputPowerWarningClear
Default severity	informational

Property name	Value
Message format string	The output power measured for channel channel_num of the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The output power of the optical channel has increased
Effect	Low output power may affect transceiver performance

10.39 transceiverHighInputPowerAlarm

transceiverHighInputPowerAlarm:chassis

Table 132: *transceiverHighInputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverHighInputPowerAlarm
Default severity	critical
Message format string	The input power measured for the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The input power of the optics has increased
Effect	High input power may affect transceiver performance

10.40 transceiverHighInputPowerAlarmClear

transceiverHighInputPowerAlarmClear:chassis

Table 133: *transceiverHighInputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverHighInputPowerAlarmClear
Default severity	informational
Message format string	The input power measured for the transceiver associated with interface interface_name has decreased below high_threshold dBm

Property name	Value
Cause	The input power of the optics has decreased
Effect	High input power may affect transceiver performance

10.41 transceiverHighInputPowerWarning

transceiverHighInputPowerWarning:chassis

Table 134: transceiverHighInputPowerWarning properties

Property name	Value
Application name	chassis
Event name	transceiverHighInputPowerWarning
Default severity	warning
Message format string	The input power measured for the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The input power of the optics has increased
Effect	High input power may affect transceiver performance

10.42 transceiverHighInputPowerWarningClear

transceiverHighInputPowerWarningClear:chassis

Table 135: transceiverHighInputPowerWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverHighInputPowerWarningClear
Default severity	informational
Message format string	The input power measured for the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The input power of the optics has decreased
Effect	High input power may affect transceiver performance

10.43 transceiverHighLaserBiasCurrentAlarm

transceiverHighLaserBiasCurrentAlarm:chassis

Table 136: transceiverHighLaserBiasCurrentAlarm properties

Property name	Value
Application name	chassis
Event name	transceiverHighLaserBiasCurrentAlarm
Default severity	critical
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has increased to high_threshold mA or more
Cause	Laser bias increases with temperature and age. Consider lowering the ambient temperature or replacing the laser.
Effect	High laser bias may affect transceiver performance

10.44 transceiverHighLaserBiasCurrentAlarmClear

transceiverHighLaserBiasCurrentAlarmClear:chassis

Table 137: transceiverHighLaserBiasCurrentAlarmClear properties

Property name	Value
Application name	chassis
Event name	transceiverHighLaserBiasCurrentAlarmClear
Default severity	informational
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has decreased below high_threshold mA
Cause	Laser bias current has decreased
Effect	High laser bias may affect transceiver performance

10.45 transceiverHighLaserBiasCurrentWarning

transceiverHighLaserBiasCurrentWarning:chassis

Table 138: *transceiverHighLaserBiasCurrentWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverHighLaserBiasCurrentWarning
Default severity	warning
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has increased to high_threshold mA or more
Cause	Laser bias increases with temperature and age. Consider lowering the ambient temperature or replacing the laser.
Effect	High laser bias may affect transceiver performance

10.46 transceiverHighLaserBiasCurrentWarningClear

transceiverHighLaserBiasCurrentWarningClear:chassis

Table 139: *transceiverHighLaserBiasCurrentWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverHighLaserBiasCurrentWarningClear
Default severity	informational
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has decreased below high_threshold mA
Cause	Laser bias current has decreased
Effect	High laser bias may affect transceiver performance

10.47 transceiverHighOutputPowerAlarm

transceiverHighOutputPowerAlarm:chassis

Table 140: *transceiverHighOutputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverHighOutputPowerAlarm
Default severity	critical
Message format string	The output power measured for the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The output power of the optics has increased
Effect	High output power may affect transceiver performance

10.48 transceiverHighOutputPowerAlarmClear

transceiverHighOutputPowerAlarmClear:chassis

Table 141: *transceiverHighOutputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverHighOutputPowerAlarmClear
Default severity	informational
Message format string	The output power measured for the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The output power of the optics has decreased
Effect	High output power may affect transceiver performance

10.49 transceiverHighOutputPowerWarning

transceiverHighOutputPowerWarning:chassis

Table 142: *transceiverHighOutputPowerWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverHighOutputPowerWarning
Default severity	warning
Message format string	The output power measured for the transceiver associated with interface interface_name has increased to high_threshold dBm or more
Cause	The output power of the optics has increased
Effect	High output power may affect transceiver performance

10.50 transceiverHighOutputPowerWarningClear

transceiverHighOutputPowerWarningClear:chassis

Table 143: *transceiverHighOutputPowerWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverHighOutputPowerWarningClear
Default severity	informational
Message format string	The output power measured for the transceiver associated with interface interface_name has decreased below high_threshold dBm
Cause	The output power of the optics has decreased
Effect	High output power may affect transceiver performance

10.51 transceiverLowInputPowerAlarm

transceiverLowInputPowerAlarm:chassis

Table 144: *transceiverLowInputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverLowInputPowerAlarm
Default severity	critical
Message format string	The input power measured for the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The input power of the optics has decreased
Effect	Low input power may affect transceiver performance

10.52 transceiverLowInputPowerAlarmClear

transceiverLowInputPowerAlarmClear:chassis

Table 145: *transceiverLowInputPowerAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverLowInputPowerAlarmClear
Default severity	informational
Message format string	The input power measured for the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The input power of the optics has increased
Effect	Low input power may affect transceiver performance

10.53 transceiverLowInputPowerWarning

transceiverLowInputPowerWarning:chassis

Table 146: *transceiverLowInputPowerWarning* properties

Property name	Value
Application name	chassis

Property name	Value
Event name	transceiverLowInputPowerWarning
Default severity	warning
Message format string	The input power measured for the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The input power of the optics has decreased
Effect	Low input power may affect transceiver performance

10.54 transceiverLowInputPowerWarningClear

transceiverLowInputPowerWarningClear:chassis

Table 147: transceiverLowInputPowerWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverLowInputPowerWarningClear
Default severity	informational
Message format string	The input power measured for the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The input power of the optics has increased
Effect	Low input power may affect transceiver performance

10.55 transceiverLowLaserBiasCurrentAlarm

transceiverLowLaserBiasCurrentAlarm:chassis

Table 148: transceiverLowLaserBiasCurrentAlarm properties

Property name	Value
Application name	chassis
Event name	transceiverLowLaserBiasCurrentAlarm
Default severity	critical

Property name	Value
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has decreased to low_threshold mA or less
Cause	The laser bias current of the optics has decreased
Effect	Low laser bias current may affect transceiver performance

10.56 transceiverLowLaserBiasCurrentAlarmClear

transceiverLowLaserBiasCurrentAlarmClear:chassis

Table 149: *transceiverLowLaserBiasCurrentAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverLowLaserBiasCurrentAlarmClear
Default severity	informational
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has increased above low_threshold mA
Cause	The laser bias current of the optics has increased
Effect	Low laser bias current may affect transceiver performance

10.57 transceiverLowLaserBiasCurrentWarning

transceiverLowLaserBiasCurrentWarning:chassis

Table 150: *transceiverLowLaserBiasCurrentWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverLowLaserBiasCurrentWarning
Default severity	warning
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has decreased to low_threshold mA or less

Property name	Value
Cause	The laser bias current of the optics has decreased
Effect	Low laser bias current may affect transceiver performance

10.58 transceiverLowLaserBiasCurrentWarningClear

transceiverLowLaserBiasCurrentWarningClear:chassis

Table 151: *transceiverLowLaserBiasCurrentWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverLowLaserBiasCurrentWarningClear
Default severity	informational
Message format string	The laser bias current supplied to the transceiver associated with interface interface_name has increased above low_threshold mA
Cause	The laser bias current of the optics has increased
Effect	Low laser bias current may affect transceiver performance

10.59 transceiverLowOutputPowerAlarm

transceiverLowOutputPowerAlarm:chassis

Table 152: *transceiverLowOutputPowerAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverLowOutputPowerAlarm
Default severity	critical
Message format string	The output power measured for the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The output power of the optics has decreased

Property name	Value
Effect	Low output power may affect transceiver performance

10.60 transceiverLowOutputPowerAlarmClear

transceiverLowOutputPowerAlarmClear:chassis

Table 153: transceiverLowOutputPowerAlarmClear properties

Property name	Value
Application name	chassis
Event name	transceiverLowOutputPowerAlarmClear
Default severity	informational
Message format string	The output power measured for the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The output power of the optics has increased
Effect	Low output power may affect transceiver performance

10.61 transceiverLowOutputPowerWarning

transceiverLowOutputPowerWarning:chassis

Table 154: transceiverLowOutputPowerWarning properties

Property name	Value
Application name	chassis
Event name	transceiverLowOutputPowerWarning
Default severity	warning
Message format string	The output power measured for the transceiver associated with interface interface_name has decreased to low_threshold dBm or less
Cause	The output power of the optics has decreased
Effect	Low output power may affect transceiver performance

10.62 transceiverLowOutputPowerWarningClear

transceiverLowOutputPowerWarningClear:chassis

Table 155: *transceiverLowOutputPowerWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverLowOutputPowerWarningClear
Default severity	informational
Message format string	The output power measured for the transceiver associated with interface interface_name has increased above low_threshold dBm
Cause	The output power of the optics has increased
Effect	Low output power may affect transceiver performance

10.63 transceiverModuleDown

transceiverModuleDown:chassis

Table 156: *transceiverModuleDown* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleDown
Default severity	warning
Message format string	The transceiver associated with the interface interface_name is now down
Cause	The transceiver oper-state has transitioned from the up state to any lower state
Effect	The transceiver is not operational

10.64 transceiverModuleHighTemperatureAlarm

transceiverModuleHighTemperatureAlarm:chassis

Table 157: *transceiverModuleHighTemperatureAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighTemperatureAlarm
Default severity	critical
Message format string	The temperature of the transceiver associated with the interface interface_name has increased to high_threshold degrees C or more
Cause	The temperature of the transceiver module has increased
Effect	High temperatures may affect transceiver performance

10.65 transceiverModuleHighTemperatureAlarmClear

transceiverModuleHighTemperatureAlarmClear:chassis

Table 158: *transceiverModuleHighTemperatureAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighTemperatureAlarmClear
Default severity	informational
Message format string	The temperature of the transceiver associated with the interface interface_name has decreased below high_threshold degrees C
Cause	The temperature of the transceiver module has decreased
Effect	High temperatures may affect transceiver performance

10.66 transceiverModuleHighTemperatureWarning

transceiverModuleHighTemperatureWarning:chassis

Table 159: *transceiverModuleHighTemperatureWarning* properties

Property name	Value
Application name	chassis

Property name	Value
Event name	transceiverModuleHighTemperatureWarning
Default severity	warning
Message format string	The temperature of the transceiver associated with the interface interface_name has increased to high_threshold degrees C or more
Cause	The temperature of the transceiver module has increased
Effect	High temperatures may affect transceiver performance

10.67 transceiverModuleHighTemperatureWarningClear

transceiverModuleHighTemperatureWarningClear:chassis

Table 160: transceiverModuleHighTemperatureWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighTemperatureWarningClear
Default severity	informational
Message format string	The temperature of the transceiver associated with the interface interface_name has decreased below high_threshold degrees C
Cause	The temperature of the transceiver module has decreased
Effect	High temperatures may affect transceiver performance

10.68 transceiverModuleHighVoltageAlarm

transceiverModuleHighVoltageAlarm:chassis

Table 161: transceiverModuleHighVoltageAlarm properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighVoltageAlarm
Default severity	critical

Property name	Value
Message format string	The voltage of the transceiver associated with the interface interface_name has increased to high_threshold Volts or more
Cause	The voltage supplied to the transceiver module has increased
Effect	High voltages may affect transceiver performance

10.69 transceiverModuleHighVoltageAlarmClear

transceiverModuleHighVoltageAlarmClear:chassis

Table 162: *transceiverModuleHighVoltageAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighVoltageAlarmClear
Default severity	informational
Message format string	The voltage of the transceiver associated with the interface interface_name has decreased below high_threshold Volts
Cause	The voltage supplied to the transceiver module has decreased
Effect	High voltages may affect transceiver performance

10.70 transceiverModuleHighVoltageWarning

transceiverModuleHighVoltageWarning:chassis

Table 163: *transceiverModuleHighVoltageWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighVoltageWarning
Default severity	warning
Message format string	The voltage of the transceiver associated with the interface interface_name has increased to high_threshold Volts or more

Property name	Value
Cause	The voltage supplied to the transceiver module has increased
Effect	High voltages may affect transceiver performance

10.71 transceiverModuleHighVoltageWarningClear

transceiverModuleHighVoltageWarningClear:chassis

Table 164: transceiverModuleHighVoltageWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverModuleHighVoltageWarningClear
Default severity	informational
Message format string	The voltage of the transceiver associated with the interface interface_name has decreased below high_threshold Volts
Cause	The voltage supplied to the transceiver module has decreased
Effect	High voltages may affect transceiver performance

10.72 transceiverModuleLowTemperatureAlarm

transceiverModuleLowTemperatureAlarm:chassis

Table 165: transceiverModuleLowTemperatureAlarm properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowTemperatureAlarm
Default severity	critical
Message format string	The temperature of the transceiver associated with the interface interface_name has decreased to low_threshold degrees C or less
Cause	The temperature of the transceiver module has decreased
Effect	Low temperatures may affect transceiver performance

10.73 transceiverModuleLowTemperatureAlarmClear

transceiverModuleLowTemperatureAlarmClear:chassis

Table 166: *transceiverModuleLowTemperatureAlarmClear* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowTemperatureAlarmClear
Default severity	informational
Message format string	The temperature of the transceiver associated with the interface interface_name has increased above low_threshold degrees C
Cause	The temperature of the transceiver module has increased
Effect	Low temperatures may affect transceiver performance

10.74 transceiverModuleLowTemperatureWarning

transceiverModuleLowTemperatureWarning:chassis

Table 167: *transceiverModuleLowTemperatureWarning* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowTemperatureWarning
Default severity	warning
Message format string	The temperature of the transceiver associated with the interface interface_name has decreased to low_threshold degrees C or less
Cause	The temperature of the transceiver module has decreased
Effect	Low temperatures may affect transceiver performance

10.75 transceiverModuleLowTemperatureWarningClear

transceiverModuleLowTemperatureWarningClear:chassis

Table 168: *transceiverModuleLowTemperatureWarningClear* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowTemperatureWarningClear
Default severity	informational
Message format string	The temperature of the transceiver associated with the interface interface_name has increased above low_threshold degrees C
Cause	The temperature of the transceiver module has increased
Effect	Low temperatures may affect transceiver performance

10.76 transceiverModuleLowVoltageAlarm

transceiverModuleLowVoltageAlarm:chassis

Table 169: *transceiverModuleLowVoltageAlarm* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowVoltageAlarm
Default severity	critical
Message format string	The voltage of the transceiver associated with the interface interface_name has decreased to low_threshold Volts or less
Cause	The voltage supplied to the transceiver module has decreased
Effect	Low voltages may affect transceiver performance

10.77 transceiverModuleLowVoltageAlarmClear

transceiverModuleLowVoltageAlarmClear:chassis

Table 170: *transceiverModuleLowVoltageAlarmClear* properties

Property name	Value
Application name	chassis

Property name	Value
Event name	transceiverModuleLowVoltageAlarmClear
Default severity	informational
Message format string	The voltage of the transceiver associated with the interface interface_name has increased above low_threshold Volts
Cause	The voltage supplied to the transceiver module has increased
Effect	Low voltages may affect transceiver performance

10.78 transceiverModuleLowVoltageWarning

transceiverModuleLowVoltageWarning:chassis

Table 171: transceiverModuleLowVoltageWarning properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowVoltageWarning
Default severity	warning
Message format string	The voltage of the transceiver associated with the interface interface_name has decreased to low_threshold Volts or less
Cause	The voltage supplied to the transceiver module has decreased
Effect	Low voltages may affect transceiver performance

10.79 transceiverModuleLowVoltageWarningClear

transceiverModuleLowVoltageWarningClear:chassis

Table 172: transceiverModuleLowVoltageWarningClear properties

Property name	Value
Application name	chassis
Event name	transceiverModuleLowVoltageWarningClear
Default severity	informational

Property name	Value
Message format string	The voltage of the transceiver associated with the interface interface_name has increased above low_threshold Volts
Cause	The voltage supplied to the transceiver module has increased
Effect	Low voltages may affect transceiver performance

10.80 transceiverModuleUp

transceiverModuleUp:chassis

Table 173: *transceiverModuleUp* properties

Property name	Value
Application name	chassis
Event name	transceiverModuleUp
Default severity	notice
Message format string	The transceiver associated with the interface interface_name is now up
Cause	The transceiver oper-state has transitioned from any other state to the up state
Effect	The transceiver is now operational

11 debug

11.1 setAllConfigLevels

setAllConfigLevels:debug

Table 174: *setAllConfigLevels* properties

Property name	Value
Application name	debug
Event name	setAllConfigLevels
Default severity	informational
Message format string	App config debug log levels set to: new_level .
Cause	Configuration of debug log levels that can be received by program parameter or via idb.
Effect	Sticky levels are losable only to another configuration setting.

11.2 setAllStartupLevels

setAllStartupLevels:debug

Table 175: *setAllStartupLevels* properties

Property name	Value
Application name	debug
Event name	setAllStartupLevels
Default severity	informational
Message format string	App debug startup log levels set to: new_level (configuration can override).
Cause	Restrain of logging verbosity internal to some programs
Effect	If configuration is set, and goes away, the startup levels are respected.

11.3 setHighBaselineLogLevels

setHighBaselineLogLevels:debug

Table 176: *setHighBaselineLogLevels* properties

Property name	Value
Application name	debug
Event name	setHighBaselineLogLevels
Default severity	informational
Message format string	Default (startup), and runtime app debug log levels set to: new_level . Except for modules: { configured_list }
Cause	Boot phase time is up, and verbose messages are suppressed in a beta build with .
Effect	Internal setting to all levels. If module levels are configured, they restore to the setting.

12 dhcp

12.1 dhcp6ClientAddressDeclined

dhcp6ClientAddressDeclined:dhcp

Table 177: *dhcp6ClientAddressDeclined* properties

Property name	Value
Application name	dhcp
Event name	dhcp6ClientAddressDeclined
Default severity	notice
Message format string	DHCPv6 client running on subinterface_name was given a duplicate IPv6 address by the DHCP server server_ip
Cause	The DHCP server assigned an IPv6 address that is already in use on the same subnet
Effect	The subinterface will try to acquire a new IPv6 address

12.2 dhcp6ClientIpv6AddressValidLifetimeExpired

dhcp6ClientIpv6AddressValidLifetimeExpired:dhcp

Table 178: *dhcp6ClientIpv6AddressValidLifetimeExpired* properties

Property name	Value
Application name	dhcp
Event name	dhcp6ClientIpv6AddressValidLifetimeExpired
Default severity	warning
Message format string	The IPv6 address assigned_ip obtained by the DHCPv6 client running on subinterface_name has become invalid
Cause	The DHCPv6 client was not successful in renewing or rebinding the IA_NA lease before the valid lifetime of the IPv6 address expired
Effect	The subinterface has no DHCP-assigned IPv6 address

12.3 dhcp6ClientRebindAttempted

dhcp6ClientRebindAttempted:dhcp

Table 179: dhcp6ClientRebindAttempted properties

Property name	Value
Application name	dhcp
Event name	dhcp6ClientRebindAttempted
Default severity	informational
Message format string	DHCPv6 client running on subinterface_name is attempting to rebind its IA_NA lease for the IPv6 address requested_ip
Cause	The DHCPv6 client could not renew its assigned IPv6 address before the timer T2 expired
Effect	The IPv6 address may become deprecated and then invalid if the rebind is not successful

12.4 dhcp6ClientReconfigureMsgDropped

dhcp6ClientReconfigureMsgDropped:dhcp

Table 180: dhcp6ClientReconfigureMsgDropped properties

Property name	Value
Application name	dhcp
Event name	dhcp6ClientReconfigureMsgDropped
Default severity	notice
Message format string	The DHCPv6 client running on subinterface_name dropped a RECONFIGURE message received from the server server_ip
Cause	The DHCPv6 client received a message that it was not supposed to receive (because it did not include a Reconfigure Accept option in its SOLICIT msg)
Effect	None

12.5 dhcp6ClientRenewSuccess

dhcp6ClientRenewSuccess:dhcp

Table 181: dhcp6ClientRenewSuccess properties

Property name	Value
Application name	dhcp
Event name	dhcp6ClientRenewSuccess
Default severity	informational
Message format string	DHCPv6 client running on subinterface_name successfully renewed the IPv6 address requested_ip for a new lease duration of new_lease_time seconds from server server_ip
Cause	The DHCPv6 client received a success REPLY in response to its RENEW
Effect	The subinterface remains operational with its existing DHCP-assigned IPv6 address

12.6 dhcpClientAddressDeclined

dhcpClientAddressDeclined:dhcp

Table 182: dhcpClientAddressDeclined properties

Property name	Value
Application name	dhcp
Event name	dhcpClientAddressDeclined
Default severity	notice
Message format string	DHCP client running on subinterface_name was given a duplicate IPv4 address by the DHCP server server_ip
Cause	The DHCP server assigned an IPv4 address that is already in use on the same subnet
Effect	The subinterface will try to acquire a new IPv4 address after a 10s delay

12.7 dhcpClientLeaseExpired

dhcpClientLeaseExpired:dhcp

Table 183: *dhcpClientLeaseExpired* properties

Property name	Value
Application name	dhcp
Event name	dhcpClientLeaseExpired
Default severity	warning
Message format string	The DHCP lease for address assigned_ip obtained by the DHCP client running on subinterface_name and obtained from server server_ip has expired
Cause	The DHCP client was not successful in renewing or rebinding the lease
Effect	The subinterface has no DHCP-assigned IPv4 address

12.8 dhcpClientRebindAttempted

dhcpClientRebindAttempted:dhcp

Table 184: *dhcpClientRebindAttempted* properties

Property name	Value
Application name	dhcp
Event name	dhcpClientRebindAttempted
Default severity	informational
Message format string	DHCP client running on subinterface_name is attempting to rebind its lease for the IP address requested_ip
Cause	The DHCP client could not renew its assigned IPv4 address before the timer T2 expired
Effect	The lease may expire if the rebind is not successful

12.9 dhcpClientRenewSuccess

dhcpClientRenewSuccess:dhcp

Table 185: *dhcpClientRenewSuccess* properties

Property name	Value
Application name	dhcp
Event name	dhcpClientRenewSuccess
Default severity	informational
Message format string	DHCP client running on subinterface_name successfully renewed the IP address requested_ip for a new lease duration of new_lease_time seconds from server server_ip
Cause	The DHCP client received a DHCPACK response to its DHCPREQUEST
Effect	The subinterface remains operational with its existing DHCP-assigned IPv4 address

12.10 dhcpv4RelayAdminDisable

dhcpv4RelayAdminDisable:dhcp

Table 186: *dhcpv4RelayAdminDisable* properties

Property name	Value
Application name	dhcp
Event name	dhcpv4RelayAdminDisable
Default severity	warning
Message format string	DHCPv4 Relay on sub-interface subinterface_name has changed to administrative disable state
Cause	The DHCPv4 Relay admin state has changed from enable to disable due to configuration change
Effect	The DHCPv4 Relay admin state is disable on the mentioned sub-interface

12.11 dhcpv4RelayAdminEnable

dhcpv4RelayAdminEnable:dhcp

Table 187: dhcpv4RelayAdminEnable properties

Property name	Value
Application name	dhcp
Event name	dhcpv4RelayAdminEnable
Default severity	warning
Message format string	DHCPv4 Relay on sub-interface subinterface_name has changed to administrative enable state
Cause	The DHCPv4 Relay admin state has changed from disable to enable due to configuration change
Effect	The DHCPv4 Relay admin state is enable on the mentioned sub-interface

12.12 dhcpv4RelayAllDhcpv4ServersUnreachable

dhcpv4RelayAllDhcpv4ServersUnreachable:dhcp

Table 188: dhcpv4RelayAllDhcpv4ServersUnreachable properties

Property name	Value
Application name	dhcp
Event name	dhcpv4RelayAllDhcpv4ServersUnreachable
Default severity	critical
Message format string	All DHCPv4 Servers dhcpv4_server_list configured under DHCPv4 Relay on sub-interface subinterface_name are unreachable for network instance network_instance
Cause	All The DHCPv4 Servers configured under DHCPv4 Relay are unreachable
Effect	The DHCPv4 Relay oper state is down on the mentioned sub-interface

12.13 dhcpv4RelayOperDown

dhcpv4RelayOperDown:dhcp

Table 189: dhcpv4RelayOperDown properties

Property name	Value
Application name	dhcp
Event name	dhcpv4RelayOperDown
Default severity	critical
Message format string	DHCPv4 Relay on sub-interface subinterface_name has changed to operational down state
Cause	The DHCPv4 Relay oper state has changed from up to down
Effect	The DHCPv4 Relay oper state is down on the mentioned sub-interface

12.14 dhcpv4RelayOperUp

dhcpv4RelayOperUp:dhcp

Table 190: dhcpv4RelayOperUp properties

Property name	Value
Application name	dhcp
Event name	dhcpv4RelayOperUp
Default severity	warning
Message format string	DHCPv4 Relay on sub-interface subinterface_name has changed to operational up state
Cause	The DHCPv4 Relay oper state has changed from down to up
Effect	The DHCPv4 Relay oper state is up on the mentioned sub-interface

12.15 dhcpv6RelayAdminDisable

dhcpv6RelayAdminDisable:dhcp

Table 191: dhcpv6RelayAdminDisable properties

Property name	Value
Application name	dhcp

Property name	Value
Event name	dhcpv6RelayAdminDisable
Default severity	warning
Message format string	DHCPv6 Relay on sub-interface subinterface_name has changed to administrative disable state
Cause	The DHCPv6 Relay admin state has changed from enable to disable due to configuration change
Effect	The DHCPv6 Relay admin state is disable on the mentioned sub-interface

12.16 dhcpv6RelayAdminEnable

dhcpv6RelayAdminEnable:dhcp

Table 192: dhcpv6RelayAdminEnable properties

Property name	Value
Application name	dhcp
Event name	dhcpv6RelayAdminEnable
Default severity	warning
Message format string	DHCPv6 Relay on sub-interface subinterface_name has changed to administrative enable state
Cause	The DHCPv6 Relay admin state has changed from disable to enable due to configuration change
Effect	The DHCPv6 Relay admin state is enable on the mentioned sub-interface

12.17 dhcpv6RelayAllDhcpv6ServersUnreachable

dhcpv6RelayAllDhcpv6ServersUnreachable:dhcp

Table 193: dhcpv6RelayAllDhcpv6ServersUnreachable properties

Property name	Value
Application name	dhcp

Property name	Value
Event name	dhcpv6RelayAllDhcpv6ServersUnreachable
Default severity	critical
Message format string	All DHCPv6 Servers dhcpv6_server_list configured under DHCPv6 Relay on sub-interface subinterface_name are unreachable for network instance network_instance
Cause	All The DHCPv6 Servers configured under DHCPv6 Relay are unreachable
Effect	The DHCPv6 Relay oper state is down on the mentioned sub-interface

12.18 dhcpv6RelayOperDown

dhcpv6RelayOperDown:dhcp

Table 194: dhcpv6RelayOperDown properties

Property name	Value
Application name	dhcp
Event name	dhcpv6RelayOperDown
Default severity	critical
Message format string	DHCPv6 Relay on sub-interface subinterface_name has changed to operational down state
Cause	The DHCPv6 Relay oper state has changed from up to down
Effect	The DHCPv6 Relay oper state is down on the mentioned sub-interface

12.19 dhcpv6RelayOperUp

dhcpv6RelayOperUp:dhcp

Table 195: dhcpv6RelayOperUp properties

Property name	Value
Application name	dhcp
Event name	dhcpv6RelayOperUp

Property name	Value
Default severity	warning
Message format string	DHCPv6 Relay on sub-interface subinterface_name has changed to operational up state
Cause	The DHCPv6 Relay oper state has changed from down to up
Effect	The DHCPv6 Relay oper state is up on the mentioned sub-interface

12.20 giAddressMismatch

giAddressMismatch:dhcp

Table 196: *giAddressMismatch* properties

Property name	Value
Application name	dhcp
Event name	giAddressMismatch
Default severity	critical
Message format string	Gi-Address for DHCPv4 Relay on sub-interface subinterface_name does not match any of the configured IPv4 addresses under sub-interface
Cause	The gi-address for DHCPv4 Relay does not match any of the configured IPv4 addresses under sub-interface
Effect	The DHCPv4 Relay oper state is down on the mentioned sub-interface

12.21 sourceAddressMismatch

sourceAddressMismatch:dhcp

Table 197: *sourceAddressMismatch* properties

Property name	Value
Application name	dhcp
Event name	sourceAddressMismatch
Default severity	critical

Property name	Value
Message format string	source-address for DHCPv6 Relay on sub-interface subinterface_ name does not match any of the configured IPv6 addresses under sub- interface
Cause	The source-address for DHCPv6 Relay does not match any of the configured IPv6 addresses under sub-interface
Effect	The DHCPv6 Relay oper state is down on the mentioned sub-interface

13 evpn

13.1 ethernetsegmentNetworkInstanceBgpInstanceDfStatusChanged

ethernetsegmentNetworkInstanceBgpInstanceDfStatusChanged:evpn

Table 198: ethernetsegmentNetworkInstanceBgpInstanceDfStatusChanged properties

Property name	Value
Application name	evpn
Event name	ethernetsegmentNetworkInstanceBgpInstanceDfStatusChanged
Default severity	notice
Message format string	BGP-EVPN attachment circuit on ethernet segment ethernet-segment on network instance network-instance and bgp instance bgp-instance is now a designated-forwarding-status .
Cause	This event is generated when there is a change in the ethernet segment attachment circuit designated forwarder state.
Effect	The forwarding state of the ethernet segment attachment circuit is changed.

13.2 ethernetsegmentPreferenceOperValueChanged

ethernetsegmentPreferenceOperValueChanged:evpn

Table 199: ethernetsegmentPreferenceOperValueChanged properties

Property name	Value
Application name	evpn
Event name	ethernetsegmentPreferenceOperValueChanged
Default severity	notice
Message format string	The Oper DF preference value changed to oper-preference and/or the DP value changed to do-not-preempt on ethernet-segment ethernet-segment

Property name	Value
Cause	This event is generated when there is a change in the ethernet segment operational preference value or the do not preempt value.
Effect	The designated forwarder state of the ethernet segment's attachment circuit might change.

13.3 evpnAutoDiscoveryEviRouteAddDroppedDueToUnexpectedEthTag

evpnAutoDiscoveryEviRouteAddDroppedDueToUnexpectedEthTag:evpn

Table 200: *evpnAutoDiscoveryEviRouteAddDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn
Event name	evpnAutoDiscoveryEviRouteAddDroppedDueToUnexpectedEthTag
Default severity	warning
Message format string	BGP-EVPN Auto Discovery Evi route received with route-distinguisher route-distinguisher and ethernet segment identifier ethernet-segment-id add on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The designated forwarder election on this ethernet-segment-id for this EVI will be affected. The mac-address's on this ethernet-segment will not be programmed in the bridge-table

13.4 evpnAutoDiscoveryEviRouteWithdrawDroppedDueToUnexpectedEthTag

evpnAutoDiscoveryEviRouteWithdrawDroppedDueToUnexpectedEthTag:evpn

Table 201: *evpnAutoDiscoveryEviRouteWithdrawDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn

Property name	Value
Event name	evpnAutoDiscoveryEviRouteWithdrawDroppedDueToUnexpectedEth Tag
Default severity	warning
Message format string	BGP-EVPN Auto Discovery Evi route received with route-distinguisher route-distinguisher and ethernet segment identifier ethernet-segment-id delete on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The designated forwarder election on this ethernet-segment-id for this EVI will be affected. The mac-address's on this ethernet-segment if programmed in the bridge-table, will not be deleted or updated

13.5 evpnAutoDiscoveryEviRouteWithdrawnDueToUnexpectedVni

evpnAutoDiscoveryEviRouteWithdrawnDueToUnexpectedVni:evpn

Table 202: *evpnAutoDiscoveryEviRouteWithdrawnDueToUnexpectedVni* properties

Property name	Value
Application name	evpn
Event name	evpnAutoDiscoveryEviRouteWithdrawnDueToUnexpectedVni
Default severity	warning
Message format string	BGP-EVPN Auto Discovery Evi route received with route-distinguisher route-distinguisher and ethernet segment identifier ethernet-segment-id on network instance network-instance and bgp instance bgp-instance is withdrawn because the VXLAN Network Identifier received-vni received in the route, does not match locally configured VXLAN Network Identifier local-vni on the bgp-instance
Cause	This event is generated when a received VXLAN Network Identifier does not match the one configured locally on the bgp-instance in the network instance

Property name	Value
Effect	The designated forwarder election on this ethernet-segment-id for this EVI will be affected. The mac-address's on this ethernet-segment will not be programmed in the bridge-table

13.6 evpnInclMcastRouteAddDroppedDueToUnexpectedEthTag

evpnInclMcastRouteAddDroppedDueToUnexpectedEthTag:evpn

Table 203: *evpnInclMcastRouteAddDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn
Event name	evpnInclMcastRouteAddDroppedDueToUnexpectedEthTag
Default severity	warning
Message format string	BGP-EVPN Inclusive Multicast route received with route-distinguisher route-distinguisher and originating IP originating-ip-address add on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The Virtual Tunnel End Point for the received VXLAN Network Identifier is not programmed in the multicast flood list of bridge-table

13.7 evpnInclMcastRouteWithdrawDroppedDueToUnexpectedEthTag

evpnInclMcastRouteWithdrawDroppedDueToUnexpectedEthTag:evpn

Table 204: *evpnInclMcastRouteWithdrawDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn
Event name	evpnInclMcastRouteWithdrawDroppedDueToUnexpectedEthTag
Default severity	warning

Property name	Value
Message format string	BGP-EVPN Inclusive Multicast route received with route-distinguisher route-distinguisher and originating IP originating-ip-address withdraw on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The Virtual Tunnel End Point for the received VXLAN Network Identifier if programmed in the multicast flood list of bridge-table, might not be removed

13.8 evpnInclMcastRouteWithdrawnDueToUnexpectedVni

evpnInclMcastRouteWithdrawnDueToUnexpectedVni:evpn

Table 205: *evpnInclMcastRouteWithdrawnDueToUnexpectedVni* properties

Property name	Value
Application name	evpn
Event name	evpnInclMcastRouteWithdrawnDueToUnexpectedVni
Default severity	warning
Message format string	BGP-EVPN Inclusive Multicast route received with route-distinguisher route-distinguisher and originating IP originating-ip-address on network instance network-instance and bgp instance bgp-instance is withdrawn because the VXLAN Network Identifier received-vni received in the route, does not match locally configured VXLAN Network Identifier local-vni on the bgp-instance
Cause	This event is generated when a received VXLAN Network Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The Virtual Tunnel End Point for the received VXLAN Network Identifier is not programmed in the multicast flood list of bridge-table

13.9 evpnIpPrefixRouteNotImportedDueToUnexpectedVni

evpnIpPrefixRouteNotImportedDueToUnexpectedVni:evpn

Table 206: *evpnIpPrefixRouteNotImportedDueToUnexpectedVni* properties

Property name	Value
Application name	evpn
Event name	evpnIpPrefixRouteNotImportedDueToUnexpectedVni
Default severity	warning
Message format string	BGP-EVPN IP-PREFIX ip-prefix LENGTH prefix-length received with route-distinguisher route-distinguisher on network instance network-instance and bgp instance bgp-instance is not imported because the VXLAN Network Identifier received-vni received in the route, does not match the locally configured VXLAN Network Identifier on the bgp-instance
Cause	This event is generated when a received VXLAN Network Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The IP-Prefix is not programmed in the route-table

13.10 evpnIpPrefixRouteWithdrawnDueToNoGwMac

evpnIpPrefixRouteWithdrawnDueToNoGwMac:evpn

Table 207: *evpnIpPrefixRouteWithdrawnDueToNoGwMac* properties

Property name	Value
Application name	evpn
Event name	evpnIpPrefixRouteWithdrawnDueToNoGwMac
Default severity	warning
Message format string	BGP-EVPN IP-PREFIX ip-prefix LENGTH prefix-length received with route-distinguisher route-distinguisher on network instance network-instance and bgp instance bgp-instance is withdrawn because the route is received without a Gateway MAC Address and that is not allowed in an EVPN Interface-less bgp instance for VXLAN tunnels
Cause	This event is generated when a received IP Prefix route does not contain the required GW Mac and therefore it is not allowed in the local EVPN Interface-less bgp instance of the network-instance
Effect	The ip-prefix is not programmed in the route table of the network instance

13.11 evpnIpPrefixRouteWithdrawnDueToUnexpectedGwIp

evpnIpPrefixRouteWithdrawnDueToUnexpectedGwIp:evpn

Table 208: *evpnIpPrefixRouteWithdrawnDueToUnexpectedGwIp* properties

Property name	Value
Application name	evpn
Event name	evpnIpPrefixRouteWithdrawnDueToUnexpectedGwIp
Default severity	warning
Message format string	BGP-EVPN IP-PREFIX ip-prefix LENGTH prefix-length received with route-distinguisher route-distinguisher on network instance network-instance and bgp instance bgp-instance is withdrawn because the non-zero Gateway IP Address gw-ip-address received in the route is not allowed in an EVPN Interface-less bgp instance of the network-instance
Cause	This event is generated when a received Gateway IP Address in the IP Prefix routes is non-zero and therefore not allowed in the local EVPN Interface-less bgp instance of the network-instance
Effect	The ip-prefix is not programmed in the route table of the network instance

13.12 evpnMacRouteAddDroppedDueToUnexpectedEthTag

evpnMacRouteAddDroppedDueToUnexpectedEthTag:evpn

Table 209: *evpnMacRouteAddDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn
Event name	evpnMacRouteAddDroppedDueToUnexpectedEthTag
Default severity	warning
Message format string	BGP-EVPN MAC mac-address IP ip-address received with route-distinguisher route-distinguisher add on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance

Property name	Value
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The mac-address is not programmed in the bridge-table AND/OR the mac-address/ip-address pair is not programmed in the ARP or Neighbor discovery table

13.13 evpnMacRouteWithdrawDroppedDueToUnexpectedEthTag

evpnMacRouteWithdrawDroppedDueToUnexpectedEthTag:evpn

Table 210: *evpnMacRouteWithdrawDroppedDueToUnexpectedEthTag* properties

Property name	Value
Application name	evpn
Event name	evpnMacRouteWithdrawDroppedDueToUnexpectedEthTag
Default severity	warning
Message format string	BGP-EVPN MAC mac-address IP ip-address received with route-distinguisher route-distinguisher delete on network instance network-instance and bgp instance bgp-instance is dropped because the Ethernet Tag Identifier received-ethernet-tag received in the route, does not match locally configured Ethernet Tag Identifier local-ethernet-tag on the bgp-instance
Cause	This event is generated when a received Ethernet Tag Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The mac-address if programmed in the bridge-table AND/OR the mac-address/ip-address pair if programmed in the ARP or Neighbor discovery table, might not be removed

13.14 evpnMacRouteWithdrawnDueToUnexpectedVni

evpnMacRouteWithdrawnDueToUnexpectedVni:evpn

Table 211: *evpnMacRouteWithdrawnDueToUnexpectedVni* properties

Property name	Value
Application name	evpn
Event name	evpnMacRouteWithdrawnDueToUnexpectedVni
Default severity	warning
Message format string	BGP-EVPN MAC mac-address IP ip-address received with route-distinguisher route-distinguisher on network instance network-instance and bgp instance bgp-instance is withdrawn because the VXLAN Network Identifier received-vni received in the route, does not match locally configured VXLAN Network Identifier local-vni on the bgp-instance
Cause	This event is generated when a received VXLAN Network Identifier does not match the one configured locally on the bgp-instance in the network instance
Effect	The mac-address is not programmed in the bridge-table AND/OR the mac-address/ip-address pair is not programmed in the ARP or Neighbor discovery table

14 gnmi

14.1 globalConfigUpdate

globalConfigUpdate:gnmi

Table 212: *globalConfigUpdate* properties

Property name	Value
Application name	gnmi
Event name	globalConfigUpdate
Default severity	informational
Message format string	gNMI server global configuration updated.
Cause	A global configuration change has been made, resulting in gNMI configuration being regenerated.
Effect	May result in gNMI server(s) start or stop depending on the configuration change.

14.2 gnmiServerStart

gnmiServerStart:gnmi

Table 213: *gnmiServerStart* properties

Property name	Value
Application name	gnmi
Event name	gnmiServerStart
Default severity	informational
Message format string	gNMI server started for network instance network_instance source address source_address port number gnmi_socket .
Cause	gNMI server has started for the mentioned network instance, source address and port number.

Property name	Value
Effect	gNMI server is ready to receive and process requests for the mentioned network instance, source address and port number.

14.3 gnmiServerStop

gnmiServerStop:gnmi

Table 214: *gnmiServerStop* properties

Property name	Value
Application name	gnmi
Event name	gnmiServerStop
Default severity	informational
Message format string	gNMI server stopped for network network_instance source address source_address port number gnmi_socket .
Cause	gNMI server has stopped for the mentioned network instance, source address and port number.
Effect	gNMI server is not ready to receive and process requests for the mentioned network instance, source address and port number.

14.4 networkInstanceConfigUpdate

networkInstanceConfigUpdate:gnmi

Table 215: *networkInstanceConfigUpdate* properties

Property name	Value
Application name	gnmi
Event name	networkInstanceConfigUpdate
Default severity	informational
Message format string	gNMI server network instance network_instance configuration updated.
Cause	A configuration change has been made in the mentioned network instance, resulting in gNMI server configuration being regenerated.

Property name	Value
Effect	May result in gNMI server start or stop depending on the configuration change.

14.5 subscriptionEnd

subscriptionEnd:gnmi

Table 216: *subscriptionEnd* properties

Property name	Value
Application name	gnmi
Event name	subscriptionEnd
Default severity	informational
Message format string	Subscription for path ' path ' requested by peer_address:socket has finished.
Cause	A subscription has finished based on the request from mentioned peer.
Effect	none.

14.6 subscriptionRequestReceived

subscriptionRequestReceived:gnmi

Table 217: *subscriptionRequestReceived* properties

Property name	Value
Application name	gnmi
Event name	subscriptionRequestReceived
Default severity	informational
Message format string	Subscription request from peer peer_address:socket is received.
Cause	A subscription request is received from the mentioned peer.
Effect	gNMI server will process the request.

14.7 subscriptionStart

subscriptionStart:gnmi

Table 218: subscriptionStart properties

Property name	Value
Application name	gnmi
Event name	subscriptionStart
Default severity	informational
Message format string	Subscription for path ' path ' requested by peer_address:socket has started.
Cause	A subscription has started based on the request from mentioned peer.
Effect	none.

14.8 unixSocketGnmiOperDown

unixSocketGnmiOperDown:gnmi

Table 219: unixSocketGnmiOperDown properties

Property name	Value
Application name	gnmi
Event name	unixSocketGnmiOperDown
Default severity	critical
Message format string	Unix Domain Socket gNMI server is no longer operational.
Cause	The Unix domain socket gNMI server has transitioned from any other operational state to the down state.
Effect	Unix Domain Socket gNMI server is now down.

14.9 unixSocketGnmiOperUp

unixSocketGnmiOperUp:gnmi

Table 220: unixSocketGnmiOperUp properties

Property name	Value
Application name	gnmi
Event name	unixSocketGnmiOperUp
Default severity	warning
Message format string	Unix domain socket gNMI server is operational.
Cause	The Unix domain socket gNMI server has transitioned from any other operational state to the up state.
Effect	Unix domain socket gNMI server is now up.

15 gribi

15.1 globalConfigUpdate

globalConfigUpdate:gribi

Table 221: *globalConfigUpdate* properties

Property name	Value
Application name	gribi
Event name	globalConfigUpdate
Default severity	informational
Message format string	Gribi server global configuration updated.
Cause	A global configuration change has been made, resulting in Gribi configuration being regenerated.
Effect	May result in Gribi server(s) start or stop depending on the configuration change.

15.2 gribiServerStart

gribiServerStart:gribi

Table 222: *gribiServerStart* properties

Property name	Value
Application name	gribi
Event name	gribiServerStart
Default severity	informational
Message format string	Gribi server started for network instance network_instance source address source_address port number gribi_socket .
Cause	Gribi server has started for the mentioned network instance, source address and port number.

Property name	Value
Effect	Gribi server is ready to receive and process requests for the mentioned network instance, source address and port number.

15.3 gribiServerStop

gribiServerStop:gribi

Table 223: *gribiServerStop* properties

Property name	Value
Application name	gribi
Event name	gribiServerStop
Default severity	informational
Message format string	Gribi server stopped for network network_instance source address source_address port number gribi_socket .
Cause	Gribi server has stopped for the mentioned network instance, source address and port number.
Effect	Gribi server is not ready to receive and process requests for the mentioned network instance, source address and port number.

15.4 networkInstanceConfigUpdate

networkInstanceConfigUpdate:gribi

Table 224: *networkInstanceConfigUpdate* properties

Property name	Value
Application name	gribi
Event name	networkInstanceConfigUpdate
Default severity	informational
Message format string	Gribi server network instance network_instance configuration updated.
Cause	A configuration change has been made in the mentioned network instance, resulting in Gribi server configuration being regenerated.

Property name	Value
Effect	May result in Gribi server start or stop depending on the configuration change.

15.5 unixSocketGribiOperDown

unixSocketGribiOperDown:gribi

Table 225: *unixSocketGribiOperDown* properties

Property name	Value
Application name	gribi
Event name	unixSocketGribiOperDown
Default severity	critical
Message format string	Unix Domain Socket Gribi server is no longer operational.
Cause	The Unix domain socket Gribi server has transitioned from any other operational state to the down state.
Effect	Unix Domain Socket Gribi server is now down.

15.6 unixSocketGribiOperUp

unixSocketGribiOperUp:gribi

Table 226: *unixSocketGribiOperUp* properties

Property name	Value
Application name	gribi
Event name	unixSocketGribiOperUp
Default severity	warning
Message format string	Unix domain socket Gribi server is operational.
Cause	The Unix domain socket Gribi server has transitioned from any other operational state to the up state.
Effect	Unix domain socket Gribi server is now up.

16 isis

16.1 isisAdjacencyBfdSessionSetupFailed

isisAdjacencyBfdSessionSetupFailed:isis

Table 227: *isisAdjacencyBfdSessionSetupFailed* properties

Property name	Value
Application name	isis
Event name	isisAdjacencyBfdSessionSetupFailed
Default severity	warning
Message format string	In network-instance network_instance , BFD session setup failed for the level IS-IS adjacency with system sys_id , using interface subinterface . Failure reason: bfd_failure_reason .
Cause	This event is generated when BFD session setup fails with an adjacent neighbor.
Effect	Fast failure detection may not be possible.

16.2 isisAdjacencyChange

isisAdjacencyChange:isis

Table 228: *isisAdjacencyChange* properties

Property name	Value
Application name	isis
Event name	isisAdjacencyChange
Default severity	warning
Message format string	In network-instance network_instance , the level IS-IS adjacency with system sys_id , using interface subinterface , moved to state adj_state .

Property name	Value
Cause	This event is generated when an IS-IS adjacency enters or leaves the up state.
Effect	IS-IS traffic can only be forwarded along adjacencies that are up.

16.3 isisAdjacencyRestartStatusChange

isisAdjacencyRestartStatusChange:isis

Table 229: *isisAdjacencyRestartStatusChange* properties

Property name	Value
Application name	isis
Event name	isisAdjacencyRestartStatusChange
Default severity	warning
Message format string	In network-instance network_instance , the graceful restart status for the level IS-IS adjacency on interface subinterface moved to new state restart_status .
Cause	This event is generated when the graceful restart status of a neighbor changes.
Effect	None

16.4 isisAreaMismatch

isisAreaMismatch:isis

Table 230: *isisAreaMismatch* properties

Property name	Value
Application name	isis
Event name	isisAreaMismatch
Default severity	warning
Message format string	In network-instance network_instance , a level1 PDU was received on interface subinterface with no Area Addresses matching the areas to which this IS router belongs. The PDU starts with: pdu_fragment

Property name	Value
Cause	This event is generated to alert of a possible area-id misconfiguration inside a L1 area.
Effect	L1 adjacency cannot form

16.5 isisAuthDataFail

isisAuthDataFail:isis

Table 231: *isisAuthDataFail* properties

Property name	Value
Application name	isis
Event name	isisAuthDataFail
Default severity	warning
Message format string	In network-instance network_instance , a level PDU was received on interface subinterface with unexpected or incorrect data in the Authentication TLV. The PDU starts with: pdu_fragment
Cause	This event could be caused by incorrect keychain configuration in this router or its neighbor.
Effect	PDU's are dropped, with the effect depending on the PDU type

16.6 isisAuthTypeMismatch

isisAuthTypeMismatch:isis

Table 232: *isisAuthTypeMismatch* properties

Property name	Value
Application name	isis
Event name	isisAuthTypeMismatch
Default severity	warning
Message format string	In network-instance network_instance , a level PDU was received on interface subinterface with an unrecognized or unsupported authentication type in TLV 10. The PDU starts with: pdu_fragment

Property name	Value
Cause	This event could be caused by incorrect keychain configuration in this router or its neighbor.
Effect	PDU's are dropped, with the effect depending on the PDU type

16.7 isisCircuitIdsExhausted

isisCircuitIdsExhausted:isis

Table 233: *isisCircuitIdsExhausted* properties

Property name	Value
Application name	isis
Event name	isisCircuitIdsExhausted
Default severity	warning
Message format string	In network-instance network_instance , the IS-IS interface subinterface is operationally down because the limit of 255 circuit IDs available to LAN interfaces was reached.
Cause	This event is caused by having too many LAN interfaces.
Effect	LAN adjacencies are not formed

16.8 isisCircuitMtuTooLow

isisCircuitMtuTooLow:isis

Table 234: *isisCircuitMtuTooLow* properties

Property name	Value
Application name	isis
Event name	isisCircuitMtuTooLow
Default severity	warning
Message format string	In network-instance network_instance , a level LSP PDU or SNP PDU could not be transmitted on interface subinterface because the IP MTU is only operational_subif_mtu and an MTU of at least required_mtu is required.

Property name	Value
Cause	The port MTU is too small and/or the lsp-mtu-size is too large.
Effect	PDU's are dropped

16.9 isisCorruptedLspDetected

isisCorruptedLspDetected:isis

Table 235: *isisCorruptedLspDetected* properties

Property name	Value
Application name	isis
Event name	isisCorruptedLspDetected
Default severity	warning
Message format string	In network-instance network_instance , the LSP PDU with ID lsp_id in the level database has become corrupted.
Cause	Memory corruption or other.
Effect	LSP is removed

16.10 isisLdpSyncExited

isisLdpSyncExited:isis

Table 236: *isisLdpSyncExited* properties

Property name	Value
Application name	isis
Event name	isisLdpSyncExited
Default severity	warning
Message format string	In network-instance network_instance , the LDP synchronization state has ended on IS-IS interface subinterface , and now the state is sync_state
Cause	The LDP synchronization timer can be stopped because of a tools command, hold-down timer expiry or indication from the LDP peer that

Property name	Value
	End-of-LIB has been received. When LDP sync is exited IS-IS resumes advertising a normal metric for the interface.
Effect	Transit traffic can start using this interface again.

16.11 isisLdpSyncTimerStarted

isisLdpSyncTimerStarted:isis

Table 237: *isisLdpSyncTimerStarted* properties

Property name	Value
Application name	isis
Event name	isisLdpSyncTimerStarted
Default severity	warning
Message format string	In network-instance network_instance , the LDP synchronization timer has started on IS-IS interface subinterface
Cause	The sync timer is started when LDP synchronization is configured and the LDP adjacency comes up with the LDP peer. When this timer expires IS-IS will resume advertisement of a normal metric for the interface.
Effect	Transit traffic will continue to avoid using this interface.

16.12 isisLspFragmentTooLarge

isisLspFragmentTooLarge:isis

Table 238: *isisLspFragmentTooLarge* properties

Property name	Value
Application name	isis
Event name	isisLspFragmentTooLarge
Default severity	warning
Message format string	In network-instance network_instance , the level LSP PDU fragment lsp_id received on interface subinterface could not be accepted

Property name	Value
	because the configured LSP MTU size is too small. An LSP MTU size of at least required_lsp_mtu bytes is required.
Cause	Misconfiguration of LSP MTU size
Effect	LSP PDU is not accepted

16.13 isisLspPurge

isisLspPurge:isis

Table 239: *isisLspPurge* properties

Property name	Value
Application name	isis
Event name	isisLspPurge
Default severity	warning
Message format string	In network-instance network_instance , the LSP PDU with ID lsp_id in the level database has been purged by purge_originator .
Cause	LSP lifetime expired or other reason
Effect	The PDU is removed

16.14 isisLspSequenceNumberSkip

isisLspSequenceNumberSkip:isis

Table 240: *isisLspSequenceNumberSkip* properties

Property name	Value
Application name	isis
Event name	isisLspSequenceNumberSkip
Default severity	warning
Message format string	In network-instance network_instance , the LSP with id lsp_id in the level database was re-originated with a sequence number that incremented by more than one.

Property name	Value
Cause	There may be another IS router configured with the same system ID.
Effect	None

16.15 isisMaxAreaAddressesMismatch

isisMaxAreaAddressesMismatch:isis

Table 241: *isisMaxAreaAddressesMismatch* properties

Property name	Value
Application name	isis
Event name	isisMaxAreaAddressesMismatch
Default severity	warning
Message format string	In network-instance network_instance , a level PDU was received on interface subinterface with an unexpected Max Area Addresses value in the IS-IS PDU header. The PDU starts with: pdu_fragment
Cause	Misconfiguration of max area addresses in the neighbor
Effect	The PDU is dropped

16.16 isisMaxLspSequenceNumberExceeded

isisMaxLspSequenceNumberExceeded:isis

Table 242: *isisMaxLspSequenceNumberExceeded* properties

Property name	Value
Application name	isis
Event name	isisMaxLspSequenceNumberExceeded
Default severity	warning
Message format string	In network-instance network_instance , the LSP with id lsp_id in the level database was purged because the sequence number was already at its maximum value and could not be incremented.
Cause	A possible cause could be that the same system-id is configured on multiple systems; when 2 systems have the same system-id they both

Property name	Value
	keep incrementing the LSP sequence number, causing the sequence counter to rollover.
Effect	The PDU is purged and reachability may be temporarily lost

16.17 isisOverloadEntry

isisOverloadEntry:isis

Table 243: *isisOverloadEntry* properties

Property name	Value
Application name	isis
Event name	isisOverloadEntry
Default severity	warning
Message format string	In the IS-IS instance of network-instance network_instance , the level database has entered the overload state.
Cause	Overload bit configuration
Effect	No transit traffic is routed through the overloaded router.

16.18 isisOverloadExit

isisOverloadExit:isis

Table 244: *isisOverloadExit* properties

Property name	Value
Application name	isis
Event name	isisOverloadExit
Default severity	warning
Message format string	In the IS-IS instance of network-instance network_instance , the level database has exited from the overload state.
Cause	Overload bit configuration
Effect	Transit traffic can again be routed through the router.

16.19 isisOwnLspPurge

isisOwnLspPurge:isis

Table 245: *isisOwnLspPurge* properties

Property name	Value
Application name	isis
Event name	isisOwnLspPurge
Default severity	warning
Message format string	In network-instance network_instance , a level LSP PDU was received with the system ID of this IS router and age equal to zero. The purge originator was purge_originator .
Cause	LSP lifetime expired or other reason
Effect	The PDU is removed

16.20 isisSystemIdLengthMismatch

isisSystemIdLengthMismatch:isis

Table 246: *isisSystemIdLengthMismatch* properties

Property name	Value
Application name	isis
Event name	isisSystemIdLengthMismatch
Default severity	warning
Message format string	In network-instance network_instance , a level PDU was received on interface subinterface with an unexpected System ID length in the IS-IS PDU header. The PDU starts with: pdu_fragment
Cause	Misconfiguration of system ID length in the neighbor
Effect	The PDU is dropped

16.21 isisVersionMismatch

isisVersionMismatch:isis

Table 247: *isisVersionMismatch* properties

Property name	Value
Application name	isis
Event name	isisVersionMismatch
Default severity	warning
Message format string	In network-instance network_instance , a level PDU was received on interface subinterface with an IS-IS protocol version not matching the expected value. The PDU starts with: pdu_fragment
Cause	Unsupported IS-IS version
Effect	PDUs cannot be exchanged

17 json

17.1 authenticationError

authenticationError:json

Table 248: authenticationError properties

Property name	Value
Application name	json
Event name	authenticationError
Default severity	informational
Message format string	No username/password received, authentication needed
Cause	A user has failed to authenticate.
Effect	That user can't establish a configuration session.

17.2 globalConfigUpdate

globalConfigUpdate:json

Table 249: globalConfigUpdate properties

Property name	Value
Application name	json
Event name	globalConfigUpdate
Default severity	informational
Message format string	JSON RPC server global configuration updated.
Cause	A global configuration change has been made, resulting in json rpc configuration being regenerated.
Effect	May result in json rpc process(es) start or stop depending on the configuration change.

17.3 httpJsonRpcOperDown

httpJsonRpcOperDown.json

Table 250: *httpJsonRpcOperDown* properties

Property name	Value
Application name	json
Event name	httpJsonRpcOperDown
Default severity	critical
Message format string	HTTP JSON RPC server for network instance network_instance is no longer operational.
Cause	The httpJsonRpcOperDown event is generated when HTTP JSON RPC server on the mentioned network instance has transitioned from any other operational state to the down state.
Effect	HTTP JSON RPC server on the mentioned network instance is now down.

17.4 httpJsonRpcOperUp

httpJsonRpcOperUp.json

Table 251: *httpJsonRpcOperUp* properties

Property name	Value
Application name	json
Event name	httpJsonRpcOperUp
Default severity	warning
Message format string	HTTP JSON RPC server for network instance network_instance is operational.
Cause	The httpJsonRpcOperUp event is generated when HTTP JSON RPC server on the mentioned network instance has transitioned from any other operational state to the up state.
Effect	HTTP JSON RPC server on the mentioned network instance is now up.

17.5 httpsJsonRpcOperDown

httpsJsonRpcOperDown.json

Table 252: *httpsJsonRpcOperDown* properties

Property name	Value
Application name	json
Event name	httpsJsonRpcOperDown
Default severity	critical
Message format string	HTTPS JSON RPC server for network instance network_instance is no longer operational.
Cause	The httpsJsonRpcOperDown event is generated when HTTPs JSON RPC server on the mentioned network instance has transitioned from any other operational state to the down state.
Effect	HTTPS JSON RPC server on the mentioned network instance is now down.

17.6 httpsJsonRpcOperUp

httpsJsonRpcOperUp.json

Table 253: *httpsJsonRpcOperUp* properties

Property name	Value
Application name	json
Event name	httpsJsonRpcOperUp
Default severity	warning
Message format string	HTTPS JSON RPC server for network instance network_instance is operational.
Cause	The httpsJsonRpcOperUp event is generated when HTTPs JSON RPC server on the mentioned network instance has transitioned from any other operational state to the up state.
Effect	HTTPS JSON RPC server on the mentioned network instance is now up.

17.7 jsonRpcRequestReceived

jsonRpcRequestReceived:json

Table 254: *jsonRpcRequestReceived* properties

Property name	Value
Application name	json
Event name	jsonRpcRequestReceived
Default severity	informational
Message format string	Request received for session id session_id username username .
Cause	A JSON RPC Request is received.
Effect	JSON RPC server processes That Request.

17.8 jsonRpcResponseSent

jsonRpcResponseSent:json

Table 255: *jsonRpcResponseSent* properties

Property name	Value
Application name	json
Event name	jsonRpcResponseSent
Default severity	informational
Message format string	Response sent for session id session_id username username .
Cause	A JSON RPC Response is sent.
Effect	none.

17.9 networkInstanceConfigUpdate

networkInstanceConfigUpdate:json

Table 256: *networkInstanceConfigUpdate* properties

Property name	Value
Application name	json
Event name	networkInstanceConfigUpdate
Default severity	informational
Message format string	JSON RPC server network instance network_instance configuration updated.
Cause	A configuration change has been made in the mentioned network instance, resulting in json rpc configuration being regenerated.
Effect	May result in json rpc process(es) start or stop depending on the configuration change.

17.10 unixSocketJsonRpcOperDown

unixSocket.JsonRpcOperDown:json

Table 257: *unixSocket.JsonRpcOperDown* properties

Property name	Value
Application name	json
Event name	unixSocketJsonRpcOperDown
Default severity	critical
Message format string	Unix Domain Socket JSON RPC server is no longer operational.
Cause	The Unix Domain Socket JSON RPC server has transitioned from any other operational state to the down state.
Effect	Unix Domain Socket JSON RPC server is now down.

17.11 unixSocketJsonRpcOperUp

unixSocket.JsonRpcOperUp:json

Table 258: *unixSocketJsonRpcOperUp* properties

Property name	Value
Application name	json
Event name	unixSocketJsonRpcOperUp
Default severity	warning
Message format string	Unix Domain Socket JSON RPC server is operational.
Cause	The Unix Domain Socket JSON RPC server has transitioned from any other operational state to the up state.
Effect	Unix Domain Socket JSON RPC server is now up.

17.12 userAuthenticated

userAuthenticated:json

Table 259: *userAuthenticated* properties

Property name	Value
Application name	json
Event name	userAuthenticated
Default severity	informational
Message format string	User username authenticated.
Cause	A user has been successfully authenticated.
Effect	That user is ready to start a configuration session.

17.13 userAuthenticationErrorWrongPassword

userAuthenticationErrorWrongPassword:json

Table 260: *userAuthenticationErrorWrongPassword* properties

Property name	Value
Application name	json

Property name	Value
Event name	userAuthenticationErrorWrongPassword
Default severity	informational
Message format string	User username authentication failure, invalid username or password.
Cause	A user has failed to authenticate.
Effect	That user can't establish a configuration session.

18 lag

18.1 lagDown

lagDown:lag

Table 261: lagDown properties

Property name	Value
Application name	lag
Event name	lagDown
Default severity	warning
Message format string	LAG Interface interface_name : The operational state has transitioned to Down
Cause	This warning is generated when a LAG transitions to the down state.
Effect	The LAG is now down and any associated subinterfaces will also be brought down.

18.2 lagDownMinLinks

lagDownMinLinks:lag

Table 262: lagDownMinLinks properties

Property name	Value
Application name	lag
Event name	lagDownMinLinks
Default severity	warning
Message format string	LAG Interface interface_name : The active number of member links has fallen below the min-links threshold
Cause	This warning is generated when a LAG transitions to the down state because the number of active links has dropped below the min-link threshold

Property name	Value
Effect	The LAG is now down and any associated subinterfaces will also be brought down.

18.3 lagMemberLinkAdded

lagMemberLinkAdded:lag

Table 263: lagMemberLinkAdded properties

Property name	Value
Application name	lag
Event name	lagMemberLinkAdded
Default severity	notice
Message format string	LAG Interface interface_name : The member-link member-interface has been added
Cause	This notification is generated when a new member-link is added to a LAG.
Effect	A new member link is now available to the LAG bundle.

18.4 lagMemberLinkRemoved

lagMemberLinkRemoved:lag

Table 264: lagMemberLinkRemoved properties

Property name	Value
Application name	lag
Event name	lagMemberLinkRemoved
Default severity	notice
Message format string	LAG Interface interface_name : The member-link member-interface has been removed
Cause	This notification is generated when a new member-link is removed from a LAG.

Property name	Value
Effect	The specified interfaces is no longer a member of the LAG bundle.

18.5 lagMemberOperDown

lagMemberOperDown:lag

Table 265: lagMemberOperDown properties

Property name	Value
Application name	lag
Event name	lagMemberOperDown
Default severity	warning
Message format string	LAG Interface interface_name : The member-link member-interface operational state has transitioned to Down
Cause	This notification is generated when a member-link transitions to the down state.
Effect	The member link is now down and will not forward traffic.

18.6 lagMemberOperUp

lagMemberOperUp:lag

Table 266: lagMemberOperUp properties

Property name	Value
Application name	lag
Event name	lagMemberOperUp
Default severity	warning
Message format string	LAG Interface interface_name : The member-link member-interface operational state has transitioned to Up
Cause	This notification is generated when a member-link transitions to the up state.
Effect	The member link is now operational.

18.7 lagUp

lagUp:lag

Table 267: lagUp properties

Property name	Value
Application name	lag
Event name	lagUp
Default severity	notice
Message format string	LAG Interface interface_name : The operational state has transitioned to Up
Cause	This notification is generated when a LAG transitions to the up state.
Effect	The LAG is now operational.

19 ldp

19.1 ldpInterfaceDown

ldpInterfaceDown:ldp

Table 268: ldpInterfaceDown properties

Property name	Value
Application name	ldp
Event name	ldpInterfaceDown
Default severity	warning
Message format string	In network-instance network_instance , LDP has changed oper-state to DOWN on interface subinterface . The reason is oper_down_reason
Cause	This event is generated when LDP ceases to be functional on a subinterface.
Effect	LDP drops its adjacencies and sessions with other routers reachable through this subinterface.

19.2 ldpInterfaceUp

ldpInterfaceUp:ldp

Table 269: ldpInterfaceUp properties

Property name	Value
Application name	ldp
Event name	ldpInterfaceUp
Default severity	notice
Message format string	In network-instance network_instance , LDP is now up and functional on interface subinterface .

Property name	Value
Cause	This event is generated when LDP becomes functional on a subinterface.
Effect	LDP can form adjacencies and sessions with other routers reachable through this subinterface.

19.3 Idplpv4InstanceDown

ldplpv4InstanceDown:ldp

Table 270: *ldplpv4InstanceDown* properties

Property name	Value
Application name	ldp
Event name	ldplpv4InstanceDown
Default severity	warning
Message format string	In network-instance network_instance , LDP-IPv4 has changed oper-state to DOWN. The reason is oper_down_reason
Cause	This event is generated when LDP ceases to becomes functional for IPv4 adjacencies, FECs and addresses.
Effect	LDP cannot form IPv4 adjacencies and sessions with other such routers.

19.4 Idplpv4InstanceUp

ldplpv4InstanceUp:ldp

Table 271: *ldplpv4InstanceUp* properties

Property name	Value
Application name	ldp
Event name	ldplpv4InstanceUp
Default severity	notice
Message format string	In network-instance network_instance , LDP-IPv4 is now up and functional.

Property name	Value
Cause	This event is generated when LDP becomes functional for IPv4 adjacencies, FECs and addresses.
Effect	LDP can form IPv4 adjacencies and sessions with other such routers reachable through LDP interfaces that are operational.

19.5 ldpSessionDown

ldpSessionDown:ldp

Table 272: ldpSessionDown properties

Property name	Value
Application name	ldp
Event name	ldpSessionDown
Default severity	warning
Message format string	In network-instance network_instance , the LDP session with peer peer_ldp_id has changed to non-existent.
Cause	This event is generated when an LDP session transitions into the non-existent state from a higher state.
Effect	LDP immediately deletes FEC-label and address bindings received from this peer.

19.6 ldpSessionFecLimitReached

ldpSessionFecLimitReached:ldp

Table 273: ldpSessionFecLimitReached properties

Property name	Value
Application name	ldp
Event name	ldpSessionFecLimitReached
Default severity	warning
Message format string	The number of FECs received from the LDP peer peer_ldp_id has reached the configured limit of fec_limit .

Property name	Value
Cause	The number of FECs accepted from the peer has reached the configured limit. If the number of FECs go below the limit and again start to increase and hit the limit a second time, a new event is generated if 2 or more minutes have elapsed since the previous event. If the FEC limit is changed and the current number of FECs is equal to or higher than the limit then the event is generated immediately.
Effect	If the peer supports the overload capability then the session will go into overload. If the peer doesn't support the overload capability then excess FECs will trigger the sending of label release messages back to the peer.

19.7 ldpSessionLocalIPv4Overload

ldpSessionLocalIPv4Overload:ldp

Table 274: ldpSessionLocalIPv4Overload properties

Property name	Value
Application name	ldp
Event name	ldpSessionLocalIPv4Overload
Default severity	warning
Message format string	The LDP session with peer peer_ldp_id has entered overload for IPv4 FECs because this router sent an overload TLV to the peer.
Cause	The local router has received too many IPv4 FECs.
Effect	The local router is requesting the peer to stop sending further IPv4 FECs.

19.8 ldpSessionPeerIPv4Overload

ldpSessionPeerIPv4Overload:ldp

Table 275: ldpSessionPeerIPv4Overload properties

Property name	Value
Application name	ldp
Event name	ldpSessionPeerIPv4Overload

Property name	Value
Default severity	warning
Message format string	The LDP session with peer peer_ldp_id has entered overload for IPv4 FECs because the peer sent an overload TLV.
Cause	The peer router has received too many IPv4 FECs.
Effect	The local router stops sending further IPv4 FECs to the peer.

19.9 ldpSessionUp

ldpSessionUp:ldp

Table 276: *ldpSessionUp* properties

Property name	Value
Application name	ldp
Event name	ldpSessionUp
Default severity	notice
Message format string	In network-instance network_instance , an LDP session is now up and operational with peer peer_ldp_id .
Cause	This event is generated when an LDP session transitions into the operational state from a lower state.
Effect	LDP can exchange FEC-label and address bindings with this peer.

20 linux

20.1 cpuUsageCritical

cpuUsageCritical:linux

Table 277: *cpuUsageCritical* properties

Property name	Value
Application name	linux
Event name	cpuUsageCritical
Default severity	critical
Message format string	CPU utilization on component_type module slot is above 90% on average for the last minute, current usage cpu_usage_percentage %
Cause	Applications or other system tasks have consumed more than 90% of available CPU resources on average over the last minute.
Effect	Processes may be scheduled at a slower rate than required, resulting in potential application failures or slow downs.

20.2 cpuUsageHigh

cpuUsageHigh:linux

Table 278: *cpuUsageHigh* properties

Property name	Value
Application name	linux
Event name	cpuUsageHigh
Default severity	warning
Message format string	CPU utilization on component_type module slot is above 80% on average for the last minute, current usage cpu_usage_percentage %
Cause	Applications or other system tasks have consumed more than 80% of available CPU resources on average over the last minute.

Property name	Value
Effect	No immediate effect, if utilization continues to increase, processes may be scheduled at a slower rate than required, resulting in potential application failures or slow downs.

20.3 cpuUsageNormal

cpuUsageNormal:linux

Table 279: *cpuUsageNormal* properties

Property name	Value
Application name	linux
Event name	cpuUsageNormal
Default severity	notice
Message format string	CPU utilization on component_type module slot is below 70% on average for the last minute, current usage cpu_usage_percentage%
Cause	CPU consumption on the specified slot has returned to normal levels - below 70%, after triggering a cpuUsageHigh/cpuUsageCritical event.
Effect	None.

20.4 dateAndTimeChanged

dateAndTimeChanged:linux

Table 280: *dateAndTimeChanged* properties

Property name	Value
Application name	linux
Event name	dateAndTimeChanged
Default severity	notice
Message format string	System date and time changed to date_and_time
Cause	The system time has been changed either manually, or via NTP, to the specified time.

Property name	Value
Effect	Local time on the system has changed.

20.5 domainChanged

domainChanged:linux

Table 281: domainChanged properties

Property name	Value
Application name	linux
Event name	domainChanged
Default severity	informational
Message format string	System domain name changed to domain_name
Cause	System configuration change to the domain name has been made.
Effect	The system uses the new domain name.

20.6 hostnameChanged

hostnameChanged:linux

Table 282: hostnameChanged properties

Property name	Value
Application name	linux
Event name	hostnameChanged
Default severity	informational
Message format string	System host name changed to host_name
Cause	System configuration change to the host name has been made.
Effect	The system uses the new host name.

20.7 memoryUsageCritical

memoryUsageCritical:linux

Table 283: *memoryUsageCritical* properties

Property name	Value
Application name	linux
Event name	memoryUsageCritical
Default severity	critical
Message format string	Memory utilization on component_type module slot is above 90%, current usage memory_usage_percentage %
Cause	Applications or other in-memory items have consumed more than 90% of the memory on the specified module.
Effect	No immediate effect, if utilization continues to increase, new memory allocations may fail, resulting in potential application failures.

20.8 memoryUsageFull

memoryUsageFull:linux

Table 284: *memoryUsageFull* properties

Property name	Value
Application name	linux
Event name	memoryUsageFull
Default severity	emergency
Message format string	Memory utilization on component_type module slot is full
Cause	Applications or other in-memory items have consumed 100% of the memory on the specified module.
Effect	Further memory allocations will fail, likely leading to application failures and eventual module restart.

20.9 memoryUsageHigh

memoryUsageHigh:linux

Table 285: *memoryUsageHigh* properties

Property name	Value
Application name	linux
Event name	memoryUsageHigh
Default severity	warning
Message format string	Memory utilization on component_type module slot is above 70%, current usage memory_usage_percentage%
Cause	Applications or other in-memory items have consumed more than 70% of the memory on the specified slot.
Effect	No immediate effect, if utilization continues to increase, new memory allocations may fail, resulting in potential application failures.

20.10 memoryUsageNormal

memoryUsageNormal:linux

Table 286: *memoryUsageNormal* properties

Property name	Value
Application name	linux
Event name	memoryUsageNormal
Default severity	notice
Message format string	Memory utilization on component_type module slot is below 60%, current usage memory_usage_percentage%
Cause	Memory consumption on the specified slot has returned to normal levels - below 60%
Effect	None.

20.11 partitionStateChange

partitionStateChange:linux

Table 287: *partitionStateChange* properties

Property name	Value
Application name	linux
Event name	partitionStateChange
Default severity	alert
Message format string	Partition partition has changed state to current_state
Cause	The specified partition has transitioned to a new state.
Effect	Depending on the state, the partition may now be unusable, read-only, or read-write.

20.12 partitionUsageCritical

partitionUsageCritical:linux

Table 288: *partitionUsageCritical* properties

Property name	Value
Application name	linux
Event name	partitionUsageCritical
Default severity	critical
Message format string	Partition partition_label usage on component_type module slot is higher than 90%, current usage partition_usage_percentage%
Cause	The specified partition is almost full, and action should be taken to remove unneeded files.
Effect	None.

20.13 partitionUsageFull

partitionUsageFull:linux

Table 289: *partitionUsageFull* properties

Property name	Value
Application name	linux
Event name	partitionUsageFull
Default severity	alert
Message format string	Partition partition_label on component_type module slot is full
Cause	The specified partition is full.
Effect	Write actions to this partition will fail.

20.14 partitionUsageNormal

partitionUsageNormal:linux

Table 290: *partitionUsageNormal* properties

Property name	Value
Application name	linux
Event name	partitionUsageNormal
Default severity	notice
Message format string	Partition partition_label on component_type module slot is below 70%, current usage partition_usage_percentage%
Cause	Utilization of the specified partition is below 70%, after previously being higher than 80%.
Effect	None.

20.15 partitionUsageWarning

partitionUsageWarning:linux

Table 291: *partitionUsageWarning* properties

Property name	Value
Application name	linux

Property name	Value
Event name	partitionUsageWarning
Default severity	warning
Message format string	Partition partition_label usage on component_type module slot is higher than 80%, current usage partition_usage_percentage %
Cause	The specified partition is almost full, and action should be taken to remove unneeded files.
Effect	None.

20.16 serviceConfigChanged

serviceConfigChanged:linux

Table 292: *serviceConfigChanged* properties

Property name	Value
Application name	linux
Event name	serviceConfigChanged
Default severity	notice
Message format string	Service service_name configuration changed, service reloaded
Cause	The specified service configuration has been changed, and linux_mgr has reloaded the service.
Effect	New configuration for the service is now in effect.

20.17 serviceDownInNetworkInstance

serviceDownInNetworkInstance:linux

Table 293: *serviceDownInNetworkInstance* properties

Property name	Value
Application name	linux
Event name	serviceDownInNetworkInstance

Property name	Value
Default severity	warning
Message format string	Service service_name is no longer operational in network instance net_inst
Cause	The specified service has been disabled in the specified network instance.
Effect	Functionality provided by the service is no longer available in the specified network instance.

20.18 serviceUpInNetworkInstance

serviceUpInNetworkInstance:linux

Table 294: *serviceUpInNetworkInstance* properties

Property name	Value
Application name	linux
Event name	serviceUpInNetworkInstance
Default severity	notice
Message format string	Service service_name is now operational in network instance net_inst
Cause	The specified service has been started in the specified network instance.
Effect	Functionality provided by the service is now available in the specified network instance.

20.19 tlsProfileExpired

tlsProfileExpired:linux

Table 295: *tlsProfileExpired* properties

Property name	Value
Application name	linux
Event name	tlsProfileExpired

Property name	Value
Default severity	warning
Message format string	Certificate in TLS profile tls_profile has expired
Cause	The certificate used in the specified TLS profile has an expiration date in the past.
Effect	Authentication using the specified TLS profile may fail.

20.20 tlsProfileExpiresSoon

tlsProfileExpiresSoon:linux

Table 296: *tlsProfileExpiresSoon* properties

Property name	Value
Application name	linux
Event name	tlsProfileExpiresSoon
Default severity	warning
Message format string	Certificate in TLS profile tls_profile expires at expires_at_date_time
Cause	The certificate used in the specified TLS profile will expire in the next 30 days.
Effect	Authentication using the specified TLS profile may fail once the certificate expires.

21 lldp

21.1 remotePeerAdded

remotePeerAdded:lldp

Table 297: remotePeerAdded properties

Property name	Value
Application name	lldp
Event name	remotePeerAdded
Default severity	informational
Message format string	LLDP remote peer added on interface interface_name : System remote_system_name with chassis ID remote_chassis_id , port remote_port_id with MAC remote_port_mac
Cause	A new LLDP PDU has been received on the interface, resulting in the creation of an LLDP peer.
Effect	A new peer has been added to LLDP.

21.2 remotePeerRemoved

remotePeerRemoved:lldp

Table 298: remotePeerRemoved properties

Property name	Value
Application name	lldp
Event name	remotePeerRemoved
Default severity	informational
Message format string	LLDP remote peer removed on interface interface_name : System remote_system_name with chassis ID remote_chassis_id , port remote_port_id with MAC remote_port_mac

Property name	Value
Cause	The TTL for the remote peer has expired without a new LLDP PDU being received.
Effect	The peer has been removed from LLDP.

21.3 remotePeerUpdated

remotePeerUpdated:lldp

Table 299: remotePeerUpdated properties

Property name	Value
Application name	lldp
Event name	remotePeerUpdated
Default severity	informational
Message format string	LLDP remote peer updated on interface interface_name : System remote_system_name with chassis ID remote_chassis_id , port remote_port_id with MAC remote_port_mac
Cause	The LLDP peer has sent new information in a LLDP PDU, without the TTL for the peer expiring.
Effect	The peer has been updated in LLDP.

22 log

22.1 bufferRollover

bufferRollover:log

Table 300: *bufferRollover* properties

Property name	Value
Application name	log
Event name	bufferRollover
Default severity	informational
Message format string	Buffer buffer_name has been rolled over
Cause	The buffer has reached its configured max size, and log manager has rolled it over.
Effect	A new buffer has been opened for writing, and the old buffer has been archived. This may result in older buffers being removed from the system.

22.2 configUpdate

configUpdate:log

Table 301: *configUpdate* properties

Property name	Value
Application name	log
Event name	configUpdate
Default severity	informational
Message format string	Logging configuration updated
Cause	A configuration change has been made, resulting in rsyslogd configuration being regenerated.

Property name	Value
Effect	Rsyslogd configuration has been modified, and the process has been restarted.

22.3 fileRollover

fileRollover:log

Table 302: *fileRollover* properties

Property name	Value
Application name	log
Event name	fileRollover
Default severity	informational
Message format string	File file_path/ file_name has been rolled over
Cause	The file has reached its configured max size, and log manager has rolled it over.
Effect	A new log file has been opened for writing, and the old log file has been archived. This may result in older logs being removed from the system.

22.4 networkNamespaceChanged

networkNamespaceChanged:log

Table 303: *networkNamespaceChanged* properties

Property name	Value
Application name	log
Event name	networkNamespaceChanged
Default severity	informational
Message format string	Logging network namespace has changed from old_net_namespace to new_net_namespace
Cause	Configuration has been modified, resulting in the rsyslogd using the new network namespace to reach remote syslog servers.

Property name	Value
Effect	Rsyslogd will use the new network namespace for reachability to remote syslog servers.

22.5 subsystemFacilityChanged

subsystemFacilityChanged:log

Table 304: *subsystemFacilityChanged* properties

Property name	Value
Application name	log
Event name	subsystemFacilityChanged
Default severity	informational
Message format string	Logging output facility has changed from old_facility to new_facility
Cause	Configuration has been modified, resulting in the output facility of our subsystems changing.
Effect	Subsystems will now output logs to the newly configured facility.

23 mgmt

23.1 checkpointGenerated

checkpointGenerated:mgmt

Table 305: *checkpointGenerated* properties

Property name	Value
Application name	mgmt
Event name	checkpointGenerated
Default severity	informational
Message format string	Generated checkpoint checkpoint_name with comment checkpoint_comment on the following path checkpoint_file_path .
Cause	A configuration checkpoint generated on the mentioned path.
Effect	The mentioned checkpoint is stored to the filesystem.

23.2 checkpointRevertRequestReceived

checkpointRevertRequestReceived:mgmt

Table 306: *checkpointRevertRequestReceived* properties

Property name	Value
Application name	mgmt
Event name	checkpointRevertRequestReceived
Default severity	warning
Message format string	Configuration is going to be reverted to checkpoint checkpoint_id name checkpoint_name comment checkpoint_comment .
Cause	Configuration revert request was received.
Effect	Configuration is going to be reverted to the specified checkpoint and applied to running datastore.

23.3 commitFailed

commitFailed:mgmt

Table 307: *commitFailed* properties

Property name	Value
Application name	mgmt
Event name	commitFailed
Default severity	warning
Message format string	Error while committing configuration changes for user username session session_id (message).
Cause	Unsuccessful commit due to error(s)
Effect	Configuration changes are not applied to running datastore

23.4 commitSucceeded

commitSucceeded:mgmt

Table 308: *commitSucceeded* properties

Property name	Value
Application name	mgmt
Event name	commitSucceeded
Default severity	informational
Message format string	All changes have been committed successfully by user username session session_id .
Cause	A successful commit
Effect	Configuration changes applied to running datastore

23.5 exclusiveConfigSessionBlockedByOtherSessionError

exclusiveConfigSessionBlockedByOtherSessionError:mgmt

Table 309: *exclusiveConfigSessionBlockedByOtherSessionError* properties

Property name	Value
Application name	mgmt
Event name	exclusiveConfigSessionBlockedByOtherSessionError
Default severity	informational
Message format string	Cannot start an exclusive configuration session for candidate name candidate_name , there is other configuration session in progress - session id session_id username username candidate name candidate_name .
Cause	Candidate datastore is locked due to other active session in progress
Effect	Exclusive configuration session Error

23.6 exclusiveConfigSessionError

exclusiveConfigSessionError:mgmt

Table 310: *exclusiveConfigSessionError* properties

Property name	Value
Application name	mgmt
Event name	exclusiveConfigSessionError
Default severity	informational
Message format string	Cannot start an exclusive configuration session, there is already another exclusive configuration session in progress - session id session_id username username candidate name candidate_name .
Cause	Candidate datastore is locked due to other active session in progress
Effect	Exclusive configuration session Error

23.7 privateConfigSessionError

privateConfigSessionError:mgmt

Table 311: *privateConfigSessionError* properties

Property name	Value
Application name	mgmt
Event name	privateConfigSessionError
Default severity	informational
Message format string	Cannot start a configuration session for candidate name candidate_name by user username , the candidate is owned by user candidate_username .
Cause	Candidate datastore is owned by different user
Effect	Private configuration session Error

23.8 privateSharedMismatch

privateSharedMismatch:mgmt

Table 312: *privateSharedMismatch* properties

Property name	Value
Application name	mgmt
Event name	privateSharedMismatch
Default severity	informational
Message format string	Cannot start a configuration session for candidate name candidate_name by user username , cannot use private candidate with shared session or vice versa.
Cause	Candidate was created as private and the requested configuration session is shared or vice versa
Effect	Private shared configuration mismatch Error

23.9 sharedConfigSessionBlockedByOtherSessionError

sharedConfigSessionBlockedByOtherSessionError:mgmt

Table 313: *sharedConfigSessionBlockedByOtherSessionError* properties

Property name	Value
Application name	mgmt
Event name	sharedConfigSessionBlockedByOtherSessionError
Default severity	informational
Message format string	Cannot start a shared configuration session for candidate name candidate_name , there is other configuration session in progress - session id session_id username username candidate name candidate_name .
Cause	Candidate datastore is locked due to other active session in progress
Effect	Shared configuration session Error

24 mirror

24.1 mirrorDestinationDelete

mirrorDestinationDelete:mirror

Table 314: *mirrorDestinationDelete* properties

Property name	Value
Application name	mirror
Event name	mirrorDestinationDelete
Default severity	warning
Message format string	Mirror destination mirror_destination is removed from configuration under mirror instance mirror_instance_name
Cause	Mirror destination is removed from configuration under the mentioned mirror instance
Effect	Packets will no longer be mirrored towards the mentioned mirror destination under the mentioned mirror instance

24.2 mirrorDestinationOperDown

mirrorDestinationOperDown:mirror

Table 315: *mirrorDestinationOperDown* properties

Property name	Value
Application name	mirror
Event name	mirrorDestinationOperDown
Default severity	critical
Message format string	Mirror destination mirror_destination is operationally down under mirror instance mirror_instance_name
Cause	Mirror destination oper state has changed from up to down the mentioned mirror instance

Property name	Value
Effect	The oper state is down for the mentioned mirror destination under the mentioned mirror instance. Packets will no longer be mirrored towards the mentioned mirror destination

24.3 mirrorDestinationOperUP

mirrorDestinationOperUP:mirror

Table 316: *mirrorDestinationOperUP* properties

Property name	Value
Application name	mirror
Event name	mirrorDestinationOperUP
Default severity	warning
Message format string	Mirror destination mirror_destination is operationally up under mirror instance mirror_instance_name
Cause	Mirror destination oper state has changed from down to up the mentioned mirror instance
Effect	The oper state is up for the mentioned mirror destination under the mentioned mirror instance

24.4 mirrorDestnationAdd

mirrorDestnationAdd:mirror

Table 317: *mirrorDestnationAdd* properties

Property name	Value
Application name	mirror
Event name	mirrorDestnationAdd
Default severity	warning
Message format string	Mirror destination mirror_destination is added to configuration under mirror instance mirror_instance_name

Property name	Value
Cause	Mirror destination is added in configuration under the mentioned mirror instance
Effect	Packets from mirror source(s) configured under the mentioned mirror instance will be mirrored towards the mentioned mirror destination configured under the same mirror instance if mirror instance, mirror source(s) and mirror dest are operational up

24.5 mirrorInstanceAdminDisable

mirrorInstanceAdminDisable:mirror

Table 318: *mirrorInstanceAdminDisable* properties

Property name	Value
Application name	mirror
Event name	mirrorInstanceAdminDisable
Default severity	warning
Message format string	Mirror instance mirror_instance_name has changed to administrative disable state
Cause	The mirror instance admin state has changed from enable to disable due to configuration change
Effect	The admin state is disable for the mentioned mirror instance

24.6 mirrorInstanceAdminEnable

mirrorInstanceAdminEnable:mirror

Table 319: *mirrorInstanceAdminEnable* properties

Property name	Value
Application name	mirror
Event name	mirrorInstanceAdminEnable
Default severity	warning

Property name	Value
Message format string	Mirror instance mirror_instance_name has changed to administrative enable state
Cause	The mirror instance admin state has changed from disable to enable due to configuration change
Effect	The admin state is enable for the mentioned mirror instance

24.7 mirrorInstanceOperDown

mirrorInstanceOperDown:mirror

Table 320: *mirrorInstanceOperDown* properties

Property name	Value
Application name	mirror
Event name	mirrorInstanceOperDown
Default severity	critical
Message format string	Mirror instance mirror_instance_name has changed to operational down state due to oper_down_reason
Cause	The mirror instance oper state has changed from up to down
Effect	The oper state is down on the mentioned mirror instance

24.8 mirrorInstanceOperUp

mirrorInstanceOperUp:mirror

Table 321: *mirrorInstanceOperUp* properties

Property name	Value
Application name	mirror
Event name	mirrorInstanceOperUp
Default severity	warning
Message format string	Mirror instance mirror_instance_name has changed to operational up state

Property name	Value
Cause	The mirror instance oper state has changed from down to up
Effect	The oper state is up for the mentioned mirror instance

24.9 mirrorSourceAdd

mirrorSourceAdd:mirror

Table 322: *mirrorSourceAdd* properties

Property name	Value
Application name	mirror
Event name	mirrorSourceAdd
Default severity	warning
Message format string	Mirror source mirror_source is added to configuration under mirror instance mirror_instance_name
Cause	Mirror source is added in configuration under the mentioned mirror instance
Effect	Packets on the mentioned mirror source will be mirrored towards the mirror destination configured under the mentioned mirror instance if mirror instance, mirror source and mirror dest are operational up

24.10 mirrorSourceDelete

mirrorSourceDelete:mirror

Table 323: *mirrorSourceDelete* properties

Property name	Value
Application name	mirror
Event name	mirrorSourceDelete
Default severity	warning
Message format string	Mirror source mirror_source is removed from configuration under mirror instance mirror_instance_name

Property name	Value
Cause	Mirror source is removed from configuration under the mentioned mirror instance
Effect	Packets on the mentioned mirror source will no longer be mirrored towards the mirror destination configured under the mentioned mirror instance

25 netinst

25.1 networkInstanceInterfaceDown

networkInstanceInterfaceDown:netinst

Table 324: networkInstanceInterfaceDown properties

Property name	Value
Application name	netinst
Event name	networkInstanceInterfaceDown
Default severity	warning
Message format string	The interface networkinstance_interface_name in network-instance networkinstance_name is now down for reason: oper_down_reason
Cause	This event is generated when the network instance interface has transitioned from the up state to the down state
Effect	The network instance interface is now down

25.2 networkInstanceInterfaceUp

networkInstanceInterfaceUp:netinst

Table 325: networkInstanceInterfaceUp properties

Property name	Value
Application name	netinst
Event name	networkInstanceInterfaceUp
Default severity	notice
Message format string	The interface networkinstance_interface_name in network-instance networkinstance_name is now up
Cause	This event is generated when the network instance interface has transitioned from the down state to the up state.
Effect	The network instance interface is now up

25.3 networkInstanceStateDown

networkInstanceStateDown:netinst

Table 326: networkInstanceStateDown properties

Property name	Value
Application name	netinst
Event name	networkInstanceStateDown
Default severity	warning
Message format string	Network Instance networkinstance_name is now down
Cause	The network instance has transitioned from the up state to the down state
Effect	The network instance is now down

25.4 networkInstanceStateUp

networkInstanceStateUp:netinst

Table 327: networkInstanceStateUp properties

Property name	Value
Application name	netinst
Event name	networkInstanceStateUp
Default severity	notice
Message format string	Network Instance networkinstance_name is now up
Cause	The network instance has transitioned from the down state to the up state
Effect	The network instance is now up

26 ospf

26.1 ospfAdjacencyBfdSessionSetupFailed

ospfAdjacencyBfdSessionSetupFailed:ospf

Table 328: ospfAdjacencyBfdSessionSetupFailed properties

Property name	Value
Application name	ospf
Event name	ospfAdjacencyBfdSessionSetupFailed
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : BFD session setup failed for the OSPF neighbor ospfNbrRtrId , using interface subinterface . Failure reason: bfd_failure_reason .
Cause	This event is generated when BFD session setup fails with an adjacent OSPF neighbor.
Effect	Fast failure detection may not be possible.

26.2 ospfAdjacencyChange

ospfAdjacencyChange:ospf

Table 329: ospfAdjacencyChange properties

Property name	Value
Application name	ospf
Event name	ospfAdjacencyChange
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : Adjacency with neighbor ospfNbrRtrId , using interface subinterface , moved to state ospfNbrState due to event ospfNbrEvent .
Cause	This event is generated when an OSPF Neighbor changes state.

Property name	Value
Effect	OSPF routing information can only utilized from neighbors in an up state.

26.3 ospfAdjacencyRestartStatusChange

ospfAdjacencyRestartStatusChange:ospf

Table 330: *ospfAdjacencyRestartStatusChange* properties

Property name	Value
Application name	ospf
Event name	ospfAdjacencyRestartStatusChange
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : The graceful restart status for OSPF neighbor ospfNbrRtrId on interface subinterface moved to new state restart_status .
Cause	This event is generated when the graceful restart status of a neighbor changes.
Effect	None

26.4 ospfAsMaxAgeLSA

ospfAsMaxAgeLSA:ospf

Table 331: *ospfAsMaxAgeLSA* properties

Property name	Value
Application name	ospf
Event name	ospfAsMaxAgeLSA
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance area ospfAreald : Max aged LSA ospfLsdbLsid type ospfLsdbType advertising router ospfLsdbRtrId .

Property name	Value
Cause	One of the LSAs in the router's link-state database has reached its maximum age limit.
Effect	The Max Age LSA will be flushed from the LSDB.

26.5 ospfExportLimitReached

ospfExportLimitReached:ospf

Table 332: *ospfExportLimitReached* properties

Property name	Value
Application name	ospf
Event name	ospfExportLimitReached
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : The export-limit ospfExportLimit is reached, additional routes will not be exported by OSPF.
Cause	This event is generated when OSPF has exported the maximum number of routes.
Effect	OSPF will not export any more routes.

26.6 ospfExportLimitWarning

ospfExportLimitWarning:ospf

Table 333: *ospfExportLimitWarning* properties

Property name	Value
Application name	ospf
Event name	ospfExportLimitWarning
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : OSPF has reached ospfExportLimitLogPercent % of the export-limit ospfExportLimit .

Property name	Value
Cause	This event is generated when OSPF has exported the maximum number of routes.
Effect	OSPF will not export any more routes.

26.7 ospfFailure

ospfFailure:ospf

Table 334: ospfFailure properties

Property name	Value
Application name	ospf
Event name	ospfFailure
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : has failed due to ospfFailureReason .
Cause	OSPF encountered an event forcing it to go down.
Effect	OSPF goes down and will restart after a timeout.

26.8 ospflLdpSyncStateChange

ospflLdpSyncStateChange:ospf

Table 335: ospflLdpSyncStateChange properties

Property name	Value
Application name	ospf
Event name	ospflLdpSyncStateChange
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : Interface subinterface , ldp-sync-state moved to state ospflLdpSync State

Property name	Value
Cause	This event is generated when an OSPF interface ldp-synchronization changes state.
Effect	Metric of the interface changes to or from infinity.

26.9 ospflfRxBadPacket

ospflfRxBadPacket:ospf

Table 336: ospflfRxBadPacket properties

Property name	Value
Application name	ospf
Event name	ospflfRxBadPacket
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : A bad packet was received on interface subinterface from ospfPacket SrcAddress in packet type ospfPacketType
Cause	This event is generated An OSPF packet has been received on an interface that cannot be parsed.
Effect	Bad packet is discarded

26.10 ospflfStateChange

ospflfStateChange:ospf

Table 337: ospflfStateChange properties

Property name	Value
Application name	ospf
Event name	ospflfStateChange
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfInstance : Interface subinterface , moved to state ospflfState due to event ospf IfEvent

Property name	Value
Cause	This event is generated when an OSPF interface changes state.
Effect	An OSPF adjacency can not be established if the interface state is down or loop.

26.11 ospfLsdbApproachingOverflow

ospfLsdbApproachingOverflow:ospf

Table 338: ospfLsdbApproachingOverflow properties

Property name	Value
Application name	ospf
Event name	ospfLsdbApproachingOverflow
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : The number of external LSAs has exceeded 90% of the configured limit ospfExtLsdbLimit .
Cause	The number of external LSAs in the router's link-state database has exceeded ninety percent of the configured limit.
Effect	Warning only, normal behavior will continue.

26.12 ospfLsdbOverflow

ospfLsdbOverflow:ospf

Table 339: ospfLsdbOverflow properties

Property name	Value
Application name	ospf
Event name	ospfLsdbOverflow
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : The number of external LSAs has exceeded the configured limit ospfExtLsdbLimit .

Property name	Value
Cause	The number of external LSAs in the router's link-state database has exceeded the configured limit.
Effect	No additional external LSA will be added.

26.13 ospfNbrMtuMismatch

ospfNbrMtuMismatch:ospf

Table 340: ospfNbrMtuMismatch properties

Property name	Value
Application name	ospf
Event name	ospfNbrMtuMismatch
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : Neighbor ospfNbrRtrId , using interface subinterface , signaled an unacceptable MTU.
Cause	This event is generated when an OSPF Neighbor signals an incorrect MTU.
Effect	An OSPF adjacency cannot be established if there is an MTU mismatch.

26.14 ospfOverloadEntry

ospfOverloadEntry:ospf

Table 341: ospfOverloadEntry properties

Property name	Value
Application name	ospf
Event name	ospfOverloadEntry
Default severity	warning

Property name	Value
Message format string	Network-instance network_instance - OSPF instance ospfinstance : the LSDB database has entered the overload state due to ospf OverloadReason .
Cause	Overload bit configuration
Effect	No transit traffic is routed through the overloaded router.

26.15 ospfOverloadExit

ospfOverloadExit:ospf

Table 342: ospfOverloadExit properties

Property name	Value
Application name	ospf
Event name	ospfOverloadExit
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : the LSDB database has exited the overload state.
Cause	Overload bit cleared
Effect	The OSPF instance has cleared the overload state.

26.16 ospfOverloadWarning

ospfOverloadWarning:ospf

Table 343: ospfOverloadWarning properties

Property name	Value
Application name	ospf
Event name	ospfOverloadWarning
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : ospfOverloadReason .

Property name	Value
Cause	Overload bit configuration
Effect	No transit traffic is routed through the overloaded router.

26.17 ospfSpfRunRestarted

ospfSpfRunRestarted:ospf

Table 344: ospfSpfRunRestarted properties

Property name	Value
Application name	ospf
Event name	ospfSpfRunRestarted
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : SPF runs resumed - memory resources available.
Cause	There are sufficient memory resources on the system to run the SPF to completion.
Effect	OSPF stops running SPFs until enough memory resources become available OSPF will resume running the SPFs as required.

26.18 ospfSpfRunsStopped

ospfSpfRunsStopped:ospf

Table 345: ospfSpfRunsStopped properties

Property name	Value
Application name	ospf
Event name	ospfSpfRunsStopped
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : SPF runs stopped - insufficient memory resources.

Property name	Value
Cause	There are insufficient memory resources on the system to run the SPF to completion.
Effect	OSPF stops running SPFs until enough memory resources become available.

26.19 ospfAuthDataFailure

ospfAuthDataFailure:ospf

Table 346: ospfAuthDataFailure properties

Property name	Value
Application name	ospf
Event name	ospfAuthDataFailure
Default severity	warning
Message format string	Network-instance network_instance - OSPF instance ospfinstance : A packet received on interface subinterface from ospfPacketSrc Address and packet type ospfPacketType , failed authentication with ospfAuthError
Cause	This event is caused by interface from a router whose authentication key or authentication type conflicts with this router's authentication key or authentication type.
Effect	PDU's are dropped, with the effect depending on the PDU type

27 platform

27.1 airflowCorrected

airflowCorrected:platform

Table 347: *airflowCorrected* properties

Property name	Value
Application name	platform
Event name	airflowCorrected
Default severity	notice
Message format string	The type in slot slot now matches the dominant airflow of other modules in the system
Cause	The specified module is now part of the majority (either front to back, or back to front) fans + PSUs in the system. This clearance is triggered when a module moves from being part of the minority to the majority, typically through other modules being plugged/unplugged.
Effect	The specified module is providing correct airflow to the system.

27.2 airflowMismatch

airflowMismatch:platform

Table 348: *airflowMismatch* properties

Property name	Value
Application name	platform
Event name	airflowMismatch
Default severity	critical
Message format string	The type in slot slot does not match the airflow of other modules in the system

Property name	Value
Cause	The inserted module does not match the airflow direction of other modules in the system.
Effect	The system is working with inefficient cooling, and may trigger thermal protection.

27.3 componentBooting

componentBooting:platform

Table 349: *componentBooting* properties

Property name	Value
Application name	platform
Event name	componentBooting
Default severity	informational
Message format string	Component type slot has started initialization
Cause	The componentBooting event is generated when the active control module has started initializing the component.
Effect	The specified component has started initializing.

27.4 componentDown

componentDown:platform

Table 350: *componentDown* properties

Property name	Value
Application name	platform
Event name	componentDown
Default severity	critical
Message format string	Component type slot is no longer operational
Cause	The componentDown event is generated when a component has transitioned from any other operational state to the down state.

Property name	Value
Effect	The specified component is now down.

27.5 componentFailed

componentFailed:platform

Table 351: componentFailed properties

Property name	Value
Application name	platform
Event name	componentFailed
Default severity	critical
Message format string	Component type slot has failed, reason reason
Cause	The componentFailed event is generated when a component has transitioned from any other operational state to the failed state.
Effect	The specified component is now failed.

27.6 componentInserted

componentInserted:platform

Table 352: componentInserted properties

Property name	Value
Application name	platform
Event name	componentInserted
Default severity	notice
Message format string	Component type slot has been inserted into the system
Cause	The componentInserted event is generated when a component has been initially detected by the active control module.
Effect	The specified component is detected.

27.7 componentLocatorDisabled

componentLocatorDisabled:platform

Table 353: *componentLocatorDisabled* properties

Property name	Value
Application name	platform
Event name	componentLocatorDisabled
Default severity	notice
Message format string	Locator LED disabled on type slot
Cause	The componentLocatorDisabled event is generated when the locator LED for the component has been disabled, either via timeout, or via operator action.
Effect	The specified component's LED is no longer flashing with locator functionality.

27.8 componentLocatorEnabled

componentLocatorEnabled:platform

Table 354: *componentLocatorEnabled* properties

Property name	Value
Application name	platform
Event name	componentLocatorEnabled
Default severity	notice
Message format string	Locator LED enabled on type slot for duration seconds
Cause	The componentLocatorEnabled event is generated when the locator LED for the component has been enabled by an operator action.
Effect	The specified component's LED is now flashing with locator functionality.

27.9 componentRemoved

componentRemoved:platform

Table 355: *componentRemoved* properties

Property name	Value
Application name	platform
Event name	componentRemoved
Default severity	critical
Message format string	Component type slot has been removed from the system
Cause	The componentRemoved event is generated when a component has is no longer detected in the system. This does not necessarily indicate that the component has been physically removed, but indicates that it is no longer detected by the active control module.
Effect	The specified component is no longer detected by the active control module.

27.10 componentRestarted

componentRestarted:platform

Table 356: *componentRestarted* properties

Property name	Value
Application name	platform
Event name	componentRestarted
Default severity	critical
Message format string	Component type slot has been restarted
Cause	The componentRestarting event is generated when the a component has been restarted.
Effect	The specified component has been restarted.

27.11 componentTemperatureExceeded

componentTemperatureExceeded:platform

Table 357: *componentTemperatureExceeded* properties

Property name	Value
Application name	platform
Event name	componentTemperatureExceeded
Default severity	warning
Message format string	Component type slot has exceeded its temperature threshold, current temperature temperatureC
Cause	The componentTemperatureExceeded event is generated when the component has exceeded its temperature threshold.
Effect	The specified component has a temperature sensor that is overheating, the component may shut down by thermal protection.

27.12 componentTemperatureFailure

componentTemperatureFailure:platform

Table 358: *componentTemperatureFailure* properties

Property name	Value
Application name	platform
Event name	componentTemperatureFailure
Default severity	warning
Message format string	Component type slot has exceeded its safe operating temperature, component will be powered down in 10 seconds. Current temperature temperatureC
Cause	The componentTemperatureFailure event is generated when the component has exceeded its maximum temperature.
Effect	The specified component has a temperature sensor that has overheated, the component will shut down in 10 seconds for thermal protection.

27.13 componentTemperatureNormal

componentTemperatureNormal:platform

Table 359: *componentTemperatureNormal* properties

Property name	Value
Application name	platform
Event name	componentTemperatureNormal
Default severity	notice
Message format string	Component type slot temperature is now normal, current temperature temperatureC
Cause	The componentTemperatureNormal event is generated when the component has recovered from a temperature exceeded state.
Effect	The specified component is now within temperature operating limits.

27.14 componentUp

componentUp:platform

Table 360: *componentUp* properties

Property name	Value
Application name	platform
Event name	componentUp
Default severity	notice
Message format string	Component type slot is now operational
Cause	The componentUp event is generated when a component has transitioned from any other operational state to the up state.
Effect	The specified component is now up.

27.15 controlModuleActivityChange

controlModuleActivityChange:platform

Table 361: controlModuleActivityChange properties

Property name	Value
Application name	platform
Event name	controlModuleActivityChange
Default severity	critical
Message format string	Control module slot has become activity_state
Cause	The controlModuleActivityChange event is generated when there has been an activity change on either control module.
Effect	The specified control module has transitioned to the specified state.

27.16 controlModuleConfigSynchronized

controlModuleConfigSynchronized:platform

Table 362: controlModuleConfigSynchronized properties

Property name	Value
Application name	platform
Event name	controlModuleConfigSynchronized
Default severity	informational
Message format string	Configuration synchronization with standby control module standby_slot has succeeded
Cause	Configuration has been successfully synchronized between the active and standby control modules.
Effect	The standby control module now has the same configuration as the active.

27.17 controlModuleImageSynchronized

controlModuleImageSynchronized:platform

Table 363: controlModuleImageSynchronized properties

Property name	Value
Application name	platform
Event name	controlModuleImageSynchronized
Default severity	informational
Message format string	Image synchronization with standby control module standby_slot has succeeded
Cause	Images have been successfully synchronized between the active and standby control modules.
Effect	The standby control module now has the same images as the active.

27.18 controlModuleInSync

controlModuleInSync:platform

Table 364: controlModuleInSync properties

Property name	Value
Application name	platform
Event name	controlModuleInSync
Default severity	informational
Message format string	Active and standby control modules are now synchronized
Cause	All synchronization activities have completed between the active and standby control modules.
Effect	The standby control module is now ready for a control module switchover, if necessary.

27.19 controlModuleOverlaySynchronized

controlModuleOverlaySynchronized:platform

Table 365: controlModuleOverlaySynchronized properties

Property name	Value
Application name	platform
Event name	controlModuleOverlaySynchronized
Default severity	informational
Message format string	Overlay synchronization with standby control module standby_slot has succeeded
Cause	Overlays have been successfully synchronized between the active and standby control modules.
Effect	The standby control module now has the same overlay as the active.

27.20 controlModuleSyncLost

controlModuleSyncLost:platform

Table 366: controlModuleSyncLost properties

Property name	Value
Application name	platform
Event name	controlModuleSyncLost
Default severity	critical
Message format string	Active control module has lost visibility of the standby control module
Cause	Connection between the active and standby control modules has been lost.
Effect	The standby control module is no longer capable of taking over in the event of a failure of the active, no configuration or images are being synchronized.

27.21 controlModuleSyncStart

controlModuleSyncStart:platform

Table 367: controlModuleSyncStart properties

Property name	Value
Application name	platform
Event name	controlModuleSyncStart
Default severity	informational
Message format string	Active and standby control modules are now synchronizing synchronization_category
Cause	A synchronization has been triggered between the active and standby control modules.
Effect	Configuration, images, or persistent storage is being synchronized between the active and standby control module.

27.22 fantrayEmpty

fantrayEmpty:platform

Table 368: fantrayEmpty properties

Property name	Value
Application name	platform
Event name	fantrayEmpty
Default severity	critical
Message format string	Component fan-tray slot is not present in the system
Cause	The fantrayEmpty event is generated when a fan-tray has transitioned from any other operational state to the empty state, or is never present.
Effect	The system may have cooling issues.

27.23 linecardCapacityDegraded

linecardCapacityDegraded:platform

Table 369: *linecardCapacityDegraded* properties

Property name	Value
Application name	platform
Event name	linecardCapacityDegraded
Default severity	critical
Message format string	Linecard slot forwarding complex forwarding-complex fabric capacity degraded
Cause	The specified linecard's forwarding complex has insufficient operational fabric links.
Effect	Packets may be dropped if the linecard's forwarding complex is sending and receiving significant amounts of traffic to the fabric.

27.24 linecardCapacityNormal

linecardCapacityNormal:platform

Table 370: *linecardCapacityNormal* properties

Property name	Value
Application name	platform
Event name	linecardCapacityNormal
Default severity	informational
Message format string	Linecard slot forwarding complex forwarding-complex fabric capacity normal
Cause	The specified linecard's forwarding complex has sufficient operational fabric links again.
Effect	Normal behavior is restored for sending and receiving traffic to the fabric.

27.25 platformLowPower

platformLowPower:platform

Table 371: *platformLowPower* properties

Property name	Value
Application name	platform
Event name	platformLowPower
Default severity	emergency
Message format string	Insufficient power for currently installed components, current_powerW available, required_powerW required
Cause	Available power from operational power supplies is insufficient to power all components in the system.
Effect	Components in the system will be powered down until required power is lower than what is supplied by operational power supplies.

27.26 platformLowReservePower

platformLowReservePower:platform

Table 372: *platformLowReservePower* properties

Property name	Value
Application name	platform
Event name	platformLowReservePower
Default severity	critical
Message format string	Insufficient reserve power for currently installed components, current_powerW available, required_powerW required
Cause	Available power is less than one power supply capacity extra to power all components in the system.
Effect	Power will be insufficient if one operational power supply is lost.

27.27 platformNormalPower

platformNormalPower:platform

Table 373: platformNormalPower properties

Property name	Value
Application name	platform
Event name	platformNormalPower
Default severity	informational
Message format string	Sufficient power for currently installed components, current_powerW available, required_powerW required
Cause	Available power from operational power supplies is sufficient to power all components in the system.
Effect	Enough power is available.

27.28 psulInputDown

psulInputDown:platform

Table 374: psulInputDown properties

Property name	Value
Application name	platform
Event name	psulInputDown
Default severity	warning
Message format string	Power input on power-supply slot is down
Cause	Input fault on the specified power supply is set.
Effect	The specified power supply can no longer supply power to the system.

27.29 psulInputUp

psulInputUp:platform

Table 375: psulInputUp properties

Property name	Value
Application name	platform

Property name	Value
Event name	psuInputUp
Default severity	notice
Message format string	Power input on power-supply slot is up
Cause	Input fault on the specified power supply is clear.
Effect	The specified power supply can now supply power to the system.

27.30 psuOutputDown

psuOutputDown:platform

Table 376: psuOutputDown properties

Property name	Value
Application name	platform
Event name	psuOutputDown
Default severity	warning
Message format string	Power output on power-supply slot is down
Cause	Output fault on the specified power supply is set.
Effect	The specified power supply can no longer supply power to the system.

27.31 psuOutputUp

psuOutputUp:platform

Table 377: psuOutputUp properties

Property name	Value
Application name	platform
Event name	psuOutputUp
Default severity	notice
Message format string	Power output on power-supply slot is up

Property name	Value
Cause	Output fault on the specified power supply is clear.
Effect	The specified power supply can now supply power to the system.

27.32 psuTemperatureFault

psuTemperatureFault:platform

Table 378: *psuTemperatureFault* properties

Property name	Value
Application name	platform
Event name	psuTemperatureFault
Default severity	warning
Message format string	Component type slot has raised a temperature fault, current temperature temperatureC
Cause	The psuTemperatureFault event is generated when the power supply raises a temperature fault.
Effect	The power supply is overheating, and may shut down by thermal protection.

27.33 psuTemperatureNormal

psuTemperatureNormal:platform

Table 379: *psuTemperatureNormal* properties

Property name	Value
Application name	platform
Event name	psuTemperatureNormal
Default severity	notice
Message format string	Component type slot temperature fault is now clear, current temperature temperatureC

Property name	Value
Cause	The psuTemperatureNormal event is generated when the power supply recovered from a temperature fault state.
Effect	The power supply is now within temperature operating limits.

27.34 systemInServiceSoftwareUpgrade

systemInServiceSoftwareUpgrade:platform

Table 380: *systemInServiceSoftwareUpgrade* properties

Property name	Value
Application name	platform
Event name	systemInServiceSoftwareUpgrade
Default severity	critical
Message format string	System is upgrading from old_version to new_version , utilizing warm reboot
Cause	The systemInServiceSoftwareUpgrade event is generated when a software triggered in service software upgrade request has been made.
Effect	The control and management plane of the system will go offline, the datapath will continue forwarding based on current state. The system will upgrade the kernel, operating system, and/or applications as needed.

27.35 systemReboot

systemReboot:platform

Table 381: *systemReboot* properties

Property name	Value
Application name	platform
Event name	systemReboot
Default severity	critical
Message format string	System going down for reboot

Property name	Value
Cause	The systemReboot event is generated when a software triggered reboot has been made.
Effect	The system will go offline for reboot.

27.36 systemWarmReboot

systemWarmReboot:platform

Table 382: *systemWarmReboot* properties

Property name	Value
Application name	platform
Event name	systemWarmReboot
Default severity	critical
Message format string	System going down for warm reboot
Cause	The systemWarmReboot event is generated when a software triggered warm reboot has been made.
Effect	The control and management plane of the system will go offline, the datapath will continue forwarding based on current state.

27.37 systemWarmRebootAborted

systemWarmRebootAborted:platform

Table 383: *systemWarmRebootAborted* properties

Property name	Value
Application name	platform
Event name	systemWarmRebootAborted
Default severity	critical
Message format string	System has aborted a requested warm reboot due to reason

Property name	Value
Cause	The systemWarmRebootAborted event is generated when a software triggered warm reboot request has been aborted, typically due to unsupported configuration.
Effect	The in progress warm reboot has been aborted, no effect to system configuration or state.

28 qos

28.1 platformQoSProfileHighUtilization

platformQoSProfileHighUtilization:qos

Table 384: platformQoSProfileHighUtilization properties

Property name	Value
Application name	qos
Event name	platformQoSProfileHighUtilization
Default severity	warning
Message format string	The QoS resource called resource-name has reached threshold% or more utilization on linecard linecard , forwarding complex forwarding-complex . Only free-entries entries are remaining.
Cause	This event is generated when the utilization of a QoS resource has increased to a level that may warrant concern if further resources are consumed
Effect	None

28.2 platformQoSProfileHighUtilizationLowered

platformQoSProfileHighUtilizationLowered:qos

Table 385: platformQoSProfileHighUtilizationLowered properties

Property name	Value
Application name	qos
Event name	platformQoSProfileHighUtilizationLowered
Default severity	notice
Message format string	The QoS resource called resource-name has decreased back to threshold% or less utilization on linecard linecard , forwarding complex forwarding-complex .

Property name	Value
Cause	This event is generated when the utilization of a QoS resource has decreased to a level that may no longer warrant concern
Effect	None

29 ra_guard-agent

29.1 ra_guardAdd

ra_guardAdd:ra_guard-agent

Table 386: ra_guardAdd properties

Property name	Value
Application name	ra_guard-agent
Event name	ra_guardAdd
Default severity	notice
Message format string	RA Guard Policy pol-name associated with subinterface if-name , VLAN vlan
Cause	This notification is generated when an RA policy is added to a subinterface.
Effect	The associated RA Policy is now applied to the subinterface.

29.2 ra_guardRemove

ra_guardRemove:ra_guard-agent

Table 387: ra_guardRemove properties

Property name	Value
Application name	ra_guard-agent
Event name	ra_guardRemove
Default severity	notice
Message format string	RA Guard Policy pol-name removed from subinterface if-name , VLAN vlan
Cause	This notification is generated when an RA policy is removed from a subinterface.
Effect	An RA Policy is no longer associated with the specified subinterface.

30 sflow

30.1 sFlowAgentChange

sFlowAgentChange:sflow

Table 388: sFlowAgentChange properties

Property name	Value
Application name	sflow
Event name	sFlowAgentChange
Default severity	notice
Message format string	SFLOW: The global sFlow Agent has administratively been changed to state
Cause	This notification is generated when a sFlow global process changes administrative state.
Effect	The sFlow global process state has changed.


30.2 sFlowCollectorUnreachable

sFlowCollectorUnreachable:sflow

Table 389: sFlowCollectorUnreachable properties

Property name	Value
Application name	sflow
Event name	sFlowCollectorUnreachable
Default severity	warning
Message format string	SFLOW: Collector collector-id - IP address: collector-ip is unreachable
Cause	This notification is generated when the specified sFlow collector will no longer receive sflow sample data until reachability is restored
Effect	Restore IP reachability to the sFlow collector.

Customer document and product support



Customer documentation

[Customer documentation welcome page](#)



Technical support

[Product support portal](#)



Documentation feedback

[Customer documentation feedback](#)